

Parth Shukla
Lab 5
190905104

DDL + Data Dump

```
CREATE TABLE EMPLOYEE (  
  Fname VARCHAR(20),  
  Minit CHAR(1),  
  Lname VARCHAR(20),  
  Ssn CHAR(9),  
  Bdate DATE,  
  Address VARCHAR(30),  
  Sex CHAR(1),  
  Salary NUMBER(5),  
  Super_Ssn CHAR(9),  
  Dno NUMBER(1),  
  PRIMARY KEY (Ssn),  
  FOREIGN KEY (Super_ssn) REFERENCES EMPLOYEE (Ssn)  
);
```

```
INSERT INTO EMPLOYEE VALUES ('James', 'E', 'Justin', '123456789', DATE '1937-11-10', '450  
Stone, Houston, TX', 'M', 55000, NULL, 1);  
INSERT INTO EMPLOYEE VALUES ('Jennifer', 'S', 'Tonanis', '987654321', DATE '1941-06-20',  
'291 Berry, Bellaire, Tx', 'F', 37000, '123456789', 2);  
INSERT INTO EMPLOYEE VALUES ('Franklin', 'T', 'George', '333445555', DATE '1955-12-08',  
'638 Voss, Houston, TX', 'M', 40000, '987654321', 3);  
INSERT INTO EMPLOYEE VALUES ('John', 'B', 'Smith', '123412341', DATE '1965-01-09', '731  
Fondren, Houston, TX', 'M', 30000, '333445555', 2);  
INSERT INTO EMPLOYEE VALUES ('Alicia', 'J', 'Keys', '123412342', DATE '1968-01-19', '3321  
castle, Spring, TX', 'F', 25000, '987654321', 3);
```

```
CREATE TABLE DEPARTMENT(  
  Dname VARCHAR(20),  
  Dnumber NUMBER(1),  
  Mgr_ssn CHAR(9),  
  Mgr_start_date DATE,  
  PRIMARY KEY (Dnumber),  
  FOREIGN KEY (Mgr_ssn) REFERENCES EMPLOYEE (Ssn)  
);
```

```
INSERT INTO DEPARTMENT VALUES ('Research', 1, '333445555', DATE '1988-05-22');
```

```
INSERT INTO DEPARTMENT VALUES ('Administration', 2, '987654321', DATE '1995-01-01');
INSERT INTO DEPARTMENT VALUES ('Headquarters', 3, '123456789', DATE '1981-06-19');
```

```
ALTER TABLE EMPLOYEE ADD FOREIGN KEY (Dno) REFERENCES
DEPARTMENT(Dnumber);
```

```
CREATE TABLE DEPT_LOCATIONS (
Dnumber NUMBER(1),
Dlocation VARCHAR(20),
PRIMARY KEY (Dnumber, Dlocation),
FOREIGN KEY (Dnumber) REFERENCES DEPARTMENT(Dnumber)
);
```

```
INSERT INTO DEPT_LOCATIONS VALUES (1, 'Houston');
INSERT INTO DEPT_LOCATIONS VALUES (2, 'Stanford');
INSERT INTO DEPT_LOCATIONS VALUES (3, 'Bellaire');
INSERT INTO DEPT_LOCATIONS VALUES (2, 'Sugarland');
INSERT INTO DEPT_LOCATIONS VALUES (3, 'Austin');
```

```
CREATE TABLE PROJECT (
Pname VARCHAR(20),
Pnumber NUMBER(2),
Plocation VARCHAR(20),
Dnum NUMBER(1),
PRIMARY KEY (Pnumber),
FOREIGN KEY (Dnum) REFERENCES DEPARTMENT(Dnumber)
);
```

```
INSERT INTO PROJECT VALUES ('ProductX', 1, 'Bellaire', 1);
INSERT INTO PROJECT VALUES ('ProductY', 2, 'Sugarland', 2);
INSERT INTO PROJECT VALUES ('ProductZ', 3, 'Houston', 3);
INSERT INTO PROJECT VALUES ('Computerization', 10, 'Stanford', 1);
INSERT INTO PROJECT VALUES ('Reorganization', 20, 'Houston', 2);
INSERT INTO PROJECT VALUES ('Newbenefits', 30, 'Stanford', 2);
```

```
CREATE TABLE WORKS_ON (
Essn CHAR(9),
Pno NUMBER(2),
Hours NUMBER(3,1),
PRIMARY KEY (Essn, Pno),
FOREIGN KEY (Essn) REFERENCES EMPLOYEE (Ssn),
FOREIGN KEY (Pno) REFERENCES PROJECT(Pnumber)
);
```

```

INSERT INTO WORKS_ON VALUES ('123456789', 1, 32.0);
INSERT INTO WORKS_ON VALUES ('123456789', 2, 8.0);
INSERT INTO WORKS_ON VALUES ('987654321', 1, 20.0);
INSERT INTO WORKS_ON VALUES ('987654321', 2, 20.0);
INSERT INTO WORKS_ON VALUES ('333445555', 3, 5.0);
INSERT INTO WORKS_ON VALUES ('333445555', 10, 10.0);
INSERT INTO WORKS_ON VALUES ('333445555', 20, 10.0);
INSERT INTO WORKS_ON VALUES ('333445555', 30, 5.0);
INSERT INTO WORKS_ON VALUES ('123412341', 30, 30.0);
INSERT INTO WORKS_ON VALUES ('123412341', 10, 10.0);
INSERT INTO WORKS_ON VALUES ('123412342', 30, 20.0);
INSERT INTO WORKS_ON VALUES ('123412342', 20, 15.0);

```

```

CREATE TABLE DEPENDENT(
Essn CHAR(9),
Dependent_name VARCHAR(20),
Sex CHAR(1),
Bdate DATE,
Relationship VARCHAR(10),
PRIMARY KEY (Essn, Dependent_name),
FOREIGN KEY (Essn) REFERENCES EMPLOYEE (Ssn)
);

```

```

INSERT INTO DEPENDENT VALUES ('333445555', 'Alice', 'F', DATE '1986-04-05', 'Daughter');
INSERT INTO DEPENDENT VALUES ('333445555', 'Theodore', 'M', DATE '1983-10-25', 'Son');
INSERT INTO DEPENDENT VALUES ('333445555', 'Joy', 'F', DATE '1958-05-03', 'Spouse');
INSERT INTO DEPENDENT VALUES ('123412341', 'Abner', 'M', DATE '1988-01-04', 'Son');
INSERT INTO DEPENDENT VALUES ('123412341', 'Jennifer', 'F', DATE '1988-01-04',
'Daughter');
INSERT INTO DEPENDENT VALUES ('123456789', 'John', 'M', DATE '1988-02-28', 'Son');
INSERT INTO DEPENDENT VALUES ('123456789', 'Alice', 'F', DATE '1988-12-30', 'Daughter');
INSERT INTO DEPENDENT VALUES ('123456789', 'Elizabeth', 'F', DATE '1967-05-05',
'Spouse');
INSERT INTO DEPENDENT VALUES ('123412342', 'Joyce', 'F', DATE '1990-04-05', 'Daughter');

```

1. Retrieve the birth date and address of the employee(s) whose name is 'John B. Smith'.
Retrieve the name and address of all employees who work for the 'Research'
Department.

Select bdate,address

```
from employee
where fname='John'
and minit='B'
and lname='Smith';
```

```
Select fname,minit,lname,address
from employee
natural join department
where dname='Research';
```

2. For every project located in 'Stanford', list the project number, the controlling department number, and the department manager's last name, address, and birth date.

```
Select dname, lname, address, bdate, dnumber
from department natural join project,employee
where employee.ssn=mgr_ssn and plocation='Stanford';
```

3. Find all distinct salaries of employees.

```
Select distinct(salary) from employee;
```

4. For each employee, retrieve the employee's first and last name and the first and last name of his or her immediate supervisor.

```
Select T.lname,T.fname,S.lname,S.fname
from employee T,employee S where T.ssn=S.super_ssn;
```

5. Make a list of all project numbers for projects that involve an employee whose last name is 'Smith', either as a worker or as a manager of the department that controls the Project.

```
Select pnumber from employee,works_on,project
where lname='Smith'
and employee.ssn=works_on.essn and works_on.pno=project.pnumber;
```

6. Retrieve all employees who reside in Houston, Texas.

```
Select * from employee
where address like '%Houston, TX%';
```

7. Show the resulting salaries if every employee working on the 'ProductX' project is given a 10 percent raise.

```
Update employee set salary=1.1*salary where employee.ssn in
```

(Select essn from works_on,project
where works_on.pno=project.pnumber and pname='ProductX');

select salary from employee where employee.ssn in
(select essn from works_on, project
where works_on.pno=project.pnumber and pname='ProductX');

8. Retrieve all employees in department 5 whose salary is between 30,000 and 40,000.

Select fname from department,employee where dnumber=5 and salary between 30000 and
40000 and employee.dno=department.dnumber;

9. Retrieve a list of employees and the projects they are working on, ordered by
department and, within each department, ordered alphabetically by last name, then first
Name.

Select fname,lname from employee,project,works_on
where works_on.pno=project.pnumber and works_on.essn=employee.ssn
order by pnumber,fname,lname;

10. Retrieve the names of all employees who do not have supervisors.

Select fname,lname from employee where super_ssn is NULL;

11. Retrieve the name of each employee who has a dependent with the same first name and
is the same sex as the employee.

Select lname,fname from employee,dependent where
employee.fname=dependent.dependent_name and employee.sex=dependent.sex;

12. Retrieve the names of employees who have no dependents.

Select distinct(fname) from employee,dependent where employee.ssn not in (Select essn
from dependent);

13. List the names of managers who have at least one dependent.

select fname, lname from employee
where (select count(*) from dependent where ssn=essn) >= 1;

14. Retrieve the Social Security numbers of all employees who work on project numbers
1, 2, or 3.

select distinct(essn) from works_on where pno in (1, 2, 3);

15. Find the sum of the salaries of all employees, the maximum salary, the minimum salary, and the average salary.

```
select sum(salary),max(salary),min(salary),avg(salary) from employee;
```

16. Find the sum of the salaries of all employees of the 'Research' department, as well as the maximum salary, the minimum salary, and the average salary in this department.

```
Select sum(salary),max(salary),min(salary),avg(salary) from employee, department  
where employee.dno=department.dnumber and dname='Research';
```

17. For each project, retrieve the project number, the project name, and the number of employees who work on that project.

```
select pnumber, pname, count(*) from project, works_on  
where pnumber=pno group by pnumber, pname;
```

18. For each project on which more than two employees work, retrieve the project number, the project name, and the number of employees who work on the project.

```
select pnumber, pname, count(*) as total from project, works_on  
where pnumber=pno group by pnumber, pname  
having count(*)>=2;
```

19. For each department that has more than five employees, retrieve the department number and the number of its employees who are making more than 40,000.

```
select dno, count(*) from department, employee  
where dno=dnumber and salary > 40000 and  
dno in (select dno from employee group by dno having count(*) > 5)  
group by dno;
```