

190905104
Parth Shukla
Lab 1

1)

```
create table employee(  
emp_no int,  
emp_name char(50),  
emp_address char(100)  
);
```

2)

```
insert into employee values('1', 'One', 'First');  
insert into employee values('2', 'Two', 'Second');  
insert into employee values('3', 'Three', 'Third');  
insert into employee values('4', 'Four', 'Fourth');  
insert into employee values('5', 'Five', 'Fifth');
```

3)

```
select emp_name from employee;
```

4) [Had to insert entries with manipal as address before executing]

```
insert into employee values('6', 'Six', 'Manipal');  
insert into employee values('7', 'Seven', 'Manipal');  
select * from employee where emp_address='Manipal';
```

5)

```
alter table employee add(  
salary int  
);
```

6)

```
update employee set salary=60000 where emp_no = 1;  
update employee set salary=55000 where emp_no = 2;  
update employee set salary=75000 where emp_no = 3;  
update employee set salary=80000 where emp_no = 4;  
update employee set salary=72000 where emp_no = 5;
```

7)

```
Desc employee;
```

8)

[Had to insert entries with Mangalore as address before executing]

```
insert into employee values('7', 'Seven', 'Mangalore', '90000');
```

```
delete from employee where emp_address='Mangalore';
```

9)

```
rename employee to employee1;
```

10)

```
drop table employee1;
```