

Scenario Name: Scenario 01

Weak Prompt: Search Functionality

What I Feel is Missing: In this Scenario, “It is not clear in which application and what needs to be searched.”

I-Instruction

[MANDATORY] Generate Selenium Java Script with Selenium version 4.0 in the page object model

[STRICT] Generate only the code no other text

[MANDATORY] Add Explicit waits

[CRITICAL] Do not add thread.sleep

[HIGHPRIORITY] Implement Retry mechanism

[HIGHPRIORITY] Implement Exception Handling

[MANDATORY] Add Assertions

[STRICT]: Include only positive test cases.

[STRICT]: Use locators id, name and relative xpath

[STRICT]: Don't use absolute xpath

[Mandatory]: Maintain Separate class files to read and print the data in excel, collect the locators, and do the actions.

[LOWPRIORITY] Add comments to explain the code

C-Context

Act as a senior QA engineer to create a Hybrid framework using a Maven project for searching the iPhone 12 in the Amazon search bar and adding it to the cart

Example

```
// =====
```

```
// FILENAME: ExcelUtil.java
```

```
// =====
```

```
package com.flipkart.qa.utils;
```

```
import org.apache.poi.ss.usermodel.*;
```

```
import java.io.File;
```

```
import java.io.FileInputStream;
import java.io.FileOutputStream;
import java.util.ArrayList;
import java.util.List;

public class ExcelUtil {
    private String filePath;
    private Workbook workbook;

    public ExcelUtil(String filePath) {
        this.filePath = filePath;
        try {
            FileInputStream fis = new FileInputStream(new File(filePath));
            this.workbook = WorkbookFactory.create(fis);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }

    public List<Object[]> getSheetData(String sheetName) {
        List<Object[]> data = new ArrayList<>();
        Sheet sheet = workbook.getSheet(sheetName);
        int rowCount = sheet.getLastRowNum();

        for (int i = 1; i <= rowCount; i++) {
            Row row = sheet.getRow(i);
            if (row == null) continue;

            String tcId = getCellValueAsString(row.getCell(0));
```

```

        String scenario = getCellValueAsString(row.getCell(1));
        String username = getCellValueAsString(row.getCell(2));
        String password = getCellValueAsString(row.getCell(3));
        String expected = getCellValueAsString(row.getCell(4));

        data.add(new Object[]{tcId, scenario, username, password, expected,
i});
    }
    return data;
}

public void writeResult(String sheetName, int rowIdx, String status, String
actualResult) {
    try {
        Sheet sheet = workbook.getSheet(sheetName);
        Row row = sheet.getRow(rowIdx);

        Cell statusCell = row.createCell(5);
        statusCell.setCellValue(status);

        Cell resultCell = row.createCell(6);
        resultCell.setCellValue(actualResult);

        FileOutputStream fos = new FileOutputStream(new File(filePath));
        workbook.write(fos);
        fos.close();
    } catch (Exception e) {
        e.printStackTrace();
    }
}

```

```

private String getCellValueAsString(Cell cell) {
    if (cell == null) return "";
    switch (cell.getCellType()) {
        case STRING: return cell.getStringCellValue();
        case NUMERIC: return String.valueOf((long)cell.getNumericCellValue());
        case BOOLEAN: return String.valueOf(cell.getBooleanCellValue());
        default: return "";
    }
}
}
}

```

```
// =====
```

```
// FILENAME: FlipkartLocators.java
```

```
// =====
```

```
package com.flipkart.qa.locators;
```

```
public class FlipkartLocators {
```

```
    // Relative XPaths, IDs, Names adhering strictly to Selenium-style definitions
    via Playwright locators
```

```
    public static final String LOGIN_LINK_XPATH = "//a[contains(@href,
'login')]";
```

```
    public static final String INPUT_USERNAME_XPATH =
"//input[@class='_2lX_2- _2LYh31']";
```

```
    public static final String INPUT_PASSWORD_XPATH =
"//input[@type='password']";
```

```
    public static final String BUTTON_LOGIN_XPATH =
"//button[contains(., 'Login') or @type='submit']";
```

```
    public static final String SIGNUP_LINK_XPATH = "//a[contains(., 'New to
Flipkart? Create an account')]";
```

```
public static final String INPUT_SIGNUP_MOBILE_XPATH =  
"//input[@class='_2lX_2- _2LYh31']";  
  
public static final String BUTTON_CONTINUE_XPATH =  
"//button[contains(.,'CONTINUE')]";  
  
public static final String ERROR_TEXT_XPATH =  
"//span[contains(@class,'_2YULgZ')]";  
}
```

P-Persona

Act as a Automation Lead to Review the testscripts and Give the Score

O-Output Format

Download Test data as excel file and java code as text file.

Please share the pom.xml file; it will help me understand what dependencies are added in that file.

T-Tone

Generate the output in a professional and concise manner,
focusing on the technical aspects of the code.

Observations:

In the week scenario, the application name is missing. The text to search in the search bar is also missing. After searching for the product, the destination details of where it should go are missing from the prompt.