



router ospf 1

 distance ospf intra-area 105

 distance ospf inter-area 105

end

router ospfv3

 router-id 192.168.0.1

 auto-cost reference-bandwidth 100000

 passive-interface default

 area 0.0.0.1 stub

 area 0.0.0.2 stub no-summary

!

address-family ipv4

!

address-family ipv6

!

interface Lo0

 ospfv3 ipv4 area 0.0.0.0

 ospfv3 ipv6 area 0.0.0.0

!

interface eth1-3

 no ospfv3 passive-interface

!

interface eth1-2

 ospfv3 ipv4 area 0.0.0.0

 ospfv3 ipv6 area 0.0.0.0

!

interface eth3

 ospfv3 ipv4 area 0.0.0.1

 ospfv3 ipv6 area 0.0.0.1

!

R2 ja 4

router ospfv3

 router-id 192.168.0.4

 auto-cost reference-bandwidth 100000

 passive-interface default

 area 0.0.0.1 stub

 area 0.0.0.2 stub no-summary

```
!
address-family ipv4
!
address-family ipv6
!

interface Lo0
 ospfv3 ipv4 area 0.0.0.0
 ospfv3 ipv6 area 0.0.0.0
!

interface eth1-3
 no ospfv3 passive-interface
!

interface eth1-2
 ospfv3 ipv4 area 0.0.0.0
 ospfv3 ipv6 area 0.0.0.0
!

interface eth3
 ospfv3 ipv4 area 0.0.0.2
 ospfv3 ipv6 area 0.0.0.2
!
```

```
R5
router ospfv3
 router-id 192.168.0.6
 auto-cost reference-bandwidth 100000
 passive-interface default
```

```
area 0.0.0.1 stub  
area 0.0.0.2 stub no-summary
```

```
!
```

```
address-family ipv4
```

```
!
```

```
address-family ipv6
```

```
!
```

```
interface Lo0
```

```
  ospfv3 ipv4 area 0.0.0.1  
  ospfv3 ipv6 area 0.0.0.1
```

```
interface eth1-2
```

```
  no ospfv3 passive-interface
```

```
interface eth1-2
```

```
  ospfv3 ipv4 area 0.0.0.1  
  ospfv3 ipv6 area 0.0.0.1
```

```
!
```

```
interface eth3
```

```
  ipv6 address 2001:db8:46:25::1/64  
  ospfv3 ipv4 area 0.0.0.1  
  ospfv3 ipv6 area 0.0.0.1
```

```
!
```

r7

```
router ospfv3
```

```
router-id 192.168.0.7
auto-cost reference-bandwidth 100000
passive-interface default
area 0.0.0.1 stub
area 0.0.0.2 stub no-summary
```

```
!
```

```
address-family ipv4
```

```
!
```

```
address-family ipv6
```

```
!
```

```
interface Lo0
```

```
  ospfv3 ipv4 area 0.0.0.2
```

```
  ospfv3 ipv6 area 0.0.0.2
```

```
!
```

```
interface eth1-2
```

```
  no ospfv3 passive-interface
```

```
!
```

```
interface eth1-2
```

```
  ospfv3 ipv4 area 0.0.0.2
```

```
  ospfv3 ipv6 area 0.0.0.2
```

```
!
```

```
interface eth3
```

```
  ipv6 address 2001:db8:46:22::1/64
```

```
  ospfv3 ipv4 area 0.0.0.2
```

```
  ospfv3 ipv6 area 0.0.0.2
```

```
!
```

r2

```
router ospfv3
address-family ipv4
default-information originate
```

r2

ipv6 route ::/0 2001:db8:0:1::

r4

ipv6 route ::/0 2001:db8:0:2::

```
sh ospfv3 database
```

r2 ja 4

```
router ospfv3
address-family ipv4
default-information originate metric-type 1
```

r2 ja r4 step2

start route

ipv6 routing 2001:db8:46:666::1

kaikkiin reitittimiin step3

router ospf 1

shutdown

ip ospf area 0.0.0.0

ipv6 route 2001:db8:26:666::1

ipv6 address 2001:db8:46:26::1/64

router ospfv3

address-family ipv6

default-information originate metric-type 1