

The LNM Institute of Information Technology, Jaipur

CS325 DESIGN AND ANALYSIS OF ALGORITHM

Quiz-I

Tuesday, Feb 13, 2018

Time: 45 Minutes

Maximum Marks: 40

Name: _____ Roll No: _____

Read the Instructions Carefully:

All are objective questions with 4 choices. There may be more than one correct answers. Each question carry three marks. You need to select all the correct answers to get full marks. For example, if a question has 2 correct choices and you did only one correctly you will get 1 mark. If out of your choices even one choice is wrong then there won't be any marks given (even if there are correct choices that you have made). So be careful when you are finding and marking the correct choices. **Encircle all the correct answer/s. Any other marking will be considered as invalid.** Do not write anything in the answer sheet except the answer. No justification is required. **There is no negative marking for wrong answer/s.**

1. Which is the correct order of the following algorithms with respect to their time complexity in the best case ?
 - (a) Merge sort > selection sort > quick sort > insertion sort
 - (b) Merge sort > Quick sort > selection sort > insertion sort
 - (c) Merge sort > Quick sort > Insertion sort > selection sort
 - (d) insertion sort < Quick sort < Merge sort < selection sort
2. What is the worst-case running time complexity of bucket sort?
 - (a) $\mathcal{O}(n \log n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\mathcal{O}(n^2 \log n)$
 - (d) $\mathcal{O}(n)$
3. There are two functions f and g defined by $f(n) = 2^{n+1}$ and $g(n) = 2^n$. Pick the correct answer(s) from the following:
 - (a) $f(n) = \Omega(g(n))$
 - (b) $f(n) = \mathcal{O}(g(n))$
 - (c) $f(n) = \Theta(g(n))$
 - (d) None of the above
4. What is the maximum number of nodes at height h in any n -element heap?
 - (a) $n/2^h$
 - (b) $n/2^{h-1}$
 - (c) $n/2^{h+1}$
 - (d) $n/2^{2^h}$

5. Strassen's multiplication algorithm works for two square matrices of size $n \times n$. How about multiplying two non-square matrices? Pick the correct choice in the following:
 - (a) Make it as square matrices by padding with extra zeroes and then apply Strassen's method
 - (b) For non-square matrices it won't work
 - (c) Get the maximum square matrix out of the non-square matrix apply Strassen on to that. For the remainder apply the normal matrix multiplication
 - (d) None of the above
6. When RANDOMIZED-QUICKSORT runs, how many calls are made to the random number generator RANDOM in the worst case?
 - (a) $\mathcal{O}(n^2)$
 - (b) $\Theta(\log n)$
 - (c) $\Theta(n)$
 - (d) $\Theta(n \log n)$
7. In Heapsort algorithm if instead of using BUILD-MAX-HEAP algorithm we use MAX-HEAP-INSERT algorithm to build the heap what will be the resulting complexity of the Heapsort algorithm?
 - (a) $\mathcal{O}(n \log^2 n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\mathcal{O}(n \log n)$
 - (d) $\mathcal{O}(n^2 \log n)$
8. What is the maximum number of counting inversions possible in a given sequence of n numbers?
 - (a) n
 - (b) $n(n+1)/2$
 - (c) n^2
 - (d) $n(n-1)/2$
9. Banks often record transactions on an account in order of the times of the transactions, but many people like to receive their bank statements with checks listed in order by check number. People usually write checks in order by check number, and merchants usually cash them with reasonable dispatch. The problem now is to convert time-of-transaction ordering to check-number ordering. Which sorting is best suited for this purpose?
 - (a) Quicksort
 - (b) Heapsort
 - (c) Counting Sort
 - (d) Insertion Sort
10. There are two functions f and g defined by $f(n) = 2^{2n}$ and $g(n) = 2^n$. Pick the correct answer(s) from the following:
 - (a) $f(n) = \Omega(g(n))$
 - (b) $f(n) = \mathcal{O}(g(n))$
 - (c) $f(n) = \Theta(g(n))$
 - (d) None of the above

11. Donald Knuth conducts a quiz for his DAA students of strength 100. Quiz is for total marks of 15. He has the list of marks together with the names of the students listed in alphabetical order. He would like to do a sorting on the basis of the marks scored. Which sorting is best suited for this purpose?
 - (a) Insertion Sort
 - (b) Counting Sort
 - (c) Quicksort
 - (d) Heapsort
12. An Airline stores the PNR of its passengers as a five letter English alphabet. It has already stored this information in its database. Now it intends to sort it with respect to the PNR. What sorting method would be ideal for this situation?
 - (a) Bucket Sort
 - (b) Radix Sort
 - (c) Quicksort
 - (d) Counting Sort

13. Consider the following recurrence equation:

$$T(n) = 2T(n - 1) + 1$$

What is $T(n)$?

- (a) 2^{2^n}
 - (b) 2^n
 - (c) n^2
 - (d) $\log n$
14. When RANDOMIZED-QUICKSORT runs, how many calls are made to the random number generator RANDOM in the best case?
 - (a) $\Theta(n \log n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\Theta(\log n)$
 - (d) $\Theta(n)$
15. Which is asymptotically larger: $f(n) = \log(\log^* n)$ or $g(n) = \log^*(\log n)$?
 - (a) Both are growing almost at the same pace
 - (b) $f(n)$
 - (c) Both the functions are not well-defined
 - (d) $g(n)$

16. Consider the following recurrence equation:

$$T(n) = 2T((n/2) + 17) + n$$

What is $T(n)$?

- (a) n^2
 - (b) $\log^2 n$
 - (c) $\mathcal{O}(n \log n)$
 - (d) $\log n$
17. Multiplication algorithm that we had studied for multiplying two n -bit numbers is called as Karatsuba's algorithm. Which of the following statement(s) is (are) NOT true about Karatsuba's algorithm?
- (a) It can only be applied to two integers of same size
 - (b) It can be applied to all integers
 - (c) It can be only applied to integers of size n where $n = 2^k$
 - (d) It can be only applied to integers of same size and the size is of the form $n = 2^k$
18. Suppose we are sorting an array of eight integers using quicksort, and we have just finished the first partitioning with the array looking like this:

2, 5, 1, 7, 9, 10, 12, 11

Which statement(s) is (are) correct and how?

- (a) The pivot could be 10
 - (b) The pivot could be 7
 - (c) The pivot could be 9
 - (d) This situation cannot arise
19. Which of the following sorting algorithms are stable: insertion sort, merge sort, heapsort, and quicksort?
- (a) Only insertion sort is stable
 - (b) insertion sort and merge sort are both stable but not others
 - (c) insertion sort and heapsort are both stable but not others
 - (d) insertion sort and quicksort are both stable but not others
20. What is the best case complexity of heapsort algorithm?
- (a) $\mathcal{O}(n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\mathcal{O}(n \log n)$
 - (d) $\mathcal{O}(\log n)$

Answer Key for Exam A

1. Which is the correct order of the following algorithms with respect to their time complexity in the best case ?
 - (a) Merge sort > selection sort > quick sort > insertion sort
 - (b) Merge sort > Quick sort > selection sort > insertion sort
 - (c) Merge sort > Quick sort > Insertion sort > selection sort
 - (d) insertion sort < Quick sort < Merge sort < selection sort
2. What is the worst-case running time complexity of bucket sort?
 - (a) $\mathcal{O}(n \log n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\mathcal{O}(n^2 \log n)$
 - (d) $\mathcal{O}(n)$
3. There are two functions f and g defined by $f(n) = 2^{n+1}$ and $g(n) = 2^n$. Pick the correct answer(s) from the following:
 - (a) $f(n) = \Omega(g(n))$
 - (b) $f(n) = \mathcal{O}(g(n))$
 - (c) $f(n) = \Theta(g(n))$
 - (d) None of the above
4. What is the maximum number of nodes at height h in any n -element heap?
 - (a) $n/2^h$
 - (b) $n/2^{h-1}$
 - (c) $n/2^{h+1}$
 - (d) $n/2^{2^h}$
5. Strassen's multiplication algorithm works for two square matrices of size $n \times n$. How about multiplying two non-square matrices? Pick the correct choice in the following:
 - (a) Make it as square matrices by padding with extra zeroes and then apply Strassen's method
 - (b) For non-square matrices it won't work
 - (c) Get the maximum square matrix out of the non-square matrix apply Strassen on to that. For the reminder apply the normal matrix multiplication
 - (d) None of the above
6. When RANDOMIZED-QUICKSORT runs, how many calls are made to the random number generator RANDOM in the worst case?
 - (a) $\mathcal{O}(n^2)$
 - (b) $\Theta(\log n)$
 - (c) $\Theta(n)$
 - (d) $\Theta(n \log n)$

7. In Heapsort algorithm if instead of using BUILD-MAX-HEAP algorithm we use MAX-HEAP-INSERT algorithm to build the heap what will be the resulting complexity of the Heapsort algorithm?
- ☒ (a) $\mathcal{O}(n \log^2 n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\mathcal{O}(n \log n)$
 - (d) $\mathcal{O}(n^2 \log n)$
8. What is the maximum number of counting inversions possible in a given sequence of n numbers?
- (a) n
 - (b) $n(n+1)/2$
 - (c) n^2
 - ☒ (d) $n(n-1)/2$
9. Banks often record transactions on an account in order of the times of the transactions, but many people like to receive their bank statements with checks listed in order by check number. People usually write checks in order by check number, and merchants usually cash them with reasonable dispatch. The problem now is to convert time-of-transaction ordering to check-number ordering. Which sorting is best suited for this purpose?
- (a) Quicksort
 - (b) Heapsort
 - (c) Counting Sort
 - ☒ (d) Insertion Sort
10. There are two functions f and g defined by $f(n) = 2^{2n}$ and $g(n) = 2^n$. Pick the correct answer(s) from the following:
- ☒ (a) $f(n) = \Omega(g(n))$
 - (b) $f(n) = \mathcal{O}(g(n))$
 - (c) $f(n) = \Theta(g(n))$
 - (d) None of the above
11. Donald Knuth conducts a quiz for his DAA students of strength 100. Quiz is for total marks of 15. He has the list of marks together with the names of the students listed in alphabetical order. He would like to do a sorting on the basis of the marks scored. Which sorting is best suited for this purpose?
- (a) Insertion Sort
 - ☒ (b) Counting Sort
 - (c) Quicksort
 - (d) Heapsort
12. An Airline stores the PNR of its passengers as a five letter English alphabet. It has already stored this information in its database. Now it intends to sort it with respect to the PNR. What sorting method would be ideal for this situation?
- (a) Bucket Sort
 - ☒ (b) Radix Sort
 - (c) Quicksort
 - (d) Counting Sort

13. Consider the following recurrence equation:

$$T(n) = 2T(n - 1) + 1$$

What is $T(n)$?

- (a) 2^{2^n}
 - ☒ (b) 2^n
 - (c) n^2
 - (d) $\log n$
14. When RANDOMIZED-QUICKSORT runs, how many calls are made to the random number generator RANDOM in the best case?
- (a) $\Theta(n \log n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\Theta(\log n)$
 - ☒ (d) $\Theta(n)$
15. Which is asymptotically larger: $f(n) = \log(\log^* n)$ or $g(n) = \log^*(\log n)$?
- (a) Both are growing almost at the same pace
 - (b) $f(n)$
 - (c) Both the functions are not well-defined
 - ☒ (d) $g(n)$

16. Consider the following recurrence equation:

$$T(n) = 2T((n/2) + 17) + n$$

What is $T(n)$?

- (a) n^2
 - (b) $\log^2 n$
 - ☒ (c) $\mathcal{O}(n \log n)$
 - (d) $\log n$
17. Multiplication algorithm that we had studied for multiplying two n -bit numbers is called as Karatsuba's algorithm. Which of the following statement(s) is (are) NOT true about Karatsuba's algorithm?
- ☒ (a) It can only be applied to two integers of same size
 - (b) It can be applied to all integers
 - ☒ (c) It can be only applied to integers of size n where $n = 2^k$
 - ☒ (d) It can be only applied to integers of same size and the size is of the form $n = 2^k$

18. Suppose we are sorting an array of eight integers using quicksort, and we have just finished the first partitioning with the array looking like this:

2, 5, 1, 7, 9, 10, 12, 11

Which statement(s) is (are) correct and how?

- ☐ (a) The pivot could be 10
 - ☐ (b) The pivot could be 7
 - ☐ (c) The pivot could be 9
 - ☐ (d) This situation cannot arise
19. Which of the following sorting algorithms are stable: insertion sort, merge sort, heapsort, and quicksort?
- ☐ (a) Only insertion sort is stable
 - ☐ (b) insertion sort and merge sort are both stable but not others
 - ☐ (c) insertion sort and heapsort are both stable but not others
 - ☐ (d) insertion sort and quicksort are both stable but not others
20. What is the best case complexity of heapsort algorithm?
- ☐ (a) $\mathcal{O}(n)$
 - ☐ (b) $\mathcal{O}(n^2)$
 - ☐ (c) $\mathcal{O}(n \log n)$
 - ☐ (d) $\mathcal{O}(\log n)$

The LNM Institute of Information Technology, Jaipur

CS325 DESIGN AND ANALYSIS OF ALGORITHM

Quiz-I

Tuesday, Feb 13, 2018

Time: 45 Minutes

Maximum Marks: 40

Name: _____ Roll No: _____

Read the Instructions Carefully:

All are objective questions with 4 choices. There may be more than one correct answers. Each question carry three marks. You need to select all the correct answers to get full marks. For example, if a question has 2 correct choices and you did only one correctly you will get 1 mark. If out of your choices even one choice is wrong then there won't be any marks given (even if there are correct choices that you have made). So be careful when you are finding and marking the correct choices. **Encircle all the correct answer/s. Any other marking will be considered as invalid.** Do not write anything in the answer sheet except the answer. No justification is required. **There is no negative marking for wrong answer/s.**

1. Consider the following recurrence equation:

$$T(n) = 2T(n-1) + 1$$

What is $T(n)$?

- (a) 2^{2^n}
 - (b) 2^n
 - (c) n^2
 - (d) $\log n$
2. There are two functions f and g defined by $f(n) = 2^{n+1}$ and $g(n) = 2^n$. Pick the correct answer(s) from the following:
- (a) $f(n) = \Omega(g(n))$
 - (b) $f(n) = \mathcal{O}(g(n))$
 - (c) $f(n) = \Theta(g(n))$
 - (d) None of the above
3. What is the maximum number of nodes at height h in any n -element heap?
- (a) $n/2^h$
 - (b) $n/2^{h-1}$
 - (c) $n/2^{h+1}$
 - (d) $n/2^{2^h}$
4. An Airline stores the PNR of its passengers as a five letter English alphabet. It has already stored this information in its database. Now it intends to sort it with respect to the PNR. What sorting method would be ideal for this situation?
- (a) Bucket Sort
 - (b) Radix Sort
 - (c) Quicksort
 - (d) Counting Sort

5. Which of the following sorting algorithms are stable: insertion sort, merge sort, heapsort, and quicksort?
 - (a) Only insertion sort is stable
 - (b) insertion sort and merge sort are both stable but not others
 - (c) insertion sort and heapsort are both stable but not others
 - (d) insertion sort and quicksort are both stable but not others
6. Strassen's multiplication algorithm works for two square matrices of size $n \times n$. How about multiplying two non-square matrices? Pick the correct choice in the following:
 - (a) Make it as square matrices by padding with extra zeroes and then apply Strassen's method
 - (b) For non-square matrices it won't work
 - (c) Get the maximum square matrix out of the non-square matrix apply Strassen on to that. For the remainder apply the normal matrix multiplication
 - (d) None of the above
7. What is the maximum number of counting inversions possible in a given sequence of n numbers?
 - (a) n
 - (b) $n(n + 1)/2$
 - (c) n^2
 - (d) $n(n - 1)/2$
8. Donald Knuth conducts a quiz for his DAA students of strength 100. Quiz is for total marks of 15. He has the list of marks together with the names of the students listed in alphabetical order. He would like to do a sorting on the basis of the marks scored. Which sorting is best suited for this purpose?
 - (a) Insertion Sort
 - (b) Counting Sort
 - (c) Quicksort
 - (d) Heapsort
9. Suppose we are sorting an array of eight integers using quicksort, and we have just finished the first partitioning with the array looking like this:

2, 5, 1, 7, 9, 10, 12, 11

Which statement(s) is (are) correct and how?

- (a) The pivot could be 10
- (b) The pivot could be 7
- (c) The pivot could be 9
- (d) This situation cannot arise

10. Banks often record transactions on an account in order of the times of the transactions, but many people like to receive their bank statements with checks listed in order by check number. People usually write checks in order by check number, and merchants usually cash them with reasonable dispatch. The problem now is to convert time-of-transaction ordering to check-number ordering. Which sorting is best suited for this purpose?
 - (a) Quicksort
 - (b) Heapsort
 - (c) Counting Sort
 - (d) Insertion Sort
11. There are two functions f and g defined by $f(n) = 2^{2n}$ and $g(n) = 2^n$. Pick the correct answer(s) from the following:
 - (a) $f(n) = \Omega(g(n))$
 - (b) $f(n) = \mathcal{O}(g(n))$
 - (c) $f(n) = \Theta(g(n))$
 - (d) None of the above
12. Consider the following recurrence equation:

$$T(n) = 2T((n/2) + 17) + n$$

What is $T(n)$?

- (a) n^2
 - (b) $\log^2 n$
 - (c) $\mathcal{O}(n \log n)$
 - (d) $\log n$
13. When RANDOMIZED-QUICKSORT runs, how many calls are made to the random number generator RANDOM in the worst case?
 - (a) $\mathcal{O}(n^2)$
 - (b) $\Theta(\log n)$
 - (c) $\Theta(n)$
 - (d) $\Theta(n \log n)$
14. Multiplication algorithm that we had studied for multiplying two n -bit numbers is called as Karatsuba's algorithm. Which of the following statement(s) is (are) NOT true about Karatsuba's algorithm?
 - (a) It can only be applied to two integers of same size
 - (b) It can be applied to all integers
 - (c) It can be only applied to integers of size n where $n = 2^k$
 - (d) It can be only applied to integers of same size and the size is of the form $n = 2^k$
15. When RANDOMIZED-QUICKSORT runs, how many calls are made to the random number generator RANDOM in the best case?
 - (a) $\Theta(n \log n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\Theta(\log n)$
 - (d) $\Theta(n)$

16. What is the best case complexity of heapsort algorithm?
- (a) $\mathcal{O}(n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\mathcal{O}(n \log n)$
 - (d) $\mathcal{O}(\log n)$
17. Which is the correct order of the following algorithms with respect to their time complexity in the best case ?
- (a) Merge sort > selection sort > quick sort > insertion sort
 - (b) Merge sort > Quick sort > selection sort > insertion sort
 - (c) Merge sort > Quick sort > Insertion sort > selection sort
 - (d) insertion sort < Quick sort < Merge sort < selection sort
18. In Heapsort algorithm if instead of using BUILD-MAX-HEAP algorithm we use MAX-HEAP-INSERT algorithm to build the heap what will be the resulting complexity of the Heapsort algorithm?
- (a) $\mathcal{O}(n \log^2 n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\mathcal{O}(n \log n)$
 - (d) $\mathcal{O}(n^2 \log n)$
19. Which is asymptotically larger: $f(n) = \log(\log^* n)$ or $g(n) = \log^*(\log n)$?
- (a) Both are growing almost at the same pace
 - (b) $f(n)$
 - (c) Both the functions are not well-defined
 - (d) $g(n)$
20. What is the worst-case running time complexity of bucket sort?
- (a) $\mathcal{O}(n \log n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\mathcal{O}(n^2 \log n)$
 - (d) $\mathcal{O}(n)$

Answer Key for Exam B

1. Consider the following recurrence equation:

$$T(n) = 2T(n-1) + 1$$

What is $T(n)$?

- (a) 2^{2^n}
 - (b) 2^n
 - (c) n^2
 - (d) $\log n$
2. There are two functions f and g defined by $f(n) = 2^{n+1}$ and $g(n) = 2^n$. Pick the correct answer(s) from the following:
- (a) $f(n) = \Omega(g(n))$
 - (b) $f(n) = \mathcal{O}(g(n))$
 - (c) $f(n) = \Theta(g(n))$
 - (d) None of the above
3. What is the maximum number of nodes at height h in any n -element heap?
- (a) $n/2^h$
 - (b) $n/2^{h-1}$
 - (c) $n/2^{h+1}$
 - (d) $n/2^{2^h}$
4. An Airline stores the PNR of its passengers as a five letter English alphabet. It has already stored this information in its database. Now it intends to sort it with respect to the PNR. What sorting method would be ideal for this situation?
- (a) Bucket Sort
 - (b) Radix Sort
 - (c) Quicksort
 - (d) Counting Sort
5. Which of the following sorting algorithms are stable: insertion sort, merge sort, heapsort, and quicksort?
- (a) Only insertion sort is stable
 - (b) insertion sort and merge sort are both stable but not others
 - (c) insertion sort and heapsort are both stable but not others
 - (d) insertion sort and quicksort are both stable but not others

6. Strassen's multiplication algorithm works for two square matrices of size $n \times n$. How about multiplying two non-square matrices? Pick the correct choice in the following:
- ☐ (a) Make it as square matrices by padding with extra zeroes and then apply Strassen's method
 - ☐ (b) For non-square matrices it won't work
 - ☒ (c) Get the maximum square matrix out of the non-square matrix apply Strassen on to that. For the remainder apply the normal matrix multiplication
 - ☐ (d) None of the above
7. What is the maximum number of counting inversions possible in a given sequence of n numbers?
- ☐ (a) n
 - ☐ (b) $n(n+1)/2$
 - ☐ (c) n^2
 - ☒ (d) $n(n-1)/2$
8. Donald Knuth conducts a quiz for his DAA students of strength 100. Quiz is for total marks of 15. He has the list of marks together with the names of the students listed in alphabetical order. He would like to do a sorting on the basis of the marks scored. Which sorting is best suited for this purpose?
- ☐ (a) Insertion Sort
 - ☒ (b) Counting Sort
 - ☐ (c) Quicksort
 - ☐ (d) Heapsort
9. Suppose we are sorting an array of eight integers using quicksort, and we have just finished the first partitioning with the array looking like this:

2, 5, 1, 7, 9, 10, 12, 11

Which statement(s) is (are) correct and how?

- ☒ (a) The pivot could be 10
 - ☒ (b) The pivot could be 7
 - ☒ (c) The pivot could be 9
 - ☐ (d) This situation cannot arise
10. Banks often record transactions on an account in order of the times of the transactions, but many people like to receive their bank statements with checks listed in order by check number. People usually write checks in order by check number, and merchants usually cash them with reasonable dispatch. The problem now is to convert time-of-transaction ordering to check-number ordering. Which sorting is best suited for this purpose?
- ☐ (a) Quicksort
 - ☐ (b) Heapsort
 - ☐ (c) Counting Sort
 - ☒ (d) Insertion Sort

11. There are two functions f and g defined by $f(n) = 2^{2n}$ and $g(n) = 2^n$. Pick the correct answer(s) from the following:

- ☒ (a) $f(n) = \Omega(g(n))$
- (b) $f(n) = \mathcal{O}(g(n))$
- (c) $f(n) = \Theta(g(n))$
- (d) None of the above

12. Consider the following recurrence equation:

$$T(n) = 2T((n/2) + 17) + n$$

What is $T(n)$?

- (a) n^2
- (b) $\log^2 n$
- ☒ (c) $\mathcal{O}(n \log n)$
- (d) $\log n$

13. When RANDOMIZED-QUICKSORT runs, how many calls are made to the random number generator RANDOM in the worst case?

- (a) $\mathcal{O}(n^2)$
- (b) $\Theta(\log n)$
- ☒ (c) $\Theta(n)$
- (d) $\Theta(n \log n)$

14. Multiplication algorithm that we had studied for multiplying two n -bit numbers is called as Karatsuba's algorithm. Which of the following statement(s) is (are) NOT true about Karatsuba's algorithm?

- ☒ (a) It can only be applied to two integers of same size
- (b) It can be applied to all integers
- ☒ (c) It can be only applied to integers of size n where $n = 2^k$
- ☒ (d) It can be only applied to integers of same size and the size is of the form $n = 2^k$

15. When RANDOMIZED-QUICKSORT runs, how many calls are made to the random number generator RANDOM in the best case?

- (a) $\Theta(n \log n)$
- (b) $\mathcal{O}(n^2)$
- (c) $\Theta(\log n)$
- ☒ (d) $\Theta(n)$

16. What is the best case complexity of heapsort algorithm?

- (a) $\mathcal{O}(n)$
- (b) $\mathcal{O}(n^2)$
- ☒ (c) $\mathcal{O}(n \log n)$
- (d) $\mathcal{O}(\log n)$

17. Which is the correct order of the following algorithms with respect to their time complexity in the best case ?
- (a) Merge sort > selection sort > quick sort > insertion sort
 - (b) Merge sort > Quick sort > selection sort > insertion sort
 - (c) Merge sort > Quick sort > Insertion sort > selection sort
 - ☒ (d) insertion sort < Quick sort < Merge sort < selection sort
18. In Heapsort algorithm if instead of using BUILD-MAX-HEAP algorithm we use MAX-HEAP-INSERT algorithm to build the heap what will be the resulting complexity of the Heapsort algorithm?
- ☒ (a) $\mathcal{O}(n \log^2 n)$
 - (b) $\mathcal{O}(n^2)$
 - (c) $\mathcal{O}(n \log n)$
 - (d) $\mathcal{O}(n^2 \log n)$
19. Which is asymptotically larger: $f(n) = \log(\log^* n)$ or $g(n) = \log^*(\log n)$?
- (a) Both are growing almost at the same pace
 - (b) $f(n)$
 - (c) Both the functions are not well-defined
 - ☒ (d) $g(n)$
20. What is the worst-case running time complexity of bucket sort?
- (a) $\mathcal{O}(n \log n)$
 - ☒ (b) $\mathcal{O}(n^2)$
 - (c) $\mathcal{O}(n^2 \log n)$
 - (d) $\mathcal{O}(n)$