

# Core Task Progress Notes

Team: \_\_\_\_\_

November 13, 2025

## Sanity-Check Run

- **Command.** `OMP_NUM_THREADS=1 python3 pico-llm.py --tinystories_weight 0.0 --input_files 3seqs.txt --block_size 32 --max_steps_per_epoch 1 --kgram_k 2 --embed_size 64 --device_id cpu`
- **Environment tweaks.** Installed the missing `tiktoken` package and pinned OpenMP threads to avoid shared-memory warnings in the sandboxed environment.
- **Outcome.** Training loop completed three abbreviated epochs for the LSTM baseline on `3seqs.txt`, producing loss values ( $10.82 \rightarrow 10.80 \rightarrow 10.77$ ) and sample generations at greedy,  $p = 0.95$ , and  $p = 1.0$  settings. This confirms data loading, tokenization, model forward/backward, and text generation pathways function end-to-end on CPU-only hardware.

## Key Observations

- The current nucleus sampling placeholder yields identical outputs across different  $p$  values, reinforcing the need to implement true top- $p$  sampling before the presentation.
- LSTM outputs trained on the minimal dataset remain nonsensical, which is expected given the toy corpus and tiny training budget; future sanity checks on TinyStories or richer data should improve qualitative quality.
- Installing dependencies on the target machine (e.g., `tiktoken`) should be part of setup instructions to prevent runtime failures during the live demo.

## Sample Interview Questions & Answers

1. **What did you verify in the sanity-check run, and why did you choose the custom dataset?**

We confirmed that the default training loop, tokenizer, and generation routines run without crashing on CPU. The `3seqs.txt` data ships with the repo, so it avoids the network dependency of downloading TinyStories and shortens iteration time.

2. **Why did the generated samples look incoherent, and is that a concern?**

The dataset contains synthetic numeric sequences and we limited training to one gradient step per epoch. With minimal data and budget, the LSTM cannot learn meaningful structure; the purpose of this run was functionality, not quality. Larger datasets and more steps will address coherence.

3. **You pinned OMP\_NUM\_THREADS to 1—will that hurt performance later?**

For this quick CPU smoke test it eliminated shared-memory errors. On a full training environment we can remove or raise the cap once OpenMP shared-memory permissions are available, restoring multithreaded BLAS performance.

4. **What additional checks will you run before the presentation?**

We plan to repeat the sanity check on TinyStories once Transformer and k-gram models are implemented, capture training curves for the required figures, and verify qualitative outputs under true top- $p$  sampling to demonstrate improved diversity.

## KGramMLPSeqModel Design Options

1. **Baseline One-Hot MLP.**

*Structure:* Flatten the  $k$  one-hot context vectors into a  $(k \times |V|)$  input and feed through stacked Linear  $\rightarrow$  SiLU blocks ending in a Linear layer to logits.

*Pros:* Direct translation of the docstring; simplest to reason about; no extra embeddings needed.

*Cons:* Extremely high input dimensionality (tens of thousands) makes each forward/backward pass slow and memory hungry; scales poorly with larger vocab or  $k$ .

*Performance expectations:* Works for tiny vocab toy data but may be impractical for full TinyStories unless chunking is aggressive.

2. **Token Embedding + MLP (Shared Projection).**

*Structure:* Map each context token through a learned embedding matrix ( $|V| \rightarrow d$ ), concatenate the  $k$  embeddings (size  $k \times d$ ), then apply a compact MLP that projects back to vocabulary logits.

*Pros:* Input dimensionality drops dramatically; parameters scale with  $d$  instead of  $|V|$ ; embeddings can be reused or initialized from LSTM/Transformer values.

*Cons:* Slightly more complex; must ensure embeddings are trained jointly; loses the “pure” one-hot formulation.

*Performance expectations:* Much faster and fits GPU memory; still expressive enough for k-gram patterns when  $d$  is moderate.

3. **Embedding + Depthwise 1D Convolution Hybrid.**

*Structure:* Embed tokens as above, stack along temporal dimension, then use 1D convolution(s) over the  $k$  context positions followed by a projection to logits.

*Pros:* Weight sharing across positions reduces parameters; convolutional kernels capture local order efficiently; fits well with chunked inference.

*Cons:* Deviates from strict MLP requirement; requires reshaping logic in the provided forward loop; debugging convolutional behavior may be harder.

*Performance expectations:* Efficient on GPU and handles longer  $k$  gracefully; offers inductive bias similar to CNNs for n-gram features.

## Action Plan: Implementing KGramMLPSeqModel

1. **Select architecture.** Choose between one-hot MLP, embedding-based MLP, or convolution hybrid based on desired trade-offs.

2. **Define network layers.** Instantiate embedding (if needed), hidden Linear layers with activation, dropout if desired, and final Linear layer to  $|V|$  logits.

3. **Integrate into forward loop.** Replace the `self.net = None` stub and ensure tensors are moved to the correct device, handling chunked processing without altering the provided outer loops.
4. **Add safety checks.** Validate input shapes, raise informative errors if `self.net` is misconfigured, and confirm gradients flow through embeddings.
5. **Test in notebook.** Run the reduced configuration from the sanity check, compare loss trajectories, and profile runtime to confirm expected improvements.

## Forward Pass Rationale

- **Responsibility.** The `forward()` method ingests a tensor of token IDs with shape (sequence length, batch size), walks through the sequence in micro-batches, extracts the preceding  $k$  tokens for each position, pads when history is short, one-hot encodes that context, and ships the flattened vector through the chosen sub-network to obtain logits.
- **Chunking.** Iterating in blocks of size `chunk_size` lowers peak memory usage, making the naive Python loop feasible even for long sequences.
- **Why it matters.** Without this logic, the  $k$ -gram model would never transform context into next-token distributions—no logits means no loss, no gradients, and no generation. This function therefore defines the core behavior we train and evaluate.
- **Postconditions.** Concatenating the outputs from each chunk restores the expected (seq\_len, batch,  $|V|$ ) tensor that downstream code (loss, sampling) depends on.

## Action Plan: Implementing Nucleus Sampling

1. **Normalize logits.** Convert logits to probabilities via `softmax` to obtain a stable distribution over the vocabulary.
2. **Rank tokens.** Sort probabilities in descending order while keeping token indices to identify the highest-mass prefix.
3. **Cumulative cutoff.** Compute the running probability mass and retain the smallest slice whose sum exceeds the user-specified  $p$  threshold.
4. **Renormalize.** Scale the retained probabilities so they sum to one, ensuring a valid categorical distribution.
5. **Sample token.** Draw the next token from the truncated distribution (fall back to the full distribution if  $p$  never triggers).
6. **Surface API.** Expose the sampler through `generate_text` so notebook experiments can vary  $p$  without extra wiring.

## Nucleus Sampling Observations

- **Setup.** Used the quick LSTM sanity-check run (one optimization step on the synthetic corpus) and generated 20 new tokens from the prompt “Once upon a” with different top- $p$  thresholds.
- **Greedy ( $p = \text{None}$ ).** *“Once upon a office sofa Iz ACA King investigate likeness ancestorRegarding speaker dive Dum wavesMagikarp Gleaming Authorization Asset hamHor Clinton”*
- **Top- $p = 0.8$ .** *“Once upon a retroald Continuous Istanbul ’/ Issa kids recourse fa Gly EMP (\$) Dig ProxybpJu ceilings RailwayiversityIto”*
- **Top- $p = 0.95$ .** *“Once upon a Saulfocus340headed Dietaryindividual ideologicallyCW intendederen contributMA tours ML Contribut Nottingham European CHRIST Readers dere”*
- **Top- $p = 1.0$ .** *“Once upon a Jordan speciesotomy started Cousoccupied Shootifestyle DRMBoot Colorsinav Sit Actionuren dunk now 29 rarity Nguyen”*
- **Takeaway.** Higher  $p$  values admit a larger tail of low-probability tokens, yielding more diverse (but noisier) completions. Greedy decoding sticks to the modal choice and repeats motifs, while  $p = 1.0$  allows maximum randomness.

## Performance Comparison Strategy

- **Feasibility.** It is practical to compare all three architectures visually: log training loss and wall-clock time per step for each variant while running identical hyperparameters, then plot the metrics using `matplotlib` inside the standalone notebook. GPU execution is optional but accelerates experimentation.
- **Instrumentation plan.**
  - Wrap the training loop to record (loss, step, elapsed seconds) tuples for each KGramMLPSeqModel option via separate helper functions.
  - Store results in a shared list or `pandas` DataFrame, noting architecture label and configuration (e.g., embedding dimension).
  - After each run, generate line plots for loss vs. step and bar charts for tokens/sec to highlight efficiency differences.
- **Caveats.** Full TinyStories runs may be slow in Colab CPU mode; expect to subsample the dataset or limit training steps for a fair yet tractable comparison. Ensure random seeds are fixed for reproducibility.

## Empirical Results (Synthetic Corpus)

- **Setup.** CPU only;  $k=2$ , embedding size 64, two inner MLP layers, Adam with learning rate  $1 \times 10^{-3}$ , 20 mini-batches per variant (batch size 32) over the `3seqs.txt` dataset.
- **Metrics.**

- One-hot MLP: average loss *approx*10.63, throughput *approx*17.6 tokens/s, runtime *approx*1161 seconds.
  - Embedding MLP: average loss *approx*9.49, throughput *approx*42.3 tokens/s, runtime *approx*485 seconds.
  - Conv Hybrid: average loss *approx*10.23, throughput *approx*32.3 tokens/s, runtime *approx*634 seconds.
- **Decision.** The embedding-based MLP achieves the best trade-off (lowest loss and highest throughput), so we will proceed with this architecture for the full implementation and upcoming experiments.

## TransformerModel Implementation Outline

### 1. Surface Configuration.

- Expose `d_model`, `n_heads`, `n_blocks` (capped at ten), feed-forward width multiplier, dropout rates, and rotary-frequency toggles so we can sweep sizes without rewriting layers.
- Share a `transformer_variant` flag to map onto the presets listed below (GPT2, GPT-oss, Llama3-lite, minGPT).

### 2. Token and Positional Embeddings.

- Reuse the shared token embedding matrix for the output projection (weight tying).
- Implement learned positional embeddings by default; include a rotary positional embedding helper so GPT-oss and Llama-style presets can opt in.

### 3. RMSNorm and Block Skeleton.

- Finish the RMSNorm stub: compute the mean square per hidden vector, scale by `weight`, and broadcast the epsilon guard.
- Each Transformer block follows Pre-Norm layout: `RMSNorm`  $\rightarrow$  Multi-Head Attention + residual  $\rightarrow$  `RMSNorm`  $\rightarrow$  Feed-Forward + residual.

### 4. Multi-Head Attention.

- Compute query, key, value tensors via shared Linear projections; reshape to `(seq, batch, heads, head_dim)`.
- Apply rotary or additive position bias if enabled, mask with causal upper-triangular mask, scale by  $\frac{1}{\sqrt{\text{head\_dim}}}$ , and reuse the cache-friendly loop already provided in the stub comments.

### 5. Feed-Forward Network.

- Default to GELU two-layer MLP with width multiplier 4 $\times$ ; allow toggling to SwiGLU for the Llama3-lite preset.

- Insert dropout hooks that become no-ops during evaluation to match the starter code style.

## 6. Forward Pass and Output Head.

- Accept input as `(seq, batch)`, emit logits `(seq, batch, vocab)`.
- Tie the embedding weights for the output linear layer unless a variant explicitly disables sharing.

## 7. Initialization and Guard Rails.

- Adopt variant-specific initializers (GPT2 uses scaled normal, Llama-style uses Xavier uniform).
- Assert `n_heads` divides `d_model` and `n_blocks`  $\leq 10$  to keep runs within the assignment budget.

## 8. Testing Hooks.

- Add unit checks that random inputs produce finite logits and that the KV-cache path matches the dense attention for small sequences.
- Benchmark the synthetic dataset with three quick batches to record loss and throughput per variant.

# Transformer Variants and Feasibility

### • minGPT-inspired (Feasible).

- Architecture: `d_model` 384, `n_heads` 6, `n_blocks` 6, GELU feed-forward width 1536, learned positional embeddings, tied output weights.
- Implementation status: fully achievable with the outline above; requires no external dependencies.
- Metrics plan: reuse the synthetic benchmark harness (20 batches, batch size 32) and report loss/tokens-per-second next to the KGram results.

### • GPT2-small style (Feasible with scaling).

- Architecture: adapt GPT-2 small to assignment limits by using `d_model` 768, `n_heads` 12, `n_blocks` 8 (reduced from 12 to stay  $\leq 10$ ), learned absolute positions, MLP width 3072, GELU activation, tied output head.
- Implementation status: feasible once RMSNorm is replaced with LayerNorm for this preset or we supply a LayerNorm toggle; compute cost is higher but manageable on the synthetic corpus.
- Metrics plan: same synthetic harness; for TinyStories we will downscale batch size to keep runtimes under the cap.

### • GPT-oss (Feasible, requires rotary).

- Architecture: `d_model` 512, `n_heads` 8, `n_blocks` 8, rotary positional embeddings, SwiGLU feed-forward width 2048, untied output head per reference design.

- Implementation status: feasible after we add a light-weight rotary embedding helper; no external kernels needed.
  - Metrics plan: record synthetic benchmark figures and optionally a short TinyStories run (max steps per epoch = 1) to stay within time limits.
- **Llama3-lite (Partially feasible).**
    - Architecture: distilled from the published spec with `d_model` 1024, `n_heads` 16, `n_blocks` 8, rotary positions, SwiGLU feed-forward width 8192, RMSNorm everywhere, untied output head.
    - Implementation status: core building blocks (rotary, SwiGLU, RMSNorm, attention) fit our codebase; full Llama3 features (grouped-query attention, sliding window) exceed current scope. We propose implementing a simplified variant without the extra attention optimizations.
    - Metrics plan: we can capture synthetic benchmark numbers; collecting full TinyStories metrics would demand GPU time beyond the assignment budget, so we will document only CPU synthetic runs unless instructed otherwise.
- **Performance Collection Summary.**
    - All small-batch synthetic metrics are attainable once the Transformer is implemented.
    - Full-scale TinyStories training for GPT2-small or Llama3-lite is out of scope without extensive runtime; we will note this limitation in results to keep expectations clear.
- **Recorded Metrics (Synthetic Corpus, 3 batches, batch size 16).**
    - GPT-oss: average loss 11.05, throughput 11.94 tokens/s, elapsed 1.26 s.
    - Benchmarks are gated behind `--collect_transformer_metrics`; the number above matches the `RECORDED_TRANSFORMER_BENCHMARK` entry in `pico-llm.py`.