



DB2 for z/OS Best Practices

Log Activity and Miscellaneous

John Campbell
Distinguished Engineer
DB2 for z/OS Development

CAMPBELJ@uk.ibm.com





Disclaimer/Trademarks

THE INFORMATION CONTAINED IN THIS DOCUMENT HAS NOT BEEN SUBMITTED TO ANY FORMAL IBM TEST AND IS DISTRIBUTED AS IS. THE USE OF THIS INFORMATION OR THE IMPLEMENTATION OF ANY OF THESE TECHNIQUES IS A CUSTOMER RESPONSIBILITY AND DEPENDS ON THE CUSTOMER'S ABILITY TO EVALUATE AND INTEGRATE THEM INTO THE CUSTOMER'S OPERATIONAL ENVIRONMENT. WHILE IBM MAY HAVE REVIEWED EACH ITEM FOR ACCURACY IN A SPECIFIC SITUATION, THERE IS NO GUARANTEE THAT THE SAME OR SIMILAR RESULTS WILL BE OBTAINED ELSEWHERE. ANYONE ATTEMPTING TO ADAPT THESE TECHNIQUES TO THEIR OWN ENVIRONMENTS DO SO AT THEIR OWN RISK.

ANY PERFORMANCE DATA CONTAINED IN THIS DOCUMENT WERE DETERMINED IN VARIOUS CONTROLLED LABORATORY ENVIRONMENTS AND ARE FOR REFERENCE PURPOSES ONLY. CUSTOMERS SHOULD NOT ADAPT THESE PERFORMANCE NUMBERS TO THEIR OWN ENVIRONMENTS AS SYSTEM PERFORMANCE STANDARDS. THE RESULTS THAT MAY BE OBTAINED IN OTHER OPERATING ENVIRONMENTS MAY VARY SIGNIFICANTLY. USERS OF THIS DOCUMENT SHOULD VERIFY THE APPLICABLE DATA FOR THEIR SPECIFIC ENVIRONMENT.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml



Writing to the Active Log

- When does DB2 write to the active log?
 - UR-related events
 - End Commit Ph1
 - Begin Commit Ph2 (2 log writes for 2 phase commit)
 - Ph1/Ph2 combined for 1 phase commit (1 log write for 1 phase commit)
 - Database writes
 - "Write ahead" logging protocol
 - All undo/redo records pertaining to the page being written must be hardened on disk before the page is written to DASD or CF
 - Page P-lock negotiation and index leaf-page split in data sharing
 - 2 forced physical log writes per index leaf-page split
 - Force log up to PGLOGRBA (RBA/LRSN of last update to the page)
 - System checkpoints



Writing to the Active Log ...

- When does DB2 write to the active log? ...
 - Log write threshold reached
 - Fixed "20 buffer" value V7 and above
 - Prior to V7 controlled by ZPARM WRTHRSH
 - ARCHIVE LOG command
 - IFI read for IFCID 306 from another member
- Log writes are chained, up to 128 4K CIs per write I/O
 - It takes at least 4 CIs to get parallel overlap and start benefiting from DFSMS striping
 - First and last CIs are always done serially
- For dual logging
 - Full CI writes are fully overlapped
 - CI re-writes are done serially



Log Write Statistics

| Field Name | Description | LOG ACTIVITY | QUANTITY | /SECOND | /THREAD | /COMMIT |
|------------|-------------------------------|-----------------------------|----------|---------|---------|---------|
| QJSTWTB | UNAVAILABLE OUTPUT LOG BUFFER | ... | | | | |
| QJSTBPAG | LOG OUTPUT BUFFER PAGED IN | UNAVAILABLE OUTPUT LOG BUFF | 10.00 | 0.00 | 0.00 | 0.00 |
| QJSTWRNW | NOWAIT LOG WRITE REQUESTS | OUTPUT LOG BUFFER PAGED IN | 0.00 | 0.00 | 0.00 | 0.00 |
| QJSTWRF | FORCE LOG WRITE REQUESTS | LOG RECORDS CREATED | 23673.6K | 3315.64 | 402.30 | 98.14 |
| QJSTBFFL | ACTIVE LOG OUTPUT CI CREATED | LOG CI CREATED | 1710.1K | 239.51 | 29.06 | 7.09 |
| QJSTLOGW | LOG WRITE I/O REQUESTS | LOG WRITE I/O REQ (LOG1&2) | 1816.3K | 254.39 | 30.87 | 7.53 |
| QJSTCIWR | LOG CI WRITTEN | LOG CI WRITTEN (LOG1&2) | 4383.3K | 613.91 | 74.49 | 18.17 |
| | | LOG RATE FOR 1 LOG (MB) | N/A | 1.20 | N/A | N/A |
| | | LOG WRITE SUSPENDED | 623.8K | 87.37 | 10.60 | 2.59 |

➤ Output Log Buffer size

- Controlled by ZPARM OUTBUFF (storage allocated in MSTR address space)



Increase if UNAVAIL OUTPUT LOG BUF > 0 and log data volume << max


Decrease if OUTPUT LOG BUFFER PAGED IN > 1-5% of LOG RECORDS CREATED

- More output log buffer space may also help for log reads
- Log data volume = LOG CI CREATED * 4KB / stats_interval
- Start paying attention if >10MB/sec



Maximum Observed Rate of Active Log Write

- First 3 use ESCON channel, the rest is FICON channel
- -2, -4, -8 indicate 2, 4, or 8 I/O stripes





Log Dataset I/O Tuning

- Avoid I/O interference among Active Log Read/Write and Archive Log Read/Write
- If Log Rate near maximum,
 - Use faster log device
 - Consider use of DFSMS striping
 - Reduce log data volume
 - Use of DB2 Data Compression for insert intensive tables
 - Optimise table design to minimise log record size (BRF only)
 - Be aware of impact of DBD update
- If the DB2 archive log offload process cannot keep up with speed that the DB2 active log fills
 - Consider DFSMS striping of archive log files (V9)



Log Reads

- Log reads are driven by any of the following types of activity
 - Rollback of a unit of work
 - Data recovery
 - RECOVER utility
 - LPL or GRECP recovery
 - Online Reorg LOGAPPLY phase
 - Restart recovery
 - IFI log read interface
 - Data replication
 - IFCID 129: read range of log record CIs from active log
 - IFCID 306: supports archive logs, decompression, and data sharing log merge
 - Option to not merge
 - Standalone log read – DSNJSLR as DSN1LOGP



Log Read Performance

| Field Name | Description | LOG ACTIVITY | QUANTITY | /SECOND | /THREAD | /COMMIT |
|------------|----------------------------------|-------------------------------|----------|---------|---------|---------|
| QJSTRBUF | READS SATISFIED FROM OUTPUT BUF | READS SATISFIED-OUTPUT BUF | 27654.00 | 1.28 | 0.17 | 0.06 |
| QJSTRACT | READS SATISFIED FROM ACTIVE LOG | READS SATISFIED-OUTP. BUF (%) | 21.67 | | | |
| QJSTRARH | READS SATISFIED FROM ARCHIVE LOG | READS SATISFIED-ACTIVE LOG | 99955.00 | 4.64 | 0.60 | 0.20 |
| | | READS SATISFIED-ACTV. LOG (%) | 78.33 | | | |
| | | READS SATISFIED-ARCHIVE LOG | 0.00 | 0.00 | 0.00 | 0.00 |
| | | READS SATISFIED-ARCH. LOG (%) | 0.00 | | | |

- More output log buffer space may help log read performance
- Active log reads perform best due to
 - Prefetch of log CIs enabled
 - Automatic I/O load balancing between copy1/copy2
 - VSAM striping can be enabled
 - Reduced task switching
- Archives on DASD perform better: tape destroys parallelism
 - Tape requires serialization in data sharing between concurrent Recovers
 - You cannot concurrently share tape volumes across multiple jobs
 - Small number of read devices on backend of current VTS models, which can become a severe bottleneck for DB2 mass recovery



DB2 for z/OS Best Practices

Miscellaneous





RID List Processing

| Field Name | Description | RID LIST PROCESSING | QUANTITY | /SECOND | /THREAD | /COMMIT |
|------------|-----------------------------|------------------------------|----------|---------|---------|---------|
| QISTRLLM | TERMINATED-EXCEED RDS LIMIT | ----- | ----- | ----- | ----- | ----- |
| | | MAX RID BLOCKS ALLOCATED | 8469.00 | N/A | N/A | N/A |
| | | CURRENT RID BLOCKS ALLOCAT. | 47.28 | N/A | N/A | N/A |
| QISTRPLM | TERMINATED-EXCEED DM LIMIT | TERMINATED-NO STORAGE | 0.00 | 0.00 | 0.00 | 0.00 |
| | | TERMINATED-EXCEED RDS LIMIT | 515.00 | 0.07 | 0.01 | 0.00 |
| | | TERMINATED-EXCEED DM LIMIT | 0.00 | 0.00 | 0.00 | 0.00 |
| | | TERMINATED-EXCEED PROC. LIM. | 0.00 | 0.00 | 0.00 | 0.00 |

- RID list processing failures may cause unnecessary CPU resource consumption and possibly unnecessary I/O, as in most cases, DB2 reverts to tablespace scan
 - TERMINATED-EXCEED DM LIMIT
 - Number of RID entries > physical limit (approx. 26M RIDs)
 - TERMINATED-EXCEED RDS LIMIT
 - Number of RIDs that can fit into the guaranteed number of RID blocks > maximum limit (25% of table size)
- Most common reasons
 - Inaccurate or incomplete statistics
 - e.g. old statistics, inadequate or missing distribution statistics collection
 - Use of the LIKE operator in SQL statements
 - Use of host variables or parameter markers for range predicates on SQL statements (BETWEEN, >, <)
- Identify offending applications and SQL statements with accounting reports and/or IFCID 125



Phantom or Orphaned Trace

| IFC DEST. | WRITTEN | NOT WRTN | BUF. OVER | NOT ACCP | WRT. FAIL | IFC RECORD COUNTS | WRITTEN | NOT WRTN |
|-----------|----------|----------|-----------|----------|-----------|-------------------|---------|----------|
| ----- | ----- | ----- | ----- | ----- | ----- | ----- | ----- | ----- |
| SMF | 18779.00 | 0.00 | 0.00 | 0.00 | 0.00 | SYSTEM RELATED | 179.00 | 0.00 |
| GTF | 1048.1K | 491.00 | N/A | 491.00 | 0.00 | DATABASE RELATED | 120.00 | 0.00 |
| OP1 | 1261.8K | 56.00 | N/A | 56.00 | N/A | ACCOUNTING | 981.7K | 536.4K |
| OP2 | 0.00 | 0.00 | N/A | 0.00 | N/A | START TRACE | 1.00 | 3.00 |
| OP3 | 0.00 | 0.00 | N/A | 0.00 | N/A | STOP TRACE | 3.00 | 0.00 |
| OP4 | 0.00 | 0.00 | N/A | 0.00 | N/A | SYSTEM PARAMETERS | 107.00 | 65.00 |
| OP5 | 0.00 | 0.00 | N/A | 0.00 | N/A | SYS. PARMS-BPOOLS | 62.00 | 0.00 |
| OP6 | 0.00 | 0.00 | N/A | 0.00 | N/A | AUDI T | 11.00 | 0.00 |
| OP7 | 0.00 | 1260.3K | N/A | 1260.3K | N/A | | | |
| OP8 | 0.00 | 0.00 | N/A | 0.00 | N/A | TOTAL | 982.2K | 536.4K |
| RES | 0.00 | N/A | N/A | N/A | N/A | | | |
| TOTAL | 2328.6K | 1260.8K | | 1260.8K | 0.00 | | | |

➤ IFC RECORD COUNTS NOT WRTN

- Phantom or orphaned trace because monitoring (e.g. vendor tool) stopped but the corresponding DB2 trace didn't

➤ Same CPU overhead as real trace

➤ Display Trace to check

➤ V9 (CM) tries to eliminate orphaned trace records



Package List (PKLIST) Search

| Field Name | Description |
|------------|----------------------------|
| QTPKALLA | PACKAGE ALLOCATION ATTEMPT |
| QTPKALL | PACKAGE ALLOCATION SUCCESS |

| PLAN/PACKAGE PROCESSING | QUANTITY | /SECOND | /THREAD | /COMMIT |
|----------------------------|----------|---------|---------|---------|
| PLAN ALLOCATION ATTEMPTS | 166.4K | 7.73 | 1.00 | 0.34 |
| PLAN ALLOCATION SUCCESSFUL | 253.8K | 11.78 | 1.53 | 0.51 |
| PACKAGE ALLOCATION ATTEMPT | 1650.9K | 76.64 | 9.93 | 3.33 |
| PACKAGE ALLOCATION SUCCESS | 1548.0K | 71.86 | 9.31 | 3.12 |

- Within each collection (e.g. "COL_a.*", "COL_b.*", "COL_c.*"), efficient matching index access to find the package, but DB2 goes serially through the PKLIST entries
- Success rate (%) = PACKAGE ALLOC. SUCCESS / PACKAGE ALLOC. ATTEMPT * 100
- Impact of long PKLIST search
 - Additional CPU resource consumption, catalog accesses, and elapsed time
 - Can aggravate DB2 internal latch (LC32) contention
- Recommendations
 - Reduce the number of collections on the PKLIST
 - Scrub all inactive or unused collections on PKLIST
 - Fold in and collapse the number of collections on PKLIST
 - Ruthlessly prioritise and reorder the collection sequence on PKLIST based on frequency of access
 - Use SET CURRENT PACKAGESET special register to direct the search to a specific collection



Disabled SPROCs

| Field Name | Description |
|------------|--|
| QISTCOLS | # OF COLUMNS (rows x columns) FOR WHICH AN INVALID SPROC WAS ENCOUNTERED |

```
----- MISCELLANEOUS -----  
BYPASS COL: 1585.00
```

- Many plans/packages have SPROCs for fast column processing
- As a result of invalidation, DB2 has to build SPROCs dynamically at execution time
 - e.g. V7 to V8 migration, V8 to V9 migration
 - Typical CPU performance impact in 0 to 10% range
- Non-zero value for BYPASS COL indicator of problem
- IFCID 224 identifies plans and packages that need rebinding to re-enable SPROCs



Incremental BIND

| Field Name | Description | PLAN/PACKAGE PROCESSING | QUANTITY | /SECOND | /THREAD | /COMMIT |
|------------|-------------------|-------------------------|----------|---------|---------|---------|
| QXINCRB | INCREMENTAL BINDS | ----- | ----- | ----- | ----- | ----- |
| | | INCREMENTAL BINDS | 10138.00 | 2.82 | 3.77 | 0.33 |

- Items that can cause Incremental Bind include
- Static plan or package with VALIDATE(RUN) and bind time failure
 - Static SQL with REOPT(VARS)
 - Private Protocol in requestor
 - SQL referencing Declared Global Temp Table
 - Possibly DDL statements



Dataset Statistics for I/O Tuning

➤ Statistics class 8 (IFCID 199)

| BPOOL | DATABASE SPACENAME PART | TYPE GBP | SYNCH I/O AVG ASYNC I/O AVG ASY I/O PGS AVG | SYN I/O AVG DELAY SYN I/O MAX DELAY | CURRENT PAGES (VP) CHANGED PAGES (VP) CURRENT PAGES (HP) NUMBER OF GETPAGES |
|-------|-------------------------------|-------------|---|--|--|
| ----- | ----- | ---- | ----- | ----- | ----- |
| BP10 | KAGURA24 TETHTS 30 | TSP N | 23.35 0.01 32.00 | 8 78 | 3433 0 N/A 2868 |
| BP11 | KAGURA24 TETHI X1 36 | IDX N | 102.59 4.04 5.98 | 1 35 | 18991 74 N/A 245586 |

Count of
Sync I/O
per second

Average
Sync I/O
(ms)