

0-1 Knapsack

- Given a knapsack with maximum capacity W , and a set S consisting of n items
- Each item i has some weight w_i and benefit value b_i (**all w_i and W are integer values**)

0-1 Knapsack problem

- Pack the knapsack to achieve maximum total value of packed items

$$\max \sum_{i \in T} b_i \quad \text{subject to} \quad \sum_{i \in T} w_i \leq W$$

- “0-1”: Because items are indivisible; each item must be entirely accepted or rejected.

0-1 Knapsack Example

$n = 4$ (Number of elements)

$W = 5$ (Max capacity)

Elements (Weight, Benefit):

$(2,3), (3,4), (4,5), (5,6)$

Example (2)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1						
2						
3						
4						

for $w = 0$ to W
 $V[0,w] = 0$

Example (3)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0					
2	0					
3	0					
4	0					

for $i = 1$ to n
 $V[i,0] = 0$

Example (4)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0				
2	0					
3	0					
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Example (5)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3			
2	0					
3	0					
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Example (6)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3		
2	0					
3	0					
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Example (7)

i\W	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	
2	0					
3	0					
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Example (8)

i\W	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0					
3	0					
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Example (9)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0				
3	0					
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Example (10)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3			
3	0					
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Example (11)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4		
3	0					
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Example (12)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	
3	0					
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Example (13)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0					
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Example (14)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	↓ 0	↓ 3	↓ 4		
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Example (15)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	0	3	4	5	
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

if $w_i \leq w$ // item i can be part of the solution

if $b_i + V[i-1, w-w_i] > V[i-1, w]$

$V[i, w] = b_i + V[i-1, w-w_i]$

else

$V[i, w] = V[i-1, w]$

else $V[i, w] = V[i-1, w]$ // $w_i > w$

Example (16)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	0	3	4	5	7
4	0					

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

if $w_i \leq w$ // item i can be part of the solution

if $b_i + V[i-1, w-w_i] > V[i-1, w]$

$V[i, w] = b_i + V[i-1, w-w_i]$

else

$V[i, w] = V[i-1, w]$

else $V[i, w] = V[i-1, w]$ // $w_i > w$

Example (17)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	0	3	4	5	7
4	0	↓ 0	↓ 3	↓ 4	↓ 5	

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

if $w_i \leq w$ // item i can be part of the solution

if $b_i + V[i-1, w-w_i] > V[i-1, w]$

$V[i, w] = b_i + V[i-1, w-w_i]$

else

$V[i, w] = V[i-1, w]$

else $V[i, w] = V[i-1, w]$ // $w_i > w$

Example (18)

$i \backslash W$	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	0	3	4	5	7
4	0	0	3	4	5	\downarrow 7

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

if $w_i \leq w$ // item i can be part of the solution

if $b_i + V[i-1, w-w_i] > V[i-1, w]$

$V[i, w] = b_i + V[i-1, w-w_i]$

else

$V[i, w] = V[i-1, w]$

else $V[i, w] = V[i-1, w]$ // $w_i > w$

Recursive Formula

$$V[k, w] = \begin{cases} V[k-1, w] & \text{if } w_k > w \\ \max\{V[k-1, w], V[k-1, w - w_k] + b_k\} & \text{else} \end{cases}$$

0-1 Knapsack Algorithm

for $w = 0$ to W

$V[0,w] = 0$

for $i = 1$ to n

$V[i,0] = 0$

for $i = 1$ to n

for $w = 0$ to W

if $w_i \leq w$ // item i can be part of the solution

if $b_i + V[i-1, w-w_i] > V[i-1, w]$

$V[i, w] = b_i + V[i-1, w-w_i]$

else

$V[i, w] = V[i-1, w]$

else $V[i, w] = V[i-1, w]$ // $w_i > w$

Finding the Items

i\W	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	0	3	4	5	7
4	0	0	3	4	5	7

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Finding the Items (2)

i\W	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	0	3	4	5	7
4	0	0	3	4	5	7

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Finding the Items (3)

i\W	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	0	3	4	5	7
4	0	0	3	4	5	7

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Finding the Items (4)

i\W	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	0	3	4	5	7
4	0	0	3	4	5	7

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Finding the Items (5)

i\W	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	0	3	4	5	7
4	0	0	3	4	5	7

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

Finding the Items (6)

i\W	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	3	3	3	3
2	0	0	3	4	4	7
3	0	0	3	4	5	7
4	0	0	3	4	5	7

Items:

1: (2,3)

2: (3,4)

3: (4,5)

4: (5,6)

The optimal knapsack
should contain {1, 2}

Algorithm: Finding the Items

- All of the information we need is in the table.
 - $V[n, W]$ is the maximal value of items that can be placed in the Knapsack.
-
- Let $i=n$ and $k=W$
if $V[i, k] \neq V[i-1, k]$ then
mark the i^{th} item as in the knapsack
 $i = i-1, k = k-w_i$
else
 $i = i-1$



Thank You



Stay Safe