Ex.NoPANDAS

+

To analyse and study the best performance point of Reciprocating pumps using Pandas.

PROCEDURE:

1. DatasetCreation:

Create a hypothetical dataset containing information about a ctual discharge (m3/s), input power (W), and output power (W).

2. CorrelationAnalysis:

Calculate the correlation matrix to examine the relationships between actual Discharge, input power, and output power using pandas "corr() function.

3. Efficiencycalculation:

Calculatetheefficiencyforeachinputvalueusingthegivenformula:Efficiency(%)

=Output_power/Input_power*100

4. Headcalculation:

Calculatethetotalheadforeachperformanceusingthegivenformula: Head

(m)=output_power/actualdischarge *pg

5. BestEfficiencyPoint(BEP):

Identify the Best Efficiency Point of the reciprocating pump from

theefficiencybyselectingthehighestindexvaluesusingthepandas' 'nlargest()' functi

on

PROGRAM:

```
importpandasaspd data={
    'ActualDischarge':[40,50,60,70,80,90], Input
    Power':[1,2,3,4,5,10],
    'OutputPower':[70,30,90,100,140,170]
}
density=1000
gravity=9.81a=pd.DataFra
me(data)
a['Efficiency']=(a['OutputPower']/a['InputPower'])*100
a['Head']=(a['Output Power']/a['Actual Discharge'])/(density*gravity)
corr_matrix=a.corr()print(corr_matrix)
max_efficiency=corr_matrix['Efficiency'].nlargest(2).iloc[1]
print("\nParameterwiththehighestcorrelationwithefficiency=",max_efficiency)
```

OUTPUT:

	Actual Discharge	Input Power	Output Power	Efficiency	1
Actual Discharge	1.000000	0.922018	0.901611	-0.614487	
Input Power	0.922018	1.000000	0.881684	-0.533271	
Output Power	0.901611	0.881684	1.000000	-0.227847	
Efficiency	-0.614487	-0.533271	-0.227847	1.000000	
Head	0.466245	0.489913	0.797480	0.391574	
	Head				
Actual Discharge	0.466245				
Input Power	0.489913				
Output Power	0.797480				
Efficiency	0.391574				
Head	1.000000				

Result:

Theprograms wererunsuccessfully