

Results of the 2018 IEEE CEC Competition on Evolutionary Many-Objective Optimization

R. Cheng, M. Li, Y. Tian, X. Xiang, X. Zhang, S. Yang, Y. Jin, and X. Yao

*2018 IEEE Congress on Evolutionary Computation,
Rio de Janeiro, Brazil, July 8-13, 2018*

Outline

I. Introduction

II. Entries

III. Results

IV. Summary


Motivation

- Optimization problems with more than three objectives (i.e. many-objective) pose great challenge to existing evolutionary algorithms for traditional multi-objective optimization
- This competition aims at proposing 15 many-objective test problems with diverse properties, and investigating the performance of evolutionary algorithms on these problems [1]

Test problems

Test problem	Modified from	Difficulty
MaF1	DTLZ1 [2]	Inverted PF
MaF2	DTLZ2BZ [3]	Concurrent convergence
MaF3	DTLZ3 [2]	Convex PF, multimodal
MaF4	DTLZ3 [2]	Inverted and scaled PF, multimodal
MaF5	DTLZ4 [2]	Scaled PF, highly biased distribution
MaF6	DTLZ5(I,M) [4]	Degenerate PF
MaF7	DTLZ7 [2]	Disconnected PF
MaF8	MP-DMP [5]	Large search space
MaF9	ML-DMP [6]	Large search space
MaF10	WFG1 [7]	Complicated mixed PF
MaF11	WFG2 [7]	Scaled disconnected PF
MaF12	WFG9 [7]	Complicated fitness landscape
MaF13	PF7 [8]	Degenerate PF, complicated variable linkage
MaF14	LSMOP3 [9]	Complicated fitness landscape, large-scale
MaF15	LSMOP8 [9]	Inverted PF, complicated fitness landscape, large-scale

Pareto front of the test problems



Experimental platform

- We provide the benchmark problems respectively embedded in two platforms
- PlatEMO [10]: Open-source MATLAB platform
- jMetal [11]: Open-source Java platform



PlatEMO



About PlatEMO

- PlatEMO includes more than 70 algorithms and 120 multi-objective test problems, which are all open-source and fully commented
- PlatEMO provides friendly GUI for users to perform experiments and obtain experimental results in the format of $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$, without writing any code



About PlatEMO

- Specially tailored GUI for this competition – One click to obtain all the results.



Competition entries

- Ten entries from four different countries
- Four new algorithms
- Six existing algorithms

Algorithm	Author	Description
AGE-II [12]	Markus Wagner	Approximation-guided evolution II
AMPDEA	Huangke Chen	Multi-population-driven evolutionary algorithm
BCE-IBEA [13]	Miqing Li	Bi-criterion evolution based IBEA
CVEA3	Jiawei Yuan	Cost value based evolutionary algorithm 3
fastCAR	Mingde Zhao	Fast clustering based algorithm with reference point redistribution
HHcMOEA	Gian Fritsche	Hyper-heuristic collaborative MOEA
KnEA [14]	Xingyi Zhang	Knee point driven evolutionary algorithm
RPEA [15]	Yiping Liu	Reference points-based evolutionary algorithm
RSEA [16]	Cheng He	Radial space division based evolutionary algorithm
RVEA [17]	Ran Cheng	Reference vector guided evolutionary algorithm

Performance indicators

- Inverted generational distance (IGD) [18]

10,000 uniformly distributed reference points sampled on the Pareto front

$$IGD(P, P^*) = \frac{\sum_{x \in P^*} \min_{y \in P} \text{dis}(x, y)}{|P^*|}$$

- Hypervolume (HV) [19]

Normalize the population by the nadir point of the Pareto front

Monte Carlo estimation method with 1,000,000 points is adopted

$$HV(P, R) = \lambda(H(P, R))$$

$$H(P, R) = \{z \in Z | \exists x \in P, \exists r \in R : f(x) \leq z \leq r\}$$


$$\lambda(H(P, R)) = \int_{\mathbb{R}^n} 1_{H(P, R)}(z) dz$$

Ranking strategy


- Each algorithm executes on each problem with 5, 10 and 15 objectives for 20 runs, respectively (i.e., 900 results)
- Sort the means of each indicator value on each problem with each number of objectives (i.e., 90 ranks)
- The SCORE achieved by each algorithm is the sum of the reciprocal values of the ranks.

Overview of the Results

- IGD values of the results (5-, 10- 15-objective)



- HV values of the results (5-, 10- 15-objective)



Overview of the Ranks

- Ranks according to IGD values

	AGE-II	AMPDEA	BCE-IBEA	CVEA3	fastCAR	HHcMOEA	KnEA	RPEA	RSEA	RVEA		AGE-II	AMPDEA	BCE-IBEA	CVEA3	fastCAR	HHcMOEA	KnEA	RPEA	RSEA	RVEA		AGE-II	AMPDEA	BCE-IBEA	CVEA3	fastCAR	HHcMOEA	KnEA	RPEA	RSEA	RVEA
MaF1	1	4	3	5	6	8	2	9	7	10	MaF1	6	1	2	4	8	7	3	9	5	10	MaF1	9	1	2	5	6	8	3	7	4	10
MaF2	1	2	3	4	7	5	6	10	8	9	MaF2	7	5	3	2	8	4	1	6	10	9	MaF2	6	1	8	2	7	5	3	4	9	10
MaF3	4	3	8	1	2	6	9	10	7	5	MaF3	5	2	10	6	1	4	9	7	8	3	MaF3	6	2	10	5	1	4	9	7	8	3
MaF4	9	2	3	1	4	7	6	5	8	10	MaF4	9	1	6	2	4	8	5	3	7	10	MaF4	8	1	5	3	6	10	4	2	7	9
MaF5	4	9	1	2	5	8	3	10	7	6	MaF5	9	4	1	2	7	10	5	3	6	8	MaF5	9	4	1	3	7	8	5	2	6	10
MaF6	5	4	1	2	7	6	3	8	10	9	MaF6	5	2	9	1	4	7	10	3	8	6	MaF6	6	2	9	1	4	3	10	5	8	7
MaF7	6	4	2	1	7	5	3	10	8	9	MaF7	5	4	1	2	7	6	3	8	9	10	MaF7	5	3	6	1	10	4	7	2	9	8
MaF8	1	4	2	3	6	5	9	8	7	10	MaF8	2	6	1	3	9	4	5	8	7	10	MaF8	8	3	1	2	9	4	5	6	7	10
MaF9	1	5	6	2	3	4	10	8	9	7	MaF9	1	7	9	3	4	5	10	6	2	8	MaF9	4	8	6	1	7	3	2	10	5	9
MaF10	7	10	1	5	6	8	3	9	4	2	MaF10	8	9	1	6	2	7	3	10	5	4	MaF10	10	9	1	8	5	6	3	7	4	2
MaF11	8	6	5	4	9	7	3	10	2	1	MaF11	3	7	4	2	9	1	6	8	5	10	MaF11	9	1	2	7	10	6	3	8	5	4
MaF12	6	10	1	2	4	9	3	8	7	5	MaF12	10	9	2	1	6	7	5	4	8	3	MaF12	9	10	3	1	5	8	4	6	7	2
MaF13	2	9	4	1	5	3	6	8	7	10	MaF13	5	9	2	1	8	3	4	6	7	10	MaF13	5	7	2	1	8	3	4	6	9	10
MaF14	4	1	8	2	3	7	5	10	6	9	MaF14	6	1	9	2	4	8	10	5	7	3	MaF14	8	1	9	2	4	5	10	6	7	3
MaF15	2	3	8	1	4	5	10	9	7	6	MaF15	3	2	9	1	5	8	10	7	6	4	MaF15	5	2	9	1	3	7	10	8	6	4
Total	3	4	2	1	5	7	6	10	8	9	Total	4	2	3	1	5	6	7	8	9	10	Total	10	2	3	1	7	5	4	6	8	9

- Ranks according to HV values

	AGE-II	AMPDEA	BCE-IBEA	CVEA3	fastCAR	HHcMOEA	KnEA	RPEA	RSEA	RVEA		AGE-II	AMPDEA	BCE-IBEA	CVEA3	fastCAR	HHcMOEA	KnEA	RPEA	RSEA	RVEA		AGE-II	AMPDEA	BCE-IBEA	CVEA3	fastCAR	HHcMOEA	KnEA	RPEA	RSEA	RVEA
MaF1	1	2	4	5	6	8	3	9	7	10	MaF1	6	4	2	7	3	9	5	8	1	10	MaF1	4	6	3	7	2	8	9	10	1	5
MaF2	7	4	3	1	8	10	2	6	5	9	MaF2	8	4	6	3	5	9	10	2	1	7	MaF2	7	4	3	2	8	6	9	5	1	10
MaF3	7	3	6	1	2	4	9	10	8	5	MaF3	6	1	8	2	4	3	10	7	9	5	MaF3	6	4	8	5	2	1	9	7	10	3
MaF4	6	5	8	1	7	9	2	3	4	10	MaF4	8	3	9	2	7	6	4	5	1	10	MaF4	5	9	8	2	6	3	4	10	1	7
MaF5	6	9	4	3	1	10	5	8	7	2	MaF5	9	4	2	3	1	10	5	7	8	6	MaF5	10	5	2	1	4	9	3	6	7	8
MaF6	2	4	1	3	6	7	5	9	8	10	MaF6	6	1	9	2	3	5	10	4	7	8	MaF6	7	1	8	2	4	5	10	3	9	6
MaF7	6	4	1	2	7	8	5	10	3	9	MaF7	10	3	7	5	4	9	8	2	1	6	MaF7	10	6	5	3	7	9	8	2	1	4
MaF8	1	4	3	2	6	7	8	9	5	10	MaF8	4	5	3	2	9	7	6	8	1	10	MaF8	8	2	5	3	10	6	4	7	1	9
MaF9	2	5	6	1	3	4	10	7	9	8	MaF9	1	6	9	3	4	5	10	7	2	8	MaF9	5	9	6	1	8	4	2	7	3	10
MaF10	8	10	3	1	9	7	4	5	2	6	MaF10	10	9	6	1	3	7	5	4	2	8	MaF10	10	9	7	1	6	3	8	4	2	5
MaF11	10	8	3	1	4	5	7	9	2	6	MaF11	10	1	4	2	6	5	7	9	3	8	MaF11	10	1	5	4	6	2	7	8	3	9
MaF12	7	10	5	1	3	9	2	8	6	4	MaF12	10	9	6	1	3	8	2	7	4	5	MaF12	10	9	5	4	7	8	1	6	2	3
MaF13	1	10	4	2	5	3	7	6	8	9	MaF13	7	10	4	1	3	5	6	2	9	8	MaF13	5	10	3	1	8	4	6	2	9	7
MaF14	4	2	8	1	3	6	5	9	7	10	MaF14	6	2	8	1	4	7	10	5	9	3	MaF14	8	2	9	1	4	6	10	5	7	3
MaF15	2	3	9	1	4	6	10	8	7	5	MaF15	5	1	7	2	4	6	9	10	8	3	MaF15	8	5	7	1	2	4	9	10	6	3
Total	3	5	2	1	4	8	6	10	7	9	Total	9	2	6	1	3	7	10	5	4	8	Total	10	4	5	1	6	3	9	7	2	8

Winner Algorithms



CVEA3

NEW

Cost value based evolutionary algorithm 3
Jiawei Yuan, Hai-Lin Liu, and Fangqing Gu
Guangdong University of Technology, China



AMPDEA

NEW

Multi-population-driven evolutionary algorithm
Huangke Chen and Guohua Wu
National University of Defense Technology, China



BCE-IBEA

Bi-criterion evolution based IBEA
Miqing Li, Shengxiang Yang, and Xiaohui Liu
Brunel University, U. K.

Conclusion

- 15 many-objective test problems were proposed for this competition
- 10 many-objective evolutionary algorithms joined the competition
- According to the final ranking based on IGD and HV metrics, the winner is CVEA3 (Cost value based evolutionary algorithm 3)

Future work

- Re-organize this competition with further enhancements (C code, better computational efficiency, etc.)
- Attract more effective algorithms to join the competition

Q & A

R. Cheng (ranchengcn@gmail.com)

Y. Tian (field910921@gmail.com)

X. Zhang (xyzhanghust@gmail.com)

Y. Jin (yaochu.jin@surrey.ac.uk)

M. Li (limitsing@gmail.com)

X. Xiang (xxs1394@163.com)

S. Yang (syang@dmu.ac.uk)

X. Yao (x.yao@cs.bham.ac.uk)

Competition Homepage:

http://www.cs.bham.ac.uk/~chengr/CEC_Comp_on_MaOO/2018/webpage.html

References

- [1] Cheng R, Li M, Tian Y, et al. A Benchmark Test Suite for Evolutionary Many-objective Optimization. *Complex & Intelligent Systems*, 3(1): 67-81, 2017.
- [2] Deb K, Thiele L, Laumanns M, et al. Scalable test problems for evolutionary multiobjective optimization[M]. Springer London, 2005.
- [3] Brockhoff D, Zitzler E. Objective reduction in evolutionary multiobjective optimization: Theory and applications[J]. *Evolutionary Computation*, 2009, 17(2): 135-166.
- [4] Deb K, Saxena D. Searching for Pareto-optimal solutions through dimensionality reduction for certain large-dimensional multi-objective optimization problems[C]//*Proceedings of the World Congress on Computational Intelligence (WCCI-2006)*. 2006: 3352-3360.
- [5] Köppen M, Yoshida K. Substitute distance assignments in NSGA-II for handling many-objective optimization problems[C]//*Evolutionary multi-criterion optimization*. Springer Berlin/Heidelberg, 2007: 727-741.
- [6] Li M, Grosan C, Yang S, et al. Multi-line distance minimization: A visualized many-objective test problem suite[J]. *IEEE Transactions on Evolutionary Computation*, 2017.
- [7] Huband S, Hingston P, Barone L, et al. A review of multiobjective test problems and a scalable test problem toolkit[J]. *IEEE Transactions on Evolutionary Computation*, 2006, 10(5): 477-506.
- [8] Saxena D K, Zhang Q, Duro J A, et al. Framework for many-objective test problems with both simple and complicated Pareto-set shapes[C]//*International Conference on Evolutionary Multi-Criterion Optimization*. Springer Berlin Heidelberg, 2011: 197-211.
- [9] Cheng R, Jin Y, Olhofer M, et al. Test problems for large-scale multiobjective and many-objective optimization[J]. *IEEE Transactions on Cybernetics*, 2016.
- [10] Tian Y, Cheng R, Zhang X, et al. PlatEMO: A MATLAB Platform for Evolutionary Multi-Objective Optimization[J]. *IEEE Computational Intelligence Magazine*, 2017, 12(4): 73-87.
- [11] Durillo J J, Nebro A J. jMetal: A Java framework for multi-objective optimization[J]. *Advances in Engineering Software*, 2011, 42(10):760-771.
- [12] Wagner M, Neumann F. A fast approximation-guided evolutionary multi-objective algorithm[C]//*Proceedings of the 15th annual conference on Genetic and evolutionary computation*. ACM, 2013: 687-694.
- [13] Li M, Yang S, Liu X. Pareto or Non-Pareto: Bi-Criterion Evolution in Multiobjective Optimization[J]. *IEEE Transactions on Evolutionary Computation*, 2016, 20(5): 645-665.
- [14] Zhang X, Tian Y, Jin Y. A knee point-driven evolutionary algorithm for many-objective optimization[J]. *IEEE Transactions on Evolutionary Computation*, 2015, 19(6): 761-776.
- [15] Liu Y, Gong D, Sun X, et al. Many-objective Evolutionary Optimization Based on Reference Points[J]. *Applied Soft Computing*, 2016, 50.
- [16] He C, Tian Y, Jin Y, et al. A Radial Space Division Based Evolutionary Algorithm for Many-Objective Optimization[J]. *Applied Soft Computing*, 2017, 61.
- [17] Cheng R, Jin Y, Olhofer M, et al. A reference vector guided evolutionary algorithm for many-objective optimization[J]. *IEEE Transactions on Evolutionary Computation*, 2016, 20(5): 773-791.
- [18] Zhou A, Jin Y, Zhang Q, et al. Combining model-based and genetics-based offspring generation for multi-objective optimization using a convergence criterion[C]//*Evolutionary Computation*, 2006. CEC 2006. IEEE Congress on. IEEE, 2006: 892-899.
- [19] While L, Hingston P, Barone L, et al. A faster algorithm for calculating hypervolume[J]. *IEEE transactions on evolutionary computation*, 2006, 10(1): 29-38.