

Function Classification with Neural Networks

Pascal S.P. Steger

Theory, Simulation, Programming of Neural Networks, 2010

1 Introduction

- Neural Network: Topology
- Backpropagation

2 Methods

- Functions
- Program Flux

3 Output

- Logic Functions on Two Input Neurons (a, b)
- Output Window
- Applied on Training Data
- Applied on Noisy Data

4 Errors

- Parametrization of Sigmoid Function
- Learning Rate, Number of Iterations
- Number of Hidden Neurons

5 To Be Done

- Projects

Literature



R. D. Jones et al.

Function approximation and time series prediction with neural networks.

Proc. Int. Joint Conf. on Neural Networks, 1990.



U. Lämmel and J. Cleve.

Künstliche Intelligenz.

Carl Hanser Verlag München Wien, 2004.



R. Rojas.

Neural Networks - A Systematic Introduction.

Springer-Verlag, Berlin, New-York, 1996.




R. Stoop.

Theorie und Simulation Neuronaler Netze.

lecture notes, 2010.

Neural Network: Topology



Backpropagation

```
ohh  =  sigmoid[whh.in];
oh   =  sigmoid[wh.ohh];
out  =  sigmoid[wo.oh];

e     =  t - out;
od    =  e out (1 - out);
hd    =  oh (1 - oh) [wo'].od;
hhd   =  ohh (1 - ohh) [wh'].hd;

wo    +=  eta Outer[Times, od, oh];
wh    +=  eta Outer[Times, hd, ohh];
whh   +=  eta Outer[Times, hhd, in];
```

1 Introduction

- Neural Network: Topology
- Backpropagation

2 Methods

- Functions
- Program Flux

3 Output

- Logic Functions on Two Input Neurons (a, b)
- Output Window
- Applied on Training Data
- Applied on Noisy Data


4 Errors

- Parametrization of Sigmoid Function
- Learning Rate, Number of Iterations
- Number of Hidden Neurons

5 To Be Done

- Projects


Functions



$$x^n$$

$$\exp(nx)$$

$$x^{1/(1+n)}$$




$$\log(nx)$$

$$\cos(n\pi x)$$

$$e^{-(2n(x-0.5))^2}$$

Program Flux



Input

$$\mathbf{r}'_i = \mathbf{r}_i - \tilde{\mathbf{r}},$$

$$\mathbf{r}''_i = \mathbf{s} \cdot \mathbf{r}'_i,$$

$$\mathbf{e}''_i = \mathbf{s} \cdot \mathbf{e}'_i,$$

original			normalized		
(6.7,49.6)	±	(1.7,2.5)	(0.0,0.4)	±	(0.02,0.02)
(46.6,69.8)	±	(2.7,2.9)	(0.4,0.6)	±	(0.03,0.03)
(93.5,20.2)	±	(1.6,3.3)	(1.0,0.1)	±	(0.01,0.03)
(58.5,96.2)	±	(4.7,0.8)	(0.5,1.0)	±	(0.05,0.00)
(23.7,10.0)	±	(2.5,2.8)	(0.1,0.0)	±	(0.02,0.03)
...	±	±	...

```
void train(int nitmax, double a, double eta) {  
    for (int nit = 0; nit < nitmax; ++nit) {  
        int i = (ttout.size() * Math.random());  
        setInput(ttin.elementAt(i));  
        setTarget(ttout.elementAt(i));  
  
        fireCascade(a);  
        getErr();  
        correctW(eta);  
    }  
}
```

findFunction

```
@Override public SFunction findFunction() {  
    double a = 0.2, eta = 0.9;  
    int nitmax = 10000;  
    generateTraining();  
    n.train(nitmax, a, eta);  
    n.setInput( in );  
    Matrix fin = new Matrix(n.fireCascade(a));  
    double type = fin.get(0, 0) * 6.0;  
    double deg = fin.get(1, 0) * 4.0;  
    return new SFunction(type, deg);  
}
```

1 Introduction

- Neural Network: Topology
- Backpropagation

2 Methods

- Functions
- Program Flux

3 Output

- Logic Functions on Two Input Neurons (a, b)
- Output Window
- Applied on Training Data
- Applied on Noisy Data

4 Errors


- Parametrization of Sigmoid Function
- Learning Rate, Number of Iterations
- Number of Hidden Neurons

5 To Be Done

- Projects

Logic Functions on Two Input Neurons (a, b)

(0, 0)	(0, 1)	(1, 0)	(1, 1)	error e
0	0	0	0	0.0000
1	0	0	0	0.0005
...				
1	0	1	0	0.0003
0	1	1	0	0.0021
1	1	1	0	0.0007
0	0	0	1	0.0009
1	0	0	1	0.0010
0	1	0	1	0.0004
...				
0	1	1	1	0.0006
1	1	1	1	0.0000









Applied on Training Data

type	deg	found	
1	1	0.968	1.018
1	2	1.000	2.022
1	3	1.024	3.035
1	4	1.019	3.982
2	1	2.003	1.016
2	2	2.019	2.012
2	3	1.983	2.989
2	4	2.010	3.938
3	1	2.955	1.041
3	2	3.039	2.008
3	3	2.972	3.029
3	4	3.029	3.901

type	deg	found	
4	1 ... 4	4.001	2.587
5	1	5.010	1.075
5	2	5.026	2.065
5	3	4.997	3.086
5	4	4.991	3.974
6	1	5.906	1.077
6	2	5.965	2.089
6	3	5.974	3.061
6	4	5.938	3.946

Applied on Noisy Data



$$10(1 - \delta)\%$$

1 Introduction

- Neural Network: Topology
- Backpropagation

2 Methods

- Functions
- Program Flux

3 Output

- Logic Functions on Two Input Neurons (a, b)
- Output Window
- Applied on Training Data
- Applied on Noisy Data

4 Errors


- Parametrization of Sigmoid Function
- Learning Rate, Number of Iterations
- Number of Hidden Neurons

5 To Be Done







- Projects

Parametrization of Sigmoid Function

$$\text{sig}_a(x) \equiv \frac{1}{1 + \exp(-ax)}$$
$$\text{sig}'_a(x) = a \cdot \text{sig}_a(x)[1 - \text{sig}_a(x)]$$



Learning Rate, Number of Iterations



·1000

Number of Hidden Neurons

$n_{\text{hid},(1,2)}$	error	time [s]
1	86.23	1.7
2	30.56	1.9
3	14.84	2.5
4	12.38	2.9
5	9.31	3.5
6	10.79	4.0
7	10.00	4.7
8	9.32	5.3
9	9.33	6.0
10	7.32	6.7
15	7.64	11.3
20	6.58	17.5

- more sampling points
- random input
- linear superposition
- three-dimensional data
- holographic neuron (with 2D FFT)
- ...