


AN INVESTIGATIONAL STUDY INTO THE DESIGN OF A LOW COST, ADAPTIVE HEARING AID

KAYLA-JADE BUTKOW & KELVIN DA SILVA SCHOOL OF ELECTRICAL & INFORMATION ENGINEERING, UNIVERSITY OF THE WITWATERSRAND



Introduction

Hearing loss is a prevalent problem that affects people in all parts of the world. It is caused by many factors including age, disease and trauma, and often results in a decreased quality of life [1]. Existing hearing aids are expensive, which makes them inaccessible to the majority of South Africans. It is therefore necessary to develop an inexpensive hearing aid that has all of the functionality of a high-end hearing aid.

This functionality includes:

- Amplifying specific frequency bands according to a person's audiogram
- The ability of the user to select the direction in which they wish to listen and to hear sounds in that direction louder than other directions

OBJECTIVES

- To create a full software hearing aid simulation
- To create a hardware proof of concept of a hearing aid which demonstrates limited functionality

SYSTEM DESIGN




Figure 1: Hearing aid system overview

Simulated vs Hardware Hearing Aid

 Table 1: Comparison of Simulated and Hardware hearing aids

Property	Simulation	Hardware
# of Microphones	10	4
Bandwidth	0.25-8 kHz	2.8-3.5kHz and 5.6-7 kHz
Filter order	14	2
Type of filters	$\frac{1}{3}$ Octave bandpass	$\frac{1}{3}$ Octave bandpass
Number of filters	16 per microphone	2 per microphone

Testing




Figure 2: Procedure for testing the hearing aid

RESULTS

Simulation Results





Figure 3: Audiogram



Hardware Results





Figure 6: 0°






Figure 4: FFT Software

Figure 5: 90°




Figure 7: 60°

Figure 8: 90°

FUTURE WORK

This project has been a proof of concept that an inexpensive adaptive hearing aid can be produced. For future development of the hearing aid, a number of improvements could be made including:

- Making use of higher quality omni-directional microphones
- Creating an integrated circuit chip to handle the preprocessing of the audio signals
- Making use of more microphones to improve the precision of the directionality feature

CONCLUSION

REFERENCES

[1] D. V. Anderson, R. W. Harris, and D. M. Chabries. Evaluation of a hearing compensation algorithm. *1995 International Conference on Acoustics, Speech, and Signal Processing*, 5:3531–3533, 1995.