

Name - Bolonghe B.P.M

Index No - 190095C

GitHub repository - <https://github.com/Pasindu-Manodara/Image-Processing-Home-Work-Exercise.git>

Question 1 & 2

```
In [ ]: import numpy as np
import cv2 as cv
import matplotlib.pyplot as plt

f = open(r'./Images/templeSparseRing/templeSR_par.txt', 'r')
assert f is not None

n = int(f.readline())
l = f.readline().split()
im1_fn = l[0]

K1 = np.array([float(i) for i in l[1:10]]).reshape((3,3))
R1 = np.array([float(i) for i in l[10:19]]).reshape((3,3))
t1 = np.array([float(i) for i in l[19:22]]).reshape((3,1))

l = f.readline().split()
im2_fn = l[0]

K2 = np.array([float(i) for i in l[1:10]]).reshape((3,3))
R2 = np.array([float(i) for i in l[10:19]]).reshape((3,3))
t2 = np.array([float(i) for i in l[19:22]]).reshape((3,1))



im1 = cv.imread(r'./Images/templeSparseRing/'+im1_fn, cv.IMREAD_COLOR)
im2 = cv.imread(r'./Images/templeSparseRing/'+im2_fn, cv.IMREAD_COLOR)
assert im1 is not None

fig, ax = plt.subplots(1, 2, figsize=(12, 10))
ax[0].imshow(cv.cvtColor(im1, cv.COLOR_BGR2RGB))
ax[1].imshow(cv.cvtColor(im2, cv.COLOR_BGR2RGB))

P1 = K1 @ np.hstack((R1, t1))
P2 = K2 @ np.hstack((R2, t2))

print('P1 =', P1)
print('P2 =', P2)

P1 = [[ 4.80251845e+01  1.44011271e+03 -5.71648932e+02  7.53293366e+01]
 [ 1.53577034e+03 -6.41434324e+01 -1.63127843e+02  1.85810055e+02]
 [ 4.88387837e-02 -1.81568392e-01 -9.82164799e-01  6.14604846e-01]]
P2 = [[-1.55882371e+02  1.44377186e+03 -5.42436214e+02  6.81806220e+01]
 [ 1.34928131e+03 -8.41979541e+01 -7.49443961e+02  1.99929996e+02]
 [-3.40999743e-01 -1.74474039e-01 -9.23730472e-01  6.00850565e-01]]
```



Question 3

```
In [ ]: from scipy.linalg import null_space
def skew(x):
    x = x.ravel()
    return np.array([[0, -x[2], x[1]], [x[2], 0, -x[0]], [-x[1], x[0], 0]])

C = null_space(P1)
C = C * np.sign(C[0, 0])
e2 = P2 @ C
e2x = skew(e2)

F = e2x @ P2 @ np.linalg.pinv(P1)
print('F =', F)

x = np.array([130, 115, 1])
cv.circle(im1, (x[0], x[1]), 5, (0, 0, 255), -1)



l2 = F @ x.T

p1 = np.array([0, (l2[0]*0+l2[2])/l2[1]]).astype(int)
p2 = np.array([500, (l2[0]*500+l2[2])/l2[1]]).astype(int)
cv.line(im2, (p1[0], p1[1]), (p2[0], p2[1]), (255, 0, 0), 5)

fig, ax = plt.subplots(1, 2, figsize=(12, 10))
ax[0].imshow(cv.cvtColor(im1, cv.COLOR_BGR2RGB))
ax[1].imshow(cv.cvtColor(im2, cv.COLOR_BGR2RGB))

F = [[-2.87071497e-04 -3.96261289e-02  2.94221686e+02]
      [-3.55039713e-02  1.65329260e-04  1.78860854e+01]
      [-2.76702814e+02  2.12942175e+01 -9.06669374e+03]]
<matplotlib.image.AxesImage at 0x1360b2d80a0>
```

Out []:



Question 4

```
In [ ]: import numpy as np
import cv2 as cv
from matplotlib import pyplot as plt
```

```

img1 = cv.imread(r'./Images/templeSparseRing/'+im1_fn,0)
img2 = cv.imread(r'./Images/templeSparseRing/'+im2_fn,0)
sift = cv.SIFT_create()

keypoint1, descriptor1 = sift.detectAndCompute(img1,None)
keypoint2, descriptor2 = sift.detectAndCompute(img2,None)

FLANN_INDEX_KDTREE = 1
index_params = dict(algorithm = FLANN_INDEX_KDTREE, trees = 5)
search_params = dict(checks=50)
flann = cv.FlannBasedMatcher(index_params,search_params)
matches = flann.knnMatch(descriptor1,descriptor2,k=2)
pts1 = []
pts2 = []

for i,(m,n) in enumerate(matches):
    if m.distance < 0.8*n.distance:
        pts2.append(keypoint2[m.trainIdx].pt)
        pts1.append(keypoint1[m.queryIdx].pt)

```

```

In [ ]: pts1 = np.int32(pts1)
pts2 = np.int32(pts2)
F, mask = cv.findFundamentalMat(pts1,pts2,cv.FM_LMEDS)

pts1 = pts1[mask.ravel()==1]
pts2 = pts2[mask.ravel()==1]

```

```

In [ ]: import matplotlib.pyplot as plt
def drawlines(img1,img2,lines,pts1,pts2):
    ''' img1 - image on which we draw the epilines for the points in img2
        lines - corresponding epilines '''
    r,c = img1.shape
    img1 = cv.cvtColor(img1,cv.COLOR_GRAY2BGR)
    img2 = cv.cvtColor(img2,cv.COLOR_GRAY2BGR)
    for r,pt1,pt2 in zip(lines,pts1,pts2):
        color = tuple(np.random.randint(0,255,3).tolist())
        x0,y0 = map(int, [0, -r[2]/r[1] ])
        x1,y1 = map(int, [c, -(r[2]+r[0]*c)/r[1] ])
        img1 = cv.line(img1, (x0,y0), (x1,y1), color,1)
        img1 = cv.circle(img1,tuple(pt1),5,color,-1)
        img2 = cv.circle(img2,tuple(pt2),5,color,-1)
    return img1,img2

lines1 = cv.computeCorrespondEpilines(pts2.reshape(-1,1,2), 2,F)
lines1 = lines1.reshape(-1,3)
img5,img6 = drawlines(img1,img2,lines1,pts1,pts2)

lines2 = cv.computeCorrespondEpilines(pts1.reshape(-1,1,2), 1,F)
lines2 = lines2.reshape(-1,3)
img3,img4 = drawlines(img2,img1,lines2,pts2,pts1)
plt.figure(figsize=(18,16))
plt.subplot(121),plt.imshow(img5)
plt.subplot(122),plt.imshow(img3)
plt.show()

```

