Hands-On Activity 8 | Visualizing Variability

Close

```
Name : Al Twain D. Pasion<br>
Course Code and Title : CPE031 || Visuali
Date Submitted : 9/19/2026 <br>
Instructor : Engr. Jimlord Quejado


---
```

Name : Al Twain D. Pasion
Course Code and Title : CPE031 || Visualization and Data Analysis
Date Submitted : 9/19/2026
Instructor : Engr. Jimlord Quejado

1. Objectives:

This activity aims to develop students' ability to visualize deviations in data, and analyze variability with sample statistics and estimates.

2. Intended Learning Outcomes (ILOs):

By the end of this module the students should be able to:

1. Analyze how charts display represent categorical and quantitative data distribution.
2. Evaluate feature distribution and statistical measures of location and variability.
3. Create clear and coherent visualizations of sample statistics and prediction estimates.

3. Discussions:

Deviations in data values can appear within a single variable, such as the ages of Olympic gymnasts. It explains different chart types for showing how a variable's values are distributed. The choice of visualization depends on factors like whether the data is categorical or quantitative, the dataset size, and the number of variables being compared. To better interpret these visualizations, the chapter introduces basic

statistical measures of central tendency and variability. It concludes with methods for visually representing variability in sample statistics and prediction estimates.

4. Procedures:

Creating Distributions from Data

In data analysis, understanding how variables vary is essential for making informed decisions. Distributions help engineers and analysts identify patterns, detect anomalies, and model real-world systems. A random variable represents a quantity whose values are uncertain, while realizations are the past observed values collected through sampling. Since it is rarely practical to analyze an entire population, analysts work with representative samples to generalize findings. Visualization techniques like histograms, frequency polygons, and relative frequency plots are critical tools for revealing the structure and variability of data.

Core Concepts

1. Random Variables and Variation
    - Random variables represent uncertain values affected by external factors.
    - Variation occurs when a variable's values differ across observations, such as over time or across customers.
    - Descriptive analytics uses data visualization to understand these variations and their impact.
2. Types of Data -.Categorical Data: Consists of labels or names that cannot be mathematically manipulated (e.g., beverage types, product categories).
    - Quantitative Data: Numeric values that can be mathematically analyzed (e.g., sales numbers, temperatures).
3. Frequency Distributions
    - Show how often specific values or ranges of values occur.
    - Categorical Example: Soft drink sales distribution to compare popularity.
    - Quantitative Example: Age distribution using ranges (bins) to capture continuous data.
4. Relative and Percent Frequency
    - Relative frequency expresses counts as proportions of the total.
    - Percent frequency provides percentages, useful for estimating

- Percent frequency provides percentages, useful for estimating probabilities.
- Example: Using purchase data to predict required stock for a concert.

5. Benford's Law
    - Observes that in many natural datasets, lower digits (like 1) appear more frequently as the first digit.
    - Used in fraud detection and anomaly detection, especially in financial datasets.

Visualization Techniques

1. Histograms
    - Best for quantitative data.
    - Columns without spaces represent continuous ranges of values.
    - The number of bins and bin width strongly affect clarity:
    - Too many bins make data noisy.
    - Too few bins oversimplify patterns.
2. Frequency Polygons
    - Use lines instead of bars, allowing easier comparison between multiple variables.
    - Example: Comparing age distributions of male and female individuals.
3. Skewness
    - Left-skewed: Most values are high, few are low (e.g., exam scores).
    - Right-skewed: Most values are low, few are high (e.g., income data).
    - Symmetric: Balanced distribution, like heights or standardized test scores.

Key Steps for Building Distributions

1. Define Bins: Decide the number and range of bins (typically 5–20).
2. Calculate Frequencies: Use software functions like COUNTIF or FREQUENCY in Excel.
3. Visualize:
    - Clustered column charts for categorical data.
    - Histograms or frequency polygons for quantitative data.
4. Interpret Patterns: Identify trends, anomalies, or potential risks.

Coding Procedure

```
#Import libraries
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

# Seed for reproducibility
np.random.seed(42)
```

```
# Setup
# ========================================
# Generate sample quantitative data
# ========================================
# Simulated data: 200 random ages between 15 and 70
ages = np.random.randint(15, 70, 200)

# Define bin ranges for age groups
bins = [15, 25, 35, 45, 55, 65, 75]

# ========================================
# Part 1: Core Concepts
# ========================================
# Calculate frequency and relative frequency
frequency, bin_edges = np.histogram(ages, bins=bins)
relative_frequency = frequency / len(ages)

# Create a frequency table
distribution_df = pd.DataFrame({
    "Age Range": [f"{bins[i]}-{bins[i+1]-1}" for i in range(len(bins)-1
    "Frequency": frequency,
    "Relative Frequency": relative_frequency.round(3)
})

print("=== Part 1: Core Concepts ===")
print("Frequency and Relative Frequency Table:")
print(distribution_df)

# ========================================
# Part 2: Visualization Techniques
# ========================================
# Calculate midpoints for the frequency polygon
midpoints = 0.5 * (bin_edges[1:] + bin_edges[:-1])

plt.figure(figsize=(10, 5))

# Histogram
plt.hist(ages, bins=bins, color='skyblue', edgecolor='black', alpha=0.7

# Frequency Polygon
plt.plot(midpoints, frequency, color='red', marker='o', linewidth=2, la
```

```
plt.plot(midpoints, frequency, color='red', marker='o', linewidth=2, la

print("=== Part 2: Visualization Techniques ===")
plt.title("Part 2: Visualization Techniques - Age Distribution")
plt.xlabel("Age Range")
plt.ylabel("Frequency")
plt.xticks(bins)
plt.legend()
plt.grid(axis='y', alpha=0.3)
plt.show()

# ========================================
# Part 3: Key Steps for Building Distributions
# ========================================

print("\n=== Part 3: Key Steps for Building Distributions ===")

# Step 1: Define bins
print(f"Step 1: Bins defined as {bins}")

# Step 2: Calculate frequency and relative frequency
frequency, bin_edges = np.histogram(ages, bins=bins)
relative_frequency = frequency / len(ages)

step2_df = pd.DataFrame({
    "Age Range": [f"{bins[i]}-{bins[i+1]-1}" for i in range(len(bins)-1
    "Frequency": frequency,
    "Relative Frequency": relative_frequency.round(3)
})

print("\nStep 2: Frequency Table")
print(step2_df)

# Step 3: Visualize the data
plt.figure(figsize=(10, 5))
plt.hist(ages, bins=bins, color='lightgreen', edgecolor='black', alpha=
plt.plot(midpoints, frequency, color='blue', marker='o', linewidth=2, l

plt.title("Step 3: Visualization of Age Distribution")
plt.xlabel("Age Range")
plt.ylabel("Frequency")
plt.xticks(bins)
plt.legend()
plt.grid(axis='y', alpha=0.3)
plt.show()

# Step 4: Interpret Patterns
max_freq_index = np.argmax(frequency)
most_common_range = step2_df.iloc[max_freq_index]["Age Range"]

print("\nStep 4: Interpretation")
```


```
print(f"- The most common age range is {most_common_range} with {freque

# Check skewness
lower_half = sum(frequency[:len(frequency)//2])
upper_half = sum(frequency[len(frequency)//2:])

if lower_half < upper_half:
    print("- The data is LEFT-SKEWED (more older individuals).")
elif lower_half > upper_half:
    print("- The data is RIGHT-SKEWED (more younger individuals).")
else:
    print("- The data is approximately symmetric.")

```


```
=== Part 1: Core Concepts ===
Frequency and Relative Frequency Table:
  Age Range  Frequency  Relative Frequency
0     15-24         37               0.185
1     25-34         31               0.155
2     35-44         44               0.220
3     45-54         35               0.175
4     55-64         34               0.170
5     65-74         19               0.095
=== Part 2: Visualization Techniques ===
```




```
=== Part 3: Key Steps for Building Distributions ===
Step 1: Bins defined as [15, 25, 35, 45, 55, 65, 75]

Step 2: Frequency Table
  Age Range  Frequency  Relative Frequency
0     15-24         37               0.185
1     25-34         31               0.155
2     35-44         44               0.220
3     45-54         35               0.175
4     55-64         34               0.170
```

```
4       55-64           34              0.170
5       65-74           19              0.095
```




```
Step 4: Interpretation
- The most common age range is 35-44 with 44 individuals.
- The data is RIGHT-SKEWED (more younger individuals).
```

Task 1: Creating Distributions from Data

Modify the provided code to see how **bin size** affects the shape of the distribution.

Instructions:

1. Update the `bins` variable to use **different bin groupings**, such as:
   - `[15, 30, 45, 60, 75]`
   - `[15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75]` (many narrow bins)
2. Run the code after each change and observe how the **histogram** and **frequency polygon** change.
3. Add labels or a note in the print statements describing which bin setting is being

3. Add labels or a note in the print statements describing which bin setting is being used.

```
ages = np.random.randint(15, 75, 200)

# Define bin ranges for age groups
bins = [15, 30, 45, 60, 75]

frequency, bin_edges = np.histogram(ages, bins=bins)
relative_frequency = frequency / len(ages)

# Create a frequency table
distribution_df = pd.DataFrame({
    "Age Range": [f"{bins[i]}-{bins[i+1]-1}" for i in range(len(bins)-1)
    "Frequency": frequency,
    "Relative Frequency": relative_frequency.round(3)
})

print("Frequency and Relative Frequency Table:")
print(distribution_df)

# Calculate midpoints for the frequency polygon
midpoints = 0.5 * (bin_edges[1:] + bin_edges[:-1])

plt.figure(figsize=(10, 5))

# Histogram
plt.hist(ages, bins=bins, color='skyblue', edgecolor='black', alpha=0.7,

# Frequency Polygon
plt.plot(midpoints, frequency, color='red', marker='o', linewidth=2, lab

print("=== Visualization Techniques ===")
plt.title("Part 1: Visualization Techniques - Age Distribution")
plt.xlabel("Age Range")
plt.ylabel("Frequency")
plt.xticks(bins)
plt.legend()
plt.grid(axis='y', alpha=0.3)
plt.show()

print(" bins being used: [15, 30, 45, 60, 75]\n")

bins = [15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75]

# Calculate frequency and relative frequency
frequency, bin_edges = np.histogram(ages, bins=bins)
relative_frequency = frequency / len(ages)

# Create a frequency table
```

```
distribution_df = pd.DataFrame({
    "Age Range": [f"{bins[i]}-{bins[i+1]-1}" for i in range(len(bins)-1)
    "Frequency": frequency,
    "Relative Frequency": relative_frequency.round(3)
})

print("Frequency and Relative Frequency Table:")
print(distribution_df)

# Calculate midpoints for the frequency polygon
midpoints = 0.5 * (bin_edges[1:] + bin_edges[:-1])


plt.figure(figsize=(11, 5))


# Histogram
plt.hist(ages, bins=bins, color='skyblue', edgecolor='black', alpha=0.7,

# Frequency Polygon
plt.plot(midpoints, frequency, color='red', marker='o', linewidth=2, lab

print("=== Visualization Techniques ===")
plt.title("Part 2: Visualization Techniques - Age Distribution")
plt.xlabel("Age Range")
plt.ylabel("Frequency")
plt.xticks(bins)
plt.legend()
plt.grid(axis='y', alpha=0.3)
plt.show()
print(" bins being used: [15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70
```


```
Frequency and Relative Frequency Table:
  Age Range  Frequency  Relative Frequency
0     15-29         46                0.23
1     30-44         48                0.24
2     45-59         48                0.24
3     60-74         58                0.29
=== Visualization Techniques ===
```






```
 bins being used: [15, 30, 45, 60, 75]

Frequency and Relative Frequency Table:
   Age Range  Frequency  Relative Frequency
0      15-19         15               0.075
1      20-24         16               0.080
2      25-29         15               0.075
3      30-34         17               0.085
4      35-39         13               0.065
5      40-44         18               0.090
6      45-49         17               0.085
7      50-54         21               0.105
8      55-59         10               0.050
9      60-64         21               0.105
10     65-69         23               0.115
11     70-74         14               0.070
=== Visualization Techniques ===
```




```
 bins being used: [15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75]
```

QUESTION: How does increasing the number of bins affect the smoothness or detail of the visualization?

By increasing the number of bins, the pillars itself narrows. With less bins,they get wider. This can affect on how much we can see the information of the histogram at a single glance

OBSERVATION: The histogram bars widened and the polygon frequency got more dots.

Statistical Analysis of Distributions of Quantitative Variables

Understanding data distributions is essential for engineers and analysts working with real-world datasets. Statistical measures and visualization techniques help summarize, analyze, and interpret data patterns effectively. This section focuses on methods for identifying central tendencies, variability, and outliers in quantitative variables. These concepts are foundational for data-driven decision-making, predictive modeling, and system optimization in computer engineering applications.

Measures of Location (Central Tendency):

- Identify the "center" of a dataset, which represents a typical value.
- Mean (Average):
  - Sensitive to extreme values or outliers.
  - Useful when data is evenly distributed.
- Median (Middle Value):
  - Preferred when data contains extreme values or is skewed.
  - More robust than the mean for smaller datasets.
- Mode (Most Frequent Value):
  - Best for datasets with a limited range of distinct values.
  - In continuous data, represents the range with the highest frequency in a histogram.

Measures of Variability (Dispersion):

- Quantify how spread out the data values are.
- Range:
  - Simple to compute but overly affected by outliers.
- Standard Deviation:
  - Indicates average deviation from the mean.
  - Best for symmetric, bell-shaped distributions.
- Percentiles and Interquartile Range (IQR):
  - Describe data spread without being distorted by extreme values.
  - Useful for skewed datasets.
  - IQR highlights the middle 50% of data values.

Visualization Techniques: Box-and-Whisker Plots

- Combine statistical measures into a clear visual summary.
- Show median, quartiles, range, and potential outliers.
- Useful for comparing multiple datasets, such as performance metrics across different systems.
- Outliers are easily identifiable, helping engineers detect anomalies in system behavior or sensor data.

Applications in Engineering

- Identifying network latency anomalies using skewness and outlier detection.
- Analyzing processor performance data through measures of variability.
- Monitoring sensor outputs in IoT systems with box plots for quality control.
- Selecting appropriate summary measures for predictive models and machine learning pipelines.

Statistical analysis of quantitative data involves understanding central tendency, variability, and outlier behavior. Combining numerical measures with effective visualizations like box plots enables engineers to interpret data more accurately. By applying these concepts, computer engineers can improve decision-making in areas such as performance optimization, anomaly detection, and predictive analytics.

```
# ================================================
# Statistical Analysis of Distributions of Quantitative Variables
# ================================================

import numpy as np
import pandas as pd
```


```
 7 import matplotlib.pyplot as plt
 8
 9 # Generate sample quantitative data: 200 random ages between 15 and 70
10 ages = np.random.randint(15, 70, 200)
11
12 # ------------------------------------------------
13 # PART 1: CORE CONCEPTS - Measures of Central Tendency and Variability
14 # ------------------------------------------------
15
16 print("=== PART 1: CORE CONCEPTS ===")
17
18 # Calculate measures of central tendency
19 mean_age = np.mean(ages)
20 median_age = np.median(ages)
21 mode_age = pd.Series(ages).mode()[0]  # mode() returns a Series
22
23 # Calculate measures of variability
24 range_age = np.max(ages) - np.min(ages)
25 std_dev_age = np.std(ages)
26 q1 = np.percentile(ages, 25)
27 q3 = np.percentile(ages, 75)
28 iqr = q3 - q1
29
30 # Display results
31 print(f"Mean Age: {mean_age:.2f}")
32 print(f"Median Age: {median_age}")
33 print(f"Mode Age: {mode_age}")
34 print(f"Range: {range_age}")
35 print(f"Standard Deviation: {std_dev_age:.2f}")
36 print(f"Interquartile Range (IQR): {iqr}")
37
38 # Interpretation example
39 if std_dev_age > 10:
40     print("- The data has high variability.")
41 else:
42     print("- The data has low variability.")
43
44 # ------------------------------------------------
45 # PART 2: VISUALIZATION TECHNIQUES - Box Plot and Histogram
46 # ------------------------------------------------
47
48 print("\n=== PART 2: VISUALIZATION TECHNIQUES ===")
49
50 plt.figure(figsize=(12, 5))
51
52 # Box plot to visualize spread and outliers
53 plt.subplot(1, 2, 1)
54 plt.boxplot(ages, vert=True, patch_artist=True, boxprops=dict(facecolor
55 plt.title("Box-and-Whisker Plot of Ages")
56 plt.ylabel("Age")
57
```

```
58 # Histogram to show frequency distribution
59 plt.subplot(1, 2, 2)
60 plt.hist(ages, bins=10, color='skyblue', edgecolor='black')
61 plt.title("Histogram of Ages")
62 plt.xlabel("Age")
63 plt.ylabel("Frequency")
64
65 plt.tight_layout()
66 plt.show()
67
68 # ------------------------------------------------
69 # PART 3: KEY STEPS FOR BUILDING DISTRIBUTIONS
70 # ------------------------------------------------
71
72 print("\n=== PART 3: KEY STEPS FOR BUILDING DISTRIBUTIONS ===")
73
74 # Step 1: Define bins for age ranges
75 bins = [15, 25, 35, 45, 55, 65, 75]
76
77 # Step 2: Calculate frequencies and relative frequencies
78 frequency, bin_edges = np.histogram(ages, bins=bins)
79 relative_frequency = frequency / len(ages)
80
81 # Step 3: Create a frequency table
82 distribution_df = pd.DataFrame({
83     "Age Range": [f"{bins[i]}-{bins[i+1]-1}" for i in range(len(bins)-1
84     "Frequency": frequency,
85     "Relative Frequency": relative_frequency.round(3)
86 })
87
88 print("Frequency Distribution Table:")
89 print(distribution_df)
90
91 # Step 4: Visualize frequency polygon with histogram
92 midpoints = 0.5 * (bin_edges[1:] + bin_edges[:-1])
93
94 plt.figure(figsize=(8, 5))
95 plt.hist(ages, bins=bins, color='lightgray', edgecolor='black', alpha=0
96 plt.plot(midpoints, frequency, color='red', marker='o', linewidth=2, la
97 plt.title("Age Distribution with Frequency Polygon")
98 plt.xlabel("Age Range")
99 plt.ylabel("Frequency")
100 plt.xticks(bins)
101 plt.legend()
102 plt.grid(axis='y', alpha=0.3)
103 plt.show()
104
105 # Interpretation: Skewness
106 lower_half = np.sum(ages < median_age)
107 upper_half = np.sum(ages > median_age)
```


```
108
109 print("\nSkewness Interpretation:")
110 if lower_half < upper_half:
111     print("- The data is LEFT-SKEWED (more older individuals, tail on t
112 elif lower_half > upper_half:
113     print("- The data is RIGHT-SKEWED (more younger individuals, tail o
114 else:
115     print("- The data is approximately symmetric.")
116
```


```
=== PART 1: CORE CONCEPTS ===
Mean Age: 42.54
Median Age: 44.0
Mode Age: 47
Range: 54
Standard Deviation: 15.98
Interquartile Range (IQR): 25.0
- The data has high variability.

=== PART 2: VISUALIZATION TECHNIQUES ===
```




```
=== PART 3: KEY STEPS FOR BUILDING DISTRIBUTIONS ===
Frequency Distribution Table:
  Age Range  Frequency  Relative Frequency
0     15-24         36               0.180
1     25-34         32               0.160
2     35-44         35               0.175
3     45-54         45               0.225
4     55-64         32               0.160
5     65-74         20               0.100
```






```
Skewness Interpretation:
- The data is RIGHT-SKEWED (more younger individuals, tail on the right).
```

Task 2: Statistical Analysis of Distributions of Quantitative Variables

Modify the provided code to explore how data distribution and visualization methods affect interpretation.

Part 1 (Core Concepts):

- Change the randomly generated data to simulate different scenarios, such as network latency or response times.
- Compare how the mean and median behave when outliers are introduced.
- Add at least one extreme value manually (e.g., very high age or latency).

Part 2 (Visualization Techniques):

- Adjust the box plot color scheme to make outliers more visible.
- Experiment with the number of bins in the histogram (try 5, 10, and 15) and

- Experiment with the number of bins in the histogram (try 5, 10, and 15) and observe how it changes the view of the data.

Part 3 (Building Distributions):

- Modify the bin ranges to group values differently, then observe how the frequency table and frequency polygon are affected.
- Add a title and axis labels that match the new dataset you created.

```
 1
 2
 3 import numpy as np
 4 import pandas as pd
 5 import matplotlib.pyplot as plt
 6
 7 # Generate sample quantitative data: 200 random ages between 15 and 70
 8 late = [1,2,22,45,54,64,34,33,122,10,999]
 9
10 print("=== PART 1: CORE CONCEPTS ===")
11
12 # Calculate measures of central tendency
13 mean_latency = np.mean(late)
14 median_latency = np.median(late)
15 mode_latency = pd.Series(late).mode()[0]  # mode() returns a Series
16
17 # Calculate measures of variability
18 range_latency = np.max(late) - np.min(late)
19 std_dev_latency = np.std(late)
20 q1 = np.percentile(late, 25)
21 q3 = np.percentile(late, 75)
22 iqr = q3 - q1
23
24 # Display results
25 print(f"Mean Latency: {mean_latency:.2f}")
26 print(f"Median Latency: {median_latency}")
27 print(f"Mode Latency: {mode_latency}")
28 print(f"Range: {range_latency}")
29 print(f"Standard Deviation: {std_dev_latency:.2f}")
30 print(f"Interquartile Range (IQR): {iqr}")
31
32
33 # ------------------------------------------------
34 # PART 2: VISUALIZATION TECHNIQUES - Box Plot and Histogram
35 # ------------------------------------------------
36
37 print("\n=== PART 2: VISUALIZATION TECHNIQUES ===")
38
39 plt.figure(figsize=(12, 5))
40
```

```
# Box plot to visualize spread and outliers
plt.subplot(1, 2, 1)
plt.boxplot(late, vert=True, patch_artist=True, boxprops=dict(facecolor=
plt.title("Box-and-Whisker Plot of Latency")
plt.ylabel("Latency")

# Histogram to show frequency distribution
plt.subplot(1, 2, 2)
plt.hist(late, bins=15, color='skyblue', edgecolor='black')
plt.title("Histogram of Latency")
plt.xlabel("Latency")
plt.ylabel("Frequency")

plt.tight_layout()
plt.show()

# ------------------------------------------------
# PART 3: KEY STEPS FOR BUILDING DISTRIBUTIONS
# ------------------------------------------------

print("\n=== PART 3: KEY STEPS FOR BUILDING DISTRIBUTIONS ===")

# Step 1: Define bins for age ranges
bins = [1, 5, 10, 50, 100, 200]

# Step 2: Calculate frequencies and relative frequencies
frequency, bin_edges = np.histogram(ages, bins=bins)
relative_frequency = frequency / len(ages)

# Step 3: Create a frequency table
distribution_df = pd.DataFrame({
    "Rank Range": [f"{bins[i]}-{bins[i+1]-1}" for i in range(len(bins)-1
    "Frequency": frequency,
    "Relative Frequency": relative_frequency.round(3)
})

print("Frequency Distribution Table:")
print(distribution_df)


# Step 4: Visualize frequency polygon with histogram
midpoints = 0.5 * (bin_edges[1:] + bin_edges[:-1])

plt.figure(figsize=(15, 5))
plt.hist(ages, bins=bins, color='lightgray', edgecolor='black', alpha=0.
plt.plot(midpoints, frequency, color='red', marker='o', linewidth=2, lab
plt.title("Rank Distribution with Frequency Polyogon")
plt.xlabel("Rank Range")
plt.ylabel("Frequency")
plt.xticks(bins)
plt.legend()
plt.grid(axis='y', alpha=0.3)
```


```
plt.show()
```

```
=== PART 1: CORE CONCEPTS ===
Mean Latency: 126.00
Median Latency: 34.0
Mode Latency: 1
Range: 998
Standard Deviation: 278.00
Interquartile Range (IQR): 43.0

=== PART 2: VISUALIZATION TECHNIQUES ===
```




```
=== PART 3: KEY STEPS FOR BUILDING DISTRIBUTIONS ===
Frequency Distribution Table:
  Rank Range  Frequency  Relative Frequency
0        1-4          0               0.000
1        5-9          0               0.000
2      10-49          7               0.035
3      50-99         13               0.065
4    100-199         24               0.120
```



QUESTION: How did adding outliers affect the mean and median?

Adding outliers like a very high latency significantly affects the mean, in this case it increases the mean by a lot. This is because when adding an outlier, the sum of all the values drasticly changes. For the median, there wasn't any big change in adding outliers, it either only increased or decreased it by a few. Median looks for the size of the whole data set. Unless you add a few more, it will only change it by a little.

OBSERVATION: The mean changes drastically while the median only changes when I add more values rather than a few extremes. By adding more bins, the ranges become more specific and with lesser bins it becomes more vague.

Uncertainty in Sample Statistics

In data analysis, we often rely on samples to estimate characteristics of a larger population. However, because a sample is only a subset of the entire population, there is always uncertainty in how accurately sample results reflect the true population values. This uncertainty must be clearly communicated through statistical measures and visualizations to avoid misleading conclusions. By using tools like confidence intervals and visual aids such as error bars, analysts can provide a clearer picture of the reliability of their findings. These techniques are essential for engineers

and data scientists when making decisions based on limited data, such as system monitoring, user behavior analysis, or predictive modeling.

Statistical Inference and Sampling

- Statistical inference is the process of using a sample to draw conclusions about a population.
- Uncertainty arises because samples are incomplete representations of the population.
- Common real-world applications include political polling, market research, and quality control.

Confidence Intervals (CIs)

- A confidence interval shows a range of values that likely contains the population parameter. It can be showed in two variations:
- Formula:
    - Mean: sample mean ± margin of error
    - Proportion: sample proportion ± margin of error
- Influencing factors:
    - Sample size: Larger samples reduce uncertainty and narrow the interval.
    - Data variability: Greater variability increases uncertainty and widens the interval.
    - Confidence level: Higher confidence levels (e.g., 95% or 99%) require wider intervals.

Visualization Techniques

- Error Bars: Visually represent the margin of error around a point estimate.
- Box-and-Whisker Plots: Highlight variability, median, and outliers.
- Violin Plots: Combine box plots with density plots for a richer understanding of distribution shape.
- Starting the vertical axis at zero prevents misleading visuals unless comparing small differences.

Practical Examples

- Political Polling: Estimating the proportion of voters supporting a candidate.
- Market Research: Estimating average customer spending.
- Health Analytics: Comparing average lifespans between male and female groups.

- Engineering Context: Detecting network performance issues or system failures through error margins.

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from scipy import stats

# ================================
# PART 1: Statistical Inference and Sampling
# ================================
print("=== Part 1: Statistical Inference and Sampling ===")

# Population data: Simulate a population of 10,000 network latency value
population = np.random.normal(loc=100, scale=15, size=10000)  # mean=100

# Draw a random sample of 50
sample_size = 50
sample = np.random.choice(population, sample_size, replace=False)

# Calculate population and sample means
population_mean = np.mean(population)
sample_mean = np.mean(sample)

print(f"Population Mean (True): {population_mean:.2f} ms")
print(f"Sample Mean (Estimate): {sample_mean:.2f} ms")
print(f"Sample Size: {sample_size}", end="\n\n")

# ================================
# PART 2: Confidence Intervals
# ================================
print("=== Part 2: Confidence Intervals ===")

# Calculate 95% confidence interval for the sample mean
confidence_level = 0.95
std_error = np.std(sample, ddof=1) / np.sqrt(sample_size)
margin_of_error = stats.t.ppf((1 + confidence_level) / 2, df=sample_size

ci_lower = sample_mean - margin_of_error
ci_upper = sample_mean + margin_of_error

print(f"95% Confidence Interval: [{ci_lower:.2f}, {ci_upper:.2f}] ms")


# ================================
# PART 3: Visualization Techniques
# ================================

# Create a dataframe for plotting
population subset = np.random.choice(population, 200, replace=False)  #
```

```
47
48 # Boxplot directly from separate arrays
49 plt.figure(figsize=(8, 5))
50 plt.boxplot(
51     [population_subset, sample],
52     tick_labels=['Population (Subset of 200)', 'Sample (50)'],
53     patch_artist=True,
54     boxprops=dict(facecolor='lightblue')
55 )
56 plt.title("Population vs Sample Variability")
57 plt.ylabel("Latency (ms)")
58 plt.show()
59
```

```
=== Part 1: Statistical Inference and Sampling ===
Population Mean (True): 100.13 ms
Sample Mean (Estimate): 100.05 ms
Sample Size: 50

=== Part 2: Confidence Intervals ===
95% Confidence Interval: [95.52, 104.58] ms
```



Task 3: Uncertainty in Sample Statistics

Modify the provided code to explore how sampling decisions and visualization methods affect uncertainty in statistical analysis.

Part 1: Sampling

- Change the sample size from 50 to 30 and 100.
- Compare how the sample mean differs from the population mean for each sample size.
- Print all sample means alongside the true population mean.

Part 2: Confidence Intervals

- Compute and print the 95% confidence intervals for each sample size.
- Observe how the width of the interval changes when the sample size increases or decreases.
- Highlight which sample size provides the most reliable estimate.

Part 3: Visualization

- Adjust the boxplot to include all three sample sets side by side along with the population subset.
- Add a clear title and proper axis labels.

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from scipy import stats

# ================================
# PART 1: Statistical Inference and Sampling
# ================================
print("=== Part 1: Statistical Inference and Sampling ===")

# Population data: Simulate a population of 10,000 network latency value
population = np.random.normal(loc=100, scale=15, size=10000)  # mean=100

# Draw a random sample of 50
sample_size = 50
sample = np.random.choice(population, sample_size, replace=False)


# Draw a random sample of 50
sample_size2 = 30
sample2 = np.random.choice(population, sample_size2, replace=False)

# Draw a random sample of 50
sample_size3 = 100
sample3 = np.random.choice(population, sample_size3, replace=False)

# Calculate population and sample means
```

```
population_mean = np.mean(population)
sample_mean = np.mean(sample)

print(f"Population Mean (True): {population_mean:.2f} ms")
print(f"Sample Mean (Estimate): {sample_mean:.2f} ms")
print(f"Sample Size: {sample_size}", end="\n\n")

# ================================
# PART 2: Confidence Intervals
# ================================
print("=== Part 2: Confidence Intervals ===")

# Calculate 95% confidence interval for the sample mean
confidence_level = 0.95
std_error = np.std(sample, ddof=1) / np.sqrt(sample_size)
margin_of_error = stats.t.ppf((1 + confidence_level) / 2, df=sample_size

ci_lower = sample_mean - margin_of_error
ci_upper = sample_mean + margin_of_error

print(f"95% Confidence Interval: [{ci_lower:.2f}, {ci_upper:.2f}] ms")

# ================================
# PART 3: Visualization Techniques
# ================================


# Create a dataframe for plotting
population_subset = np.random.choice(population, 200, replace=False)  #


# Boxplot directly from separate arrays
plt.figure(figsize=(8, 5))
plt.boxplot(
    [population_subset, sample, sample2, sample3],
    tick_labels=['Population (Subset of 200)', 'Sample (50)', 'Sample (3
    patch_artist=True,
    boxprops=dict(facecolor='lightblue')
)
plt.title("Population vs Sample Variability")
plt.ylabel("Latency (ms)")
plt.show()

```

```
=== Part 1: Statistical Inference and Sampling ===
Population Mean (True): 100.11 ms
Sample Mean (Estimate): 98.11 ms
Sample Size: 50

=== Part 2: Confidence Intervals ===
95% Confidence Interval: [93.98, 102.25] ms
```





QUESTION: How did the sample size affect the accuracy of the sample mean compared to the population mean?

The closer the sample size is to the population size, the more accurate it becomes. Let's say from a population of 200, you only have a sample of 10. Your sample won't be that accurate compared to the population because the size is still insufficient for valid data.

Uncertainty in Predictive Models

Predictive analytics uses past data to create models that forecast future outcomes. These models are widely applied in engineering and business, such as predicting network latency, product sales, or travel times. However, predictions are never exact, and uncertainty must be considered. Visualization of this uncertainty helps engineers and decision-makers understand the reliability of forecasts, improving real-world decision-making.

Predictive Models and Point Estimates

- Predictive models generate point estimates, which are single predicted values for future observations.

- These estimates contain error because real-world systems involve randomness and variability.

Prediction Intervals

- A prediction interval gives a range where future outcomes are likely to occur with a certain confidence level (e.g., 95%).
- Similar to confidence intervals used in statistical inference, but focused on predicting individual future observations rather than population parameters.

Simple Linear Regression Example

- Linear regression models relationships between two variables:
  - Independent variable (x): factor used for prediction (e.g., number of requests in a delivery route).
  - Dependent variable (y): outcome being predicted (e.g., travel time).
- Visualization includes:
  - Historical data points.
  - Regression line showing predicted values.
  - Upper and lower dashed lines showing prediction interval boundaries.
- Key observation: intervals are narrower near the average values of the independent variable and wider at extremes, indicating higher uncertainty for unusual cases.

Time Series Models Example

- Used for data measured sequentially over time (e.g., quarterly sales).
- Predictions account for patterns like seasonality or trends.
- Visualization shows:
  - Past data as a continuous line.
  - Future point predictions as a lighter line.
  - Prediction intervals widening as the forecast extends further into the future.
- Important insight: uncertainty grows over time because long-term predictions are inherently less reliable.

```
# ============================================
# Uncertainty in Predictive Models
# ============================================
import numpy as np
```

```
import pandas as pd
import matplotlib.pyplot as plt
import statsmodels.api as sm
from sklearn.linear_model import LinearRegression

# ================================================
# PART 1: Predictive Models and Point Estimates
# ================================================
print("=== Part 1: Predictive Models and Point Estimates ===")

# Generate random data: relationship between requests and travel time
num_requests = np.random.randint(1, 10, size=10)  # independent variabl
travel_time = np.random.normal(loc=3, scale=0.5, size=10)  # dependent

# Fit a simple linear regression model
X = num_requests.reshape(-1, 1)
y = travel_time
model = LinearRegression().fit(X, y)

# Predict point estimates
predictions = model.predict(X)

print("Regression Model Summary:")
print(f"Intercept: {model.intercept_:.3f}, Slope: {model.coef_[0]:.3f}\

print("Sample of Predictions:")
for i, p in zip(num_requests, predictions):
    print(f"Requests: {i}, Predicted Travel Time: {p:.2f} hours")

# ================================================
# PART 2: Prediction Intervals
# ================================================
print("\n=== Part 2: Prediction Intervals ===")

# Use statsmodels to compute prediction intervals
X_with_const = sm.add_constant(X)  # statsmodels requires intercept col
ols_model = sm.OLS(y, X_with_const).fit()

# Generate prediction intervals
pred_summary = ols_model.get_prediction(X_with_const).summary_frame(alp
lower_bounds = pred_summary["obs_ci_lower"]
upper_bounds = pred_summary["obs_ci_upper"]

# Display prediction intervals
print(pred_summary[["mean", "obs_ci_lower", "obs_ci_upper"]])

# ================================================
# PART 3: Visualization for Linear Regression
# ================================================
print("\n=== Part 3: Visualization for Linear Regression ===")
```

```
55
56 # Sort data for a cleaner plot
57 sorted_indices = np.argsort(num_requests)
58 sorted_requests = num_requests[sorted_indices]
59 sorted_predictions = predictions[sorted_indices]
60 sorted_lower = lower_bounds[sorted_indices]
61 sorted_upper = upper_bounds[sorted_indices]
62 sorted_actual = travel_time[sorted_indices]
63
64 plt.figure(figsize=(8, 6))
65 plt.scatter(sorted_requests, sorted_actual, color='blue', label='Observ
66 plt.plot(sorted_requests, sorted_predictions, color='orange', label='Re
67 plt.fill_between(sorted_requests, sorted_lower, sorted_upper,
68                  color='orange', alpha=0.3, label='95% Prediction Inter
69 plt.xlabel("Number of Requests")
70 plt.ylabel("Travel Time (hours)")
71 plt.title("Linear Regression with Prediction Intervals")
72 plt.legend()
73 plt.show()
74
75 # ================================================
76 # PART 4: Time Series Forecasting with Prediction Intervals
77 # ================================================
78 print("\n=== Part 4: Time Series Forecasting ===")
79
80 # Generate random time series data for quarterly sales
81 time_periods = 17
82 quarters = np.arange(1, time_periods + 1)
83 sales = np.random.normal(loc=150, scale=20, size=time_periods)  # rando
84
85 # Create dataframe
86 df_sales = pd.DataFrame({"Quarter": quarters, "Sales": sales})
87
88 # Simulate future predictions
89 future_periods = 8
90 future_quarters = np.arange(time_periods + 1, time_periods + future_per
91
92 # Random predictions with added seasonality-like variation
93 future_sales_pred = np.random.normal(loc=150, scale=15, size=future_per
94
95 # Add growing uncertainty to future predictions
96 future_uncertainty = np.linspace(10, 30, future_periods)
97 lower_future = future_sales_pred - future_uncertainty
98 upper_future = future_sales_pred + future_uncertainty
99
100 # Combine into dataframe
101 forecast_df = pd.DataFrame({
102     "Quarter": future_quarters,
103     "Predicted_Sales": future_sales_pred,
104     "Lower_PI": lower_future,
105     "Upper_PI": upper_future
```


```
 106 })
 107
 108 # ================================================
 109 # Visualization for Time Series
 110 # ================================================
 111 plt.figure(figsize=(10, 6))
 112 plt.plot(df_sales["Quarter"], df_sales["Sales"], color='darkblue', labe
 113 plt.plot(forecast_df["Quarter"], forecast_df["Predicted_Sales"], color=
 114 plt.fill_between(forecast_df["Quarter"], forecast_df["Lower_PI"], forec
 115                  color='lightblue', alpha=0.3, label='95% Prediction In
 116 plt.xlabel("Quarter")
 117 plt.ylabel("Sales ($1000s)")
 118 plt.title("Time Series Forecast with Prediction Intervals")
 119 plt.legend()
 120 plt.show()
 121
```


```
=== Part 1: Predictive Models and Point Estimates ===
Regression Model Summary:
Intercept: 3.070, Slope: 0.001

Sample of Predictions:
Requests: 8, Predicted Travel Time: 3.07 hours
Requests: 5, Predicted Travel Time: 3.07 hours
Requests: 8, Predicted Travel Time: 3.07 hours
Requests: 8, Predicted Travel Time: 3.07 hours
Requests: 5, Predicted Travel Time: 3.07 hours
Requests: 5, Predicted Travel Time: 3.07 hours
Requests: 4, Predicted Travel Time: 3.07 hours
Requests: 1, Predicted Travel Time: 3.07 hours
Requests: 9, Predicted Travel Time: 3.08 hours
Requests: 2, Predicted Travel Time: 3.07 hours


=== Part 2: Prediction Intervals ===
       mean  obs_ci_lower  obs_ci_upper
0  3.074940      2.157701      3.992180
1  3.073143      2.191240      3.955045
2  3.074940      2.157701      3.992180
3  3.074940      2.157701      3.992180
4  3.073143      2.191240      3.955045
5  3.073143      2.191240      3.955045
6  3.072544      2.178707      3.966380
7  3.070746      2.075923      4.065570
8  3.075539      2.124274      4.026804
9  3.071346      2.120081      4.022610

=== Part 3: Visualization for Linear Regression ===
```






```
=== Part 4: Time Series Forecasting ===
```



Task 4: Uncertainty in Predictive Models

Modify the provided code to explore how uncertainty changes under different scenarios. Complete the following steps:

Part 1: Predictive Models and Point Estimates

- Increase the sample size of the random data by generating 30 data points instead of 10.
- Observe how the regression model changes with more data.

Part 2: Prediction Intervals

- Change the confidence level from 95% to 80% when generating prediction intervals.
- Compare how the width of the intervals changes.

Part 3: Visualization

- Change the scatter plot color for observed data to green.
- Increase the transparency (alpha) of the shaded prediction interval region to 0.5 for better visibility.
- Modify the plot title to: "Effect of Sample Size and Confidence Level on Prediction Intervals".

```
# ============================================
# Uncertainty in Predictive Models
# ============================================
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import statsmodels.api as sm
from sklearn.linear_model import LinearRegression

# ============================================
# PART 1: Predictive Models and Point Estimates
# ============================================
print("=== Part 1: Predictive Models and Point Estimates ===")

# Generate random data: relationship between requests and travel time
num_requests = np.random.randint(1, 10, size=30)  # independent variable
travel_time = np.random.normal(loc=3, scale=0.5, size=30)  # dependent v

```

```
19 # Fit a simple linear regression model
20 X = num_requests.reshape(-1, 1)
21 y = travel_time
22 model = LinearRegression().fit(X, y)
23
24 # Predict point estimates
25 predictions = model.predict(X)
26
27 print("Regression Model Summary:")
28 print(f"Intercept: {model.intercept_:.3f}, Slope: {model.coef_[0]:.3f}\n
29
30 print("Sample of Predictions:")
31 for i, p in zip(num_requests, predictions):
32     print(f"Requests: {i}, Predicted Travel Time: {p:.2f} hours")
33
34 # ================================================
35 # PART 2: Prediction Intervals
36 # ================================================
37 print("\n=== Part 2: Prediction Intervals ===")
38
39 # Use statsmodels to compute prediction intervals
40 X_with_const = sm.add_constant(X)  # statsmodels requires intercept colu
41 ols_model = sm.OLS(y, X_with_const).fit()
42
43 # Generate prediction intervals
44 pred_summary = ols_model.get_prediction(X_with_const).summary_frame(alph
45 lower_bounds = pred_summary["obs_ci_lower"]
46 upper_bounds = pred_summary["obs_ci_upper"]
47
48 # Display prediction intervals
49 print(pred_summary[["mean", "obs_ci_lower", "obs_ci_upper"]])
50
51 # ================================================
52 # PART 3: Visualization for Linear Regression
53 # ================================================
54 print("\n=== Part 3: Visualization for Linear Regression ===")
55
56 # Sort data for a cleaner plot
57 sorted_indices = np.argsort(num_requests)
58 sorted_requests = num_requests[sorted_indices]
59 sorted_predictions = predictions[sorted_indices]
60 sorted_lower = lower_bounds[sorted_indices]
61 sorted_upper = upper_bounds[sorted_indices]
62 sorted_actual = travel_time[sorted_indices]
63
64 plt.figure(figsize=(8, 6))
65 plt.scatter(sorted_requests, sorted_actual, color='tab:green', label='Ob
66 plt.plot(sorted_requests, sorted_predictions, color='orange', label='Reg
67 plt.fill_between(sorted_requests, sorted_lower, sorted_upper,
68                  color='orange', alpha=0.3, label='95% Prediction Interv
```

```
plt.xlabel("Number of Requests")
plt.ylabel("Travel Time (hours)")
plt.title("Linear Regression with Prediction Intervals")
plt.legend()
plt.show()
```


```
=== Part 1: Predictive Models and Point Estimates ===
Regression Model Summary:
Intercept: 2.911, Slope: 0.007

Sample of Predictions:
Requests: 4, Predicted Travel Time: 2.94 hours
Requests: 8, Predicted Travel Time: 2.97 hours
Requests: 5, Predicted Travel Time: 2.95 hours
Requests: 3, Predicted Travel Time: 2.93 hours
Requests: 9, Predicted Travel Time: 2.98 hours
Requests: 3, Predicted Travel Time: 2.93 hours
Requests: 1, Predicted Travel Time: 2.92 hours
Requests: 2, Predicted Travel Time: 2.93 hours
Requests: 6, Predicted Travel Time: 2.96 hours
Requests: 1, Predicted Travel Time: 2.92 hours
Requests: 3, Predicted Travel Time: 2.93 hours
Requests: 6, Predicted Travel Time: 2.96 hours
Requests: 5, Predicted Travel Time: 2.95 hours
Requests: 1, Predicted Travel Time: 2.92 hours
Requests: 6, Predicted Travel Time: 2.96 hours
Requests: 7, Predicted Travel Time: 2.96 hours
Requests: 4, Predicted Travel Time: 2.94 hours
Requests: 7, Predicted Travel Time: 2.96 hours
Requests: 4, Predicted Travel Time: 2.94 hours
Requests: 7, Predicted Travel Time: 2.96 hours
Requests: 8, Predicted Travel Time: 2.97 hours
Requests: 5, Predicted Travel Time: 2.95 hours
Requests: 2, Predicted Travel Time: 2.93 hours
Requests: 9, Predicted Travel Time: 2.98 hours
Requests: 8, Predicted Travel Time: 2.97 hours
Requests: 5, Predicted Travel Time: 2.95 hours
Requests: 3, Predicted Travel Time: 2.93 hours
Requests: 2, Predicted Travel Time: 2.93 hours
Requests: 8, Predicted Travel Time: 2.97 hours
Requests: 3, Predicted Travel Time: 2.93 hours

=== Part 2: Prediction Intervals ===
        mean  obs_ci_lower  obs_ci_upper
0   2.940612      2.199861      3.681362
1   2.969767      2.210743      3.728791
2   2.947901      2.208473      3.687329
3   2.933323      2.187306      3.679340
4   2.977056      2.203977      3.750135
5   2.933323      2.187306      3.679340
6   2.918745      2.150747      3.686743
7   2.926034      2.170889      3.681180
8   2.955190      2.213119      3.697260
9   2.918745      2.150747      3.686743
```

```
10  2.933323      2.187306      3.679340
11  2.955190      2.213119      3.697260
12  2.947901      2.208473      3.687329
13  2.918745      2.150747      3.686743
14  2.955190      2.213119      3.697260
15  2.962478      2.213842      3.711115
16  2.940612      2.199861      3.681362
17  2.962478      2.213842      3.711115
18  2.940612      2.199861      3.681362
19  2.962478      2.213842      3.711115
20  2.969767      2.210743      3.728791
21  2.947901      2.208473      3.687329
22  2.926034      2.170889      3.681180
23  2.977056      2.203977      3.750135
24  2.969767      2.210743      3.728791
25  2.947901      2.208473      3.687329
26  2.933323      2.187306      3.679340
27  2.926034      2.170889      3.681180
28  2.969767      2.210743      3.728791
29  2.933323      2.187306      3.679340

=== Part 3: Visualization for Linear Regression ===
```



---

5. Supplementary Activity:

Demonstrate the key steps for building, analyzing, and visualizing data distributions.

1. Create a synthetic dataset
    - Generate one dataset of 200 random ages between 15 and 70. This dataset will be used throughout all steps.
2. Core Concepts: Frequency and Relative Frequency
    - Build a frequency table showing:
        - Age ranges divided into bins of 10 years (15-24, 25-34, etc.).
        - The frequency and relative frequency of each bin.
    - *Reference the frequency table example shown in earlier parts.*
3. Visualization Techniques
    - Create a histogram to display the age distribution.
    - Overlay a frequency polygon on the same plot.
    - *Refer to the visualization section in Part 2 of earlier codes.*
4. Statistical Measures
    - Compute and print:
        - Mean, Median, Mode.
        - Range, Standard Deviation, and Interquartile Range (IQR).
    - *Use the approach shown in the Measures of Central Tendency and Variability example.*
5. Box Plot and Histogram Comparison
    - Create a box-and-whisker plot to visualize spread and detect outliers.
    - Create a separate histogram for frequency distribution.
    - *See Part 2 of the Statistical Analysis example for reference.*
6. Prediction and Uncertainty Visualization
    - Using the same dataset, simulate a simple linear regression where:
        - x is a random subset of 10 values from ages.
        - y is a random dependent variable with noise.
        - Fit the regression and plot:

- Observed data.
- Regression line.
- 95% prediction intervals shaded on the plot.

- *Reference the Predictive Models example from earlier codes.*

```
 1 ======================================================
 2 Supplementary Activity: Exploring Data Visualization
 3 ======================================================
 4
 5 iport numpy as np
 6 iport pandas as pd
 7 iport matplotlib.pyplot as plt
 8 iport statsmodels.api as sm
 9 om sklearn.linear_model import LinearRegression
10
11 ======================================================
12 Step 1: Create synthetic dataset
13 ======================================================
14 Generate a dataset of 200 random ages between 15 and 70
15 es = np.random.randint(15, 70, 200)
16
17 ======================================================
18 Step 2: Frequency and Relative Frequency Table
19 ======================================================
20
21 Define bin ranges for age groups
22 ns = [15, 25, 35, 45, 55, 65, 75]
23
24 TODO: Calculate frequency and relative frequency
25 equency, bin_edges = np.histogram(ages, bins=bins)
26 lative_frequency = frequency / len(ages)
27
28 TODO: Create a DataFrame for the frequency table
29 stribution_df = pd.DataFrame({
30   "Age Range": [f"{bins[i]}-{bins[i+1]-1}" for i in range(len(bins)-1)],
31   "Frequency": frequency,
32   "Relative Frequency": relative_frequency.round(3)
33
34
35 TODO: Print frequency table
36 int(distribution_df)
37
38 ======================================================
39 Step 3: Visualization Techniques
40 ======================================================
41
42 TODO: Calculate midpoints for frequency polygon
```

```
43 .dpoints = 0.5 * (bin_edges[1:] + bin_edges[:-1])
44
45 .t.figure(figsize=(10, 5))
46
47 TODO: Create histogram of ages
48 .t.hist(ages, bins=bins, color='tab:green', edgecolor='black', alpha=0.5,
49
50 TODO: Overlay frequency polygon on top of histogram
51 .t.title("Age Distribution with Frequency Polygon")
52 .t.xlabel("Age Range")
53 .t.ylabel("Frequency")
54 .t.xticks(bins)
55 .t.legend()
56 .t.grid(axis='y', alpha=0.3)
57 .t.show()
58
59
60 ======================================================
61 Step 4: Statistical Measures
62 ======================================================
63
64 TODO: Calculate mean, median, and mode
65 ean_age = np.mean(ages)
66 edian_age = np.median(ages)
67 ode_age = pd.Series(ages).mode()[0]
68
69 TODO: Calculate range, standard deviation, and IQR
70 nge_age = np.max(ages) - np.min(ages)
71 d_dev_age = np.std(ages)
72 . = np.percentile(ages, 25)
73 = np.percentile(ages, 75)
74 r = q3 - q1
75
76 TODO: Print results with interpretations
77 int("=== Interpretations ===")
78 int(f"Mean Age: {mean_age:.2f}")
79 int(f"Median Age: {median_age}")
80 int(f"Mode Age: {mode_age}")
81 int(f"Range: {range_age}")
82 int(f"Standard Deviation: {std_dev_age:.2f}")
83 int(f"Interquartile Range (IQR): {iqr}\n")
84
85 ======================================================
86 Step 5: Box Plot and Histogram
87 ======================================================
88
89 .t.figure(figsize=(12, 5))
90
91 TODO: Create box plot of ages
92 .t.subplot(1, 4, 1)
93 .t.boxplot(ages, vert=True, patch_artist=True, boxprops=dict(facecolor='t
```

```
 94 .t.title("Box-and-Whisker Plot of Ages")
 95 .t.ylabel("Age")
 96 .t.grid(axis='y', alpha=0.3)
 97
 98 TODO: Create histogram of ages (separate subplot)
 99 .t.subplot(1, 4, 1)
100 .t.hist(ages, bins=10, color='gold', edgecolor='black')
101 .t.title("Histogram of Ages")
102 .t.xlabel("Age")
103 .t.ylabel("Frequency")
104 .t.grid(axis='y', alpha=0.3)
105
106 .t.tight_layout()
107 .t.show()
108
109
110 ======================================================
111 Step 6: Prediction and Uncertainty Visualization
112 ======================================================
113
114 TODO: Randomly select 10 age values as x
115 = np.random.choice(ages, 10, replace=False)
116
117 TODO: Create y values with random noise
118 = np.random.normal(loc=3, scale=0.5, size=10)
119 = x.reshape(-1, 1)
120
121 Fit linear regression model
122 TODO: Fit regression model
123 odel = LinearRegression().fit(X, y)
124
125
126 TODO: Generate predictions
127 edictions = model.predict(X)
128
129 Use statsmodels to compute prediction intervals
130 TODO: Prepare data for statsmodels
131 with_const = sm.add_constant(X)
132
133 TODO: Fit OLS model
134 s_model = sm.OLS(y, X_with_const).fit()
135
136 TODO: Get prediction summary with intervals
137 ed_summary = ols_model.get_prediction(X_with_const).summary_frame(alpha=
138
139 TODO: Extract lower and upper bounds
140 wer_bounds = pred_summary["obs_ci_lower"]
141 per_bounds = pred_summary["obs_ci_upper"]
142
143 rted_indices = np.argsort(x)
144 nted_x = x[sorted_indices]
```

```
rted_x = x[sorted_indices]
rted_predictions = predictions[sorted_indices]
rted_lower = lower_bounds[sorted_indices]
rted_upper = upper_bounds[sorted_indices]
rted_y = y[sorted_indices]

Visualization
t.figure(figsize=(8, 6))

TODO: Scatter plot of observed data
t.scatter(sorted_x, sorted_y, color='tab:green', label='Observed Data')

TODO: Plot regression line
t.plot(sorted_x, sorted_predictions, color='orange', label='Regression L

TODO: Shade prediction interval region
t.fill_between(sorted_x, sorted_lower, sorted_upper,
                color='orange', alpha=0.3, label='95% Prediction Interval

t.xlabel("Number of Requests (simulated x)")
t.ylabel("Simulated Outcome (y)")
t.title("Linear Regression with Prediction Intervals")
t.legend()
t.grid(axis='y', alpha=0.3)
t.show()


==========================================================
Step 7: Interpretation and Reflection
==========================================================

TODO: Identify most common age range
x_freq_index = np.argmax(frequency)
st_common_range = distribution_df.iloc[max_freq_index]["Age Range"]

int(f"- The most common age range is {most_common_range}.")

TODO: Determine if distribution is skewed
wer_half = np.sum(ages < median_age)
per_half = np.sum(ages > median_age)


 lower_half < upper_half:
  print("- The data is LEFT-SKEWED.")
if lower_half > upper_half:
  print("- The data is RIGHT-SKEWED.")
se:
  print("- Approximately symmetric.")

Reflection prompt
int("\nReflection:")
int("1. How does the histogram compare to the box plot in showing variab
```


```
print("2. What does the width of the prediction interval tell us about unc
print("3. How would you use this information in a real-world decision-maki


```


	Age Range	Frequency	Relative Frequency
0	15-24	29	0.145
1	25-34	34	0.170
2	35-44	40	0.200
3	45-54	41	0.205
4	55-64	42	0.210
5	65-74	14	0.070




```
=== Interpretations ===
Mean Age: 43.21
Median Age: 44.0
Mode Age: 42
Range: 54
Standard Deviation: 15.09
Interquartile Range (IQR): 25.25
```







- The most common age range is 55-64.
- The data is RIGHT-SKEWED.

Reflection:
1. How does the histogram compare to the box plot in showing variability?
 The histogram, unlike the box plot, shows the complete shape, frequency coun
2. What does the width of the prediction interval tell us about uncertainty?
 The wider the width of the prediction interval, the higher the uncertainty.
3. How would you use this information in a real-world decision-making process
 These information can be used to make predictions, understand data distribut

6. Conclusion/Learnings/Analysis:

*Type it here