

IT-Sicherheit - OpenVAS

Prof. Dr. Johannes Freudenmann (DHBW Karlsruhe)
Masterprogramm Informatik

www.dhbw.de


Werkzeuge Nessus/OpenVAS

- NESSUS, 2005 unter proprietäre Lizenz gestellt.
 - 2014 5.2 55.000 Schwachstellen untersucht.
 - u.a. auch Compliance-Checks
- Alternative weiterentwickelt unter GPL – OPENVAS (Open Vulnerability Assessment System, <https://www.openvas.org/>)
 - Integriert u.a.auch Nmap
 - Läuft auf Unix
 - Bedienung über Web-Interface
 - Konfiguration über CERT-Feed
 - Hinweise auf CVEs
- Installation auf eigenem PC oder im kleinen Netz
- Beschreibung zur Entwicklung von OpenVAS:
<http://www.heise.de/ix/artikel/Der-Erbe-waechst-958563.html>

Werkzeuge Nessus/OpenVAS

- Weiterentwicklung durch Greenbone Networks
- 2025 Version 23.20.1
- Empfohlen vom BSI
- *OpenVAS – Scanner jetzt eingebaut in Greenbone Vulnerability Management (GVM)*
- 1.8.2023 > 120.000 Schwachstellen.
- Greenbone Community Edition mit Greenbone Community Feed (daneben Enterprise Feed)
 - <https://greenbone.github.io/docs/latest/index.html>

Werkzeuge Nessus/OpenVAS Demo



```
OpenVAS-7-DEMO-2.4 - VMware Workstation
File Edit View VM Tabs Help
OpenVAS-7-DEMO-2.4 x
SECURITY NOTICE:
The system comes with remote access to OpenVAS through OMP and the
Greenbone Security Assistant enabled. Please visit
    http://www.openvas.org/vm.html
for news and hints about OpenVAS DEMO Virtual Appliance. We urge
especially first-time users to carefully consider all notes on that
web page for operating the VM. To switch the keyboard layout to
German, use "switchkbd de" as root. To switch face to ITS, use
"./switchface-its" as root and switch back with "./switchface-classic".
The default root password is "root".
Default OpenVAS account: "admin" password: "admin"
Web interface .....: https://192.168.123.13/
OMP interface ..... ip 192.168.123.13 port 9390
No mail.
openvas@openvas:~$
openvas@openvas:~$ _
To direct input to this VM, click inside or press Ctrl+G.
```

Werkzeuge Nessus/OpenVAS Demo



Aufgaben 1 - 3 von 3 (gesamt: 3)

Refresh alle 30 Sek.

Filter: apply_overrides=1 rows=10 permission=any owner=any

Name	Status	Berichte		Schweregrad	Trend	Aktionen
		Gesamt	Letzter			
Immediate scan of IP 127.0.0.1	Abgeschlossen	1 (1)	May 3 2015	6.4 (Mittel)		
Immediate scan of IP 192.168.123.13	Abgeschlossen	1 (1)	May 3 2015	6.4 (Mittel)		
Immediate scan of IP localhost	Abgeschlossen	1 (1)	May 3 2015	4.3 (Mittel)		

(Angewandter Filter: apply_overrides=1 rows=10 permission=any owner=any first=1 sort=name)

1 - 3 von 3 (gesamt: 3)

Willkommen neue Anwender!

Um die umfangreichen Möglichkeiten dieser Anwendung kennenzulernen und um schnell erste Ergebnisse zu erzielen, helfe ich mit Hinweisen und Abkürzungen.

Ich erscheine automatisch dort, wo noch keine oder nur wenige Objekte vorliegen. Und verschwinde wieder, wenn mehr als 3 Objekte vorliegen. Ich kann aber über dieses Icon jederzeit wieder aktiviert werden.

Wenn Sie Hilfe bei der Erstellung neuer Scanaufgaben aber auch mehr Optionen wünschen, können Sie "Erweiterter Aufgaben-Wizard" oben in diesem Fenster auswählen, wo momentan "Aufgaben-Wizard", markiert mit einem kleinen Pfeil, steht.

Für detaillierte Information zu den Funktionen steht das integrierte Hilfe-System zur Verfügung. Dieses steht jederzeit kontext-bezogen über das Hilfe-Icon bereit: ?.

**Schnellstart: Unmittelbar eine IP-Adresse scannen**
IP-Adresse oder Hostname:

Für diese Abkürzung werde ich folgendes durchführen:

1. Erstellen eines neuen Ziels mit voreingestellter Port-Liste
2. Erstellen einer neuen Aufgabe mit diesem Ziel und voreingestellter Scan-Konfiguration
3. Direktes Starten dieser Scan-Aufgabe
4. Wechseln der Ansicht auf Seitenaktualisierung alle 30 Sekunden so dass man sich zurücklehnen und dem Scan-Fortschritt zuschauen kann

Im Grunde muss man sich aber nicht zurücklehnen. Sobald der Scan-Fortschritt über 1% liegt kann man bereits über den Link in der Spalte "Berichte Gesamt" in die Details des Scan-Berichts springen und die bisher gesammelten Ergebnisse einsehen.

Durch Anklicken des "Neue Aufgabe"-Icons kann man Aufgaben auch selbst erstellen. Hierfür wird jedoch auch ein Ziel benötigt, welches erstellt werden kann, indem man auf der Ziele-Seite aus den Konfigurations-Menü auf das Icon "Neues Ziel" klickt.

Scan-Management

Asset-Management

SecInfo-Management

Konfiguration

Extras

Administration

Hilfe

Berichte 1 - 3 von 3 (gesamt: 3) Refresh alle 30 Sek.

Filter: apply_overrides=1 rows=10 permission=any owner=any

Datum	Status	Aufgabe	Schweregrad	Scan-Ergebnisse					Aktionen
				Hoch	Mittel	Niedrig	Log	Falsch Pos.	
Sun May 3 15:33:24 2015	Abgeschlossen	Immediate scan of IP 127.0.0.1	6.4 (Mittel)	0	5	0	19	0	⚠️ ❌
Sun May 3 15:32:58 2015	Abgeschlossen	Immediate scan of IP localhost	4.3 (Mittel)	0	4	0	20	0	⚠️ ❌
Sun May 3 15:32:40 2015	Abgeschlossen	Immediate scan of IP 192.168.123.13	5.4 (Mittel)	0	5	0	19	0	⚠️ ❌

(Angewandter Filter: apply_overrides=1 rows=10 permission=any owner=any sort=reverse=date first=1)

1 - 3 von 3 (gesamt: 3)

Scan-Management

Asset-Management

SecInfo-Management

Konfiguration

Extras

Administration

Hilfe

Aufgaben-Details



Refresh alle 30 Sek.

**Name:** Immediate scan of IP 192.168.123.13

ID: 6966b247-1115-4021-bdb9-42ca65537b65

Kommentar:

Erstellt: Sun May 3 15:32:40 2015

Scan-Konfiguration: Full and fast

Zuletzt geändert: Sun May 3 15:32:43 2015

Benachrichtigungen:

Zeitplan: (Fälligkeit: abgelaufen)

Ziel: Target for immediate scan of IP 192.168.123.13

Reihfolge der Ziel-Hosts: N/A

Netzwerk-Quell-Interface:

Slave:

Status: Abgeschlossen

Berichte: 1 (Abgeschlossen: 1, Letzter: May 3 2015)

Zu Assets hinzufügen: ja

Änderbare Aufgabe: nein

Notizen: 0

Übersteuerungen: 0

Scan-Intensität

Maximal gleichzeitig ausgeführte NVT pro Host: 10

Maximal gleichzeitig gescannte Hosts: 30

Benutzer-Tags für "Immediate scan of IP 192.168.123.13": keine



Berechtigungen für "Immediate scan of IP 192.168.123.13": keine

Leserechte vergeben an

Benutzer



Name

Beschreibung

Aktionen

Scan-Management

Asset-Management

SecInfo-Management

Konfiguration

Extras

Administration

Hilfe

▼ Bericht: Ergebnisse 1 - 24 von 24 (gesamt: 24)

PDF

Abgeschlossen

Filter: sort-reverse=severity result_hosts_only=1 min_cvss_bas

Schwachstelle	Schweregrad	Host	Ort	Aktionen
Raritan Power IQ SQL Injection Vulnerability	6.4 (Mittel)	192.168.123.13	general/tcp	 
Check for SSL Weak Ciphers	4.3 (Mittel)	192.168.123.13	443/tcp	 
POODLE SSLv3 Protocol CBC ciphers Information Disclosure Vulnerability	4.3 (Mittel)	192.168.123.13	443/tcp	 
Check for SSL Weak Ciphers	4.3 (Mittel)	192.168.123.13	9390/tcp	 
POODLE SSLv3 Protocol CBC ciphers Information Disclosure Vulnerability	4.3 (Mittel)	192.168.123.13	9390/tcp	 
CPE Inventory	0.0 (Log)	192.168.123.13	general/CPE-T	 
OS fingerprinting	0.0 (Log)	192.168.123.13	general/tcp	 
DIRB (NASL wrapper)	0.0 (Log)	192.168.123.13	general/tcp	 
arachni (NASL wrapper)	0.0 (Log)	192.168.123.13	general/tcp	 
Nikto (NASL wrapper)	0.0 (Log)	192.168.123.13	general/tcp	 
Traceroute	0.0 (Log)	192.168.123.13	general/tcp	 
Services	0.0 (Log)	192.168.123.13	80/tcp	 
Identify unknown services with nmap	0.0 (Log)	192.168.123.13	80/tcp	 
wapiti (NASL wrapper)	0.0 (Log)	192.168.123.13	80/tcp	 
Identify unknown services with nmap	0.0 (Log)	192.168.123.13	111/tcp	 
Services	0.0 (Log)	192.168.123.13	443/tcp	 

Scan-Management

Asset-Management

SecInfo-Management

Konfiguration

Extras

Administration

Hilfe

Ergebnis-Details ? ☰ ⬇

Aufgabe: [Immediate scan of IP 192.168.123.13](#)

ID: 5eb9abec-6533-4861-9491-a41ca2d820a5

Schwachstelle	Schweregrad	Host	Ort	Aktionen
Raritan Power IQ SQL Injection Vulnerability	6.4 (Mittel)	192.168.123.13	general/tcp	 

Zusammenfassung

Raritan Power IQ SQL Injection Vulnerability

Ergebnis zur Schwachstellenerkennung

Schwachstelle wurde gemäß der Methode zur Schwachstellenerkennung erkannt.

Auswirkungen

Successful exploitation will allow attacker to inject or manipulate SQL queries in the back-end database, allowing for the manipulation or disclosure of arbitrary data.

LösungInstall the patch from Raritan at <https://www.raritan.com/support/product/poweriq/security-patches>**Betroffene Software/OS**

Raritan Power IQ 4.2.2, 4.1.3 and below.

Schwachstellen-Einblick

Raritan PowerIQ is vulnerable to SQL injection. A remote attacker could send specially-crafted SQL statements to the /license/records script using the sort or dir parameter, which could allow the attacker to view, add, modify or delete information in the back-end database.

Methode zur Schwachstellenerkennung

Perform a time-based blind SQL injection request.

Details: [Raritan Power IQ SQL Injection Vulnerability \(OID: 1.3.6.1.4.1.25623.1.0.105922\)](#)

Benutzte Version: \$Revision: 673 \$

Verweise

Name: Raritan Power IQ SQL Injection Vulnerability

ID: 1.3.6.1.4.1.25623.1.0.105922

Konfiguration:

Zuletzt geändert: Wed Sep 17 10:01:04 2014

Familie: Web application abuses

Erstellt: Fri Aug 15 09:50:19 2014

OID: 1.3.6.1.4.1.25623.1.0.105922

Version: \$Revision: 673 \$

Notizen: 0

Übersteuerungen: 0

Zusammenfassung

Raritan Power IQ SQL Injection Vulnerability

Betroffene Software/OS

Raritan Power IQ 4.2.2, 4.1.3 and below.

Schwachstellen-Bewertung

CVSS-Basissscore:  6.4CVSS-Basisvektor: [AV:N/AC:L/Au:N/C:P/I:P/A:N](#)

Schwachstellen-Einblick

Raritan PowerIQ is vulnerable to SQL injection. A remote attacker could send specially-crafted SQL statements to the `/license/records` script using the `sort` or `dir` parameter, which could allow the attacker to view, add, modify or delete information in the back-end database.

Methode zur Schwachstellenerkennung

Perform a time-based blind SQL injection request.

Auswirkungen

Successful exploitation will allow attacker to inject or manipulate SQL queries in the back-end database, allowing for the manipulation or disclosure of arbitrary data.

Lösung

Schwachstelle	Schweregrad		Host	Ort	Aktionen
Check for SSL Weak Ciphers	4.3 (Mittel)		192.168.123.13	443/tcp	 

Zusammenfassung

This routine search for weak SSL ciphers offered by a service.

Ergebnis zur Schwachstellenerkennung

Weak ciphers offered by this service:

SSL3_RSA_RC4_128_SHA
TLS1_RSA_RC4_128_SHA

Lösung

The configuration of this services should be changed so that it does not support the listed weak ciphers anymore.

Schwachstellen-Einblick

These rules are applied for the evaluation of the cryptographic strength:

- Any SSL/TLS using no cipher is considered weak.
- All SSLv2 ciphers are considered weak due to a design flaw within the SSLv2 protocol.
- RC4 is considered to be weak.
- Ciphers using 64 bit or less are considered to be vulnerable to brute force methods and therefore considered as weak.
- 1024 bit RSA authentication is considered to be insecure and therefore as weak.
- CBC ciphers in TLS < 1.2 are considered to be vulnerable to the BEAST or Lucky 13 attacks
- Any cipher considered to be secure for only the next 10 years is considered as medium
- Any other cipher is considered as strong

Methode zur Schwachstellenerkennung

Details: [Check for SSL Weak Ciphers \(OID: 1.3.6.1.4.1.25623.1.0.103440\)](#)

Benutzte Version: \$Revision: 733 \$

Name: Check for SSL Weak Ciphers

ID: 1.3.6.1.4.1.25623.1.0.103440

Konfiguration:

Zuletzt geändert: Mon Oct 6 07:23:48 2014

Familie: General

Erstellt: Thu Mar 1 16:16:10 2012

OID: 1.3.6.1.4.1.25623.1.0.103440

Version: \$Revision: 733 \$

Notizen: 0

Übersteuerungen: 0

Zusammenfassung

This routine search for weak SSL ciphers offered by a service.

Schwachstellen-Bewertung

CVSS-Basisscore:  4.3CVSS-Basisvektor: [AV:N/AC:M/Au:N/C:P/I:N/A:N](#)

Schwachstellen-Einblick

These rules are applied for the evaluation of the cryptographic strength:

- Any SSL/TLS using no cipher is considered weak.
- All SSLv2 ciphers are considered weak due to a design flaw within the SSLv2 protocol.
- RC4 is considered to be weak.
- Ciphers using 64 bit or less are considered to be vulnerable to brute force methods and therefore considered as weak.
- 1024 bit RSA authentication is considered to be insecure and therefore as weak.
- CBC ciphers in TLS < 1.2 are considered to be vulnerable to the BEAST or Lucky 13 attacks
- Any cipher considered to be secure for only the next 10 years is considered as medium
- Any other cipher is considered as strong

Lösung

The configuration of this services should be changed so that it does not support the listed weak ciphers anymore.

Schwachstelle	Schweregrad	Host	Ort	Aktionen
POODLE SSLv3 Protocol CBC ciphers Information Disclosure Vulnerability	4.3 (Mittel)	192.168.123.13	443/tcp	 
Zusammenfassung This host is installed with OpenSSL and is prone to information disclosure vulnerability.				
Ergebnis zur Schwachstellenerkennung Schwachstelle wurde gemäß der Methode zur Schwachstellenerkennung erkannt.				
Auswirkungen Successful exploitation will allow a man-in-the-middle attackers gain access to the plain text data stream. Impact Level: Application				
Lösung Vendor released a patch to address this vulnerabiliy, For updates contact vendor or refer to https://www.openssl.org NOTE: The only correct way to fix POODLE is to disable SSL v3.0				
Betroffene Software/OS OpenSSL through 1.0.1i				
Schwachstellen-Einblick The flaw is due to the block cipher padding not being deterministic and not covered by the Message Authentication Code				
Methode zur Schwachstellenerkennung Send a SSLv3 request and check the response. Details: POODLE SSLv3 Protocol CBC ciphers Information Disclosure Vulnerability (OID: 1.3.6.1.4.1.25623.1.0.802087) Benutzte Version: \$Revision: 787 \$				
Verweise CVE: CVE-2014-3566 BID: 70574 CERT: DFN-CERT-2014-1717 , DFN-CERT-2014-1680 , DFN-CERT-2014-1632 , DFN-CERT-2014-1564 , DFN-CERT-2014-1542 , DFN-CERT-2014-1414 , DFN-CERT-2014-1366 , DFN-CERT-2014-1354 Anderer: http://osvdb.com/113251 https://www.openssl.org/~bodo/ssl-poodle.pdf https://www.imperialviolet.org/2014/10/14/poodle.html				

**Name:****POODLE SSLv3 Protocol CBC ciphers Information Disclosure Vulnerability**

ID: 1.3.6.1.4.1.25623.1.0.802087

Zuletzt geändert: Tue Nov 4 16:25:34 2014

Erstellt: Thu Oct 16 11:59:43 2014

Konfiguration:

Familie: General

OID: 1.3.6.1.4.1.25623.1.0.802087

Version: \$Revision: 787 \$

Notizen: 0

Übersteuerungen: 0

Zusammenfassung

This host is installed with OpenSSL and is prone to information disclosure vulnerability.

Betroffene Software/OS

OpenSSL through 1.0.1i

Schwachstellen-Bewertung

CVSS-Basisscore:  4.3CVSS-Basisvektor: [AV:N/AC:M/Au:N/C:P/I:N/A:N](#)

Schwachstellen-Einblick

The flaw is due to the block cipher padding not being deterministic and not covered by the Message Authentication Code

Methode zur Schwachstellenerkennung

Send a SSLv3 request and check the response.

Auswirkungen

Successful exploitation will allow a man-in-the-middle attackers gain access to the plain text data stream.

Impact Level: Application

Zusammenfassung

This host is installed with OpenSSL and is prone to information disclosure vulnerability.

Betroffene Software/OS

OpenSSL through 1.0.1i

Schwachstellen-Bewertung

CVSS-Basisscore:  4.3

CVSS-Basisvektor: [AV:N/AC:M/Au:N/C:P/I:N/A:N](#)

Schwachstellen-Einblick

The flaw is due to the block cipher padding not being deterministic and not covered by the Message Authentication Code

Methode zur Schwachstellenerkennung

Send a SSLv3 request and check the response.

Auswirkungen

Successful exploitation will allow a man-in-the-middle attackers gain access to the plain text data stream.

Impact Level: Application

Lösung

Vendor released a patch to address this vulnerabiliy, For updates contact vendor or refer to <https://www.openssl.org>

NOTE: The only correct way to fix POODLE is to disable SSL v3.0

Verweise

CVE: [CVE-2014-3566](#)

BID: [70574](#)

CERT: [DFN-CERT-2014-1717](#), [DFN-CERT-2014-1680](#), [DFN-CERT-2014-1632](#), [DFN-CERT-2014-1564](#), [DFN-CERT-2014-1542](#), [DFN-CERT-2014-1541](#), [DFN-CERT-2014-1366](#), [DFN-CERT-2014-1354](#)

Name: CVE-2014-3566

CWE-ID: CWE-310

ID: CVE-2014-3566

Veröffentlicht: 2014-10-14T20:55:02.137-04:00

Zuletzt geändert: 2014-12-11T22:01:45.237-05:00

Zuletzt aktualisiert: 2015-01-14T08:04:00.000+0000

Beschreibung

The SSL protocol 3.0, as used in OpenSSL through 1.0.1i and other products, uses nondeterministic CBC padding, which makes it easier for man-in-the-middle attackers to obtain cleartext data via a padding-oracle attack, aka the "POODLE" issue.

CVSS

Base score	 4.3 (AV:N/AC:M/Au:N/C:P/I:N/A:N)
Access vector	NETWORK
Access Complexity	MEDIUM
Authentication	NONE
Confidentiality impact	PARTIAL
Integrity impact	NONE
Availability impact	NONE
Source	http://nvd.nist.gov
Generated	2014-10-15T14:51:12.403-04:00

Verweise

CERT

TA14-290A

<http://www.us-cert.gov/ncas/alerts/TA14-290A>

CERT-VN

VU#577193

<http://www.kb.cert.org/vuls/id/577193>

CONFIRM

<https://www.suse.com/support/kb/doc.php?id=7015773>

<https://www.suse.com/support/kb/doc.php?id=7015773>

CONFIRM

https://www.openssl.org/news/secadv_20141015.txt

https://www.openssl.org/news/secadv_20141015.txt

MISC

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

Scan-Management

Asset-Management

SecInfo-Management

Konfiguration

Extras

Administration

Hilfe

DFN-CERT-Advisory-Details ?

Name:	DFN-CERT-2014-1717	ID:	DFN-CERT-2014-1717
Titel:	OpenSSL: Mehrere Schwachstellen ermöglichen u.a. Denial-of-Service-Angriffe (Linux, Fedora)	Erstellt:	2014-12-29T08:48:26Z
Advisory-Link:	https://openvas.dfn-cert.de/adv/DFN-CERT-2014-1717/	Zuletzt geändert:	2014-12-29T09:36:42Z
Schweregrad:	6.8		

Zusammenfassung

Mehrere Schwachstellen in OpenSSL ermöglichen einem entfernten, nicht authentisierten Angreifer die Durchführung von Denial-of-Service- und Man-in-the-Middle-Angriffen, das Umgehen von Sicherheitsvorkehrungen, das Ausführen von Programmcode sowie das Ausspähen von Informationen. Für die Distributionen Fedora 20, Fedora 21 und für Fedora EPEL 7 stehen Sicherheitsupdates für mingw-openssl zur Verfügung, welche mit der Version openssl-1.0.1j-3.fc22rn synchronisiert wurden. Für Fedora EPEL 7 werden die Schwachstellen CVE-2014-3509 und CVE-2014-3566 nicht benannt.

CVE-Verweise

- [CVE-2014-3566](#)
- [CVE-2014-3511](#)
- [CVE-2014-3510](#)
- [CVE-2014-3509](#)
- [CVE-2014-3508](#)
- [CVE-2014-3507](#)
- [CVE-2014-3506](#)
- [CVE-2014-3505](#)
- [CVE-2014-3470](#)
- [CVE-2014-0224](#)
- [CVE-2014-0221](#)
- [CVE-2014-0195](#)
- [CVE-2014-0198](#)
- [CVE-2010-5298](#)

Benutzer-Tags für "DFN-CERT-2014-1717": keine ★ ?

Scan-Management

Asset-Management

SecInfo-Management

Konfiguration

Extras

Administration

Hilfe

Ergebnis-Details ? ☰ ↓

Aufgabe: [Immediate scan of IP 192.168.123.13](#)

ID: b861a4fa-5166-4df1-87d2-1d46398c083e

Schwachstelle	Schweregrad	Host	Ort	Aktionen
OS fingerprinting	0.0 (Log)	192.168.123.13	general/tcp	 

Zusammenfassung

This script performs ICMP based OS fingerprinting (as described by Ofir Arkin and Fyodor Yarochkin in Phrack #57). It can be used to determine remote operating system version.

Ergebnis zur Schwachstellenerkennung

ICMP based OS fingerprint results: (69% confidence)

HP JetDirect

Log-Methode

Details: [OS fingerprinting \(OID: 1.3.6.1.4.1.25623.1.0.102002\)](#)

Benutzte Version: \$Revision: 43 \$

Verweise

Anderer: <http://www.phrack.org/issues.html?issue=57&id=7#article>

Benutzer-Tags für dieses Ergebnis: keine ★ ?

Scan-Management

Asset-Management

SecInfo-Management

Konfiguration

Extras

Administration

Hilfe

NVT-Details ?

Name: OS fingerprinting

ID: 1.3.6.1.4.1.25623.1.0.102002

Konfiguration:

Zuletzt geändert: Mon Nov 4 19:51:40 2013

Familie: Product detection

Erstellt: Tue May 19 10:05:50 2009

OID: 1.3.6.1.4.1.25623.1.0.102002

Version: \$Revision: 43 \$

Notizen: 0

Übersteuerungen: 0

Zusammenfassung

This script performs ICMP based OS fingerprinting (as described by Ofir Arkin and Fyodor Yarochkin in Phrack #57). It can be used to determine remote operating system version.

Schwachstellen-Bewertung

CVSS-Basisscore: 0.0

CVSS-Basisvektor: AV:N/AC:L/Au:N/C:N/I:N/A:N

Verweise

Anderer: <http://www.phrack.org/issues.html?issue=57&id=7#article>

Vorgaben

Name	Standardwert	Aktionen
Timeout	Standard	



Scan-Management

Asset-Management

SecInfo-Management

Konfiguration

Extras

Administration

Hilfe

CVSS-Basiscore-Rechner?

Aus Metriken:

Access Vector: Network ▼

Access Complexity: Low ▼

Authentication: None ▼

Confidentiality: None ▼

Integrity: None ▼

Availability: None ▼

Berechnen

Aus Vektor:

AV:N/AC:L/Au:N/C:N/I:N/A:N

Berechnen

Basisvektor: AV:N/AC:L/Au:N/C:N/I:N/A:N

Basiscore: 0.0

CVSS Common Vulnerability Scoring System

- **CVSS Base Vectors**

- (AV:[L,A,N]/AC:[H,M,L]/Au:[N,S,M]/C:[N,P,C]/I:[N,P,C]/A:[N,P,C])
- **Metric:** AV = AccessVector (Related exploit range)
L = Local access, A = Adjacent network, N = Network
- **Metric:** AC = AccessComplexity (Required attack complexity)
H = High, M = Medium, L = Low
- **Metric:** Au = Authentication (Level of authentication needed to exploit)
N= None, S= Requires single instance, M= multiple
- **Metric:** C = ConfImpact (Confidentiality impact)
N = None, P = Partial, C = Complete
- **Metric:** I = IntegImpact (Integrity impact)
N = None, P = Partial, C = Complete
- **Metric:** A = AvailImpact (Availability impact)<>
N = None, P = Partial, C = Complete

CVSS Common Vulnerability Scoring System II

- Quellen dazu
- <https://nvd.nist.gov/vuln-metrics/cvss/vector-v2>
- Neben Basisvektor auch
 - Temporal Vector
 - + Exploitability, RemediationLevel, ReportConfidence
 - Environmental Vector
 - + Collateral Damage Potential, Target Distribution, System Confidentiality/Integrity/Availability Requirement

Ergebnis-Details ? ☰ ⬇

Aufgabe: [Immediate scan of IP 192.168.123.13](#)

ID: 89e03426-217f-4869-8d3e-241a75636456

Schwachstelle	Schweregrad	Host	Ort	Aktionen
Services	0.0 (Log)	192.168.123.13	80/tcp	🔍 ⭐

Zusammenfassung

This plugin attempts to guess which service is running on the remote ports. For instance, it searches for a web server which could listen on another port than 80 and set the results in the plugins knowledge base.

Ergebnis zur Schwachstellenerkennung

An unknown service is running on this port.
It is usually reserved for HTTP

Log-MethodeDetails: [Services \(OID: 1.3.6.1.4.1.25623.1.0.10330\)](#)

Benutzte Version: \$Revision: 69 \$

Benutzer-Tags für dieses Ergebnis: keine ★ ?

OpenVAS SecInfo-Management (Stand 2015)

- 37.577 NVTs – Network Vulnerability Test
- 67.928 CVEs - Common Vulnerabilities and Exposures
- 194.619 CPEs - Common Platform Enumeration
- 27.098 OVAL-Defs - Open Vulnerability and Assessment Language
- 2.971 DFN-CERT-Advisories
- Insgesamt 330.193 Schwachstellen (ggf mehrfach benannt).

OpenVAS SecInfo-Management

Stand 2017

- > 50.000 NVTs – Network Vulnerability Test
- 87.924 CVEs - Common Vulnerabilities and Exposures

Stand 2024

- >150.000 Vulnerability Tests
- 237.725 CVEs