

Question **1**

Answer saved

Marked out of 4.00

🚩 Flag question

Consider the following partial class declaration of an ADT:

```
class Employee

{

    friend ostream& operator << (ostream& outs,  const Employee & the_emp);  //output name and salary with salary in the format Rxxx.xx

public:

    Employee(string n, double sal);

    ~Employee();

    void setSalary(double sal);

    string getName()const;

    void raiseSalary(double percent); // raises an employee's salary with the percentage specified by the argument percent

private:

    string name;

    double salary;

};
```

Complete the code below by choosing the correct options in the drop-down lists. The comment with each drop-down list describes the action that the option you choose from the drop-down list should achieve.

```
Employee newEmployee ("Mpho Malebane", 123000); // Use the overloaded constructor to instantiate an object newEmployee of
the class Employee with the name "Mpho Malebane"

//and a salary of R123 000

if (newEmployee.getName() == "Mpho Malebane") // Write a statement to check whether the object newEmployee is Mpho Malebane
newEmployee.raiseSalary(10); // Raise Mpho Malebane's salary with 10%

cout << newEmployee << endl; // Use the overloaded stream insertion operator to display
the name and salary of the newEmployee on the screen
```

Question **2**

Answer saved

Marked out of 1.00

🚩 Flag question

Given the declarations

```
string *p1;

int arraySize;
```

The correct code to declare a dynamic array of strings (using the string pointer variable p1) that has arraySize elements is `p1 = new string[arraySize];`