

Question **5**

Answer saved

Marked out of 1.00

🚩 Flag question

When would you want to make a function a function template?

Select one:

- ☐ All functions should be function templates.
- ☒ When the implementation details of the function are independent of the data type(s) of the parameters.
- ☐ Only when two functions have the same type of parameters.
- ☐ When two different functions have different implementation details.

Clear my choice

Question **6**

Answer saved

Marked out of 8.00

🚩 Remove flag

For this question you have to type code in the textbox provided. You cannot attach a file as answer. NB: do not use TAB when entering your code, rather use spaces to indent.

Consider the following (partial) class declaration of an ADT provided in a file `Player.h`:

```
class Player
{
    friend bool operator > (const Player &player1, const Player &player2); // returns true if player1 has more points than player2, false otherwise

    friend ostream & operator<<(ostream & out, const Player & P); //displays player's name and points

public:
    Player();
    ~Player();
    string getName() const;
    void setPoints(int p);

private:
    string name;
    int points;
};
```

Using **separate compilation**, provide the **implementation file** for the class `Player`. Include all the necessary header files, and implement **only** the member functions in the given class declaration. There is no need for comments.

↴

A ▼

B

I

☰

☰

☰

☰

🔗

🔄

😊

🖼️

```
#include <iostream>
#include <string>
#include "Player.h"

using namespace std;

bool operator > (const Player &player1, const Player &player2) {
    return player1.points > player2.points;
};

ostream& operator <<(ostream& out, const Player &P) {
    out
        << "Player name: " << P.name
        << "Player points: " << P.points
    ;
    return out;
};

Player::Player():
```