

Question **13**

Answer saved

Marked out of 1.00

🚩 Flag question

Consider the following function headers:

```
double calcVolume (double width, double height, double length);
double calcVolume (double radius);
double calcVolume (double radius, double height);
```

The function call

```
cout << calcVolume(7.3, 5.1);
```

will execute this function

Select one:

- ☐ double calcVolume (double radius);
- ☐ It will give a compiler error.
- ☐ double calcVolume (double width, double height, double length);
- ☒ double calcVolume (double radius, double height);

Clear my choice

Question **14**

Not yet answered

Marked out of 8.00

🚩 Remove flag

For this question you have to type code in the textbox provided. You cannot attach a file as answer. NB: do not use TAB when entering your code, rather use spaces to indent.

Use **separate compilation** to **declare a class** `Player` as an **ADT**. Remember to include the necessary directives.

The class `Player` has two member variables,

- `name`, the name of the player (a string) and
- `points`, the number of points accumulated (an integer).

Provide only the class declaration (interface) for the class `Player`. The class `Player` has the following member functions:

- an overloaded constructor to initialise the member variables to specific values
- a destructor
- an accessor for the member variable `points`
- a mutator for the member variable `name`
- a member function `increment()` that increments the points by a value passed as parameter
- an overloaded stream extraction operator for the class `Player`.

↴

A ▾

B

I

≡

≡

≡

≡

🔗

🔗

😊

🖼️