



GREEN 3 D SOLUTIONS

G 30 F



Transformation method	Adaptable and self-controlled thermal dehydration
Configuration	Autonomous, mobile
Load capacity	15 Kgs minimum – 30 Kgs maximum
Average reduction	80-90 %
Treatment time	Adaptable from 9H00 to 14H00 depending on the bio-waste introduced
Electrical connection	Single-phase 20 amperes / AC 220V 50 Hz / 2P + Neutral + Ground
Electrical consumption	1.5 kW average hourly
Dimensions (L x W x H) in cm	80 x 80 x 120
Weight in kg	185
Material used	Stainless steel
Safety equipment	CE certified – Mixer stops when loading or unloading door is opened
Drying method	Indirect with air recirculation
Automated control	Process control PLC for dehydration management. Automatic stop at end of cycle with visual indication (Additional option: audible). Automated cycle
Control panel	Start commands: Push button to launch cycle (Option: delayed start) – Reset – Unloading Cooling by push button – Programmable temperature and time settings
Odour treatment	Integrated deodorisation and total odour control
Water drainage	At the back of the machine, via flexible hose Diam 12/17
Processed materials	Organic and food waste
Prohibited materials	All plastics – all metals – All types of glass – All non-organic waste
Weighing – kW consumption	Integrated weighing optional - Electrical consumption meter optional
Various options	To be defined together upon order (Maintenance and servicing contract – etc...)
Warranty	2-year warranty under normal use

USE

The GREEN G' – 30 F system is designed for use in collective catering, medium-sized supermarkets and collective catering companies.

ADVANTAGES

- Treatment of food waste on the production site
- Simple, fast and easy use of the system by unskilled staff
- No fresh water connection required
- Treatment without micro-organisms, enzymes or additives
- No environmental impact
- Reduction of their volume by 80 to 90% depending on their moisture content
- No air discharge
- Low maintenance
- The processed product is dry and stabilised for agronomic use (fertiliser) or energy use (methanisation)

PROCESS

By thermal dehydration using electrical energy and automating the control processes. The system is equipped with water recycling technology that uses condensation and controls humidity in the treatment chamber during the process. The treatment time varies according to the quantity of waste and their moisture content; it is determined automatically. The system stops and waits for unloading when the residual moisture content is reached. The duration of a treatment cycle varies between 9 and 14 hours.

TECHNICAL DESCRIPTIONS

The waste storage chamber is equipped with a mechanical agitator and a double insulated wall containing thermal oil. The inlet and outlet doors are sealed to confine odours and minimise energy consumption. The system is equipped with an air flow management and odour neutralisation device. Only an electrical connection and a condensate drainage pipe are required.

FINISH: All external surfaces are in polished 316L stainless steel.

Site: green3dsolutions.com - email: contact@green3dsolutions.com - tel: +33(0)74059668 tél: +33(0)684505985