

Symbolic Gossip

Joris Galema
Madeleine Gignoux
Djanira Gomes
Wouter Smit

Thursday 30th May, 2024

Abstract

TODO ABSTRACT

Contents

1	Introduction	2
2	Background	2
3	Gossip Scene Investigation	4
4	Transparent Transformer	7
5	Simple Transformer	8
6	Testing	10
6.1	Gossip Scene Investigation	10
6.2	Transparent Transformer	11
6.3	Simple Transformer	12
7	Conclusion	13
	Bibliography	13

1 Introduction

The Gossip Problem or *Gossip* is the problem of sharing information in a network. Many variants of Gossip exist, each with their own computational challenges. Most notably, a distinction is made between the *Transparent* Gossip Problem - the situation where all agents know which agents exchange information at any update - and the *Synchronous* Gossip Problem, where agents know when an update occurs but not which agents exchange information during that update.

For modelling Gossip, an explicit model checker for Gossip called *GoMoChe* exists [Gat23]. Explicit model checkers are generally less efficient than symbolic ones, which aim to cut down on computation time. GoMoChe too is therefore computationally limited to small examples. On the other hand, a symbolic model checker for dynamic epistemic logic (DEL) called SMCDEL exists, which is much more general than *GoMoChe*. SMCDEL is implemented for both K and $S5$ and contains symbolic representations for various logic problems, including Gossip [Gat18]. However, in terms of Gossip, SMCDEL only covers an encoding of the Synchronous Gossip Problem (in standard $S5$ DEL), and the implementation of its update function causes the model to blow up in terms of complexity.

A solution to this exponential blowup was proposed in the unpublished master's thesis by [Rei23], in the shape of a *Simple Knowledge Transformer* that should replace the *Classic Knowledge Transformer* from SMCDEL. An existing implementation by [Yuk23] extends SMCDEL to incorporate updates with Simple Transformers, but an instance of this transformer tailored to the Gossip problem wasn't included.

This project expands on SMCDEL's functionality. Section 2 contains a description of the Classic Knowledge Transformer in SMCDEL, and specifically how it is used to model updates to the state in [Gat18]. Next, Section 3 contains a number of functions that provide an interpretation of the current state, which makes the Synchronous Gossip Problem already provided in SMCDEL more user-friendly. Next we create a variant of the Classic Transformer for the transparent variant of the Gossip Problem in Section 4. To conclude our work, Section 5 describes our implementation of the Simple Transformer, which cuts down on the complexity of computing the Synchronous Gossip Problem, with the tradeoff of losing higher-order knowledge. Finally, the code of Section 3, 4, and 5 is tested in Subsections 6.1, X (see fixme), and 6.3 respectively.

2 Background

For the language and syntax of Gossip, please refer to [Gat18] (Section 6.6). We discuss how the Gossip Problem is approached in SMCDEL using [Gat18] (in particular, Section 6.6.5 on Symbolic Gossip). For an in-depth explanation, please refer to the aforementioned source.

The Gossip Problem models the flow of information called secrets. At the initial state of the problem, no information has been shared and each agent knows only their own secret. The goal is for the agents to exchange all secrets, which happens through *updates* on the model, which is called a *Knowledge Structure*. The Knowledge Structure and the actual state are described by the *vocabulary* (V), *state law* (θ), and *observations* (O_i for each agent i). The vocabulary V expresses all existing atomic propositions of the form S_{ij} , where S_{ij} denotes agent i knowing agent j 's secret. Next, the state law θ describes the possible worlds in the current

model. Following the conceptual assumption that all agents are aware of the model they reside in, θ is common knowledge among the agents. Initially, θ states that nobody knows anyone else's secret. Finally, the observations O_i describe which propositional variables agent i observes; following [Gat18], the observations are initially empty for all agents. Throughout the run of the model, propositions are added to the observables, which encode which calls each agent can observe.

For the sake of simplicity, the notions of knowing one's own secret are completely removed. Equation 1 (from [Gat18]) shows the tuple describing the initial Knowledge Structure.

$$F_{\text{init}} = (V = \{S_{ij} \mid i, j \text{ Agents}, i \neq j\}, \theta = \bigwedge_{i \neq j} \neg S_{ij}, O_i = \emptyset) \quad (1)$$

In order to transform the model after a call happens, we use a Knowledge Transformer. The crux of this paper involves changing the Knowledge Transformer for the Synchronous Gossip Problem provided in SMCDEL to fit our needs.

The Knowledge Transformer explains how the state should change after an update, in this case an arbitrary call. The vocabulary is extended with propositional variables q_{ij} , which express that agent i called agent j . Recalling that we are dealing with the Synchronous Gossip Problem, where agents only know a call occurred, but not which two agents called, we encode this into two laws θ^+ and θ_- , where θ^+ (also: *preconditions* for a call) expresses that exactly one call happens, and θ_- (also: *postconditions* of a call) expresses the conditions under which agent i can learn agent j 's secret. Finally, each agent i observes only calls they participate in, which we describe in O_i^+ .

In short, the Knowledge Transformer for The Synchronous Gossip Problem is the quintuple $\chi_{\text{call}} = (V^+, \theta^+, V_-, \theta_-, O^+)$ (see [Gat18], page 195 for the exact encoding).

The design of the Knowledge Transformer allows it to encode and check higher-order knowledge, but it also poses a problem in the form of exponential blowup. The state law (θ) keeps track of the updates in the model and is itself updated using θ^+ and θ_- . Essentially, the state law after the final update forms a conjunction of the original state law with event laws (θ^+) for each update and **changelaws** (θ_-), such that the validity of a logical formula on a given Knowledge Structure can be evaluated by solely checking if it's implied by the state law.

However, it is possible for an update to create states that previously were excluded by the state law. In order to allow this type of flexibility, each update causes all propositional variables of the form S_{ij} to be copied and labelled in the state law. For example, suppose Alice learns Bob's secret during update n . Any occurrence of the corresponding proposition $S_a b$ in the state law need to be flagged in update $n + 1$, just in case Alice would *forget* Bob's secret in some future update. A copy of $S_a b$ is added and now exists alongside the flagged version (denoted by $(S_a b)^o$ to indicate that it is an "old" proposition). Even for a small number of agents and calls (say, 4 agents and 3 calls), the blowup of the state law is as such that it's unfeasible to print an example of the representation of the resulting Knowledge Structure.

The possibility of the truth value $S_a b$ to change back to false is an unrealistic hypothetical in Gossip, as in this situation agents aren't modelled to forget any secrets. However, SMCDEL is implemented for a wide range of logical problems, which prevents it from making such assumptions.

The existing implementation ([Gat18]) includes optimization functions that discard the redundant

propositions (by checking which propositional variables are equivalent), but this optimization is only implemented to be run after running the model and is therefore not optimal.

With this background on how to model Gossip symbolically, we write our own transformer for modelling the transparent variant of The Gossip Problem, implement an adapted optimization that runs in between updates, and a simple transformer based on Daniel Reifsteck’s master’s thesis.

3 Gossip Scene Investigation

This section explains the functions that we created to make sense of the current state of a given gossip problem, i.e. gossip scene investigation. The functions only work on the unoptimized, Classic Transformer, since the code relies on the exact vocabulary being copied. First of all, the code makes use of the following imports:

```
module Explain where

--import SMCDEL.Examples.GossipS5      <-- fixme: redundant import acc. to vscode?
import SMCDEL.Symbolic.S5
import SMCDEL.Language
import SMCDEL.Other.BDD2Form
import Data.Maybe
```

One remarkable property of the SMCDEL implementation [Gat18] is how the transformer updates the vocabulary by copying all of the secret propositions. This means that in any given transformation, there will be a propositional variable representing a secret S_{ij} , as well as a copy of said variable $(S_{ij})^o$. Moreover, we have propositions for calls q_{ij} . In order to prevent overlap between the several groups of variables, a unique value is computed for each propositional variable. A propositional variable is of the form Pi , where i is generated using one of the following functions ([Gat18]):

```
-- a has the secret of b
hasSof :: Int -> Int -> Int -> Prp
hasSof n a b | a == b    = error "Let's not even talk about that."
              | otherwise = toEnum (n * a + b)

-- a calls b
thisCallProp :: (Int,Int) -> Prp
thisCallProp (i,j) | i < j    = P (100 + 10*i + j)
                  | otherwise = error $ "wrong call: " ++ show (i,j)
```

In order to make the description of a Knowledge Structure human-readable, we defined the following functions to translate the encoded propositions: `prpLibrary` checks whether a proposition denotes a secret, call proposition, or copy of a secret. The function takes the vocabulary as input, as well as the number of agents, and returns the library from which we can decipher propositions in our gossip scene investigation.

```
prpLibrary :: [Prp] -> Int -> [(Prp,String)]
prpLibrary prps n = zip prps (prpLibraryHelper prps)
  where
    -- assign the propositions to secrets, calls, and copies of secrets
    -- and decode each with the appropriate decoder
    prpLibraryHelper :: [Prp] -> [String]
```

```

prpLibraryHelper [] = []
prpLibraryHelper prps' = a ++ copyDecoder (drop (div (3*n*(n-1)) 2) prps') a " "
  where
    a =      secretDecoder (take (n*(n-1)) prps')
      ++ callDecoder 0 (take (div (n*(n-1)) 2) (drop (n*(n-1)) prps'))

-- decode secrets
secretDecoder :: [Prp] -> [String]
secretDecoder [] = []
secretDecoder ((P p):ps) = ("s" ++ show i ++ show j) : secretDecoder ps
  where (i, j) = (p 'quot' n, p 'rem' n)

-- decode calls
callDecoder :: Int -> [Prp] -> [String]
callDecoder k calls | k >= div (n*(n-1)) 2 = []
  | null calls = []
  | otherwise = ("q" ++ show i ++ show j) : callDecoder (k + 1)
    calls
  where
    (i, j) = getCNums k 0
    getCNums :: Int -> Int -> (Int, Int)
    getCNums k' r'' | (k'+1) < n = (r'', k'+1)
      | otherwise = getCNums (k'-n+2+r'') (r''+1)

-- decode copies
copyDecoder :: [Prp] -> [String] -> String -> [String]
copyDecoder [] _ _ = []
copyDecoder props lib r = map (++r) lib ++ copyDecoder (drop (length lib) props) lib
  (r++" ")

```

Additionally, we wrote the (unsafe) function `explainPrp`, which takes in a proposition as well as the library, to return its meaning (as String).

```

explainPrp :: Prp -> [(Prp, String)] -> String
explainPrp (P x) prpLib = fromJust (lookup (P x) prpLib)

```

We follow this up with `gsi`, our gossip scene investigation, which takes in a knowledge scene and the number of agents, and uses `explainPrp` to make sense of the vocabulary and observations.

```

-- Gossip Scene Investigation: GSI. ...like the tv show but with less crime and more gossip
--
gsi :: KnowScene -> IO ()
gsi kns@(KnS voc stl obs, s) = do
  putStrLn "Vocabulary: "
  mapM_ (putStrLn . (++) " -- " . \p -> explainPrp p lib) voc
  putStrLn "State Law: "
  print (ppFormWith ('explainPrp' lib) (formOf stl))
  putStrLn "Observables: "
  mapM_ (putStrLn . (++) " -- " . (\ x -> fst x ++ ": " ++ show (map ('explainPrp' lib)
    (snd x))) ) obs
  putStrLn "Actual state: "
  if null s then putStrLn " -- Nobody knows about any other secret"
  else
    mapM_ (putStrLn . (++) " -- " . \p -> explainPrp p lib) s
  where
    lib = prpLibrary voc (length $ agentsOf kns)

```

We can then run the following:

```

import SMCDEL.Examples.GossipS5
ghci> gsi $ gossipInit 3
Vocabulary:
-- s01
-- s02
-- s10

```

```

-- s12
-- s20
-- s21
State Law:
"(~s01 & ~s02 & ~s10 & ~s12 & ~s20 & ~s21)"
Observables:
-- 0: []
-- 1: []
-- 2: []
Actual state:
-- Nobody knows about any other secret

ghci> gsi $ doCall (gossipInit 3) (0,1)
Vocabulary:
-- s01
-- s02
-- s10
-- s12
-- s20
-- s21
-- q01
-- q02
-- q12
-- s01'
-- s02'
-- s10'
-- s12'
-- s20'
-- s21'
State Law:
"((s01 & ~s02 & s10 & ~s12 & ~s20 & ~s21 & q01 & ~q02
  & ~q12 & ~s01' & ~s02' & ~s10' & ~s12' & ~s20' & ~s21')
 | (~s01 & ((s02 & ~s10 & ~s12 & s20 & ~s21 & ~q01
  & q02 & ~q12 & ~s01' & ~s02' & ~s10' & ~s12' & ~s20' & ~s21')
 | (~s02 & ~s10 & s12 & ~s20 & s21 & ~q01 & ~q02
  & q12 & ~s01' & ~s02' & ~s10' & ~s12' & ~s20' & ~s21'))))"
Observables:
-- 0: ["q01","q02"]
-- 1: ["q01","q12"]
-- 2: ["q02","q12"]
Actual state:
-- s01
-- s10
-- q01

```

In the future, we hope to also show the law as its BDD (Binary Decision Diagram ¹) using the

¹A Binary Decision Diagram provides a concise representation of a Boolean formula. SMCDEL uses BDDs for the symbolic evaluation of logic problems.

tool graphviz.

4 Transparent Transformer

This section describes a variant of the Classic Knowledge Transformer that is implemented for the Transparent Gossip Problem. This transformer is tailored to the actual call that happens, which makes sure that whenever a call happens, all agents know this and also know which agents participate.

```
module Transparent where

import SMCDEL.Examples.GossipS5
import SMCDEL.Language
import SMCDEL.Symbolic.S5
```

We chose to adapt the existing function `callTrf` from `GossipS5`, which is the call transformer for the Synchronous Gossip Problem. Instead of `Int -> KnowTransformer`, the function is now `Int -> Int -> Int -> KnowTransformer`, so that agents a and b are arguments for the transformer for call ab . As in Section 2, we redefine how to update the vocabulary, law, and observations of each agent.

First, the vocabulary V^+ , called `thisCallHappens`, is now simply the call between agents a and b ; as opposed to the synchronous case, we do not need to add any other new call variables, as all agents know exactly which call happens. The `eventprops` are now empty, since we don't need extra vocabulary anymore to describe the possible calls that could be happening.

The `eventlaw` θ^+ (which originally stated that only one call happens at a time) is simplified to describe that only the specified call between a and b happens. The `changelaws` θ_- are quite different from those in the Classic Transformer TODO

The `eventobs` O_k^+ are also simplified to the call between a and b , as every agent observes the call.

```
callTrfTransparent :: Int -> Int -> Int -> KnowTransformer
callTrfTransparent n a b = KnTrf eventprops eventlaw changelaws eventobs where
  -- agent k is in the call ab if a calls k (so k==b) or k calls b (so k==a)
  -- isInCallForm k | k == a = Top
  -- | k == b = Top
  -- | otherwise = Bot

  thisCallHappens = thisCallProp (a,b)
  -- the only event proposition is the current call
  eventprops = [thisCallHappens]

  -- call ab takes place and no other calls happen
  eventlaw = Conj [PrpF thisCallHappens,
    Conj [Neg (PrpF $ thisCallProp (i,j)) | i <- gossipers n
      , j <- gossipers n
      , not ((i == a && j == b) || (i == b
        && j == a))
      , i < j ]]

  changelaws =
  -- i has secret of j
  -- case: i is not a or i is not b: then i can not have learned the secret unless it
  -- already knew it (has n i j)
  [(hasSof n i j, boolBddOf $ has n i j) | i <- gossipers n, j <- gossipers n, i /= j, i
    /= a, i /= b] ++
  -- case: i is a, j is not b: then i learned the secret if it already knew it, or b
  -- knew the secret of j
  [(hasSof n a j, boolBddOf $ Disj [ has n a j , has n b j ]) | j <- gossipers n, a /= j,
    b /= j] ++
  -- case: i is a, j is b: then Top (also: i is b, j is a)
```

```

[(hasSof n a b, boolBddOf Top)] ++ [(hasSof n b a, boolBddOf Top)] ++
-- case i is b, j is not a: synonymous to above
[(hasSof n b j, boolBddOf $ Disj [ has n b j , has n a j ]) | j <- gossipers n, a /= j,
  b /= j ]

-- *** changelaws =
-- [(hasSof n i j, boolBddOf $
--   Disj [ has n i j
--     , Conj (map isInCallForm [i,j])
--     , Conj [ isInCallForm i
--       , Disj [ Conj [ isInCallForm k, has n k j ]
--         | k <- gossipers n \\ [j], a<k && k<b ]]
--   ])
-- | i <- gossipers n, j <- gossipers n, i /= j ]

eventobs = [(show k, [thisCallHappens]) | k <- gossipers n]

```

Since the transparent transformer has the same type as the synchronous variant, we inherited its update function. The following functions were adapted from the original implementation to perform the transparent update:

```

callTransparent :: Int -> (Int,Int) -> Event
callTransparent n (a,b) = (callTrfTransparent n a b, [thisCallProp (a,b)])

doCallTransparent :: KnowScene -> (Int,Int) -> KnowScene
doCallTransparent start (a,b) = start 'update' callTransparent (length $ agentsOf start) (a,b)

afterTransparent :: Int -> [(Int,Int)] -> KnowScene
afterTransparent n = foldl doCallTransparent (gossipInit n)

isSuccessTransparent :: Int -> [(Int,Int)] -> Bool
isSuccessTransparent n cs = evalViaBdd (afterTransparent n cs) (allExperts n)

```

5 Simple Transformer

This module describes an implementation of the simple transformer as defined by Daniel Reifsteck in his master's thesis [Rei23]. The simple transformer aims to avoid the exponential blowup of variables that occurs in the classic transformer by copying propositions at each update and storing the "history" of events in the state law. The simple transformer does not change the initial state law throughout the computation. Instead, it directly applies factual change to the actual state.

```

module SimpleTransformer where

import SmpTrfS5
import SMCDEL.Symbolic.S5
import SMCDEL.Examples.GossipS5
import SMCDEL.Language
import Data.List ((\\))

```

The model is initialized by the `simpleGossipInit` function, which is based on the `gossipInit` function in the `GossipS5` file. The initial vocabulary contains all propositions of the form "*i* knows the secret of agent *j*", for all agents *i, j*.

Whereas the original state law described the situation in which agents only know their own secrets, this definition is too restrictive for the simple implementation: it prevents the learning of secrets, since the actual state should obey the state law throughout the computation. Thus, in order not to exclude any possible later states, we chose the law to be simply \top .

The observables for agent i - which equal the empty set in the classic implementation - now include the proposition " $S_{i,j}$ for all agents j ". Conceptually, these are the propositions that i can observe the truth value of these propositions at any point in the model: factual change does not influence the ability of i to observe them. This is only true for propositions involving i 's own knowledge. For example, even if Alice can "observe" that Bob does not know Charles' secret in the initial model, she cannot know this fact with certainty after a first call has occurred.

Analogous to the classic implementation, the state `actual` is initially empty, as it describes all true propositions of the form " i knows the secret of agent j ". While agents do know their own secrets, these are not encoded by propositions and therefore not mentioned in the state.

```
simpleGossipInit :: Int -> KnowScene
simpleGossipInit n = (KnS vocab law obs, actual) where
  vocab = [ hasSof n i j | i <- gossipers n, j <- gossipers n, i /= j ]
  law  = boolBddOf Top
  obs  = [ (show i, allSecretsOf n i) | i <- gossipers n ]
  actual = [ ]
```

The simple transformer is a general call transformer for any calls. This allows the transformer to be synchronous (rather than transparent): agents know that a call has taken place, but not necessarily which call.

The event vocabulary V^+ contains all fresh variables needed to describe the transformation, just like in the classical transformer. Contrary to the clasiscal case, V^+ not to V , which avoids a quick growth of the vocabulary with each call.

The state law θ_- (`changelaws`) is similarly defined as in the classic transformer, allowing the update to compute the factual change V_- and modify the state.

The transformation observables in this transformer are empty, as we will show that the specific update function will only need the observables in the original knowledge structure.

The function `simpleGossipTransformer` is the simple analogue of the classic transformer `callTrf` and the transparent variant `callTrfTransparent` from 4.

```
simpleGossipTransformer :: Int -> SimpleTransformerWithFactual
simpleGossipTransformer n = SimTrfWithF eventprops changelaws changeobs where
  -- helper functions to construct the required formulae
  thisCallHappens (i,j) = PrpF $ thisCallProp (i,j)
  isInCallForm k = Disj $ [ thisCallHappens (i,k) | i <- gossipers n \ [k], i < k ]
                        ++ [ thisCallHappens (k,j) | j <- gossipers n \ [k], k < j ]
  allCalls = [ (i,j) | i <- gossipers n, j <- gossipers n, i < j ]

  -- V+ event props stay the same as classic transformer
  eventprops = map thisCallProp allCalls

  -- Theta- change law stays same as classic transformer
  changelaws =
    [(hasSof n i j, boolBddOf $
      Disj [ has n i j -- after a call, i has the secret of j iff
            , Conj (map isInCallForm [i,j]) -- i and j are both in the call or
            , Conj [ isInCallForm i -- i is in the call and there is some k in
                  , Disj [ Conj [ isInCallForm k, has n k j ] -- the call who knew j
                        | k <- gossipers n \ [j] ] ]
            ])
      | i <- gossipers n, j <- gossipers n, i /= j ]

  -- Change obs are empty as they are not used
  changeobs = [ (show i, ([],[])) | i <- gossipers n ]
```

The following functions are analogues of those in `GossipS5.hs` and instead use the simple transformer.

```
-- a single call event with a simple transformer
```

```

simpleCall :: Int -> (Int,Int) -> StwfEvent
simpleCall n (a,b) = (simpleGossipTransformer n, [thisCallProp (a,b)])

-- execute a simple call event
doSimpleCall :: KnowScene -> (Int,Int) -> KnowScene
doSimpleCall start (a,b) = start 'update' simpleCall (length $ agentsOf start) (a,b)

-- execute repeated calls using the simple transformer
afterSimple :: Int -> [(Int, Int)] -> KnowScene
afterSimple n = foldl doSimpleCall (simpleGossipInit n)

isSuccessSimple :: Int -> [(Int,Int)] -> Bool
isSuccessSimple n cs = evalViaBdd (afterSimple n cs) (allExperts n)

-- a helper function
allSecretsOf :: Int -> Int -> [Prp]
allSecretsOf n x = [ hasSof n x j | j <- gossipers n, j /= x ]

```

6 Testing

6.1 Gossip Scene Investigation

```

module ExplainTestsSpec where

import Explain
import SMCDEL.Examples.GossipS5
import SMCDEL.Language
-- import SMCDEL.Symbolic.S5
-- import Test.QuickCheck

import Test.Hspec hiding (after)

```

Tests:

- Secret propositions are translated correctly
- The vocabulary has correct length
- After a call the state is updated correctly

```

spec :: Spec
spec = do
  describe "secret translation:" $ do
    it "init" $ do
      prpLibrary (hasSofs 1) 1 'shouldBe' []
      prpLibrary (hasSofs 2) 2 'shouldBe' [(P 1, "s01"), (P 2, "s10")]
      prpLibrary (hasSofs 5) 5 'shouldBe' zip (hasSofs 5) (enumS 5)
      prpLibrary (hasSofs 10) 10 'shouldBe' zip (hasSofs 10) (enumS 10)
    --it "after calls" $ do
    --  prpLibrary (callsVoc 3 [(0,1)]) 3 'shouldBe' [] --- How to test this?
    --it "length" $ do
      where
        hasSofs :: Int -> [Prp]
        hasSofs n = [ hasSof n i j | i <- gossipers n, j <- gossipers n, i /= j ]
        enumS :: Int -> [String]
        enumS n = ["s"++ show i ++ show j | i <- gossipers n, j <- gossipers n, i /= j ]
        --callsVoc :: Int -> [(Int, Int)] -> [Prp]
        --callsVoc n sequ = v
        --  where
        --    (KnS v _ _, _) = after n sequ

```

6.2 Transparent Transformer

We execute the following tests on the transparent variant of the Classic Transformer. The simple checks also apply to the Classic Transformer and encode the basic requirements of a transformer for a Gossip problem. However, some of the higher-order knowledge (for instance, after a call ab , agent c should know that a knows b 's secret, since c knows which call happened) is specific to the transparent implementation. Finally, we include a number of higher-order knowledge tests that are not specific to the transparent variant.

```
module ClassicTransformerSpec where

import Test.Hspec hiding ( after )
import SMCDEL.Examples.GossipS5
import SMCDEL.Language
import SMCDEL.Symbolic.S5
import Transparent (afterTransparent, isSuccessTransparent)
```

We use the following functions (previously defined in [Gat18]) concerning experts², which define the formulas "agent a is an expert" and "all agents are experts":

```
expert :: Int -> Int -> Form
expert n a = Conj [ PrpF (hasSof n a b) | b <- gossipers n, a /= b ]

allExperts :: Int -> Form
allExperts n = Conj [ expert n a | a <- gossipers n ]

isSuccess :: Int -> [(Int,Int)] -> Bool
isSuccess n cs = evalViaBdd (after n cs) (allExperts n)
```

We run the following tests, in this order:

1. For agents a, b : in the initial model, a knows that b doesn't know a 's secret
2. For agents a, b : after call ab , a knows b 's secret
3. For agents a, b, c : after call sequence $[ab, bc]$, c knows a 's secret
4. For agents a, b, c : after one call, there should be no experts
5. For agents a, b, c : after call sequence $[ab, bc, ca]$, everyone should be an expert
6. For agents a, b, c : after call ab , c knows that a knows b 's secret
7. For agents a, b, c, d : after call sequence $[ab, bc]$, d knows that c knows a 's secret
8. For agents a, b, c : after call sequence $[ab, bc, ca]$, everyone should know that everyone's an expert
9. For agents a, b : after call ab , b knows that a knows b 's secret
10. For agents a, b, c, d : after call sequence $[ab, bc, cd, ca]$, a knows that d knows a 's secret and that d knows that c knows a 's secret

²An expert is an agent who knows all secrets, that is, $\text{expert } n \ a$ is defined as $\bigwedge \{S_a b \mid b \in [1, \dots, n]\}$

```

spec :: Spec
spec = do
  -- simple tests
  it "trsTrf 1: no faulty knowledge in initial model" $ do
    eval (gossipInit 2) (K "0" (Neg (has 2 1 0))) 'shouldBe' True
  it "trsTrf 2: call shares secrets between agents" $ do
    eval (afterTransparent 2 [(0,1)]) (Conj [has 2 1 0, has 2 0 1]) 'shouldBe' True
  it "trsTrf 3: call sequence shares secrets between agents" $ do
    eval (afterTransparent 3 [(0,1),(1,2)]) (has 3 2 0) 'shouldBe' True
  it "trsTrf 4: no faulty experts" $ do
    eval (afterTransparent 3 [(0,1)]) (Disj [expert 3 i | i <- [0..3]]) 'shouldBe'
      False
  it "trsTrf 5: all are experts after the correct call sequence" $ do
    isSuccessTransparent 3 [(0,1),(1,2),(2,0)] 'shouldBe' True

  -- transparent-specific tests
  it "trsTrf 6: call is observed by other agents" $ do
    eval (afterTransparent 3 [(0,1)]) (K "2" (has 3 0 1)) 'shouldBe' True
  it "trsTrf 7: call sequence is observed by other agents" $ do
    eval (afterTransparent 4 [(0,1),(1,2)]) (K "3" (has 3 2 0)) 'shouldBe' True
  it "trsTrf 8: all agents know that all are experts after the correct call sequence"
    $ do
      eval (afterTransparent 3 [(0,1),(1,2),(2,0)]) (Conj [ K (show i) (allExperts 3)
                                                            | i <- [(0::Int)..3] ]) '
        shouldBe' True

  -- general higher-order knowledge tests
  it "trsTrf 9: higher-order knowledge after one call" $ do
    eval (afterTransparent 3 [(0,1)]) (K "1" (has 3 0 1)) 'shouldBe' True
  it "trsTrf 10: higher-order knowledge after call sequence" $ do
    eval (afterTransparent 3 [(0,1),(1,2),(2,3),(2,0)]) (K "0" $ Conj [has 3 3 0, K
      "3" (has 3 2 0)]) 'shouldBe' True

```

6.3 Simple Transformer

The Simple Transformer does not satisfy the same formulas as the Classic Transformer (and the transparent variant): some instances of higher-order knowledge fail. The following tests show how the Simple Transformer differs from the other two.

```

module SimpleTransformerSpec where

import SimpleTransformer

import Test.Hspec hiding ( after )
import SMCDEL.Examples.GossipS5
import SMCDEL.Symbolic.S5
import SMCDEL.Language

```

We test the implementation of the Simple Transformer with the following tests. The first four tests (explained below) describe instances of higher-order knowledge and aren't all satisfied by the Simple Transformer, even though they should be. The other tests are identical instances from the transparent test. From As with the transparent variant, tests 5-9 encode the basic requirements of a transformer for a Gossip problem and 10-11 encode general instances of higher-order knowledge.

New tests:

1. For agents a, b, c, d : after call sequence $[ab, bc]$, c knows that a knows that b knows a 's secret
2. For agents a, b, c : after call ab , c can infer that a knows b 's secret (since there was only one possible call)

3. For agents a, b, c : after call sequence $[ab]$, a knows that c doesn't know b 's secret
4. For agents a, b, c : after call sequence $[ab, bc, ca, ab, bc, ca]$, everyone should know that everyone's an expert

```
spec :: Spec
spec = do
  -- simple-trf-specific tests: these might fail but we'd like them to be true --
  CHECK THIS
  it "simpTrf 1: agents can reason about other agents' knowledge 1" $ do
    eval (afterSimple 4 [(0,1),(1,2)]) (K "3" (has 3 2 0)) 'shouldBe' True
  it "simpTrf 2: agents can reason about other agents' knowledge 2" $ do
    eval (afterSimple 3 [(0,1)]) (K "2" (has 3 0 1)) 'shouldBe' True
  it "simpTrf 3: agents can reason about the limits of other agents' knowledge" $ do
    eval (afterSimple 3 [(0,1)]) (K "0" (Neg (has 3 2 1))) 'shouldBe' True
  it "simpTrf 4: all agents know that all are experts after the correct call sequence" $ do
    eval (afterSimple 3 [(0,1),(1,2),(2,0),(0,1),(1,2),(2,0)]) (Conj [K (show i) (
      | i <- [(0::Int)..3] ])) '
      shouldBe' True
  -- simple tests (same tests as those for the transparent implementation)
  it "simpTrf 5: no faulty knowledge in initial model" $ do
    eval (simpleGossipInit 2) (K "0" (Neg (has 2 1 0))) 'shouldBe' True
  it "simpTrf 6: call shares secrets between agents" $ do
    eval (afterSimple 2 [(0,1)]) (Conj [has 2 1 0, has 2 0 1]) 'shouldBe' True
  it "simpTrf 7: call sequence shares secrets between agents" $ do
    eval (afterSimple 3 [(0,1),(1,2)]) (has 3 2 0) 'shouldBe' True
  it "simpTrf 8: no faulty experts" $ do
    eval (afterSimple 3 [(0,1)]) (Disj [expert 3 i | i <- [0..3]]) 'shouldBe' False
  it "simpTrf 9: all are experts after the correct call sequence" $ do
    isSuccessSimple 3 [(0,1),(1,2),(2,0)] 'shouldBe' True
  -- other general higher-order knowledge tests (same tests as those for the
  transparent implementation)
  it "simpTrf 10: higher-order knowledge after one call" $ do
    eval (afterSimple 3 [(0,1)]) (K "1" (has 3 0 1)) 'shouldBe' True
  it "simpTrf 11: higher-order knowledge after call sequence" $ do
    eval (afterSimple 3 [(0,1),(1,2),(2,3),(2,0)]) (K "0" $ Conj [has 3 3 0, K "3"
      (has 3 2 0)]) 'shouldBe' True
```

7 Conclusion

ADD CONCLUSION

References

- [Gat18] Malvin Gattinger. *New Directions in Model Checking Dynamic Epistemic Logic*. PhD thesis, University of Amsterdam, 2018.
- [Gat23] Malvin Gattinger. GoMoChe-gossip model checking. *Branch async from*, 1, 2023.
- [Rei23] Daniel Reifsteck. Comparing state representations for del planning (not public). Master's thesis, University of Freiburg, April 2023.
- [Yuk23] Haitian Yuki. SMCDEL-Hanabi. unpublished code / private git repository, 2023.