

# PRECODING IN MULTIBEAM SATELLITE COMMUNICATIONS: PRESENT AND FUTURE CHALLENGES

MIGUEL ÁNGEL VÁZQUEZ, ANA PÉREZ-NEIRA, DIMITRIOS CHRISTOPOULOS, SYMEON CHATZINOTAS, BJÖRN OTTERSTEN, PANTELIS-DANIEL ARAPOGLOU, ALBERTO GINESI, AND GIORGIO TARICCO

## ABSTRACT

Whenever multibeam satellite systems target very aggressive frequency reuse in their coverage area, inter-beam interference becomes the major obstacle for increasing the overall system throughput. As a matter of fact, users located at the beam edges suffer from very large interference for even a moderately aggressive planning of reuse-2. Although solutions for inter-beam interference management have been investigated at the satellite terminal, it turns out that the performance improvement does not justify the increased terminal complexity and cost. In this article, we pay attention to interference mitigation techniques that take place at the transmitter (i.e., the gateway). Based on this understanding, we provide our vision on advanced precoding techniques and user clustering methods for multibeam broadband fixed satellite communications. We also discuss practical challenges to deploy precoding schemes and the support introduced in the recently published DVB-S2X standard. Future challenges for novel configurations employing precoding are also provided.

## INTRODUCTION

Mimicking terrestrial cellular networks, satellite systems providing broadband IP services are moving from single-beam to multibeam architectures, typically operating in Ka-band. In this context, the payload is equipped with a multiplicity of feeds so that information is simultaneously sent to different spot beams on the ground with a certain frequency reuse pattern [1]. In such a configuration, bandwidth can efficiently be reused in beams that are sufficiently separated.

An end-to-end multibeam system architecture from the gateway (GW) to the user terminals (UTs) is depicted in Fig. 1, where it can be observed that UTs receive and transmit information through the multibeam antenna pattern, which is fed by the feeder link. The available bandwidth in the feeder link must be large enough to support the frequency reuse adopted for the user beams.

The projection of the beam generation process on Earth by the satellite allows the simultaneous transmission of different information streams at different rates. This transmission, combined with adaptive coding and modulation (ACM), can attend to the different user channel conditions over the coverage area. However, reusing the frequency over the multiple spot beams generates co-channel interference among adjacent ones. Indeed, as there is no way of having completely isolated spot beams, a carefully planned overlap between them is designed, leading to a controlled carrier to co-channel interference ratio, C/I.

Consequently, the transmit signal toward a certain beam is partially radiated to the corresponding adjacent beams through its antenna sidelobes. Although the received power levels of the adjacent beams are not as large as the intended one, the created interference accumulates, and therefore, the communication links suffer from a degradation of the achievable signal-to-interference-plus-noise ratio (SINR), which depends on the UT position.

In order to cope with this intrasystem interference, satellite operators and manufacturers try to separate the frequency bands of the adjacent beams so that the interference is mitigated. Commonly for high throughput satellite (HTS) systems, the frequency band is divided into four sub-bands so that closer adjacent beams have disjoint frequency bands (rightmost part of Fig. 2). Another degree of separation between the spot beams is offered by employing orthogonal polarizations.

Although this “cake-cutting” spectrum management sufficiently alleviates the problem of multibeam interference, it precludes scaling the system capacity by using all the available bandwidth in every beam. Therefore, to achieve a huge leap in offered data rate services, a more aggressive use of the spectrum is desirable. Notably, this vision has also been promoted in cellular systems by shifting the paradigm from single-cell to multicell systems [2].

As a result, high frequency reuse combined

Miguel Ángel Vázquez and Ana Pérez-Neira are with the Centre Tecnològic de les Telecomunicacions de Catalunya. Ana Pérez-Neira is also with the Universitat Politècnica de Catalunya.

Dimitrios Christopoulos, Symeon Chatzinotas, and Björn Ottersten are with the University of Luxembourg.

Alberto Ginesi and Pantelis-Daniel Arapoglou are with ESA's Research and Technology Centre.

Giorgio Taricco is with the Politecnico di Torino.

Digital Object Identifier: 10.1109/MWC.2016.1500047WC

with appropriate interference mitigation techniques is a natural way forward for this scenario. If these techniques are performed at the transmitter [3–5], a feedback communication (link between the UTs and the GW) must be established, leading to communication overhead. Remarkably, if the feedback information suffers from degradation (quantization errors, outdated information, transmission errors), the ability to perform interference mitigation is compromised.

Indeed, deciding whether the interference should be removed at either the transmitter or the receiver in satellite systems needs careful study encompassing all the performance metrics and hardware designs. This article focuses on the benefits of precoding techniques (i.e., transmitter-based interference mitigation) as recent results have demonstrated its large potential while keeping receiver complexity low [6].

Prior to presenting the current multibeam satellite precoding techniques, the channel model is revisited as well as the channel state information reporting method performed by the UTs.

The outline of the article is as follows. The next section describes the channel modeling of multibeam satellite systems as the required feedback mechanisms for implementing precoding. Then we describe the multicast multibeam precoding designs for dealing with multibeam interference. Following that we illustrate the challenge of multi-gateway satellite systems, and the final section presents our conclusions.

## CHANNEL MODELING

In the following, we highlight the components that need to be included in the full channel matrix of a multibeam satellite system in order to be representative of a real system. Since the channel matrix comprises complex elements, particular emphasis is placed on the phase effects that need to be accounted for in the channel matrix, as they critically impact the calculation of the precoding matrix. Moreover, accurately estimating channel phase effects is extremely challenging in long-haul satellite systems, as the round-trip delay from a geostationary satellite corresponds to about 500 ms.

In general, the entire route from transmission to reception (including all the analog and RF circuits, antennas, and propagation) should be part of the channel definition, affecting both its amplitude and phase. All other link budget parameters being fixed, the channel amplitude  $|h_{kn}|$  between receive antenna  $k$  and transmit antenna  $n$  of each element in the channel matrix depends on the satellite antenna gain and the propagation effects, predominantly rain attenuation, which is slowly varying, and so is  $|h_{kn}|$ .

Concerning the various contributors that rotate the carrier phase and create a time variant channel phase between receive antenna  $k$  and transmit antenna,  $n$   $\theta_{kn}(t)$  are:

- In the feeder link, the gateway local oscillator (LO) along with its frequency/phase instabilities, as well as the feeder link geometry. However, these phase effects are common for all the beams served by the same gateway.
- In the satellite payload, the LOs of the frequency converters along with their frequency/phase




FIGURE 1. Multibeam satellite system architecture.




FIGURE 2. Frequency reuse patterns in multibeam satellite communications. Left: full frequency reuse; right: four-color frequency reuse.

instabilities. Also, the movement of the satellite within its station keeping box modifies both the user and feeder link geometries, making the phase time variant. These effects are common to all user terminals in the coverage area.

- In the user link, the user link geometry and the LO of the user terminal's receiver low noise block (LNB). These effects are particular to each user terminal in the coverage area and are removed by the phase synchronization loop.

Assuming an ideal feeder link, Fig. 3 provides an overview of the various phase contributions for a simplified scenario involving two payload chains and two user terminal beams on the ground.

In addition, and in contrast to the cellular systems, in fixed satellite systems the channel magnitude does not vary significantly. This is due to the fact that the channel propagation is dominated by the line-of-sight component and slow atmospheric fading. However, the phase variations are not negligible, and they constitute the major source of channel impairments, as discussed in a later section. The phase estimation of any complex sub-channel is as follows:

1. The UT makes a data aided estimate of the incoming signal

$$\hat{\theta}_{\text{tot}}(t) = \theta_{\text{tot}}(t) + e(t)$$

2. The UT periodically provides phase reports  $\hat{\theta}_{\text{tot}}(t + \Delta t)$  every  $\Delta t$  to the gateway.
3. The gateway will apply this phase estimate (as well as the amplitude estimate) to compute the precoding weights and will transmit the forward link signal toward the UT (assuming zero queue-

## MULTIBEAM SATELLITE PRECODING ALGORITHMS: MULTIGROUP MULTICAST PRECODING

Apart from the difficulties in obtaining up-to-date CSI at the transmitter (CSIT), satellite precoding substantially differs from its terrestrial counterpart due to its multicast operation, which stems from the fact that a single DVB-S2X codeword (frame) contains data bits addressing multiple UTs. Although currently there is a tendency to add multicast modes to the cellular standards, the general operation is a simple multiuser model where a certain number of independent symbols,  $K$ , are intended to be transmitted to  $K$  users. In contrast, in satellite communications a given codeword always needs to be decoded by more than one receiver. This phenomenon entails a decrease of the offered spectral efficiency since the UT with the lowest SINR determines the rate allocation via ACM. In this context, the multibeam satellite forward link transmission is modeled by the multigroup multicast multiple-input single-output (MISO) channel.

From early multibeam precoding studies, it was evident that linear algorithms considering only one user per frame were performing satisfactorily, providing significant capacity gains [3]. One of the most promising designs, initially conceived for cellular communications, was regularized channel inversion, also coined minimum mean square error (MMSE) due to its similarity to the linear estimator. As a result, the first attempt to design multicast multigroup precoding was a modification of the regularized channel inversion. This was carried out in [6], where all the users served by the same frame are considered as a single user with an equivalent channel equal to the average of the different channels. Spectral efficiency results are encouraging considering this simple approximation; however, the channel averaging degrades when several users are considered per frame. In order to potentially improve performance, a technique based on the block singular value decomposition (SVD) method as presented in [7] has been investigated. In that case, the precoding matrix is constructed row by row, computing the null space each time with the aim of completely rejecting the interference to the other beams. Although the computational complexity increases severely, a certain gain in terms of spectral efficiency is obtained.

Toward obtaining the sum-rate optimal design, an optimization approach is provided in [8], where the authors formulate the optimization problem of multicast multigroup. Although optimal, this approach suffers from high computational complexity, which should be considered in order to accommodate it in commercial satellite ground segment equipment. Additionally, in [9] the sum-rate optimization for the multigroup multicast scenario with per antenna power constraints is considered jointly with user scheduling. This joint optimization, coined as 'Frame-based', offers larger rates compared with the separated optimization.

Figure 4 depicts a 100-runs simulation for a Ka-band multibeam satellite system consisting of 245-spot beams. For further details of the channel model and particularly the antenna pattern, the reader can refer to [10], where the overall




FIGURE 3. Phase contributions to the channel matrix.

ing and processing delay). The signal will be received at the UT after an additional two-hop propagation delay of 250 ms. In total, the UT phase estimate  $\hat{\theta}_{tot}(t)$  will be outdated by at least 500–600 ms.

Although this channel reporting mechanism is simple, its performance is crucial to the final precoding design. Note that since the channel amplitude does not change as often as the phase, some feedback bits could be saved since the amplitude feedback rate could be reduced. In any case, as described in the next subsections, the channel state information (CSI) errors reduce the system throughput. Prior to investigating the effects of non-perfect CSI, the precoding techniques are presented next.

## OVERVIEW OF MULTIBEAM PRECODING TECHNIQUES

The role of precoding is to “revert” the multibeam interference signals so that the receiver can perform single-user detection while maintaining a high SINR. In this way, the additional spectrum made available through higher frequency reuse can be exploited, and a larger system capacity can be delivered compared to the orthogonal transmission one.

As in cellular networks, a condition for efficient forward link precoding is that the receivers provide high-quality reports of a number of sub-channels back to the transmitter, which is responsible for deriving the appropriate precoding matrix. In the next paragraphs, we first present the design problem as a set of proposed solutions and their implementation in the recent digital video broadcasting over satellite 2 extension (DVB-S2X) standard.

channel effects are presented. The three precoding techniques briefly introduced above were considered, namely “MMSE,” “block SVD,” and “Frame-based.” For the latter, no user scheduling is considered. They are evaluated in terms of average throughput per beam based on the DVB-S2X standard posteriorly described. Precisely, for each run we obtain the SINR and we compute the DVB-S2X achievable throughput considering a packet error rate of  $10^{-6}$ . It can be observed that frame-based precoding offers a larger per-beam throughput than the other proposed techniques. Indeed, MMSE precoding shows for this case a very low performance. Indeed, compared to the conventional 4-color case which offers 0.73 Gb/s average throughputs per beam for any number of users, MMSE presents lower average throughput. On the other hand, for the more favorable case of two users per frame, Frame-based and Block-SVD gains approximately 135 percent and 120 percent over the reference 4-color case.


As a matter of fact, the larger number of users per frame is targeted, the lower the throughput gain obtained, and the three techniques present a similar decay of throughput with the number of users. The reason for this decrease is the differences between the channel vectors of the users served sequentially by the same precoding matrix. In other words, whenever all channel vectors of the users in the same beam are collinear; there will be no loss of performance due to the multi-cast transmission. Selecting which users to group together and apply precoding on is the task of a scheduler, which is discussed in the next section.

### USER SCHEDULING AND PRECODING

Addressing more than one user in the same frame increases the precoding complexity as different spatial signatures need to be considered for a single codeword. Different users belonging to the same beam will have different channel vectors, leading to poor precoding performance. However, the system designer can smartly choose the users so that they have similar channel vectors. Under this context, the scheduler must not only consider the SINR levels for grouping the users as it does for DVB-S2 [11, 12], but also its channel vector.

Finding out which are the best users to be served in a certain time instant considering that they are going to be precoded with the same precoding weights is a very challenging problem. The reason is that after the precoding effect, the SINR levels for each user vary so that the a priori modulation and coding (modcod) assignment becomes obsolete. Therefore, the optimization is a computationally demanding iterative process as described in [10].

Whenever a low-complexity non-iterative process is targeted, certain heuristics must be determined in order to come up with an easy-to-implement user grouping. A pragmatic approach in this direction can be found in [6], where a geographical user clustering (GUC) is proposed. This technique refers to user grouping carried out only taking into account the channel matrices without the phase effect. According to GUC, closely located UTs are clustered in the same group, so their information will be encoded in the same codeword (frame). The implementa-



**FIGURE 4.** Average throughput per beam vs. number of users per beam. The throughput obtained via 4-color frequency reuse pattern and without using precoding is 0.73 Gb/beam. Remarkably, for more than three users per beam, the reference four-color frequency reuse offers higher throughput than MMSE precoding. Frame-based precoding presents the highest throughput for this scenario.


tion of this technique can be performed without large computational complexity. Given a certain set of users to be served with their respective channel vectors, the  $k$ -means algorithm groups the users with the similar channel vector.

Assuming that the GW has access to both channel amplitude and phase effects, more accurate clustering can be done. It is evident that the phase effects increase the differences between the channel vectors of the users in the same beam, leading to a drastic reduction of the overall performance.

Even better heuristic user clustering can be conceived whenever we assume that the GW has full CSIT. This method, referred to as frame-based clustering (FBC), is described in [9]. The key step for FBC lies in measuring the similarity between user channels based on the readily available CSI. The underlying intuition is that users scheduled in the same frame should have co-linear (i.e., similar) channels, while interfering users, scheduled in adjacent synchronous frames, should be orthogonal to minimize interference.

Figure 5 presents a simulation where the different precoding and user clustering methods are presented. Perfect clustering refers to the technique of user grouping considering not only the magnitude of each channel but also the phase. On the contrary, GUC refers to the technique that only takes into account the magnitude of the channel (i.e., its position). Finally, FBC considers a heuristic approach, described in [8]. Consider the Block-SVD and MMSE methods; it can be observed that whenever the scheduler uses all the available CSIT (i.e., phase and magnitude), larger throughputs can be obtained. Note that even the combination of scheduling and precoding with the lowest performance (i.e., MMSE with GUC) is better than not taking into consideration the user





**FIGURE 5.** Average throughput per beam vs. users per beam when considering different user clustering techniques. Perfect clustering refers to the technique of user grouping considering not only the magnitude of the channel but also the phase effect. On the contrary, GUC refers to the technique that only takes into account the magnitude of the channel (i.e., its position). Finally, frame-based clustering considers a heuristic approach described in [8].

clustering problem (see Fig. 4 for comparison). Consequently, user clustering is an important tool for applying precoding techniques in next generation multibeam broadband satellite systems. It is worth remarking that the combination of scheduling and precoding that offers the best performance is Block-SVD jointly with perfect clustering. Finally, it is important that all methods offer larger throughput than without considering user clustering (Fig. 4).

Apart from receiving the corresponding CSI information, the enabling communication protocol must provide certain synchronization and channel estimation aspects. This is described in the following subsection. Then the performance decrease when the CSI is not accurate at the GW is also analyzed.

### DVB-S2X SPECIFICATIONS FOR PRECODING

The potential of precoding in a broadband multibeam satellite system is also linked to the support for this technique included in relevant standards. In terms of standardization developments, the DVB very recently (2014) issued the DVB-S2 extension (DVB-S2X) with an optional specification that provides the necessary framing and signaling support to interference management techniques (Annex E of [13]). Thereby, all signaling and framing elements to support precoding in terms of the physical layer have been put in place. The specification in [13] endorses a number of special features including regular channel framing structure, specific pilots, and unique words for synchronization aid as well as a feedback signalling message from the UTs to the GW.

The so-called super-frame structure supports orthogonal start of super-frame (SOSF) and pilot

fields by using Walsh-Hadamard sequences. A set of orthogonal sequences can be assigned to co-channel carriers within a multi-spot beam system (a unique sequence per beam). These features allow the UT to estimate the channel responses down to a very low SINR value. The beam-specific orthogonal sequence allows the receiver to uniquely associate the channel estimate with the beam index. The superframe also foresees an additional precoded pilot field to help amplitude and phase recovery in support of the precoded data detection. Apart from the aforementioned features, the use of this super-frame extensively helps the use of precoding due to its multicast transmission nature.

Indeed, in DVB-S2 as well as in DVB-S2X, more than one user are allocated in the same frame in order to allow for large low density parity check (LDPC) codewords, which increases the channel coding gain and the frame encapsulation efficiency. In this context, the precoding matrix needs to be computed each time there is a change on the forward error correction (FEC) block (i.e., group of users' coded information) for all beams. This is shown in the upper part of Fig. 6, where the dotted vertical line indicates each time the precoder would need to be re-computed. Aside from the computational complexity of computing the precoding matrix that often, the frame format in the upper part of Fig. 6 does not allow for the alignment of pilot fields among the beams. Nevertheless, it should be pointed out that the more often the precoding matrix is computed, the larger spectral efficiencies can be obtained.


In order to solve this problem, DVB-S2X introduced the super-frame structure shown in the lower part of Fig. 6, with the same number of symbols so that precoding can be applied on a per-super-frame basis. This structure aligns the pilot fields among the beams and also yields a periodic precoding matrix refresh period. Moreover, the fact that the frames are time aligned leads to a substantial reduction of the receiver complexity.

Focusing on the CSI feedback, when a super-frame is transmitted, each UT estimates a number of channel complex coefficients corresponding to the most significant interfering beams (16 or 32). These complex numbers are quantized and signaled back to the gateway using the signaling message described in Annex E of [13] with a maximum rate of one message every 500 ms. Note that even though multibeam satellite systems usually operate with hundreds of beams, only a small fraction of them need to be estimated and detected. This is due to the radiation pattern, which reduces the interfering power in largely separated beams.

It is important to remark that precoding can benefit from shortened codewords since in that case no user aggregation would be required. However, this would decrease the channel coding gain. Therefore, a trade-off analysis (codeword length and precoding gain) must be performed.

### PROSPECTIVE GAINS UNDER CHANNEL CSIT ERROR

Although the results presented hitherto are very promising, they do not account for practical impairments experienced in a real system. In




**FIGURE 6.** Frame transmission in DVB-S2 (up) and DVB-S2X (down). The use of precoding depends on the spatial signature of the receivers so that in the DVB-S2 structure, the precoding matrix needs to be updated at each dotted line.

order to determine the precoding performance under CSIT imperfections, a simulation is performed considering that the transmitter receives a perfect estimation of the channel magnitude, whereas the channel phase suffers from certain deviation. Remarkably, this is a close-to-real simulation set up since the channel magnitude can be easily known at the GW with negligible error as it exhibits slow dynamics. For this case, the phase uncertainty is modeled by an additional Gaussian random phase with zero mean and 10 variance (which is a rather pessimistic assumption). Figure 7 shows the dramatic decrease of performance with respect to the perfect CSI case depicted in Fig. 5 when considering Block-SVD-GUC precoding. On the other hand, MMSE-GUC is more robust to CSI errors. Indeed, although MMSE presents certain throughput decrease with respect to the perfect CSIT case, Block-SVD precoding is more sensitive to these imperfections.

## FUTURE TRENDS: MULTI-GATEWAY CONFIGURATIONS IN PRECODING

Apart from the presented issues on precoding in multibeam satellite systems, other challenges are appearing. One of the most important ones is feeder link bottleneck bandwidth and how to prevent it. Indeed, a common assumption in the literature on multibeam precoding has been ideal and unlimited bandwidth feeder link. Nonetheless, the consideration that all spot beams in the system are served by a single GW is not practical purely due to the limited feeder link spectrum even in a conventional four-color system, when a large number ( $> 200$ ) of beams is used. The situation is, of course, aggravated by moving to more aggressive frequency reuse architectures. Although there are efforts to move the feeder link to higher frequency bands like Q/V-band (40/50 GHz) and W-band (70/80 GHz) to moderate the number of GWs, for large systems a multiplicity of GWs should be accounted for.

The effects of multiple GWs in the precoding design have been studied in [14] leading to a performance loss with respect to single-GW precoding due to the fact that there is no longer a single transmitter entity in possession of the CSIT



**FIGURE 7.** Average throughput per beam vs. number of users considering imperfect CSIT. MMSE is more robust to channel uncertainties than Block-SVD as it does not present such a performance decrease with respect to the perfect CSI case (Fig. 5). Note that when more than four users are considered, the Block-SVD approach presents lower throughput than the four-color scenario.

for all UTs. This allows the GWs to pre-compensate for the co-channel interference of the UTs only for the subset of beams that each is serving (cluster). Notwithstanding this performance loss, noticeable gains by GW cooperation under the beam clustering assumptions are still reported in [14], where the deployment of non-cooperative multiple GWs improves the system performance over conventional four-color frequency reuse systems by almost 30 percent. The limiting factor in this case is the interference from adjacent beams that belong to different GWs, particularly in cluster edges. If no cooperation exists between the GWs joint processing cannot mitigate interferences from beams served by different GWs. To this end, partial cooperation among GWs that serve adjacent beam clusters is proposed.

A performance evaluation based on the current DVB-S2X standard quantified the benefit of this technique. This gain demonstrates that if multibeam satellite networks incorporate precoding mechanisms, they will be able to face the challenge of ever increasing broadband Internet traffic.

## CONCLUSIONS

This article provides a high-level overview of advanced precoding techniques, which we strongly believe will become the key technology for the next generation of very high throughput systems employing multibeam satellites. High-level requirements and practical aspects related to this technology, such as channel impairments and user grouping, as well as the DVB-S2X standard adaptation for precoding, are discussed. A performance evaluation based on the current DVB-S2X standard quantified the benefit of this technique. This gain demonstrates that if multibeam satellite networks incorporate precoding mechanisms, they will be able to face the challenge of ever increasing broadband Internet traffic.

## REFERENCES

- [1] A. Kyrgiazos et al., "A Terabit/Second Satellite System for European Broadband Access: A Feasibility Study," *Int'l. J. Sat. Commun. Sys. and Networking*, vol. 32, no. 2, 2014, pp. 63–92.
- [2] D. Gesbert et al., "Multi-Cell MIMO Cooperative Networks: A New Look at Interference," *IEEE JSAC*, vol. 28, no. 9, Dec. 2010, pp. 1380–1408.
- [3] L. Cottatellucci et al., "Interference Mitigation Techniques for Broadband Satellite Systems," *Proc. 24th AIAA Int'l. Commun. Sat. Sys. Conf.*, San Diego, CA, 11–14 June 2006.
- [4] M. Poggioni, M. Berlioli and P. Banelli, "BER Performance of Multibeam Satellite Systems with Tomlinson Harashima Precoding," *Proc. IEEE ICC*, pp. 1–6, Dresden, Germany, June 2009.
- [5] J. Arnau, B. Devillers, C. Mosquera, and A. Perez-Neira, "Performance Study of Multiuser Interference Mitigation Schemes for Hybrid Broadband Multibeam Satellite Architectures," *Proc. EURASIP J. Wireless Commun. and Networking*, 132, 2012.
- [6] G. Taricco, "Linear Precoding Methods for Multi-Beam Broadband Satellite Systems," *Proc. 20th Euro. Wireless Conf.*, 14–16 May 2014, pp. 1–6.
- [7] Y. C. B. Silva and A. Klein, "Linear Transmit Beamforming Techniques for the Multigroup Multicast Scenario," *IEEE Trans. Vehic. Tech.*, vol. 58, no. 8, Oct. 2009, pp. 4353–67.
- [8] E. Karipidis, N. D. Sidiropoulos, and Z.-Q. Luo, "Quality of Service and Max-Min Fair Transmit Beamforming to Multiple Cochannel Multicast Groups," *IEEE Trans. Signal Processing*, vol. 56, no. 3, Mar. 2008, pp. 1268–79.
- [9] D. Christopoulos, S. Chatzinotas, and B. Ottersten, "Multicast Multigroup Precoding and User Scheduling for Frame-Based Satellite Communications," *IEEE Trans. Wireless Commun.*, vol. PP, no. 99, pp. 1–1.
- [10] D. Christopoulos et al., "Linear Precoding in Multibeam Satcoms: Practical Constraints," *Proc. 31st AIAA Int'l. Commun. Sat. Sys. Conf.*, Florence, Italy, Oct. 2013.
- [11] V. Boussemart, M. Berlioli, and F. Rossetto, "User Scheduling for Large Multi-Beam Satellite MIMO Systems," *ASILOMAR*, Pacific Grove, C, Nov. 2011.
- [12] M. A. V. Castro and G. S. Granados, "Cross-Layer Packet Scheduler Design of a Multibeam Broadband Satellite System with Adaptive Coding and Modulation," *IEEE Trans. Wireless Commun.*, vol. 6, no. 1, Jan. 2007, pp. 248–58.
- [13] ETSI EN 302307-2, "Digital Video Broadcasting (DVB); Second Generation Framing Structure, Channel Coding and Modulation Systems for Broadcasting, Interactive Services, News Gathering and Other Broadband Satellite Applications; Part II: S2-Extensions (S2-X)," 2014.
- [14] G. Zheng, S. Chatzinotas, and B. Ottersten, "Multi-Gateway Cooperation in Multibeam Satellite Systems," *Proc. 23rd IEEE Symp. Personal Indoor Mobile Radio Commun.*, 2012.

## ADDITIONAL READING

- [1] A. Gharanjik et al., "Gateway Switching in Q/V Band Satellite Feeder Links," *IEEE Commun. Lett.*, vol. 17, no. 7, July 2013, pp. 1384–87.

## BIOGRAPHIES

MIGUEL ÁNGEL VÁZQUEZ is researcher at Centre Tecnològic de les Telecomunicacions de Catalunya (CTTC). He received his Telecommunication Engineering degree from the TelecomBCN Technical University of Catalonia (UPC) and his Master's degree in research on wireless communication (MERIT) in 2012. He

has completed his Ph.D. in telecommunications in 2014 from UPC, leading to a Ph.D. thesis, *Beamforming and Power Control in Spectrum Sharing Systems*. He joined CTTC in January 2010. He has been granted with a Marie Curie fellowship in the context of an FP7 European Project (SWAP). Moreover, he has participated in different EU-funded projects (FP7, ARTEMISA, CELTIC, H2020) on the topics of the internet of Things and smart grid; and with industrial contracts with local companies and the European Space Agency. His research interests include statistical and array signal processing, spectrum sharing wireless communications, licensed shared access networks, and satellite communications.

ANA I. PÉREZ-NEIRA (SM'02) is a full professor at UPC in the Signal Theory and Communication Department. Her research topic is signal processing for communications, and currently she is working on multi-antenna and multicarrier signal processing, for both satellite communications and wireless systems. She has been on the Board of Directors of ETSETB (Telecom Barcelona) from 2000 to 2003 and Vice Rector for Research at UPC (2010–2013). She created the UPC Doctoral School (2011). Currently, she is scientific coordinator at CTTC. Since 2008 she has been a member of EURASIP BoD (the European Signal Processing Association) and since 2010 of IEEE Signal Processing Theory and Methods (SPTM). She is the coordinator of the European project SANS and of the Network of Excellence on satellite communications, financed by the European Space Agency: SatnEXIV. She has been the leader of 20 projects and has participated in over 50 (10 for the European Space Agency). She is author of 50 journal papers (20 related with Satcom) and more than 200 conference papers (20 invited). She is a co-author of four books and five patents (one on satcom). She has been a Guest Editor of five Special Issues and currently she is an Editor of *IEEE Transactions on Signal Processing* and *Eurasip Signal Processing and Advances in Signal Processing*. She was the General Chair of IWCLD '09, EUSIPCO '11, EW '14, and IWSCS '14. She has participated in the organization of the ESA Conference 1996, and is the chair of IEEE ICASSP '20.

DIMITRIOS CHRISTOPOULOS (S'03M'14) received his Diploma in electrical and computer engineering from the National Technical University of Athens (NTUA) in 2010 and his Ph.D. degree in electrical engineering from the Interdisciplinary Center for Security and Trust, (SnT), University of Luxembourg, in 2014. Affiliated with SnT until 2015, he has been involved signal processing research activities in collaboration with the European Space Agency and SES. As of 2016, he is a research engineer in Newtec Cy, Belgium, involved with the development and implementation of advanced signal processing algorithms in ground-based satellite communications equipment. His research interests include applied signal processing for satellite communications, optimization methods for multiuser MIMO communications, and receiver synchronization algorithms.

SYMEON CHATZINOTAS (S'06M'09SM'13) received his M.Eng. degree in telecommunications from Aristotle University of Thessaloniki, Greece, and his M.Sc. and Ph.D. degrees in electronic engineering from the University of Surrey, United Kingdom, in 2003, 2006, and 2009, respectively. He is currently a research scientist with the SIGCOM Research Group, Interdisciplinary Centre for Security, Reliability, and Trust, University of Luxembourg, managing H2020, ESA, and FNR projects. In the past, he has worked on numerous R&D projects for the Institute of Informatics Telecommunications, National Center for Scientific Research Demokritos, Institute of Telematics and Informatics, Center of Research and Technology Hellas, and Mobile Communications Research Group, Center of Communication Systems Research, University of Surrey. He has authored more than 180 technical papers in refereed international journals, conferences, and scientific books. His research interests include multiuser information theory, cooperative/cognitive communications, and wireless network optimization. He is a corecipient of the 2014 Distinguished Contributions to Satellite Communications Award, and Satellite and Space Communications Technical Committee, IEEE Communications Society, and CROWNCOM 2015 Best Paper Award. He is one of the Editors of the book *Cooperative and Cognitive Satellite Systems* (Elsevier, 2015) and was involved in co-organizing the First International Workshop on Cognitive Radios and Networks for Spectrum Coexistence of Satellite and Terrestrial Systems.

BJÖRN OTTESTEN [S'87, M'89, SM'99, F'04] received his M.S. degree in electrical engineering and applied physics from Linköping University, Sweden, in 1986, and his Ph.D. degree in electrical engineering from Stanford University, California, in 1989. He has held research positions at the Department of Electrical Engineering, Linköping University; the Information Systems Laboratory, Stanford University; the Katholieke

Universiteit Leuven, Belgium; and the University of Luxembourg. From 1996 to 1997, he was the director of research at ArrayComm Inc, a start-up in San Jose, California, based on his patented technology. In 1991, he was appointed a professor of signal processing with the Royal Institute of Technology (KTH), Stockholm, Sweden. From 1992 to 2004, he was the head of the Department for Signals, Sensors, and Systems, KTH, and from 2004 to 2008, he was the Dean of the School of Electrical Engineering, KTH. Currently, he is the director of the Interdisciplinary Centre for Security, Reliability and Trust, University of Luxembourg. As Digital Champion of Luxembourg, he acts as an adviser to the European Commission. His research interests include security and trust, reliable wireless communications, and statistical signal processing. He is a Fellow of the EURASIP and a member of the IEEE Signal Processing Society Board of Governors. He has served as an Associate Editor for *IEEE Transactions on Signal Processing* and on the Editorial Board of *IEEE Signal Processing Magazine*. He is currently Editor-in-Chief of the *EURASIP Signal Processing Journal* and a member of the Editorial Boards of the *EURASIP Journal of Applied Signal Processing* and *Foundations and Trends in Signal Processing*. He coauthored journal papers that received the IEEE Signal Processing Society Best Paper Award in 1993, 2001, 2006, and 2013, and three IEEE conference papers receiving Best Paper Awards. He was the recipient of the IEEE Signal Processing Society Technical Achievement Award in 2011. He was the first recipient of the European Research Council Advanced Research Grant.

PANTELIS-DANIEL ARAPOGLOU received his Diploma degree in electrical and computer engineering and his Dr.Eng. degree from NTUA in 2003 and 2007, respectively. From September 2008 to October 2010, he was involved in postdoctoral research on MIMO over satellite jointly supported by NTUA and the European Space Agency Research and Technology Centre (ESA/ESTEC), The Netherlands. From October 2010 to September 2011, he was a research associate with SnT, University of Luxembourg. Since September 2011, he has been a communications system engineer at ESA/ESTEC, where he is technically supporting R&D activities and developments in the areas of satellite telecommunications, digital and optical communications, and high data rate telemetry for Earth observation applications. He was a recipient of the Ericsson Award

for Excellence in Telecommunications for his diploma thesis in 2004 and the URSI General Assembly Young Scientist Award in 2005. As a researcher, he has participated in the work of Study Group 3 of the ITU-R in SatNex III and in COST Action IC0802. Currently, he is following SatNex IV which is funded by ESA and the CCSDS Optical Working Group.

ALBERTO GINESI received his Dr. Ing. cum laude) and Ph.D degrees in electronic engineering from the University of Pisa, Italy, in 1993 and 1998, respectively. In 1996–1997 he spent one year at Carleton University, Ottawa, Canada, performing research on digital transmission for wireless applications. In 1997, he joined Nortel Networks and in 2000 Catena Networks, both in Ottawa, Canada, where he worked on digital subscriber loop technologies and contributed to the definition of the second-generation ADSL standards within the ITU-R standardization body. In 2002 he joined ESTEC, where he is currently covering the position of head of the Telecommunication-TT&C Systems & Techniques Section of the Technical and Quality Management Directorate, and is responsible for the R&D of satellite telecommunication and TT&C systems. His main research interests lie in the area of advanced digital communication systems and techniques from theory to hardware implementation.

GIORGIO TARICCO (M'91SM'03F'10) received his Electronic Engineer degree (summa cum laude) from Politecnico di Torino, Italy, in 1985. He was with the Italian Telecom Labs from 1985 to 1987, where he was involved in the design of the GSM mobile telephony standard (channel coding). In 1996, he was a research fellow at ESTEC. Currently, he is a full professor at Politecnico di Torino. His research interests include error control coding, multiuser detection, space-time coding, MIMO communications, cognitive radio, wireless sensor networks, caching systems, and satellite precoding techniques. He coauthored more than 200 papers in international journals and conferences, several book chapters, and two international patents. He is a Senior Associate Editor for *IEEE Wireless Communications Letters*. He has been an Associate Editor for the following publications: the *KICS Journal of Communications and Networks*, *IEEE Communications Letters*, and *IEEE Transactions on Information Theory*. He has served on the Technical Program Committees of several IEEE conferences and was the Treasurer of IEEE ISIT 2000, ISITA 2004, and IEEE ITW 2009.