

UDP Program

```
// Server side implementation of UDP client-server model
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <string.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <arpa/inet.h>
#include <netinet/in.h>

#define PORT 8080
#define MAXLINE 1024

// Driver code
int main() {
    int sockfd;
    char buffer[MAXLINE];
    char *hello = "Hello from server";
    struct sockaddr_in servaddr, cliaddr;

    // Creating socket file descriptor
    if ( (sockfd = socket(AF_INET, SOCK_DGRAM, 0)) < 0 ) {
        perror("socket creation failed");
        exit(EXIT_FAILURE);
    }

    memset(&servaddr, 0, sizeof(servaddr));
    memset(&cliaddr, 0, sizeof(cliaddr));

    // Filling server information
    servaddr.sin_family = AF_INET; // IPv4
    servaddr.sin_addr.s_addr = INADDR_ANY;
    servaddr.sin_port = htons(PORT);

    // Bind the socket with the server address
    if ( bind(sockfd, (const struct sockaddr *)&servaddr,
              sizeof(servaddr)) < 0 )
    {
        perror("bind failed");
        exit(EXIT_FAILURE);
    }

    int len, n;

    len = sizeof(cliaddr); //len is value/result

    n = recvfrom(sockfd, (char *)buffer, MAXLINE,
                  MSG_WAITALL, ( struct sockaddr *) &cliaddr,
                  &len);
    buffer[n] = '\0';
    printf("Client : %s\n", buffer);
}
```

```

        sendto(sockfd, (const char *)hello, strlen(hello),
                MSG_CONFIRM, (const struct sockaddr *) &cliaddr,
                len);
        printf("Hello message sent.\n");

        return 0;
}

```

```

// Client side implementation of UDP client-server model
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <string.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <arpa/inet.h>
#include <netinet/in.h>

#define PORT 8080
#define MAXLINE 1024

// Driver code
int main() {
    int sockfd;
    char buffer[MAXLINE];
    char *hello = "Hello from client";
    struct sockaddr_in servaddr;

    // Creating socket file descriptor
    if ( (sockfd = socket(AF_INET, SOCK_DGRAM, 0)) < 0 ) {
        perror("socket creation failed");
        exit(EXIT_FAILURE);
    }

    memset(&servaddr, 0, sizeof(servaddr));

    // Filling server information
    servaddr.sin_family = AF_INET;
    servaddr.sin_port = htons(PORT);
    servaddr.sin_addr.s_addr = INADDR_ANY;

    int n, len;

    sendto(sockfd, (const char *)hello, strlen(hello),
            MSG_CONFIRM, (const struct sockaddr *) &servaddr,
            sizeof(servaddr));
    printf("Hello message sent.\n");
}

```

```

        n = recvfrom(sockfd, (char *)buffer, MAXLINE,
                      MSG_WAITALL, (struct sockaddr *) &servaddr,
                      &len);
        buffer[n] = '\0';
        printf("Server : %s\n", buffer);

        close(sockfd);
        return 0;
}

```

Output :

```

$ ./server

Client : Hello from client

Hello message sent.

$ ./client

Hello message sent.

Server : Hello from server

```

TCP Program

```

#include <stdio.h>
#include <netdb.h>
#include <netinet/in.h>
#include <stdlib.h>
#include <string.h>
#include <sys/socket.h>
#include <sys/types.h>
#define MAX 80
#define PORT 8080
#define SA struct sockaddr

// Function designed for chat between client and server.
void func(int sockfd)
{
    char buff[MAX];
    int n;
    // infinite loop for chat
    for (;;) {
        bzero(buff, MAX);

```

```

        // read the message from client and copy it in buffer
        read(sockfd, buff, sizeof(buff));
        // print buffer which contains the client contents
        printf("From client: %s\t To client : ", buff);
        bzero(buff, MAX);
        n = 0;
        // copy server message in the buffer
        while ((buff[n++] = getchar()) != '\n')
            ;

        // and send that buffer to client
        write(sockfd, buff, sizeof(buff));

        // if msg contains "Exit" then server exit and chat ended.
        if (strncmp("exit", buff, 4) == 0) {
            printf("Server Exit...\n");
            break;
        }
    }
}

// Driver function
int main()
{
    int sockfd, connfd, len;
    struct sockaddr_in servaddr, cli;

    // socket create and verification
    sockfd = socket(AF_INET, SOCK_STREAM, 0);
    if (sockfd == -1) {
        printf("socket creation failed...\n");
        exit(0);
    }
    else
        printf("Socket successfully created..\n");
    bzero(&servaddr, sizeof(servaddr));

    // assign IP, PORT
    servaddr.sin_family = AF_INET;
    servaddr.sin_addr.s_addr = htonl(INADDR_ANY);
    servaddr.sin_port = htons(PORT);

    // Binding newly created socket to given IP and verification
    if ((bind(sockfd, (SA*)&servaddr, sizeof(servaddr))) != 0) {
        printf("socket bind failed...\n");
        exit(0);
    }
    else
        printf("Socket successfully binded..\n");

    // Now server is ready to listen and verification
    if ((listen(sockfd, 5)) != 0) {

```

```

        printf("Listen failed...\n");
        exit(0);
    }
    else
        printf("Server listening..\n");
    len = sizeof(cli);

    // Accept the data packet from client and verification
    connfd = accept(sockfd, (SA*)&cli, &len);
    if (connfd < 0) {
        printf("server accept failed...\n");
        exit(0);
    }
    else
        printf("server accept the client...\n");

    // Function for chatting between client and server
    func(connfd);

    // After chatting close the socket
    close(sockfd);
}

```

```

#include <netdb.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/socket.h>
#define MAX 80
#define PORT 8080
#define SA struct sockaddr
void func(int sockfd)
{
    char buff[MAX];
    int n;
    for (;;) {
        bzero(buff, sizeof(buff));
        printf("Enter the string : ");
        n = 0;
        while ((buff[n++] = getchar()) != '\n')
            ;
        write(sockfd, buff, sizeof(buff));
        bzero(buff, sizeof(buff));
        read(sockfd, buff, sizeof(buff));
        printf("From Server : %s", buff);
        if ((strncmp(buff, "exit", 4)) == 0) {
            printf("Client Exit...\n");
            break;
        }
    }
}
}

```

```

int main()
{
    int sockfd, connfd;
    struct sockaddr_in servaddr, cli;

    // socket create and varification
    sockfd = socket(AF_INET, SOCK_STREAM, 0);
    if (sockfd == -1) {
        printf("socket creation failed...\n");
        exit(0);
    }
    else
        printf("Socket successfully created..\n");
    bzero(&servaddr, sizeof(servaddr));

    // assign IP, PORT
    servaddr.sin_family = AF_INET;
    servaddr.sin_addr.s_addr = inet_addr("127.0.0.1");
    servaddr.sin_port = htons(PORT);

    // connect the client socket to server socket
    if (connect(sockfd, (SA*)&servaddr, sizeof(servaddr)) != 0) {
        printf("connection with the server failed...\n");
        exit(0);
    }
    else
        printf("connected to the server..\n");

    // function for chat
    func(sockfd);

    // close the socket
    close(sockfd);
}

```

Output –

Server side:

Socket successfully created..

Socket successfully binded..

Server listening..

server accept the client...

From client: hi

To client : hello

From client: exit

To client : exit

Server Exit...

Client side:

Socket successfully created..

connected to the server..

Enter the string : hi

From Server : hello

Enter the string : exit

From Server : exit

Client Exit...