


Start with PowerBI & AI

"From Rookie to Rock"

Learn &
Practice

Create your own DAX function with **UDF**



Patou Tips #58



Create your own function with UDF

About UDF (User Defined Function)



The new **UDF** functionality finally allows you to create your own DAX functions, which is very convenient:

- in terms of **reuse**,
- as well as business **functions specific to your business culture**
- or predefined **DAX functions that do not exist**.

In this "Patou Tips" we will see how to create simple trigonometric and business functions.




Resources on GitHub

[Patou-Tips/#52 Patou Tips \(Quick guide to develop faster with TDML\) at main · PatouTips/Patou-Tips](#)


Create your own function with UDF Get Started



- 1 In Power BI Desktop, go to File > Options > Preview features. Select the "DAX functions defined by user" option, and restart Power BI Desktop



- 2 Go to the « DAX query view » to start to write your own function



Start with PowerBI

"From Rookie to Rock"

Patou Tips #58

Create your own function with UDF

Syntax for an UDF



The general syntax for an UDF is finally easy.

DAX

```
/// Optional description above the function  
FUNCTION <FunctionName> = ( <ParameterName>: <ParameterType>, ... ) => <FunctionBody>
```

1

```
/// Optional description above the function
```

→ Document this part that help your user to understand your function, because this part appear also when your user start to use your function.

2

```
FUNCTION <FunctionName>
```

Define the name of your function by using the DAX function « **FUNCTION** ».

3


```
( <ParameterName>: <ParameterType>, ... ) =>
```

Declare one or more parameters and their type. Don't forget to end this declaration with =>

4

```
<FunctionBody>
```

Write your function.



Parameters type

Start with PowerBI

"From Rookie to Rock"

Patou Tips #58


Create your own function with UDF Geometric function (1/3)



Example 1: Area of a circle.

A simple function to calculate the area of a circle.

- 1 Go to the "DAX query view" to write the following function




```
DEFINE
/// Calculate the area of a circle of a given radius
Update model: Overwrite function
FUNCTION Area_Circle =
(
    Radius :scalar
) =>
PI() * SQRT([Radius])
```

- 2 

Don't forget to update your function (top of the view).

- 3 Now you can write a measure

```
Area of a circle = Area_Circle('Measure'[Radius])
```



Circle	Radius	Area of a circle
Circle 1	2	4,44
Circle 2	5	7,02
Circle 3	8	8,89
Circle 4	12	10,88
Circle 5	17	12,95

Start with PowerBI

"From Rookie to Rock"

Patou Tips #58


Create your own function with UDF Geometric function (2/3)




Exemple 2: Volume of a sphere (1/2)

Another simple function to calculate the volume of a sphere.

1 Go to the "DAX query view" to write the following function



```
DEFINE
/// Calculate the volume of a sphere of a given radius
Update model: Overwrite function
FUNCTION Volume_Sphere =
(
    Radius :scalar
) =>
Divide(4,3) * PI() * POWER([Radius],3)
```

2  Update model with changes (1)

Don't forget to update your function (top of the view).

3 Now you can write a measure

```
Volume of a sphere = Volume_Sphere('Measure'[Radius])
```

Circle	Radius	Volume of a sphere
Circle 1	2	33,51
Circle 2	5	523,60
Circle 3	8	2 144,66
Circle 4	12	7 238,23
Circle 5	17	20 579,53

Start with PowerBI

"From Rookie to Rock"

Patou Tips #58

Create your own function with UDF Geometric function (3/3)



Exemple 2: Volume of a sphere (2/2)

Another simple function to calculate the volume of a sphere.

4

Note: It is essential to clearly explain the "why" of your function, not only for yourself, but especially for your users...

```
DEFINE
/// Calculate the volume of a sphere of a given radius
Update model: Overwrite function
FUNCTION Volume_Sphere =
(
    Radius :scalar
) =>
Divide(4,3) * PI() * POWER([Radius],3)
```

Volume_Sphere(Radius: scalar)

Calculate the volume of a sphere of a given radius

1 Volume of a sphere = Volume_Sphere(

'Measure'

...Thus, when a user writes a measure, the function description will appear in a pop-up window and serve as a guide.

Start with PowerBI

"From Rookie to Rock"

Patou Tips #58

Create your own function with UDF

Business function (1/2)



Example 3: Last Year (LY)

Often used in activity reporting, particularly in finance, the value of an activity in the previous year can be reduced to its simplest expression.

```
DEFINE
/// Calculate the previous year's value (YoY) from the current year's value (reference value).
Update model: Overwrite function
FUNCTION Last_Year =
(
|   Reference_Value : expr
| ) =>

CALCULATE(
|   Reference_Value, DATEADD(DimDate[Date],-1,YEAR))
```

Example 4: YoY absolute variation

Another measure frequently used in activity reporting.

```
DEFINE
/// Calculate the absolute variation in a Value (Reference_Value) compared to its value Year Over Year (YoY).
Update model: Overwrite function
FUNCTION YoY_Absolute_Variation =
(
|   Reference_Value : expr
| ) =>

VAR LY = CALCULATE(
|   Reference_Value, DATEADD(DimDate[Date],-1,YEAR))

VAR Result = Reference_Value-LY

RETURN Result
```

Start with PowerBI

"From Rookie to Rock"

Patou Tips #58

Create your own function with UDF Business function (2/2)



Example 5: YoY relative variation

Relative variation, combined with absolute variation, allows us to visualize the magnitude of the variation.

DEFINE

```
/// Calculate the relative variation in a Value (Reference_Value) compared to its value  
Year Over Year (YoY). This function also works for negative values, as in finance. The  
result must be in decimal format, change it in %.
```

Update model: Overwrite function

```
FUNCTION YoY_Relative_Variation =  
(  
    Reference_Value : expr  
) =>  
  
    VAR LY = CALCULATE(  
        Reference_Value, DATEADD(DimDate[Date],-1,YEAR))  
  
    VAR Result = DIVIDE(  
        (Reference_Value-LY), ABS(LY))  
  
    RETURN Result
```

Year	Last Year (LY)	This Year (TY)	YoY absolute	YoY relative
2022				
janv	2 370 663	2 826 560	455 897	19,2 %
févr	2 843 340	2 677 182	-166 158	-5,8 %
mars	2 904 775	2 780 417	-124 358	-4,3 %
avr	2 935 235	2 826 626	-108 609	-3,7 %
mai	2 118 842	3 091 387	972 545	45,9 %
juin	2 293 254	3 339 128	1 045 874	45,6 %
juil	2 920 484	4 248 771	1 328 287	45,5 %
août	3 801 135	5 432 050	1 630 915	42,9 %
sept	4 229 031	4 525 100	296 069	7,0 %
oct	3 852 219	3 963 715	111 496	2,9 %
nov	2 674 993	3 160 262	485 269	18,1 %
déc	3 225 220	4 198 802	973 582	30,2 %

Easy to do it...

Patou Tips #12



Calculate the correct
evolution for KPI



See Patou Tips #12 about
the calculation of the
relative variation

Start with PowerBI

"From Rookie to Rock"

Patou Tips #58

Coming soon, in 2026!



Patrice Fayard

Business Intelligence WORKBOOK

Start PowerBI

"From Rookie to Rock"

Learn & Practice

- ✓ 1000 Video tutorials
- ✓ 500 Step by step
- ✓ 5 Cheat Sheet
- ✓ 100 Power Patou Tips
- ✓ Hacking & Workshops



Over 500 pages to
learn and practice: video
tutorials and resources

To develop your
knowledge, find more
explanations and exercises




Learn and practice

Find past issues of "Patou Tips" and download resources to practice on GitHub



Patou Tips #22
PowerBI projects with Teams




Patou Tips #48
Quick Guide of CALCULATE




Patou Tips #23
Quick Guide Visualization & Storytelling



Patou Tips #25
Start with PowerBI: The complete Guide



Patou Tips #42
5 Advanced Charts (with Charticulator)



Resources on GitHub
<https://github.com/PatouTips/Patou-Tips>

Patou Tips



Don't forget!
This isn't the truth, it's just my truth!

Follow me
Like me
Share me

