

LECTURE NOTE-7

FORMATTED INPUT-OUTPUT

Data can be entered & displayed in a particular format. Through format specifications, better presentation of results can be obtained.

Variations in Output for integer & floats:

```
#include<stdio.h>
int main()
{
    printf("Case 1:%6d\n",9876);
    /* Prints the number right justified within 6 columns */
    printf("Case 2:%3d\n",9876);
    /* Prints the number to be right justified to 3 columns but, there are 4 digits so number is not
    right justified */
    printf("Case 3:%.2f\n",987.6543);
    /* Prints the number rounded to two decimal places */
    printf("Case 4:%.f\n",987.6543);
    /* Prints the number rounded to 0 decimal place, i.e, rounded to integer */
    printf("Case 5:%e\n",987.6543);
    /* Prints the number in exponential notation (scientific notation) */
    return 0;
}
```

Output

Case 1: 9876

Case 2:9876

Case 3:987.65

Case 4:988

Case 5:9.876543e+002

Variations in Input for integer and floats:

```
#include <stdio.h>
int main()
{
    int a,b;
    float c,d;
    printf("Enter two integers: ");
    /*Two integers can be taken from user at once as below*/
```

```

scanf("%d%d",&a,&b);
printf("Enter integer and floating point numbers: ");
/*Integer and floating point number can be taken at once from user as below*/
scanf("%d%f",&a,&c);
return 0;
}

```

Similarly, any number of inputs can be taken at once from user.

EXERCISE:

1. To print out a and b given below, which of the following printf() statement will you use?

```

#include<stdio.h>
float a=3.14;
double b=3.14;

```

- A. printf("%f %lf", a, b);
- B. printf("%Lf %f", a, b);
- C. printf("%Lf %Lf", a, b);
- D. printf("%f %Lf", a, b);

2. To scan a and b given below, which of the following scanf() statement will you use?

```

#include<stdio.h>
float a;
double b;

```

- A. scanf("%f %f", &a, &b);
- B. scanf("%Lf %Lf", &a, &b);
- C. scanf("%f %Lf", &a, &b);
- D. scanf("%f %lf", &a, &b);

3. For a typical program, the input is taken using.
 - A. scanf
 - B. Files
 - C. Command-line
 - D. None of the mentioned

4. What is the output of this C code?

```
#include <stdio.h>
int main()
{   int i = 10, j = 2;
    printf("%d\n", printf("%d %d ", i, j));
}
```

- A. Compile time error
- B. 10 2 4
- C. 10 2 2
- D. 10 2 5

5. What is the output of this C code?

```
#include <stdio.h>
int main()
{
    int i = 10, j = 3;
    printf("%d %d %d", i, j);
}
```

- A. Compile time error
- B. 10 3
- C. 10 3 some garbage value
- D. Undefined behavior

6. What is the output of this C code?

```
#include <stdio.h>
int main()
{   int i = 10, j = 3, k = 3;
    printf("%d %d ", i, j, k);
}
```

- A. Compile time error
- B. 10 3 3
- C. 10 3
- D. 10 3 somegarbage value

7. The syntax to print a % using printf statement can be done by.
- A. %
 - B. %%
 - C. '%'
 - D. %%%

8. What is the output of this C code?

```
#include <stdio.h>
int main()
{ int n;
  scanf("%d", n);
  printf("%d\n", n);
  return 0;
}
```

- A. Compilation error
- B. Undefined behavior
- C. Whatever user types
- D. Depends on the standard

9. What is the output of this C code?

```
#include <stdio.h>
int main()
{ short int i;
  scanf("%hd", &i);
  printf("%hd", i);
  return 0;
}
```

- A. Compilation error
- B. Undefined behavior
- C. Whatever user types
- D. None of the mentioned

10. In a call to printf() function the format specifier %b can be used to print binary equivalent of an integer.

- A. True
- B. False

11. Point out the error in the program?

```
#include<stdio.h>
int main()
{
    char ch;
    int i;
    scanf("%c", &i);
    scanf("%d", &ch);
    printf("%c %d", ch, i);
    return 0;
}
```

- A. Error: suspicious char to in conversion in scanf()
- B. Error: we may not get input for second scanf() statement
- C. No error
- D. None of above

12. Which of the following is NOT a delimiter for an input in scanf?

- A. Enter
- B. Space
- C. Tab
- D. None of the mentioned