Chloé Desdouits 12 février 2012

Résumé de l'article de Rahul C. Shah et Jan M. Rabaey Energy Aware Routing for Low Energy Ad Hoc Sensor Networks

Algorithm 1 Setup phase

$Cost(N_D) = 0$
{Flood the network from N_D to N_S :}
for each intermediate node N_i **do**
  for each neighbor N_j of N_i **do**
    if $d(N_i, N_S) \geq d(N_j, N_S)$ and $d(N_i, N_D) \leq d(N_j, N_D)$ **then**
      Forward the request from N_i to N_j
    end if
  end for
end for

for each intermediate node N_i **do**
  for each neighbor N_j of N_i **do**
    On receiving a request :
    $C_{N_j,N_i} = Cost(N_i) + Metric(N_j, N_i)$
    $FT_j = \{i | C_{N_j,N_i} \leq \alpha(\min_k C_{N_j,N_k})\}$

$$P_{N_j,N_i} = \frac{\frac{1}{C_{N_j,N_i}}}{\sum_{k \in FT_j} \frac{1}{C_{N_j,N_k}}}$$

$$Cost(N_j) = \sum_{i \in FT_j} P_{N_j,N_i} C_{N_j,N_i}$$

  end for
end for

a

Algorithm 2 Data communication phase

N_S chooses randomly a number
This number points a neighbor in the forwarding table FT_S out
Send the packet from N_S to this neighbor N_j
Do the same thing for all intermediate nodes until the packet reaches the destination