How People Affect Each Other on Social Networks?



Zhiping (Patricia) Xiao University of California, Los Angeles Outline

Background

Motivation Paper List

Problem Settings & Models

Opinion Dynamics Models Data-Driven Analysis

The End

Background



Motivation

My previous works:

- ► Infer opinion from relation;
- ▶ Infer opinion from text content of posts / tweets.

More:

- Spread existing opinions;
- ► Influence some others' opinions.

Besides, nobody is satisfied with the social media environments nowadays. But we don not know what treatments can be applied yet.

Opinion dynamics models:

- Predicting Opinion Dynamics via Sociologically-Informed Neural Networks (KDD'22)
- ▶ (*) A model for the influence of media on the ideology of content in online social networks (Physical Review Research'20)

Data-Driven Analysis:

- ▶ The effect of wording on message propagation: Topic- and author-controlled natural experiments on Twitter (ACL'14)
- ▶ (*) Is a Picture Worth a Thousand Words? An Empirical Study of Image Content and Social Media Engagement (Journal of Marketing Research'20)
- (*) Some other related aspects:
 - Integrating explanation and prediction in computational social science (Nature'21)

Problem Settings & Models



Code: https://github.com/mayaokawa/opinion_dynamics

- ▶ Data unavailable, crawler script provided;
- ▶ Using Neural Networks to model opinion dynamics models.
- ▶ **NOT** considering network structure (e.g. follower-followee relations).

The idea:

- ▶ Use Neural ODE framework to learn the parameters of the social dynamical systems.
- ▶ Not using VAE for learning (i.e. NOT modeling a trajectory).



From step t to step t + 1, consider a single user x_u , given a opinion dynamics model f which predicts it as \tilde{x}_u , it says,

$$\tilde{x}_u(t+1) = x_u(t) + \int_t^{t+1} f_{\theta}(\mathbf{X}(t))dt,$$

where \mathbf{X} can be all nodes' opinions in theory (but always select some in practice). f includes some learnable parameters.

Then, they use an MLP net g_{ϕ} to model the dynamical system: code here

$$\hat{x}_u(t+1) = g_\phi(\mathbf{X}(t))$$

Note that: their code mentioned "attention" but there is no attention mechanism (https://github.com/mayaokawa/opinion_dynamics/blob/main/modules.py#L35)

Then the loss is computed as:

$$\ell_{all} = \ell_{data}(\hat{x}_u(t), x_u(t)) + \ell_{ode}(\frac{\partial g_{\phi}(\mathbf{X}(t))}{\partial t}, f_{\theta}(\mathbf{X}(t))) + \ell_{reg}(\theta),$$

where:

- ▶ ℓ_{data} : the difference (Cross Entropy Loss) between ground truth $(x_u(t))$ and predicted result $(\hat{x}_u(t))$
- ▶ ℓ_{ode} : the difference (MSE loss) between the SINN model's gradient $(\frac{\partial g}{\partial t}$, fetched via torch.autograd.grad), and the ODE gradient $(f_{\theta}(\mathbf{X}(t)))$
- ▶ ℓ_{reg} : regularization on the parameters of f, usually sum of their ℓ_1 norms (note that for different versions of opinion dynamics models, f are different, and there will be different ways of computing ℓ_{reg}).

Opinion dynamics: the study of how opinions emerge and evolve through exchanging opinions with others.

Problem Settings in General:

- \triangleright Set of users \mathcal{U}
- Each person u holds opinion $x_u(t) \in [-1, 1]$ on a specific subject at time t.
- Users' opinions will affect each other. These models use math formula to model how opinions are updated from t to t+1.
- There are many models with different **update rules**. (i.e. different versions of f as we mentioned in previous pages)

DeGroot: simple, basic

$$x_u(t+1) = x_u(t) + \sum_{u \neq u} a_{uv} x_v(t),$$

where \mathcal{U}/u denotes all other users in the system and a_{uv} is the strength of the interactions between u and v.

It models assimilation (i.e. tendency of moving opinions towards others) well.

ODE version in SINN:

$$\frac{dx_u(t)}{dt} = \sum_{\mathcal{U}/u} a_{uv} x_v(t) = \sum_{\mathcal{U}/u} \mathbf{m}_u^T \mathbf{q}_v x_v(t)$$

Friedkin-Johnsen (FJ) model: allows for stubbornness

$$x_u(t+1) = s_u \sum_{\mathcal{U}/u} x_v(t) + (1 - s_u) x_u(0),$$

where $s_u \in [0, 1]$ denotes a user's susceptibility to persuasion. The s_u , the more open-minded a person is.

It models *susceptibilities* to persuasion (i.e., the tendency to defer to others' opinions) well.

ODE version in SINN:

$$\frac{dx_u(t)}{dt} = s_u \sum_{u/u} x_v(t) + (1 - s_u)x_u(0) - x_u(t)$$

Bounded confidence model: models confirmation bias (i.e., tendency to focus on information that confirms our preconceptions). A family of model. The most popular variant, the Hegselmann-Krause (HK) model:

$$x_u(t+1) = x_u(t) + \frac{1}{|N_u(t)|} \sum_{v \in N_u(t)} (x_v(t) - x_u(t)),$$

where $N_u(t)$ denotes the set of users whose opinions fall within the bounded confidence interval of u at t:

$$N_u(t) = \{ v \in \mathcal{U} \mid |x_u(t) - x_v(t)| \le \delta \}$$

ODE version in SINN:

$$\frac{dx_u(t)}{dt} = \sum_{v \in \mathcal{U}} \sigma \Big(\delta - |x_u(t) - x_v(t)| \Big) \Big(x_u(t) - x_v(t) \Big)$$

Stochastic Bounded confidence model: incorporating stochastic interactions based on opinion differences. Use $p(z_{uv}^t = 1)$ to model the probability that u and v interact at time t.

$$p(z_{uv}^t = 1) = \frac{|x_u(t) - x_v(t)|^{-\rho}}{\sum_k |x_u(t) - x_k(t)|^{-\rho}},$$

ODE version in SINN:

$$\frac{dx_u(t)}{dt} = \sum_{v \in \mathcal{U}} \tilde{z}_{uv}^t(x_v(t) - x_u(t)),$$

where \tilde{z}_{uv}^t is computed from $\mathbf{p}_u^t \in \mathbb{R}^U$:

$$\tilde{z}_u^t = \text{Softmax}([\log(\mathbf{p}_u^t) + \mathbf{g}_u]/\tau),$$

with \mathbf{g}_u being random noise and τ a temperature parameter. When $\tau \to 0$, \tilde{z}_u^t approximates one-hot.

$$x_u(t+1) = \frac{1}{|I_u| + w} \left(wx_u(t) + \sum_{v \in \mathcal{M} + \mathcal{N}} \mathbf{A}_{uv} x_v(t) f(x_u(t), x_v(t)) \right),$$

where I_u is the set of accounts to which account u is receptive to, w is a pre-defined hyper-parameter, \mathbf{A} is the adjacency matrix of the network, f is a function that could be defined like "when [cond] then 1 else 0".

From paper: A Model for the Influence of Media on the Ideology of Content in Online Social Networks

- ► Considered network structure;
- ► Somewhat more similar to GNN update rules.
- Note: this update rule is designed for modeling **media** influence. \mathcal{M}, \mathcal{N} are the sets of media and normal accounts respectively.

- ► Efforts were made to bridge the gap between opinion dynamics models and powerful computation tools (e.g. Neural Networks).
- ▶ More and more research works have considered graph structure in modeling social influence.
- ▶ Opinion dynamics models are having strong assumptions in general, bringing about a gap between theory and practice.

The effect of wording on message propagation: Topic- and author-controlled natural experiments on Twitter

- ▶ Effect of Wording: Investigate whether a different choice of words affects message propagation, controlling speaker and the topic.
- ► Measure propagation by #retweet
- (*) Is a Picture Worth a Thousand Words? An Empirical Study of Image Content and Social Media Engagement
 - ▶ Image Content Engagement: Investigate the influence of image content on social media engagement, empirically.
 - ▶ Measure engagement by #retweet and #like

Observation: it is unexpectedly common for the same user to post different tweets regarding the same URL. ¹

Data:

- ► TAC: Topic- and Author-Controlled pairs
 - The previous one: t_1 , the later one: t_2 . Corresponding number of retweets: n_1 , n_2 .
 - ▶ How to control author: from the same account.
 - ► How to control topic: including the same URL.

Examples:

author	tweets	#retweets
natlsecuritycnn	t ₁ : FIRST ON CNN: After Petraeus scandal, Paula Broadwell looks to recapture 'normal life.' http://t.co/qy7GGuYW	$n_1 = 5$
	t2: First on CNN: Broadwell photos shared with Security Clearance as she and her family fight media portrayal of her [same URL]	$n_2 = 29$
ABC	t ₁ : Workers, families take stand against Thanksgiving hours: http://t.co/J9mQHiIEqv	$n_1 = 46$
	t ₂ : Staples, Medieval Times Workers Say Opening Thanksgiving Day Crosses the Line [same URL]	$n_2 = 27$
cactus_music	t ₁ : I know at some point you've have been saved from hunger by our rolling food trucks friends. Let's help support them!	$n_1 = 2$
	http://t.co/zg9jwA5j	
	t ₂ : Food trucks are the epitome of small independently owned LOCAL businesses! Help keep them going! Sign the petition [same	$n_2 = 13$
	URL]	

At: https://chenhaot.com/pages/wording-for-propagation.html



Three versions of Features:

- ► Customize: Combining all 39 features (any feature can be used independently), including "ask people to share (explicitly)", "1st person singular", "positive/negatibe (sentiment)", "informative" etc. These features are designed according to a lot of previous works.
- ▶ Also consider tagged bag-ofwords ("BOW") features, which includes all the unigram (word:POS pair) and bigram features.

Classifier: L2-regularized logistic regression, SVM

▶ A strong baseline: same classifier structure, including more features — time (day and hour) and follower-count, but not using TAC for training. (called ¬TAC+ff+time)

- 1. Do the wording effects exist?
 - Ask 106 humans to predict which version gets more widely spread (via Amazon Mechanical Turk experiment), and achieved an average accuracy of 61.3%.
 - ▶ It is somewhat possible to predict greater message spread from wording.
- 2. How to determine time-lag $(|t_1 t_2|)$ and follower thresholds?

$$D = \sum_{0 \le n_1 < 10} |\hat{E}(n_2|n_1) - n_1|$$

By examining D value's when other conditions are different. Here, $\hat{E}(n_2|n_1)$ is the average value of n_2 over pairs where t_1 are retweeted n_1 times.

Focus on analyzing the following aspects:

- ► Effectiveness: measured by attracting more retweets
- Author Prefer: measured by how often the authors have higher tendency of such feature in t_2 than in t_1
- Feature coefficients: measured by how well the model performs using that feature set.

Prediction performance:

- ► Human: 61.3%
- ightharpoonup ¬TAC+ff+time: 55.3%
- ▶ Using TAC: 65.6%

Some Findings:

• @-mentions and 2nd person pronouns are ineffective in promote retweeting, but these features are preferred by authors.

Is a Picture Worth a Thousand Words? An Empirical Study of Image Content and Social Media Engagement

- ▶ Similar Data Source and Ground Truth: from Twitter and Instagram, use likes and retweets counts as ground-truth engagements.
- Scope of Data narrowed to mostly commercial posts (sale, airline, etc.).
- ▶ Different Ways of Finding Pairs: Using **propensity score matching** approach to create a pseudo "treatment" (expose to image or not) group and a "control" group (1:1) on the basis of post and account characteristics.
- ▶ Models: logistic regression, multinomial naive Bayes, linear support vector machine, and random forest.

Treatment Effect: $\tau_i = Y_i(1) - Y_i(0)$

 $ightharpoonup Y_i$ refers to the outcome of whether (1) or not (0) treatment Y is applied to sample i

When there is a treatment group and a controlled group, we have Averaged Treatment Effect (ATE):

$$ATE = \mathbb{E}[Y(1) - Y(0)]$$

Propensity Score: used to estimate the likelihood that treatment is applied to every sample.

$$P(X) = P(D = 1|X),$$

where D refers to whether or not the treatment is applied.

- ► Labeling is hard even to human beings;
 - e.g. the Effect of Wording work find human average accuracy of judging which message is more widespread 61.3%
- ► Hard to observe counter-factual pairs;
- Lack of ground-truth knowledge of the offline world;
- Most problems are not well-defined. It can be hard to convince your audience what you are studying in the first place.

- (*) Integrating explanation and prediction in computational social science
 - Social Scientists
 - Pros: Interpretable, Explainable, often invoking causal mechanisms.
 - ► Cons: Fail to predict outcomes of interest, fail to offer solutions to real-world problems, fail to replicate results.
 - ► Computer Science:
 - ▶ Pros: Good at designing accurate predictive models.
 - Cons: Neglecting causal mechanism, doesn't care whether or not the models are interpretable, easily biased.

The End 26

Thank You All! ②

Please feel free to discuss with me afterwards.