

		DRAWING CON
		THIS
		1

NFORMATION AND SHALL NOT

l
l
l
l
l
l
l
l
l
l
l





	- 1	
	- 1	
	- 1	
	- 1	
	- 1	
	- 1	
	- 1	
	- 1	
	- 1	
	- 1	

ı
ı
ı
ı
ı
ı
ı
I

l
l
ı
l
l
l

l
l
l
l
l
l
l
l
l
l

164KVAR,67 uH, 2500A, 50/60HZ, 150°C, 1PH, K1

TITLE

₩ (1)

USED ON

ONYX RESERVES THE RIGHT TO MODIFY/ALTER THE DESIGN AT ANY TIME.

ENCLOSURE DIMENSIONS ARE LISTED AT MAXIMUM ALLOWABLE.

1. ALL DIMENSIONS ARE IN INCHES.

NOTES

2. TOLERANCES FOR REACTOR DIMENSIONS ARE +/- 1.0" AND

OKAY TO BLOCK SPLIT SIDE PANEL AND ONE OTHER SIDE, MUST HAVE 2 SIDES OPEN AND TOP FOR PROPER VENTILATION

CONDUIT PLATE SUPPORT (5) 4" CONDUITS. INTERNAL BEND RADIUS SUPPORTS UP TO 600MCM.

BTM VIEW

NO PLACE DECIMAL ±0.002
REE PLACE DECIMAL ±0.005

ANGULAR 20.5 BEND 1

DATE

122/1

REACTOR 3-PH ASSY, FACEBOOK

SHEET 1 OF 3

SCALE: NTS

REV X

IND-1006/32500-00 w sidecar

DWG. NO.

SIZE

CHECKED IFG, APPR