

Inclinometer. An instrument consisting of a curved glass tube, housing a glass ball, and damped with a fluid similar to kerosene. It may be used to indicate inclination, as a level, or, as used in the turn indicators, to show the relationship between gravity and centrifugal force in a turn.

Indicated airspeed (IAS). The direct instrument reading obtained from the airspeed indicator, uncorrected for variations in atmospheric density, installation error, or instrument error. Manufacturers use this airspeed as the basis for determining airplane performance. Takeoff, landing, and stall speeds listed in the AFM or POH are indicated airspeeds and do not normally vary with altitude or temperature.

Indicated altitude. The altitude read directly from the altimeter (uncorrected) when it is set to the current altimeter setting.

Induced drag. That part of total drag which is created by the production of lift. Induced drag increases with a decrease in airspeed.

Induction manifold. The part of the engine that distributes intake air to the cylinders.

Inertia. The opposition which a body offers to a change of motion.

Initial climb. This stage of the climb begins when the airplane leaves the ground and a pitch attitude has been established to climb away from the takeoff area.

Instrument Flight Rules (IFR). Rules that govern the procedure for conducting flight in weather conditions below VFR weather minimums. The term “IFR” also is used to define weather conditions and the type of flight plan under which an aircraft is operating.

Integral fuel tank. A portion of the aircraft structure, usually a wing, which is sealed off and used as a fuel tank. When a wing is used as an integral fuel tank, it is called a “wet wing.”

Intercooler. A device used to reduce the temperature of the compressed air before it enters the fuel metering device. The resulting cooler air has a higher density, which permits the engine to be operated with a higher power setting.

Internal combustion engine. An engine that produces power as a result of expanding hot gases from the combustion of fuel and air within the engine itself. A steam engine where coal is burned to heat up water inside the engine is an example of an external combustion engine.

International Standard Atmosphere (ISA). Standard atmospheric conditions consisting of a temperature of 59 °F (15 °C), and a barometric pressure of 29.92 "Hg. (1013.2 mb) at sea level. ISA values can be calculated for various altitudes using a standard lapse rate of approximately 2 °C per 1,000 feet.

Interstage turbine temperature (ITT). The temperature of the gases between the high pressure and low pressure turbines.

Inverter. An electrical device that changes DC to AC power.

Irreversible Deceleration and/or Sink Rate. Unrecoverable depletion of mechanical energy as a result of continuous loss of airspeed and/or altitude coupled with insufficient excess power available under a given flight condition. Failure to recover above a certain critical AGL altitude results in the airplane hitting the ground regardless of what the pilot does.

J

Jet-powered airplane. An aircraft powered by a turbojet or turbofan engine.

K

Kinesthesia. The sensing of movements by feel.

Kinetic energy. Amount of energy due to the airspeed, expressed as $\frac{1}{2}mV^2$ where m = airplane's mass and V = airspeed.

L

Lateral axis. An imaginary line passing through the center of gravity of an airplane and extending across the airplane from wingtip to wingtip.

Lateral stability (rolling). The stability about the longitudinal axis of an aircraft. Rolling stability or the ability of an airplane to return to level flight due to a disturbance that causes one of the wings to drop.

Lead-acid battery. A commonly used secondary cell having lead as its negative plate and lead peroxide as its positive plate. Sulfuric acid and water serve as the electrolyte.

Leading edge devices. High lift devices which are found on the leading edge of the airfoil. The most common types are fixed slots, movable slats, and leading edge flaps.

Leading edge flap. A portion of the leading edge of an airplane wing that folds downward to increase the camber, lift, and drag of the wing. The leading-edge flaps are extended for takeoffs and landings to increase the amount of aerodynamic lift that is produced at any given airspeed.

Leading edge. The part of an airfoil that meets the airflow first.

Licensed empty weight. The empty weight that consists of the airframe, engine(s), unusable fuel, and undrainable oil plus standard and optional equipment as specified in the equipment list. Some manufacturers used this term prior to GAMA standardization.

Lift coefficient. A coefficient representing the lift of a given airfoil. Lift coefficient is obtained by dividing the lift by the free-stream dynamic pressure and the representative area under consideration.

Lift. One of the four main forces acting on an aircraft. On a fixed-wing aircraft, an upward force created by the effect of airflow as it passes over and under the wing.

Lift/drag ratio (L/D). The efficiency of an airfoil section. It is the ratio of the coefficient of lift to the coefficient of drag for any given angle of attack.

Lift-off. The act of becoming airborne as a result of the wings lifting the airplane off the ground, or the pilot rotating the nose up, increasing the angle of attack to start a climb.

Limit load factor. Amount of stress, or load factor, that an aircraft can withstand before structural damage or failure occurs.

Load factor. The ratio of the load supported by the airplane's wings to the actual weight of the aircraft and its contents. Also referred to as G-loading.

Longitudinal axis. An imaginary line through an aircraft from nose to tail, passing through its center of gravity. The longitudinal axis is also called the roll axis of the aircraft. Movement of the ailerons rotates an airplane about its longitudinal axis.

Longitudinal stability (pitching). Stability about the lateral axis. A desirable characteristic of an airplane whereby it tends to return to its trimmed angle of attack after displacement.

M

Mach buffet. Airflow separation behind a shock-wave pressure barrier caused by airflow over flight surfaces exceeding the speed of sound.

Mach compensating device. A device to alert the pilot of inadvertent excursions beyond its certified maximum operating speed.

Mach critical. The Mach speed at which some portion of the airflow over the wing first equals Mach 1.0. This is also the speed at which a shock wave first appears on the airplane.

Mach tuck. A condition that can occur when operating a swept-wing airplane in the transonic speed range. A shock wave could form in the root portion of the wing and cause the air behind it to separate. This shock-induced separation causes the center of pressure to move aft. This, combined with the increasing amount of nose down force at higher speeds to maintain level flight, causes the nose to "tuck." If not corrected, the airplane could enter a steep, sometimes unrecoverable dive.

Mach. Speed relative to the speed of sound. Mach 1 is the speed of sound.

Magnetic compass. A device for determining direction measured from magnetic north.

Main gear. The wheels of an aircraft's landing gear that supports the major part of the aircraft's weight.

Maneuverability. Ability of an aircraft to change directions along a flightpath and withstand the stresses imposed upon it.

Maneuvering speed (V_A). The maximum speed where full, abrupt control movement can be used without overstressing the airframe.

Manifold pressure (MP). The absolute pressure of the fuel/ air mixture within the intake manifold, usually indicated in inches of mercury.

Maximum allowable takeoff power. The maximum power an engine is allowed to develop for a limited period of time; usually about one minute.

Maximum landing weight. The greatest weight that an airplane normally is allowed to have at landing.

Maximum ramp weight. The total weight of a loaded aircraft, including all fuel. It is greater than the takeoff weight due to the fuel that will be burned during the taxi and run-up operations. Ramp weight may also be referred to as taxi weight.

Maximum takeoff weight. The maximum allowable weight for takeoff.

Maximum weight. The maximum authorized weight of the aircraft and all of its equipment as specified in the Type Certificate Data Sheets (TCDS) for the aircraft.

Maximum zero fuel weight (GAMA). The maximum weight, exclusive of usable fuel.

Minimum controllable airspeed. An airspeed at which any further increase in angle of attack, increase in load factor, or reduction in power, would result in an immediate stall.

Minimum drag speed (L/D_{MAX}). The point on the total drag curve where the lift-to-drag ratio is the greatest. At this speed, total drag is minimized.

Mixture. The ratio of fuel to air entering the engine's cylinders.

M_{MO} . Maximum operating speed expressed in terms of a decimal of Mach speed.

Moment arm. The distance from a datum to the applied force.

Moment index (or index). A moment divided by a constant such as 100, 1,000, or 10,000. The purpose of using a moment index is to simplify weight and balance computations of airplanes where heavy items and long arms result in large, unmanageable numbers.

Moment. The product of the weight of an item multiplied by its arm. Moments are expressed in pound-inches (lb-in). Total moment is the weight of the airplane multiplied by the distance between the datum and the CG.

Movable slat. A movable auxiliary airfoil on the leading edge of a wing. It is closed in normal flight but extends at high angles of attack. This allows air to continue flowing over the top of the wing and delays airflow separation.

Mushing. A flight condition caused by slow speed where the control surfaces are marginally effective.

N

N₁, N₂, N₃. Spool speed expressed in percent rpm. N₁ on a turboprop is the gas producer speed. N₁ on a turbofan or turbojet engine is the fan speed or low pressure spool speed. N₂ is the high pressure spool speed on engine with 2 spools and medium pressure spool on engines with 3 spools with N₃ being the high pressure spool.

Nacelle. A streamlined enclosure on an aircraft in which an engine is mounted. On multiengine propeller-driven airplanes, the nacelle is normally mounted on the leading edge of the wing.

Negative static stability. The initial tendency of an aircraft to continue away from the original state of equilibrium after being disturbed.

Negative torque sensing (NTS). A system in a turboprop engine that prevents the engine from being driven by the propeller. The NTS increases the blade angle when the propellers try to drive the engine.

Neutral static stability. The initial tendency of an aircraft to remain in a new condition after its equilibrium has been disturbed.

Nickel-cadmium battery (NiCad). A battery made up of alkaline secondary cells. The positive plates are nickel hydroxide, the negative plates are cadmium hydroxide, and potassium hydroxide is used as the electrolyte.

Normal category. An airplane that has a seating configuration, excluding pilot seats, of nine or less, a maximum certificated takeoff weight of 12,500 pounds or less, and intended for nonacrobatic operation.

Normalizing (turbonormalizing). A turbocharger that maintains sea level pressure in the induction manifold at altitude.

O

Octane. The rating system of aviation gasoline with regard to its antidetonating qualities.

Overboost. A condition in which a reciprocating engine has exceeded the maximum manifold pressure allowed by the manufacturer. Can cause damage to engine components.

Overspeed. A condition in which an engine has produced more rpm than the manufacturer recommends, or a condition in which the actual engine speed is higher than the desired engine speed as set on the propeller control.

Overtemp. A condition in which a device has reached a temperature above that approved by the manufacturer or any exhaust temperature that exceeds the maximum allowable for a given operating condition or time limit. Can cause internal damage to an engine.

Overtorque. A condition in which an engine has produced more torque (power) than the manufacturer recommends, or a condition in a turboprop or turboshaft engine where the engine power has exceeded the maximum allowable for a given operating condition or time limit. Can cause internal damage to an engine.

P

Parasite drag. That part of total drag created by the design or shape of airplane parts. Parasite drag increases with an increase in airspeed.

Payload (GAMA). The weight of occupants, cargo, and baggage.

P-factor. A tendency for an aircraft to yaw to the left due to the descending propeller blade on the right producing more thrust than the ascending blade on the left. This occurs when the aircraft's longitudinal axis is in a climbing attitude in relation to the relative wind. The P-factor would be to the right if the aircraft had a counterclockwise rotating propeller.

Pilot's Operating Handbook (POH). A document developed by the airplane manufacturer and contains the FAA-approved Airplane Flight Manual (AFM) information.

Piston engine. A reciprocating engine.

Pitch. The rotation of an airplane about its lateral axis, or on a propeller, the blade angle as measured from plane of rotation.

Pivotal altitude. A specific altitude at which, when an airplane turns at a given groundspeed, a projecting of the sighting reference line to a selected point on the ground will appear to pivot on that point.

Pneumatic system. The power system in an aircraft used for operating such items as landing gear, brakes, and wing flaps with compressed air as the operating fluid.

Porpoising. Oscillating around the lateral axis of the aircraft during landing.

Position lights. Lights on an aircraft consisting of a red light on the left wing, a green light on the right wing, and a white light on the tail. CFRs require that these lights be displayed in flight from sunset to sunrise.

Positive static stability. The initial tendency to return to a state of equilibrium when disturbed from that state.

Potential energy. Amount of energy due to the altitude, expressed as mgh , where m = airplane's mass, and g = gravitational constant, and h = altitude.

Power available. The airplane's rate of energy gain due to maximum available engine thrust at a given airspeed. Expressed as TV , where T = engine thrust, and V = airspeed. Usually measured in horsepower, foot-pound per minute, or foot-pound per second.

Power distribution bus. See bus bar.

Power lever. The cockpit lever connected to the fuel control unit for scheduling fuel flow to the combustion chambers of a turbine engine.

Power required. The airplane's rate of energy loss due to total drag at a given airspeed. Expressed as DV , where D = total drag, and V = airspeed. Usually measured in horsepower, foot-pound per minute, or foot-pound per second.

Power. Implies work rate or units of work per unit of time, and as such, it is a function of the speed at which the force is developed. The term "power required" is generally associated with reciprocating engines.

Powerplant. A complete engine and propeller combination with accessories.

Practical slip limit. The maximum slip an aircraft is capable of performing due to rudder travel limits.

Precession. The tilting or turning of a gyro in response to deflective forces causing slow drifting and erroneous indications in gyroscopic instruments.

Preignition. Ignition occurring in the cylinder before the time of normal ignition. Preignition is often caused by a local hot spot in the combustion chamber igniting the fuel/air mixture.

Pressure altitude. The altitude indicated when the altimeter setting window (barometric scale) is adjusted to 29.92. This is the altitude above the standard datum plane, which is a theoretical plane where air pressure (corrected to 15 °C) equals 29.92 "Hg. Pressure altitude is used to compute density altitude, true altitude, true airspeed, and other performance data.

Profile drag. The total of the skin friction drag and form drag for a two-dimensional airfoil section.

Propeller blade angle. The angle between the propeller chord and the propeller plane of rotation.

Propeller lever. The control on a free power turbine turboprop that controls propeller speed and the selection for propeller feathering.

Propeller slipstream. The volume of air accelerated behind a propeller producing thrust.

Propeller synchronization. A condition in which all of the propellers have their pitch automatically adjusted to maintain a constant rpm among all of the engines of a multiengine aircraft.

Propeller. A device for propelling an aircraft that, when rotated, produces by its action on the air, a thrust approximately perpendicular to its plane of rotation. It includes the control components normally supplied by its manufacturer.

R

Ramp weight. The total weight of the aircraft while on the ramp. It differs from takeoff weight by the weight of the fuel that will be consumed in taxiing to the point of takeoff.

Rate of turn. The rate in degrees/second of a turn.

Reciprocating engine. An engine that converts the heat energy from burning fuel into the reciprocating movement of the pistons. This movement is converted into a rotary motion by the connecting rods and crankshaft.

Reduction gear. The gear arrangement in an aircraft engine that allows the engine to turn at a faster speed than the propeller.

Region of reverse command. Flight regime in which flight at a higher airspeed requires a lower power setting and a lower airspeed requires a higher power setting in order to maintain altitude.

Registration certificate. A State and Federal certificate that documents aircraft ownership.

Relative wind. The direction of the airflow with respect to the wing. If a wing moves forward horizontally, the relative wind moves backward horizontally. Relative wind is parallel to and opposite the flightpath of the airplane.

Reverse thrust. A condition where jet thrust is directed forward during landing to increase the rate of deceleration.

Reversing propeller. A propeller system with a pitch change mechanism that includes full reversing capability. When the pilot moves the throttle controls to reverse, the blade angle changes to a pitch angle and produces a reverse thrust, which slows the airplane down during a landing.

Roll. The motion of the aircraft about the longitudinal axis. It is controlled by the ailerons.

Roundout (flare). A pitch-up during landing approach to reduce rate of descent and forward speed prior to touchdown.

Rudder. The movable primary control surface mounted on the trailing edge of the vertical fin of an airplane. Movement of the rudder rotates the airplane about its vertical axis.

Ruddervator. A pair of control surfaces on the tail of an aircraft arranged in the form of a V. These surfaces, when moved together by the control wheel, serve as elevators, and when moved differentially by the rudder pedals, serve as a rudder.

Runway centerline lights. Runway centerline lights are installed on some precision approach runways to facilitate landing under adverse visibility conditions. They are located along the runway centerline and are spaced at 50-foot intervals. When viewed from the landing threshold, the runway centerline lights are white until the last 3,000 feet of the runway. The white lights begin to alternate with red for the next 2,000 feet, and for the last 1,000 feet of the runway, all centerline lights are red.

Runway centerline markings. The runway centerline identifies the center of the runway and provides alignment guidance during takeoff and landings. The centerline consists of a line of uniformly spaced stripes and gaps.

Runway edge lights. Runway edge lights are used to outline the edges of runways during periods of darkness or restricted visibility conditions. These light systems are classified according to the intensity or brightness they are capable of producing; they are the High Intensity Runway Lights (HIRL), Medium Intensity Runway Lights (MIRL), and the Low Intensity Runway Lights (LIRL). The HIRL and MIRL systems have variable intensity controls, whereas the LIRLs normally have one intensity setting.

Runway end identifier lights (REIL). One component of the runway lighting system. These lights are installed at many airfields to provide rapid and positive identification of the approach end of a particular runway.

Runway incursion. Any occurrence at an airport involving an aircraft, vehicle, person, or object on the ground that creates a collision hazard or results in loss of separation with an aircraft taking off, intending to takeoff, landing, or intending to land.

Runway threshold markings. Runway threshold markings come in two configurations. They either consist of eight longitudinal stripes of uniform dimensions disposed symmetrically about the runway centerline, or the number of stripes is related to the runway width. A threshold marking helps identify the beginning of the runway that is available for landing. In some instances, the landing threshold may be displaced.

S

Safety (SQUAT) switch. An electrical switch mounted on one of the landing gear struts. It is used to sense when the weight of the aircraft is on the wheels.

Scan. A procedure used by the pilot to visually identify all resources of information in flight.

Sea level. A reference height used to determine standard atmospheric conditions and altitude measurements.

Segmented circle. A visual ground based structure to provide traffic pattern information.

Service ceiling. The maximum density altitude where the best rate-of-climb airspeed will produce a 100 feet-per-minute climb at maximum weight while in a clean configuration with maximum continuous power.

Servo tab. An auxiliary control mounted on a primary control surface, which automatically moves in the direction opposite the primary control to provide an aerodynamic assist in the movement of the control.

Shaft horse power (SHP). Turboshaft engines are rated in shaft horsepower and calculated by use of a dynamometer device. Shaft horsepower is exhaust thrust converted to a rotating shaft.

Shock waves. A compression wave formed when a body moves through the air at a speed greater than the speed of sound.

Sideslip. A slip in which the airplane's longitudinal axis remains parallel to the original flightpath, but the airplane no longer flies straight ahead. Instead, the horizontal component of wing lift forces the airplane to move sideways toward the low wing.

Single engine absolute ceiling. The altitude that a twin engine airplane can no longer climb with one engine inoperative.

Single engine service ceiling. The altitude that a twin engine airplane can no longer climb at a rate greater than 50 fpm with one engine inoperative.

Skid. A condition where the tail of the airplane follows a path outside the path of the nose during a turn.

Slip. An intentional maneuver to decrease airspeed or increase rate of descent, and to compensate for a crosswind on landing. A slip can also be unintentional when the pilot fails to maintain the aircraft in coordinated flight.

Specific excess power (P_s). Measured in feet per minute or feet per second, it represents rate of energy change—the ability of an airplane to climb or accelerate from a given flight condition. Available specific excess power is found by dividing the difference between power available and power required by the airplane's weight.

Specific fuel consumption. Number of pounds of fuel consumed in 1 hour to produce 1 HP.

Speed brakes. A control system that extends from the airplane structure into the airstream to produce drag and slow the airplane.

Speed instability. A condition in the region of reverse command where a disturbance that causes the airspeed to decrease causes total drag to increase, which in turn, causes the airspeed to decrease further.

Speed sense. The ability to sense instantly and react to any reasonable variation of airspeed.

Speed. The distance traveled in a given time.

Spin. An aggravated stall that results in what is termed an “autorotation” wherein the airplane follows a downward corkscrew path. As the airplane rotates around the vertical axis, the rising wing is less stalled than the descending wing creating a rolling, yawing, and pitching motion.

Spiral instability. A condition that exists when the static directional stability of the airplane is very strong as compared to the effect of its dihedral in maintaining lateral equilibrium.

Spiraling slipstream. The slipstream of a propeller-driven airplane rotates around the airplane. This slipstream strikes the left side of the vertical fin, causing the airplane to yaw slightly. Vertical stabilizer offset is sometimes used by aircraft designers to counteract this tendency.

Split shaft turbine engine. See free power turbine engine.

Spoilers. High-drag devices that can be raised into the air flowing over an airfoil, reducing lift and increasing drag. Spoilers are used for roll control on some aircraft. Deploying spoilers on both wings at the same time allows the aircraft to descend without gaining speed. Spoilers are also used to shorten the ground roll after landing.

Spool. A shaft in a turbine engine which drives one or more compressors with the power derived from one or more turbines.

Stabilator. A single-piece horizontal tail surface on an airplane that pivots around a central hinge point. A stabilator serves the purposes of both the horizontal stabilizer and the elevator.

Stability. The inherent quality of an airplane to correct for conditions that may disturb its equilibrium, and to return or to continue on the original flightpath. It is primarily an airplane design characteristic.

Stabilized approach. A landing approach in which the pilot establishes and maintains a constant angle glidepath towards a predetermined point on the landing runway. It is based on the pilot’s judgment of certain visual cues, and depends on the maintenance of a constant final descent airspeed and configuration.

Stall strips. A spoiler attached to the inboard leading edge of some wings to cause the center section of the wing to stall before the tips. This assures lateral control throughout the stall.

Stall. A rapid decrease in lift caused by the separation of airflow from the wing’s surface brought on by exceeding the critical angle of attack. A stall can occur at any pitch attitude or airspeed.

Standard atmosphere. At sea level, the standard atmosphere consists of a barometric pressure of 29.92 inches of mercury ("Hg) or 1013.2 millibars, and a temperature of 15 °C (59 °F). Pressure and temperature normally decrease as altitude increases. The standard lapse rate in the lower atmosphere for each 1,000 feet of altitude is approximately 1 "Hg and 2 °C (3.5 °F). For example, the standard pressure and temperature at 3,000 feet mean sea level (MSL) is 26.92 "Hg (29.92 – 3) and 9 °C (15 °C – 6 °C).

Standard day. See standard atmosphere.

Standard empty weight (GAMA). This weight consists of the airframe, engines, and all items of operating equipment that have fixed locations and are permanently installed in the airplane; including fixed ballast, hydraulic fluid, unusable fuel, and full engine oil.

Standard weights. These have been established for numerous items involved in weight and balance computations. These weights should not be used if actual weights are available.

Standard-rate turn. A turn at the rate of 3° per second which enables the airplane to complete a 360° turn in 2 minutes.

Starter/generator. A combined unit used on turbine engines. The device acts as a starter for rotating the engine, and after running, internal circuits are shifted to convert the device into a generator.

Static stability. The initial tendency an aircraft displays when disturbed from a state of equilibrium.

Station. A location in the airplane that is identified by a number designating its distance in inches from the datum. The datum is, therefore, identified as station zero. An item located at station +50 would have an arm of 50 inches.

Stick puller. A device that applies aft pressure on the control column when the airplane is approaching the maximum operating speed.

Stick pusher. A device that applies an abrupt and large forward force on the control column when the airplane is nearing an angle of attack where a stall could occur.

Stick shaker. An artificial stall warning device that vibrates the control column.

Stress risers. A scratch, groove, rivet hole, forging defect, or other structural discontinuity that causes a concentration of stress.

Subsonic. Speed below the speed of sound.

Supercharger. An engine- or exhaust-driven air compressor used to provide additional pressure to the induction air so the engine can produce additional power.

Supersonic. Speed above the speed of sound.

Supplemental Type Certificate (STC). A certificate authorizing an alteration to an airframe, engine, or component that has been granted an approved type certificate.

Swept-wing. A wing planform in which the tips of the wing are farther back than the wing root.

T

Tailwheel aircraft. See conventional landing gear.

Takeoff roll (ground roll). The total distance required for an aircraft to become airborne.

Target reverser. A thrust reverser in a jet engine in which clamshell doors swivel from the stowed position at the engine tailpipe to block all of the outflow and redirect some component of the thrust forward.

Taxiway lights. Omnidirectional lights that outline the edges of the taxiway and are blue in color.

Taxiway turnoff lights. Flush lights which emit a steady green color.

Tetrahedron. A large, triangular-shaped, kite-like object installed near the runway. Tetrahedrons are mounted on a pivot and are free to swing with the wind to show the pilot the direction of the wind as an aid in takeoffs and landings.

Throttle. The valve in a carburetor or fuel control unit that determines the amount of fuel-air mixture that is fed to the engine.

Thrust line. An imaginary line passing through the center of the propeller hub, perpendicular to the plane of the propeller rotation.

Thrust reversers. Devices which redirect the flow of jet exhaust to reverse the direction of thrust.

Thrust. The force which imparts a change in the velocity of a mass. This force is measured in pounds but has no element of time or rate. The term, thrust required, is generally associated with jet engines. A forward force which propels the airplane through the air.

Timing. The application of muscular coordination at the proper instant to make flight, and all maneuvers incident thereto, a constant smooth process.

Tire cord. Woven metal wire laminated into the tire to provide extra strength. A tire showing any cord must be replaced prior to any further flight.

Torque meter. An indicator used on some large reciprocating engines or on turboprop engines to indicate the amount of torque the engine is producing.

Torque sensor. See torque meter.

Torque. 1. A resistance to turning or twisting. 2. Forces that produce a twisting or rotating motion. 3. In an airplane, the tendency of the aircraft to turn (roll) in the opposite direction of rotation of the engine and propeller.

Total drag. The sum of the parasite and induced drag.

Total energy error. An energy error where the total amount of mechanical energy is not correct. The airplane has too much or too little total energy relative to the intended altitude-speed profile. When this error occurs, the pilot will observe that altitude and airspeed deviate in the *same* direction (e.g., higher and faster than desired; or lower and slower than desired). An example would be an airplane on final approach that is above the desired glide slope and at a faster airspeed than desired.

Total mechanical energy. Sum of the energy in altitude (potential energy) and the energy in airspeed (kinetic energy).

Touchdown zone lights. Two rows of transverse light bars disposed symmetrically about the runway centerline in the runway touchdown zone.

Track. The actual path made over the ground in flight.

Trailing edge. The portion of the airfoil where the airflow over the upper surface rejoins the lower surface airflow.

Transition liner. The portion of the combustor that directs the gases into the turbine plenum.

Transonic. At the speed of sound.

Transponder. The airborne portion of the secondary surveillance radar system. The transponder emits a reply when queried by a radar facility.

Tricycle gear. Landing gear employing a third wheel located on the nose of the aircraft.

Trim tab. A small auxiliary hinged portion of a movable control surface that can be adjusted during flight to a position resulting in a balance of control forces.

Triple spool engine. Usually a turboprop engine design where the fan is the N_1 compressor, followed by the N_2 intermediate compressor, and the N_3 high pressure compressor, all of which rotate on separate shafts at different speeds.

Tropopause. The boundary layer between the troposphere and the mesosphere which acts as a lid to confine most of the water vapor, and the associated weather, to the troposphere.

Troposphere. The layer of the atmosphere extending from the surface to a height of 20,000 to 60,000 feet depending on latitude.

True airspeed (TAS). Calibrated airspeed corrected for altitude and nonstandard temperature. Because air density decreases with an increase in altitude, an airplane has to be flown faster at higher altitudes to cause the same pressure difference between pitot impact pressure and static pressure. Therefore, for a given calibrated airspeed, true airspeed increases as altitude increases; or for a given true airspeed, calibrated airspeed decreases as altitude increases.

True altitude. The vertical distance of the airplane above sea level—the actual altitude. It is often expressed as feet above mean sea level (MSL). Airport, terrain, and obstacle elevations on aeronautical charts are true altitudes.

T-tail. An aircraft with the horizontal stabilizer mounted on the top of the vertical stabilizer, forming a T.

Turbine blades. The portion of the turbine assembly that absorbs the energy of the expanding gases and converts it into rotational energy.

Turbine outlet temperature (TOT). The temperature of the gases as they exit the turbine section.

Turbine plenum. The portion of the combustor where the gases are collected to be evenly distributed to the turbine blades.

Turbine rotors. The portion of the turbine assembly that mounts to the shaft and holds the turbine blades in place.

Turbine section. The section of the engine that converts high pressure high temperature gas into rotational energy.

Turbocharger. An air compressor driven by exhaust gases, which increases the pressure of the air going into the engine through the carburetor or fuel injection system.

Turboprop engine. A turbojet engine in which additional propulsive thrust is gained by extending a portion of the compressor or turbine blades outside the inner engine case. The extended blades propel bypass air along the engine axis but between the inner and outer casing. The air is not combusted but does provide additional thrust.

Turbojet engine. A jet engine incorporating a turbine-driven air compressor to take in and compress air for the combustion of fuel, the gases of combustion being used both to rotate the turbine and create a thrust producing jet.

Turboprop engine. A turbine engine that drives a propeller through a reduction gearing arrangement. Most of the energy in the exhaust gases is converted into torque, rather than its acceleration being used to propel the aircraft.

Turbulence. An occurrence in which a flow of fluid is unsteady.

Turn coordinator. A rate gyro that senses both roll and yaw due to the gimbal being canted. Has largely replaced the turn-and-slip indicator in modern aircraft.

Turn-and-slip indicator. A flight instrument consisting of a rate gyro to indicate the rate of yaw and a curved glass inclinometer to indicate the relationship between gravity and centrifugal force. The turn-and-slip indicator indicates the relationship between angle of bank and rate of yaw. Also called a turn-and-bank indicator.

Turning error. One of the errors inherent in a magnetic compass caused by the dip compensating weight. It shows up only on turns to or from northerly headings in the Northern Hemisphere and southerly headings in the Southern Hemisphere. Turning error causes the compass to lead turns to the north or south and lag turns away from the north or south.

U

Ultimate load factor. In stress analysis, the load that causes physical breakdown in an aircraft or aircraft component during a strength test, or the load that according to computations, should cause such a breakdown.

Unfeathering accumulator. Tanks that hold oil under pressure which can be used to unfeather a propeller.

UNICOM. A nongovernment air/ground radio communication station which may provide airport information at public use airports where there is no tower or FSS.

Unusable fuel. Fuel that cannot be consumed by the engine. This fuel is considered part of the empty weight of the aircraft.

Useful load. The weight of the pilot, copilot, passengers, baggage, usable fuel, and drainable oil. It is the basic empty weight subtracted from the maximum allowable gross weight. This term applies to general aviation aircraft only.

Utility category. An airplane that has a seating configuration, excluding pilot seats, of nine or less, a maximum certificated takeoff weight of 12,500 pounds or less, and intended for limited acrobatic operation.

V

V₁. Critical engine failure speed or takeoff decision speed. It is the speed at which the pilot is to continue the takeoff in the event of an engine failure or other serious emergency. At speeds less than V₁, it is considered safer to stop the aircraft within the accelerate-stop distance. It is also the minimum speed in the takeoff, following a failure of the critical engine at V_{EF}, at which the pilot can continue the takeoff and achieve the required height above the takeoff surface within the takeoff distance.

V₂. takeoff safety speed, or a referenced airspeed obtained after lift-off at which the required one engine-inoperative climb performance can be achieved.

V_A. The design maneuvering speed. This is the “rough air” speed and the maximum speed for abrupt maneuvers. If during flight, rough air or severe turbulence is encountered, reduce the airspeed to maneuvering speed or less to minimize stress on the airplane structure. It is important to consider weight when referencing this speed. For example, V_A may be 100 knots when an airplane is heavily loaded, but only 90 knots when the load is light.

Vapor lock. A condition in which air enters the fuel system and it may be difficult, or impossible, to restart the engine. Vapor lock may occur as a result of running a fuel tank completely dry, allowing air to enter the fuel system. On fuel-injected engines, the fuel may become so hot it vaporizes in the fuel line, not allowing fuel to reach the cylinders.

V-bars. The flight director displays on the attitude indicator that provide control guidance to the pilot.

Vector. A force vector is a graphic representation of a force and shows both the magnitude and direction of the force.

Velocity. The speed or rate of movement in a certain direction.

Vertical axis. An imaginary line passing vertically through the center of gravity of an aircraft. The vertical axis is called the z-axis or the yaw axis.

Vertical card compass. A magnetic compass that consists of an azimuth on a vertical card, resembling a heading indicator with a fixed miniature airplane to accurately present the heading of the aircraft. The design uses eddy current damping to minimize lead and lag during turns.

Vertical speed indicator (VSI). An instrument that uses static pressure to display a rate of climb or descent in feet per minute. The VSI can also sometimes be called a vertical velocity indicator (VVI).

Vertical stability. Stability about an aircraft’s vertical axis. Also called yawing or directional stability.

V_{FE}. The maximum speed with the flaps extended. The upper limit of the white arc.

V_{FO}. The maximum speed that the flaps can be extended or retracted.

VFR Terminal Area Charts (1:250,000). Depict Class B airspace which provides for the control or segregation of all the aircraft within the Class B airspace. The chart depicts topographic information and aeronautical information which includes visual and radio aids to navigation, airports, controlled airspace, restricted areas, obstructions, and related data.

V-G diagram. A chart that relates velocity to load factor. It is valid only for a specific weight, configuration, and altitude and shows the maximum amount of positive or negative lift the airplane is capable of generating at a given speed. Also shows the safe load factor limits and the load factor that the aircraft can sustain at various speeds.

Visual approach slope indicator (VASI). The most common visual glidepath system in use. The VASI provides obstruction clearance within 10° of the extended runway centerline, and to 4 nautical miles (NM) from the runway threshold.

Visual Flight Rules (VFR). Code of Federal Regulations that govern the procedures for conducting flight under visual conditions.

V_{LE}. Landing gear extended speed. The maximum speed at which an airplane can be safely flown with the landing gear extended.

V_{LO}. Landing gear operating speed. The maximum speed for extending or retracting the landing gear if using an airplane equipped with retractable landing gear.

V_{LOF}. Lift-off speed. The speed at which the aircraft departs the runway during takeoff.

V_{MC}. Minimum control airspeed. This is the minimum flight speed at which a twin-engine airplane can be satisfactorily controlled when an engine suddenly becomes inoperative and the remaining engine is at takeoff power.

V_{MD}. Minimum drag speed.

V_{MO}. Maximum operating speed expressed in knots.

V_{NE}. Never-exceed speed. Operating above this speed is prohibited since it may result in damage or structural failure. The red line on the airspeed indicator.

V_{NO}. Maximum structural cruising speed. Do not exceed this speed except in smooth air. The upper limit of the green arc.

V_P. Minimum dynamic hydroplaning speed. The minimum speed required to start dynamic hydroplaning.

V_R. Rotation speed. The speed that the pilot begins rotating the aircraft prior to lift-off.

V_{S0}. Stalling speed or the minimum steady flight speed in the landing configuration. In small airplanes, this is the power-off stall speed at the maximum landing weight in the landing configuration (gear and flaps down). The lower limit of the white arc.

V_{S1}. Stalling speed or the minimum steady flight speed obtained in a specified configuration. For most airplanes, this is the power-off stall speed at the maximum takeoff weight in the clean configuration (gear up, if retractable, and flaps up). The lower limit of the green arc.

V-speeds. Designated speeds for a specific flight condition.

V_{SSE}. Safe, intentional one-engine inoperative speed. The minimum speed to intentionally render the critical engine inoperative.

V-tail. A design which utilizes two slanted tail surfaces to perform the same functions as the surfaces of a conventional elevator and rudder configuration. The fixed surfaces act as both horizontal and vertical stabilizers.

V_X. Best angle-of-climb speed. The airspeed at which an airplane gains the greatest amount of altitude in a given distance. It is used during a short-field takeoff to clear an obstacle.

V_{XSE}. Best angle of climb speed with one engine inoperative. The airspeed at which an airplane gains the greatest amount of altitude in a given distance in a light, twin-engine airplane following an engine failure.

V_Y. Best rate-of-climb speed. This airspeed provides the most altitude gain in a given period of time.

V_{YSE}. Best rate-of-climb speed with one engine inoperative. This airspeed provides the most altitude gain in a given period of time in a light, twin-engine airplane following an engine failure.

W

Wake turbulence. Wingtip vortices that are created when an airplane generates lift. When an airplane generates lift, air spills over the wingtips from the high pressure areas below the wings to the low pressure areas above them. This flow causes rapidly rotating whirlpools of air called wingtip vortices or wake turbulence.

Waste gate. A controllable valve in the tailpipe of an aircraft reciprocating engine equipped with a turbocharger. The valve is controlled to vary the amount of exhaust gases forced through the turbocharger turbine.

Weathervane. The tendency of the aircraft to turn into the relative wind.

Weight and balance. The aircraft is said to be in weight and balance when the gross weight of the aircraft is under the max gross weight, and the center of gravity is within limits and will remain in limits for the duration of the flight.

Weight. A measure of the heaviness of an object. The force by which a body is attracted toward the center of the earth (or another celestial body) by gravity. Weight is equal to the mass of the body times the local value of gravitational acceleration. One of the four main forces acting on an aircraft. Equivalent to the actual weight of the aircraft. It acts downward through the aircraft's center of gravity toward the center of the earth. Weight opposes lift.

Wheelbarrowing. A condition caused when forward yoke or stick pressure during takeoff or landing causes the aircraft to ride on the nose-wheel alone.

Wind correction angle. Correction applied to the course to establish a heading so that track will coincide with course.

Wind direction indicators. Indicators that include a wind sock, wind tee, or tetrahedron. Visual reference will determine wind direction and runway in use.

Wind shear. A sudden, drastic shift in wind speed, direction, or both that may occur in the horizontal or vertical plane.

Windmilling. When the air moving through a propeller creates the rotational energy.

Windsock. A truncated cloth cone open at both ends and mounted on a freewheeling pivot that indicates the direction from which the wind is blowing.

Wing area. The total surface of the wing (square feet), which includes control surfaces and may include wing area covered by the fuselage (main body of the airplane), and engine nacelles.

Wing span. The maximum distance from wingtip to wingtip.

Wing twist. A design feature incorporated into some wings to improve aileron control effectiveness at high angles of attack during an approach to a stall.

Wing. Airfoil attached to each side of the fuselage and are the main lifting surfaces that support the airplane in flight.

Wingtip vortices. The rapidly rotating air that spills over an airplane's wings during flight. The intensity of the turbulence depends on the airplane's weight, speed, and configuration. It is also referred to as wake turbulence. Vortices from heavy aircraft may be extremely hazardous to small aircraft.

Y

Yaw string. A string on the nose or windshield of an aircraft in view of the pilot that indicates any slipping or skidding of the aircraft.

Yaw. Rotation about the vertical axis of an aircraft.

Z

Zero fuel weight. The weight of the aircraft to include all useful load except fuel.

Zero sideslip. A maneuver in a twin-engine airplane with one engine inoperative that involves a small amount of bank and slightly uncoordinated flight to align the fuselage with the direction of travel and minimize drag.

Zero thrust (simulated feather). An engine configuration with a low power setting that simulates a propeller feathered condition.

Airplane Flying Handbook (FAA-H-8083-3C)

Index

A

Abnormal engine instrument indication	18-16
Absence of propeller:	
Drag	16-4
Effect	16-4
Slipstream	16-4
Academic material (knowledge and risk management)	5-5
Prevention through ADM and risk management	5-6
Prevention through proportional counter-response	5-6
Recovery	5-6
Accelerated stalls	5-19
Accelerate-go distance	13-10, 13-12
Accelerate-stop distance	13-10, 13-12, 13-15, 16-12
After-landing	1-15, 2-22
After-landing roll	2-22, 9-2, 9-9, 9-10, 9-16, 9-18, 9-21, 9-22, 9-23, 9-36, 9-38, 14-6, 14-7, 14-8
Aircraft energy management	4-18
Airframe and systems	17-5
Airplane-based UPRT	5-7
Airplane configuration	3-21, 5-19, 6-1, 9-1, 18-4
Airplane equipment and lighting	11-5
Airport and navigation lighting aids	11-6
Airport traffic patterns and operations	8-1
All-attitude/all-envelope flight training methods	5-8
All-engine service ceiling of multiengine airplanes	13-11
Alternator/generator	2-12, 13-6, 13-9, 18-10
Angle of attack	1-13, 1-14, 4-5, 5-1, 5-9, 5-10, 5-11, 5-12, 6-1, 9-8, 10-2, 12-1, 12-6, 13-19, 13-25, 13-26, 14-1, 15-8, 16-6, 16-7, 17-15
Anti-icing/deicing	13-9, 13-10
Approach (in an emergency)	18-4
Approach and landing (night)	11-10
Night emergencies	11-13
Approach and landing (sport)	17-14
Approaches to stalls (impending stalls), power-on, or power-off	5-17
Attitude and sink rate control	18-4
Attitude flying	3-4

Autoland systems	18-22
B	
Ballistic parachute systems	18-22
Ballooning during round out	9-32
Bank control	3-5, 6-5, 18-18
Basic safety concepts	18-2
Before start and starting engine	17-12
Before-take-off check	2-21, 13-11, 13-15, 17-4
Avionics	2-22
Electrical system	2-21
Engine operation	2-21
Flight controls	2-21
Flight instruments	2-22
Fuel system	2-21
Takeoff briefing	2-22
Trim	2-21
Vacuum system	2-22
Bouncing during touchdown	9-33
Brakes	2-10, 2-11, 2-16, 2-17, 2-19, 2-20, 2-21, 2-22, 2-23, 6-3, 6-11, 9-9, 9-10, 9-18, 9-20, 9-23, 9-24, 9-36, 9-37, 9-38, 11-8, 13-14, 13-15, 13-16, 13-17, 13-21, 14-1, 14-2, 14-3, 14-7, 14-8, 16-9, 16-10, 16-12, 16-14, 16-15, 16-16, 16-19, 16-24, 17-12
C	
Cabin fire	18-9, 18-10
Captain's briefing	16-13, 16-14
Cascade reversers	16-11
Chandelle	10-4, 10-5, 10-6
Climb gradient	12-16, 13-2, 13-3, 13-10, 13-11, 13-12, 16-20
Climbs and climbing turns	3-17
Climbing turns	3-20
Establishing a climb	3-19
Best angle of climb (V_X)	3-17, 3-18, 4-17, 13-1, 16-17
Best rate of climb (V_Y)	3-17, 3-18, 4-17, 6-4, 6-6, 13-1, 13-16, 16-17
Normal climb	3-17, 6-12, 6-13, 11-8
Combustion heater	13-8
Constant radius turn during flight	7-3
Construction	17-5
Aluminum	17-5
Composite	17-5

Steel tube and fabric	17-5
Continuous ignition	15-1
Controllable-pitch propeller	3-19, 12-1, 12-5 , 12-6
Blade angle control	12-6, 12-7
Climb	12-6, 12-7
Constant-speed propeller	10-5, 12-5 , 12-6, 12-7, 12-8, 13-3, 13-5, 13-9, 15-6, 18-9
Constant-speed propeller operation	12-8
Cruise	12-7
Fixed-pitch propellers	3-3, 10-5, 12-5, 12-8, 13-9
Governing range	12-8 , 15-5
Takeoff	12-6
Control touch	1-1, 16-16
Coordinated flight	3-11, 3-12, 3-13, 3-23, 5-1, 5-6, 5-8 , 5-9, 5-11, 5-13, 5-16, 5-17, 5-18, 5-20, 6-5, 6-6, 6-14, 7-17, 9-3, 9-13, 10-5, 10-7, 13-21, 13-27
Coordination	1-1
Correcting drift during straight-and-level flight	7-2
Cross-control stall	5-20
Crosswind after-landing roll (tailwheel)	14-7
Crosswind approach and landing	9-3, 9-10, 9-15 , 9-17, 13-21 , 17-4
Crosswind after landing roll	9-18
Crosswind final approach	9-15
Crab method	9-15
Wing-low (sideslip) method	9-15, 9-16
Crosswind round out (flare)	9-17
Crosswind touchdown	9-17
Maximum safe crosswind velocities	9-18
Crosswind takeoff	6-6 , 13-15 , 14-3
Initial climb	6-8 , 13-15, 13-16
Lift-off	6-7
Takeoff roll	6-6
Cruise	17-13
D	
Defining an airplane upset	5-1
Descents and descending turns	3-20 , 3-24, 5-10
Descent at minimum safe airspeed	3-21
Emergency descent	3-21, 10-3, 15-15, 18-8 , 18-9, 18-10, 18-22
Partial power descent	3-21
Detonation	2-7, 2-8, 12-8, 12-11

Directional control	2-19, 3-9, 5-11, 5-17, 5-22, 6-1, 6-14, 9-9, 9-18, 9-23, 9-33, 9-34, 9-37, 9-38, 13-2, 13-15, 13-17, 13-18, 13-23, 13-25, 13-26, 13-29, 13-30, 13-31, 13-32, 13-33, 13-36, 13-37, 14-1, 14-2, 14-3 , 14-5, 14-6, 14-7, 16-11, 16-14, 16-16, 16-24, 18-12, 18-13
Door opening in-flight	18-17
Drag devices	4-4, 16-9 , 16-11
Drift and ground track control	7-2
E	
Effect and use of flight controls	3-1
Feel of the airplane	3-3
Electrical fires	18-9
Elementary eights	7-10 , 7-13,
Eights across a road	7-10, 7-12
Eights along a road	7-10, 7-11 , 7-12
Eights around pylons	7-10, 7-13 , 7-14
Eights-on-pylons	7-14 , 7-15, 7-16, 7-17, 7-18
Elevator trim stall	5-20 , 5-21
Emergencies	3-23, 9-29, 11-5, 11-13, 13-35, 13-36, 15-13, 15-14, 15-15, 17-14 ,
Emergency approaches and landings (simulated)	9-28
Emergency descents	3-21, 10-3, 15-15, 18-8 , 18-9, 18-10, 18-22
Emergency landings	9-28, 18-1
Psychological hazards	18-1
Types of emergency landings	18-1
Ditching	3-23, 18-1, 18-7
Forced landing	7-2, 9-12, 11-13, 12-6
Precautionary landing	18-1, 18-8
Emergency situations	11-1, 17-14, 18-1, 18-22, 18-23
Energy balance equation	4-3, 4-4, 4-18
Energy error	4-12, 4-14, 4-19
Energy distribution error	4-12, 4-13, 4-19
Total energy error	4-12, 4-19
Energy exchange	4-2, 4-4, 4-5, 4-6, 4-8, 4-10, 4-18
Energy height or total specific energy (E_s)	4-7, 4-9, 4-19
Energy state	4-1, 4-2, 4-3, 4-6, 4-7, 4-8, 4-9, 4-10, 4-11, 4-12, 4-14, 4-18, 4-19, 5-13, 16-18
Energy system	4-1, 4-18
Engine and propeller	2-11 , 3-3, 6-1, 6-3, 13-12, 13-34, 15-3, 15-6
Engine failure:	
After lift-off	13-11
After takeoff	13-31, 13-32, 13-33

After takeoff (single-engine)	18-7
During flight	13-34
Engine fire	13-32, 18-8, 18-9
Engine inoperative approach and landing	13-34
Engine inoperative flight principles	13-23
Engines	17-6
Engine shutdown	2-23
Engine starting	2-16
Environmental factors	2-13, 5-2
Exhaust gas temperature (EGT)	12-10, 12-11, 13-15
F	
False start	15-12
Faulty approaches and landings	9-30
Feathering	2-21, 9-25, 13-3, 13-5, 13-6, 13-7, 13-29, 13-30, 13-35, 13-36, 15-1, 15-5, 18-9
Flap effectiveness	12-3
Flap control malfunction/failure	18-10
Asymmetric (split) flap	18-11
Landing gear malfunction	18-12
Loss of elevator control	18-11
Total flap failure	18-10
Flight director/autopilot	13-8
Flight environment	2-1, 15-13, 15-14, 17-8
Flight standards service	1-5
Floating during round out	9-32
Forward slip	9-4, 9-12, 9-13, 9-14, 9-15 , 9-26, 9-30
Four fundamentals	3-1 , 7-1
Climbs	3-17
Descents	3-20
Straight-and-level	3-6
Turns	3-11
Fowler flap	12-4
Fuel and oil	2-7
Fuel crossfeed	13-7
Full stalls:	
Power-off	5-17
Power-on	5-18
Function of flaps	12-1
Fundamentals of stall recovery	5-15

G

Gas turbine engine	15-1 , 15-2, 15-8, 16-2
Glides	3-21 , 3-23, 9-24
Gliding turns	3-23 , 3-24
Go-around	4-17 , 5-9, 5-17, 5-20, 5-21, 8-4, 9-6, 9-10 , 9-11, 9-12, 9-22, 9-30, 9-31, 9-32, 9-33, 9-34, 9-35, 12-4, 12-5, 13-22 , 13-23, 13-30, 13-33, 13-35, 14-5, 14-6, 16-4, 16-20, 16-22, 17-4
Rejected landings	9-10 , 9-12
Attitude	9-11
Configuration	9-11
Ground effect	9-12
Power	9-11
Ground loop	2-19, 9-9, 9-36 , 9-37, 14-6, 14-8 , 18-5
Ground operation	2-1, 2-12, 2-14 , 13-14 , 14-1, 14-8, 15-3, 15-6, 17-4

H

Hand propping	2-16 , 2-17
Hard landing	9-20, 9-22, 9-23, 9-35 , 12-4, 13-22, 16-23, 17-15
High final approach	9-30
High-performance airplane	12-1, 12-17, 12-18
High round out	9-10, 9-31
Human factors	5-2
Diversion of attention	5-2
IMC	5-2
Sensory overload/deprivation	5-3
Spatial disorientation	5-3
Startle response	5-3
Surprise response	5-3
Task saturation	5-3
VMC to IMC	5-2
Hydraulic pump	12-12, 12-14, 13-30, 18-9
Hydroplaning	9-37 , 9-38
Dynamic hydroplaning	9-37
Reverted rubber hydroplaning	9-37
Viscous hydroplaning	9-37

I

Impossible turn	18-7
Inadvertent flight into IMC	5-1, 5-2, 5-3, 5-26, 18-17
Attitude control	3-5, 18-17, 18-18

Climbs	18-20
Combined maneuvers	18-21
Descents	18-20
Maintaining airplane control	18-18
Recognition	18-17
Transition to visual flight	18-22
Turns	18-19
In-flight fire	15-14, 18-9
Initial climb	6-1, 6-5 , 6-6, 6-8 , 6-10, 6-11, 6-12 , 6-13 , 6-14, 12-16, 13-15, 13-16, 13-17, 13-29, 14-4, 15-2, 15-15, 16-2, 16-17 ,
Inside the airplane	2-21, 6-12, 17-9
Instrumentation	3-3, 3-5, 5-2, 5-4, 11-4, 17-7 , 18-15, 18-23
Integrated flight instruction	3-5 , 3-6
Intentional slips	9-12
Intentional spins	5-25 , 5-26
Interstage turbine temperature (ITT)	15-4, 15-5, 15-8
Irreversible deceleration and/or sink rate	4-1, 4-5, 4-11, 4-14 , 4-17, 4-19

J

Jet airplane approach and landing	16-17, 16-18, 16-19, 16-20, 16-21, 16-22, 16-23, 16-24
Approach speed	16-22
Glidepath control	16-22
Landing requirements	16-19
Landing speeds	16-20
Approach climb	16-20
Landing climb	16-20
V _{REF}	16-20
V _{SO}	16-20
Stabilized approach	16-21
The flare	16-23
Touchdown and rollout	16-24
Jet engine basics	16-1
Jet engine efficiency	16-4
Jet engine ignition	16-1

K

Kinetic energy	4-1, 4-7, 4-9, 4-18, 4-19, 16-10, 16-18, 16-19
----------------	--

L

Landing	9-2
---------	------------

Landing gear	2-10, 14-1
Instability	14-1
Landing gear control selected up, single-engine climb performance adequate	13-31
Checklist	13-32
Climb	13-32
Configuration	13-31
Control	13-31
Landing gear selected up, single-engine climb performance inadequate	13-30
Landing gear down	2-5, 13-16, 13-30
Late or rapid round out	9-31
Lazy eight	10-6, 10-7
Level-off and cruise	3-20, 12-8
Level turns	3-11
Establishing a turn	3-15
Medium turns	3-12
Shallow turns	3-12
Steep turns	3-12
Turn radius	3-14
Liftoff	6-4
Rotation	6-5
Light sport airplane (LSA) background	17-1
Loss of control in-flight (LOC-I)	4-1, 4-19, 5-1, 5-2, 5-3, 5-4, 5-5, 5-6, 5-27
Low final approach	9-30
Low speed flight	12-1, 16-6
LSA maintenance	17-4, 17-5
LSA synopsis	17-3

M

Mach buffet boundaries	16-6
Maneuvering by reference to ground objects	7-1
Minimum equipment list and configuration deviation list	16-24, 16-25
Multiengine training considerations	13-35

N

Night illusions	11-4
Black-hole approach	11-5
Visual autokinesis	11-4
Night vision	11-1
Noise abatement	16-14

Normal and crosswind takeoff and climb	13-15, 17-4
Normal approach and landing	9-2, 13-20
After-landing roll	9-9
Base leg	9-2
Final approach	9-3
Estimating height and movement	9-7
Use of flaps	9-1
Round out (flare)	9-8
Stabilized approach concept	9-4
Touchdown	9-9
Wrong surface landing avoidance	9-4
Normal takeoff	6-3
Initial climb	6-5
Lift-off	6-4
Takeoff roll	6-3
Nose baggage compartment	13-9
O	
Operating the jet engine	16-2
Operational considerations	15-11
Operation of systems	17-4, 13-3
Orientation and navigation	11-9
Outer wing surfaces	2-6
Outside of the airplane	2-21, 18-18
P	
Parking	2-18, 7-23, 11-8, 16-1, 17-4
Performance and limitations	13-10, 17-4
Pilot equipment	11-5
Pilot sensations in jet flying	16-11
Pitch and power	9-2, 9-3, 9-4, 9-20, 11-10, 12-4, 17-14
Pitch control	3-2, 3-5, 3-17, 3-23, 3-24, 5-10, 5-21, 10-2, 10-3, 10-4, 13-32, 16-12, 16-24, 18-9, 18-11, 18-18
Plain (hinge) flap	12-3
Porpoising	9-34, 9-35, 18-13
Post-flight	2-23, 17-15
Securing and servicing	2-23
Potential energy	4-1, 4-10, 4-18, 4-19, 16-18, 16-19
Power available	4-5, 4-14, 4-15, 4-16, 4-17, 4-18, 4-19, 13-3, 13-19, 13-29, 13-34, 16-20, 18-4
Power control	3-5, 4-6, 12-10, 16-2