


TempAMLSI: Temporal Action Model Learning Based on STRIPS Translation

Maxence Grand, Damien Pellier, Humbert Fiorino
 {Maxence.Grand, Damien.Pellier, Humbert.Fiorino}@univ-grenoble-alpes.fr

Temporal Planning



Classical STRIPS planning [1]: Some algorithms have been proposed to learn classical action model, e.g. ARMS [2], AMLS [3, 4], LSONIO [5] etc

Temporal planning [6]: Only the algorithm proposed by [7] learns Temporal domains. There exist different forms of required action concurrency [8]




Figure 1: An example of Sequential domain




Figure 2: An example of domain with Single Hard Enveloppe [9] (SHE Domain)

There are no learning algorithm able to learn SHE domains

Some planners resolve temporal problem using classical planner [9–13]

- Translate Temporal domains to Classical domains
- Solve Classical problems
- Generate Temporal Plan using the Classical Plan and scheduling techniques

TempAMLSI reuses this idea for the learning problem

The TempAMLSI Approach





Figure 3: TempAMLSI Overview

Temporal sequence:



Classical sequence:

$$\omega = \{ \text{start}(\text{light } m), \text{start}(\text{mend } f1 \text{ } m), \\ \text{end}(\text{mend } f1 \text{ } m), \text{start}(\text{mend } f2 \text{ } m), \\ \text{end}(\text{mend } f2 \text{ } m), \text{end}(\text{light } m) \}$$

Figure 4: Observation Translation

```
(:action mend-start
:parameters (?f - fuse ?m - match)
:precondition (and (handfree) (light ?m))
:effect (and (not (handfree))))
(:action mend-end
:parameters (?f - f ?m - m)
:precondition (and (light ?m))
:effect (and (mended ?f) (handfree)))

(:durative-action mend
:parameters (?f - fuse ?m - match)
:duration (= ?duration 2)
:condition (and (at start (handfree))
(over all (light ?m)))
:effect (and (at start (not (handfree)))
(at end (mended ?f))
(at end (handfree))))
```

Figure 5: Domain Translation




Figure 6: Average Performance in terms of Accuracy on 5 IPC Domains of 2-Operators and 3-Operators translation variants when the training data set size increases in number of actions

References

- [1] Richard Fikes and Nils J. Nilsson. STRIPS: A new approach to the application of theorem proving to problem solving. *Artif. Intell.*, 2(3/4):189–208, 1971.
- [2] Qiang Yang, Kangheng Wu, and Yunfei Jiang. Learning action models from plan examples using weighted MAX-SAT. *Artif. Intell.*, 171(2-3):107–143, 2007.
- [3] M. Grand, H. Fiorino, and D. Pellier. Retro-engineering state machines into pddl domains. In *Proc. ICTAI*, pages 1186–1193, 2020.
- [4] M. Grand, H. Fiorino, and D. Pellier. Amlsi: A novel and accurate action model learning algorithm. In *Proc. of the KEPS Workshop*, 2020.
- [5] Kira Mourão, Luke S. Zettlemoyer, Ronald P. A. Petrick, and Mark Steedman. Learning STRIPS operators from noisy and incomplete observations. In *Proc. of UAI*, pages 614–623, 2012.
- [6] Maria Fox and Derek Long. PDDL2.1: an extension to PDDL for expressing temporal planning domains. *J. Artif. Intell. Res.*, 20:61–124, 2003.
- [7] Antonio Garrido and Sergio Jiménez. Learning temporal action models via constraint programming. In *Proc. of ECAI*, pages 2362–2369, 2020.
- [8] William Cushing, Subbarao Kambhampati, Mausam, and Daniel S. Weld. When is temporal planning really temporal? In *Proc. of IJCAI*, pages 1852–1859, 2007.
- [9] Andrew Coles, Maria Fox, Keith Halsey, Derek Long, and Amanda Smith. Managing concurrency in temporal planning using planner-scheduler interaction. *Artif. Intell.*, 173(1):1–44, 2009.
- [10] Maria Fox and Derek Long. Fast temporal planning in a graphplan framework. In *Proc. of AIPS*, pages 9–17, 2002.
- [11] Keith Halsey, Derek Long, and Maria Fox. Crikey-a temporal planner looking at the integration of scheduling and planning. In *Proc. of the Workshop IPS*, pages 46–52. Citeseer, 2004.
- [12] Sergio Jiménez Celorrio, Anders Jonsson, and Héctor Palacios. Temporal planning with required concurrency using classical planning. In *Proc. of ICAPS*, pages 129–137, 2015.
- [13] Daniel Furelos Blanco, Anders Jonsson, Héctor Luis Palacios Verdes, and Sergio Jiménez. Forward-search temporal planning with simultaneous events. In *Proc. of AAAI*, 2018.

Acknowledgements

This research is supported by the French National Research Agency under the "Investissements d'avenir" program (ANR-15-IDEX-02) through the Cross Disciplinary Program CIRCULAR.