



DURBAN UNIVERSITY OF TECHNOLOGY
INYUVESI YASETHEKWINI YEZOBUCHWEPHESHE

FACULTY OF ACCOUNTING AND INFORMATICS

DEPARTMENT OF INFORMATION TECHNOLOGY

2024

MID YEAR SUPPLEMENTARY EXAMINATION

INSTRUCTIONAL PROGRAMME : B INFORMATION & COMMUNICATION TECHNOLOGY

INSTRUCTIONAL OFFERING : INTEGRATIVE PROGRAMMING AND TECHNOLOGIES III

PAPER NUMBER : 1

SUBJECT CODE/S : IPRT301

DATE :

DURATION : 3 HOURS

TIME : 14H00 - 17H00

TOTAL MARKS : 100

NUMBER OF PAGES : 10 (INCLUDING COVER PAGE)

EXAMINER/S : BOAMAH-ABU, CHARLES (PhD)

MODERATOR/S : IBIDUN OBAGBUWA, CHRISTIANA (PhD)

INSTRUCTIONS/REQUIREMENTS:-

1. This examination is closed book
2. Answer all questions
3. Where stated "briefly", please answer in a few lines
4. Ensure your handwriting is readable

Do not turn the page until permission is given

Question 1

6 marks

In each of the following write **T** (for **true**) or **F** (for **false**) for your answer.

- 1 Distributed applications must be tightly coupled
- 2 An abstract class cannot contain method definition
- 3 An abstract class can be instantiated
- 4 Method overload occurs in the same class
- 5 In polymorphism, an appropriate behaviour of an object is determined at run time
- 6 The adapter pattern applies if only one instance of a class is to be created

Question 2

9 marks

Briefly answer the following.

1. Explain how Integrative programming enables efficient use of organizational computing resources? **(3 marks)**
2. Give one reason why XML is important in distributed applications. **(2 marks)**
3. Give one benefit of design patterns. **(2 marks)**
4. Give one reason why Microservice architecture is preferable to Webservice. **(2 marks)**

Question 3

15 marks

1. **X**, **Y** and **Z** are interfaces. State whether the following is valid or invalid about interfaces. Explain your answer. **(8 marks)**

1.1. `X x1=new X1();`

1.2. `public interface Y implements X{`

`...`

`...`

`}`

1.3. `public interface Y extends X{`

`...`

`...`

`}`

1.4. `public interface Z, Y extends X{`

`...`


`...`

`}`

2. The UML diagram below shows class **B** inherits classes **A** and **C**.

2.1. Explain why the diagram cannot be converted to a Java program? **(3 marks)**


2.2. If **A** contains only constants and abstract methods and **B** contains instance variables and method definitions, explain how you can resolve the problem. **(4 marks)**



Question 4

20 marks

The UML diagram below shows the classes **Employee**, **PartTime**, **FullTime**, **Factory** and **Tester**.



- Employee** is an abstract class and contains **type** and **name** (of an employee); the abstract method **calcMonthlyGross()** returns the monthly gross income of an employee. **PartTime** and **FullTime** inherit **Employee**. The class contains appropriate **constructors** and **toString()** method
- PartTime** contains **numOfHours** (the number of hours an employee worked in a month) and overrides **calcMonthlyGross()** to return the monthly gross income as R80 per hour. The class contains appropriate **constructors** and **toString()** method
- FullTime** contains **annualSal** (the annual gross income of an employee) and overrides **calcMonthlyGross()** to return the monthly gross income as 1/12 of the annual gross income. The class contains appropriate **constructors** and **toString()** method
- Factory** is a factory class. **createEmployee(char type, String name, double num)** takes **type** and **name** (of an employee) and a **number** as parameters. If **type** is:
 - ‘P’: the method uses the parameters to create and return an instance of **PartTime**
 - ‘F’: the method uses the parameters to create and return an instance of **FullTime**
- Tester** creates an instance of **Factory** and calls its method to return an instance of a subclass (i.e., **PartTime** or **FullTime**) of **Employee**. The subclass is then displayed on the screen.

Use the information above to answer **Questions 1 to 5** below.

- Write the method **calcMonthlyGross()** in the class **Employee**. (2 marks)
- Write the header of the class **PartTime**. (2 marks)
- Write the method **calcMonthlyGross()** in the class **PartTime**. (3 marks)

4. Below, complete the method **createEmployee**(char type, String name, double num) in the class **Factory**. Assume the relevant classes and their methods (including **appropriate constructors**) have been implemented. (8 marks)

```
_____createEmployee(char type, String name, double num) {  
    _____  
    _____  
    _____  
    _____  
    _____  
}
```

5. Assume the relevant classes and their methods (including **appropriate constructors** and **toString()** methods) have been implemented. Below, complete **main()** in **Tester** as follows:

1. Create an instance of **Factory** called **f**. (1 mark)
2. Use **f** to call an appropriate method (with the values 'P', "Kofi Mensah", 120.00) to return the instance of a subclass. (3 marks)
3. Display the instance of the subclass on the screen. (1 mark)

```
...  
...  
public class Tester {  
    public static void main(String[] args) {  
        _____  
        _____  
        _____  
        _____  
    }  
}
```


Question 5

23 marks

The XML below is in the file **library.xml**.

```
<?xml version="1.0" encoding="UTF-8"?>
<Library>
  <book isbn="001-002-002-1">
    <title>Java for dummies</title>
  </book>
  <book isbn="001-002-002-2">
    <title>Design patterns</title>
  </book>
  <book isbn="001-002-002-3">
    <title>Data mapping and exchange</title>
  </book>
</Library>
```

An application to read the XML in **library.xml** consists of the classes **Book**, **ReadBook** and **Tester** (below).



ReadBook reads the XML to create **Book** objects. The instance variable **filename** is the name of a file. The constructor uses the parameter to initialize **filename**. The method **read()** uses **filename** to set up an **XMLStreamReader** (called **xr**) to read XML from **library.xml**.

Assume **Book** has been implemented. Below (see **next page**) are parts of the method **read()** in **ReadBook**.

1. Use the information above to answer **Questions 1.1** to **1.4**.
 - 1.1. Complete the code segment (**marked 1.1**) to open the file. (2 marks)
 - 1.2. Complete the code segment (**marked 1.2**) for a loop to read until end of the XML document. (2 marks)
 - 1.3. Complete the code segment (**marked 1.3**) as follows. If the variable **event** is the start element **<book>**, get the value of the **isbn** attribute; create an instance of **Book** and assign to **bk**; and use the value of the attribute to set the **isbn** of **bk**. (7 marks)
 - 1.4. Complete the code segment (**marked 1.4**) as follows. If the variable **event** is text, get the text and use to set the **title** of **bk**. (4 marks)


```

public void read(){
    try {
        //1.1. Complete the code below
        FileReader fr= _____;
        XMLStreamReader xr=null;//
        XMLInputFactory xmlfactory=XMLInputFactory.newInstance();
        xr=xmlfactory.createXMLStreamReader(fr);
        Book bk=null;
        int event;
        //1.2. Complete the code below
        while(_____){
            event = xr.next();
            switch(event) {
                //1.3. Complete the code below
                case _____:{
                    _____
                    _____
                    _____
                }
                break

                //1.4. Complete the code below
                case _____:{
                    _____
                    _____
                    _____
                }
                break
                ...
                ...
            }
        }
        ...
    }
}

```

2. **library.xsl** contains the XSL code to format the XML in **library.xml** to display in a web page as shown below.



2.1. Complete the code for **library.xsl**.

(6 marks)

```
...  
...  
<xsl:template match="/ Library ">  
    <xsl:for-each select="_____">  
        <_____="_____" /> &#160;  
        <_____="_____" /> <p/>  
    </xsl:for-each>  
</xsl:template>  
...  
...
```

2.2. Complete the code below in **library.xml** to link to **library.xsl**.


(2 marks)

```
<?xml-stylesheet type="_____" href="_____"?>
```

Question 6

27 marks

An RMI application allows transactions (e.g., check balance, deposit amount and withdraw amount) on a bank account. The UML diagram below shows the remote interface and remote class.



- **checkBalance**(BankAccount ba) takes a BankAccount as parameter and returns the account balance
- **deposit**(BankAccount ba, double amount) takes a BankAccount and the amount to deposit as parameters, adds the amount to the account balance and returns the updated balance
- **withdraw**(BankAccount ba, double amount) takes a BankAccount and the amount to withdraw as parameters, deducts the amount from the account balance and returns the updated balance

The class **BankAccount** (below) contains **accNum** (the account number), **balance** (the account balance) and **name** (customer name).

```

BankAccount
  ▢ accNum
  ▢ balance
  ▢ custName
  🌱 BankAccount(String, String, double)
  ● getAccNum() : String
  ● getBalance() : double
  ● getCustName() : String
  ● setAccNum(String) : void
  ● setBalance(double) : void
  ● setCustName(String) : void
  🐞 toString() : String
    
```

Use the information to answer **Questions 1 to 6** below.

1. Write the class header of **BankAccount** for this distributed application. (2 marks)
2. Write the code for **ITransaction**. (8 marks)
3. Write the class header for **TransactionImp**. (3 marks)
4. Write the method **deposit**(BankAccount ba, double amount) in **TransactionImp**. (4 marks)

5. Complete the code segment below for a class **Server** which creates, registers and binds an instance of **TransactionImp** (called **ti**) with the reference “account”. Assume **TransactionImp** has been implemented. Use port **2001**. (5 marks)

```
...  
...  
public class Server {  
    public static void main(String[] args) throws Exception{  
        TransactionImp ti= _____  
        Registry reg= _____  
        reg.rebind(_____);  
    }  
}
```

6. Complete the code segment below for a class **Client** which creates an instance of the remote object (called **it**) and calls a method to return the balance of a BankAccount (called **b**). Assume the relevant classes and their methods have been implemented. Use the local host and port number **2001**. (5 marks)

```
...  
...  
public class Client {  
    public static void main(String[] args) throws Exception{  
        BankAccount b=new BankAccount("400-000-000-1","Kofi Manu", 1000);  
        ITransaction it= _____  
        System.out.println("Balance=R "+ _____ );  
    }  
}
```