

STAT 435 Quiz 2

Pat McCornack

2022-10-10

Q1

a

Simulate the data set. There are 300 observations and 200 variables.

```
set.seed(1)
n = 300; p=200; s=5
x = matrix(rnorm(n * p), n, p)
b = c(rep(1, s), rep(0, p-s))
y = 1 + x %*% b + rnorm(n)
```

b

Create a vector of potential lambda variables.

```
L <- seq(0,2,length.out=100)
```

c

Create a lasso model for the data using the 10th element of the lambda vector L.

```
library(glmnet)

## Loading required package: Matrix
## Loaded glmnet 4.1-4

lasso.model <- glmnet(x, y, lambda = L, alpha = 1)
coef(lasso.model, s = L[10])
```

```
## 201 x 1 sparse Matrix of class "dgCMatrix"
##              s1
## (Intercept) 0.9769270
## V1          0.7594523
## V2          0.8554086
## V3          0.8465596
## V4          0.8669551
## V5          0.7791742
## V6          .
## V7          .
## V8          .
## V9          .
## V10         .
## V11         .
```

V12 .
V13 .
V14 .
V15 .
V16 .
V17 .
V18 .
V19 .
V20 .
V21 .
V22 .
V23 .
V24 .
V25 .
V26 .
V27 .
V28 .
V29 .
V30 .
V31 .
V32 .
V33 .
V34 .
V35 .
V36 .
V37 .
V38 .
V39 .
V40 .
V41 .
V42 .
V43 .
V44 .
V45 .
V46 .
V47 .
V48 .
V49 .
V50 .
V51 .
V52 .
V53 .
V54 .
V55 .
V56 .
V57 .
V58 .
V59 .
V60 .
V61 .
V62 .
V63 .
V64 .
V65 .

V66 .
V67 .
V68 .
V69 .
V70 .
V71 .
V72 .
V73 .
V74 .
V75 .
V76 .
V77 .
V78 .
V79 .
V80 .
V81 .
V82 .
V83 .
V84 .
V85 .
V86 .
V87 .
V88 .
V89 .
V90 .
V91 .
V92 .
V93 .
V94 .
V95 .
V96 .
V97 .
V98 .
V99 .
V100 .
V101 .
V102 .
V103 .
V104 .
V105 .
V106 .
V107 .
V108 .
V109 .
V110 .
V111 .
V112 .
V113 .
V114 .
V115 .
V116 .
V117 .
V118 .
V119 .

V120 .
V121 .
V122 .
V123 .
V124 .
V125 .
V126 .
V127 .
V128 .
V129 .
V130 .
V131 .
V132 .
V133 .
V134 .
V135 .
V136 .
V137 .
V138 .
V139 .
V140 .
V141 .
V142 .
V143 .
V144 .
V145 .
V146 .
V147 .
V148 .
V149 .
V150 .
V151 .
V152 .
V153 .
V154 .
V155 .
V156 .
V157 .
V158 .
V159 .
V160 .
V161 .
V162 .
V163 .
V164 .
V165 .
V166 .
V167 .
V168 .
V169 .
V170 .
V171 .
V172 .
V173 .


```
## V174      .
## V175      .
## V176      .
## V177      .
## V178      .
## V179      .
## V180      .
## V181      .
## V182      .
## V183      .
## V184      .
## V185      .
## V186      .
## V187      .
## V188      .
## V189      .
## V190      .
## V191      .
## V192      .
## V193      .
## V194      .
## V195      .
## V196      .
## V197      .
## V198      .
## V199      .
## V200      .
```

d

Compute the mean squared error (MSE) value for each model. The plot shows a monotonic increase in MSE with L until a plateau in MSE at around $\lambda = 1.2$. This suggests a lower λ value will minimize the MSE.

```
MSE = c()
for(i in 1:100){
  y.hat <- as.matrix(cbind(1, x)) %*% coef(lasso.model, s = L[i])
  MSE[i] <- mean((y - y.hat )^2)
}

plot(L, MSE)
```



e

The following computes the cross validation error for each value of lambda.

```
k = 5
ncv = ceiling(n/k) # Observations per fold
cv.ind = rep(1:k, ncv) # Fold index
cv.ind.random = sample(cv.ind, n, replace = F) # Randomize fold index
data = data.frame(y = y, x = x)

cv.error = c(); MSE.cv = c()
for(i in 1:100){ # Loop through values of lambda
  for(j in 1:k){ # Loop through folds
    train <- data[cv.ind.random != j, ]
    train.y <- train$y
    lasso.model <- glmnet(train[-1], train.y, lambda = L[i], alpha = 1)

    test = data[cv.ind.random == j,]
    test.values = test$y
    test.response <- as.matrix(cbind(1, test[-1])) %*% coef(lasso.model, s = L[i])
    MSE.cv[j] = mean((test.values - test.response)^2)
  }
  cv.error[i] = mean(MSE.cv)
}
```

```
which.min(cv.error)
```

```
## [1] 7
```

```
L[which.min(cv.error)]
```

```
## [1] 0.1212121
```

f

```
lasso.funct <- function(x, y, k, L)
{
  ncv = ceiling(dim(x)[1]/k)
  cv.ind = rep(1:k, ncv)
  cv.ind.random = sample(cv.ind, dim(x)[1], replace = F)
  data = data.frame(y = y, x = x)

  cv.error = c(); MSE.cv = c()
  for(i in 1:length(L)){
    for(j in 1:k){
      train <- data[cv.ind.random != j, ]
      train.y <- train$y
      lasso.model <- glmnet(train[-1], train.y, lambda = L[i], alpha = 1)

      test = data[cv.ind.random == j,]
      test.values = test$y
      test.response <- as.matrix(cbind(1, test[-1])) %*% coef(lasso.model, s = L[i])
      MSE.cv[j] = mean((test.values - test.response)^2)
    }
    cv.error[i] = mean(MSE.cv)
  }

  results <- list(coef(lasso.model, s = L[which.min(cv.error)]), cv.error, L, L[which.min(cv.error)])

  return(results)
}
```

g

```
output = lasso.funct(x, y, 5, L)
```

```
plot(output[[3]], output[[2]], xlab = 'L', ylab = 'CV Error' )
```

