

COMMAND - FRED command summary.

Below we summarize the commands for FRED and their default line addresses. (.) means that a command will operate on the current line if no address is specified. (.,.) means that a command will operate on the current line if no addresses are specified; if one line address is specified, the command will operate on that one line only.

Commands may be separated by one or more spaces; sometimes no spaces are necessary.

Placing an item in square brackets (e.g. [item]) in the formats below means that the item is optional.

Separating items with or-bars as in item1|item2|item3 means that the user has the choice of any of the given items.

Commands:

A)	(.)A text	Append text after line
B)	B(bufname)	Buffer
C)	(.,.)C text	Change lines
D)	(.,.)D	Delete lines
E)	E(patname)/pattern/	Name pattern
F)	F	Current buffer facts
	F filename	Set current filename
	FB	Print buffer facts
	FE	Print pattern facts
	FF	Print file facts
	FN	Print number registers
	FO	Print options
	FV	Print version
	F?	Questionable buffers
G)	(1,\$)G[~]/pattern/commands	Global
I)	(.)I text	Insert text before line
J)	JM remarks	Jump Message
	JM/remarks/	
	JP remarks	Jump Prompt
	JP/remarks/	
	JE remarks	Jump Exit
	JE/remarks/	
	JO[T F]	Jump Out
	JB[T F]	Jump Break
	J(label)[T F]]commands	Jump to label
	J[T F]	Jump line
K)	(.,.)K(bufname)	Kopy lines to buffer
L)	L[filename]	List file on terminal
M)	(.,.)M(bufname)	Move lines to buffer
N)	(.)N(regname):number	Number (assign)
	N(regname)	(absolute value)
	N(regname)-	(switch signs)
	N(regname)+number	(add)
	N(regname)-number	(subtract)
	N(regname)*number	(multiply)
	N(regname)/number	(divide)
	N(regname)%number	(remainder)
	N(regname)~	(bit complement)
	N(regname)&number	(bitwise AND)
	N(regname) number	(bit inclusive OR)
	N(regname)^number	(bit exclusive OR)
	N(regname)}number	(right bit shift)
	N(regname){number	(left bit shift)
	N(regname)=number	(test equality)
	N(regname)<number	(test less than)
	N(regname)>number	(test greater than)
	N(regname)Bnumber	(set base)
	N(regname)Dnumber	(set digits)

	N(regname)F<char>	(set fill char)
	N(regname)P	(print)
	N(regname)A	(assign line address)
	N(regname)L	(count characters)
O)	O[+ -]opt-char[parameters]	Options
	O[+ -]Bnumber	(in-core pages)
	O[+ -]C/s1/s2/	(replace s1 with s2 on input)
	O[+ -]I(	(() on names)
	O[+ -]IA/string/	(text prompt)
	O[+ -]IC/string/	(command prompt)
	O[+ -]IEchar	(set escape char)
	O[+ -]IF	(lf with return?)
	O[+ -]ILchar	(lower case input)
	O[+ -]IR/string/	(end of line prompt)
	O[+ -]IUchar	(upper case input)
	O[+ -]I\F	(is \F necessary?)
	O[+ -]M	(monitor)
	O[+ -]Ochars	(alt. output format)
	O[+ -]OL	(lower case output)
	O[+ -]OO	(oddities in octal)
	O[+ -]OU	(upper case output)
	O[+ -]Pnumber	(set pagesize)
	O[+ -]Q	(quit option)
	O[+ -]R	(default read perms)
	O[+ -]S&	(& and {}x in S)
	O[+ -]S/	(is final "/" needed?)
	O[+ -]Schars	(pattern chars)
	O[+ -]SD	(case in matches)
	O[+ -]Ttab-list	(set tabs)
P)	(,..)P	Print
	(,..)	Print addressed lines
	nl	Print ".+1"
Q)	Q	Quit
	QQ	Quit despite quest. buff
	Q!command	Quit with system call
R)	(0)R[X][filename]	Read file
S)	(,..)S/pattern/string/	Substitute
T)	(,..)T[~]/pattern/	Test for pattern
U)	(.)U[number][T F E] commands	Repeat Until
V)	V	Void last active line
W)	(1,\$)W[X][A B][filename]	Write file
Y)	Y	Why error?
Z)	(.)Z	Set address
	(.)ZA(bufname)	Append buffer
	(,..)ZB	Sort backwards
	ZC	Clear questionable flag
	ZD(bufname)	Delete buffer
	ZG(bufname)commands	Gather output
	(,..)ZI	Zap in tabs
	(,..)ZK(bufname)	Zap Kopy
	(,..)ZL[/pattern/]	Zap Lower case
	(,..)ZM(bufname)	Zap Move
	(,..)ZO	Zap out tabs
	ZP(bufname)	Print buffer
	ZR filename	Read file into new buff
	(,..)ZS	Sort forwards
	(,..)ZT/string/string/	Translate
	(,..)ZU[/pattern/]	Zap Upper case
	ZV	Void V command
	(1,\$)ZWoptions	Write append
!)	!command	Call system command
")	(.)"comment	Comment
#)	#	Print count register
=)	(.)=	Print line number
:	(.):[number]	Window around line
\)	\number	Go to sleep