Assignment 1

Yulei Sui

University of Technology Sydney, Australia

Assignment 1: Quizzes + A Coding Task

- Two sets of quizzes (15 ponts)
 - Basic C++ syntax,
 - Pointers, references and containers
 - C++ inheritance and data structures.
- One coding task (10 ponts)
 - Practicing C++ graph traversal algorithm
 - A warm up coding task for later assignments.

All the above quizzes and coding task is due by **23rd August**. You are encouraged to finish the quizzes before starting your coding task.

Graph Traversal

- You will be using what you have learned to build a C++ program.
- Goal: implement a depth first search on a graph and print path from a source node to a sink node on the graph

Graph Traversal

- You will be using what you have learned to build a C++ program.
- Goal: implement a depth first search on a graph and print path from a source node to a sink node on the graph
- Specification and code template: https://github.com/SVF-tools/ Teaching-Software-Analysis/wiki/Assignment-1

Graph Traversal

- You will be using what you have learned to build a C++ program.
- Goal: implement a depth first search on a graph and print path from a source node to a sink node on the graph
- Specification and code template: https://github.com/SVF-tools/ Teaching-Software-Analysis/wiki/Assignment-1

Depth First Search (DFS)

- An algorithm to traverse or search a graph data structure.
- Exploring as far as possible along each branch before backtracking.

Graph Traversal

- You will be using what you have learned to build a C++ program.
- Goal: implement a depth first search on a graph and print path from a source node to a sink node on the graph
- Specification and code template: https://github.com/SVF-tools/ Teaching-Software-Analysis/wiki/Assignment-1


Depth First Search (DFS)

- An algorithm to traverse or search a graph data structure.
- Exploring as far as possible along each branch before backtracking.

Why DFS?

- Efficient, linear time complexity, i.e., O(V+E), where V is nodes and E is edaes.
- One of the most commonly used graph algorithms.


Graph Traversal



Given a source node src and a destination node dst on a graph

- (1) can src reach dst?
- (2) if so, what are the possible paths from src to dst along the graph?

Graph Traversal




Given a source node src and a destination node dst on a graph

- (1) can src reach dst?
- (2) if so, what are the possible paths from src to dst along the graph?

Answer:

• (1) Yes.

Graph Traversal




Given a source node src and a destination node dst on a graph


- (1) can src reach dst?
- (2) if so, what are the possible paths from src to dst along the graph?

Answer:


- (1) Yes.
- (2) All possible paths:
 - $\operatorname{src} \to \operatorname{a} \to \operatorname{b} \to \operatorname{d} \to \operatorname{dst}$
 - $\operatorname{src} \to \operatorname{a} \to \operatorname{c} \to \operatorname{d} \to \operatorname{dst}$
 - $\operatorname{src} \to \operatorname{a} \to \operatorname{b} \to \operatorname{d} \to \operatorname{b} \to \operatorname{d} \to \operatorname{dst}$
 - $\operatorname{src} \to \operatorname{a} \to \operatorname{b} \to \operatorname{d} \to \operatorname{b} \to \operatorname{d} \to \dots \operatorname{dst}$



```
//mark the visited node
visited: set<NodeTD>
//node seq in the current path during traversal
path: vector<NodeID>
DFS(visited, path, src, dst)
   visited.insert(src);
   path.push back(src):
   if src = dst then
     Print path; //Print node seg of current path
   foreach edge e ∈ outEdges(src) do
    if (e.dst # visited)
          DFS(visited. path. e.dst. dst):
   visited.erase(src):
   path.pop_back();
```




```
//mark the visited node
visited: set<NodeTD>
//node seq in the current path during traversal
path: vector<NodeID>
DFS(visited, path, src, dst)
   visited.insert(src);
   path.push_back(src);
   if src = dst then
     Print path; //Print node seg of current path
   foreach edge e ∈ outEdges(src) do
    if (e.dst # visited)
          DFS(visited. path. e.dst. dst):
   visited.erase(src);
   path.pop_back();
```




```
//mark the visited node
visited: set<NodeID>
//node seq in the current path during traversal
path: vector<NodeID>

DFS(visited, path, src, dst)
1 visited.insert(src);
2 path.push_back(src);
3 if src = dst then
4 Print path; //Print node seq of current path
5 foreach edge e ∈ outEdges(src) do
6 if (e.dst ∉ visited)
7 DFS(visited, path, e.dst, dst);
8 visited.erase(src);
9 path.pop_back();
```




```
//mark the visited node
visited: set<NodeID>
//node seq in the current path during traversal
path: vector<NodeID>


DFS(visited, path, src, dst)
1 visited.insert(src);
2 path.push_back(src);
3 if src = dst then
4 Print path; //Print node seq of current path
5 foreach edge e c outEdges(src) do
6 if (e.dst ¢ visited)
7 DFS(visited, path, e.dst, dst);
8 visited.erase(src);
9 path.pop_back();
```




```
//mark the visited node
visited: set<NodeTD>
//node seq in the current path during traversal
path: vector<NodeID>
DFS(visited, path, src, dst)
   visited.insert(src);
   path.push back(src):
  if src = dst then
     Print path; //Print node seg of current path
   foreach edge e ∈ outEdges(src) do
    if (e.dst # visited)
          DFS(visited. path. e.dst. dst):
   visited.erase(src);
   path.pop_back();
```



```
//mark the visited node
visited: set<NodeTD>
//node seq in the current path during traversal
path: vector<NodeID>
DFS(visited, path, src, dst)
   visited.insert(src);
   path.push_back(src);
   if src = dst then
     Print path; //Print node seg of current path
   foreach edge e ∈ outEdges(src) do
    if (e.dst # visited)
          DFS(visited. path. e.dst. dst):
   visited.erase(src);
   path.pop_back();
```




```
//mark the visited node
visited: set<NodeTD>
//node seq in the current path during traversal
path: vector<NodeID>
DFS(visited, path, src, dst)
   visited.insert(src);
   path.push back(src):
   if src = dst then
     Print path; //Print node seg of current path
   foreach edge e ∈ outEdges(src) do
    if (e.dst # visited)
          DFS(visited. path. e.dst. dst):
   visited.erase(src):
   path.pop back():
```




```
//mark the visited node
visited: set<NodeTD>
//node seq in the current path during traversal
path: vector<NodeID>
DFS(visited, path, src, dst)
   visited.insert(src);
  path.push_back(src);
  if src = dst then
     Print path; //Print node seg of current path
   foreach edge e ∈ outEdges(src) do
    if (e.dst # visited)
          DFS(visited. path. e.dst. dst):
   visited.erase(src):
   path.pop back():
```


DFS algorithm



```
//mark the visited node
visited: set<NodeTD>
//node seq in the current path during traversal
path: vector<NodeID>
DFS(visited, path, src, dst)
   visited.insert(src);
   path.push back(src):
   if src = dst then
     Print path; //Print node seg of current path
   foreach edge e ∈ outEdges(src) do
    if (e.dst # visited)
          DFS(visited. path. e.dst. dst):
   visited.erase(src):
   path.pop_back();
```



```
//mark the visited node
visited: set<NodeTD>
//node seq in the current path during traversal
path: vector<NodeID>
DFS(visited, path, src, dst)
   visited.insert(src);
   path.push_back(src);
   if src = dst then
     Print path; //Print node seg of current path
   foreach edge e ∈ outEdges(src) do
    if (e.dst # visited)
          DFS(visited. path. e.dst. dst):
   visited.erase(src);
   path.pop_back();
```



```
//mark the visited node
visited: set<NodeTD>
//node seq in the current path during traversal
path: vector<NodeID>
DFS(visited, path, src, dst)
   visited.insert(src);
   path.push back(src):
   if src = dst then
     Print path; //Print node seg of current path
   foreach edge e ∈ outEdges(src) do
    if (e.dst # visited)
          DFS(visited. path. e.dst. dst):
   visited.erase(src);
   path.pop_back();
```