



Laptop0

Physical Config **Desktop** Programming Attributes

Command Prompt

```

Cisco Packet Tracer PC Command Line 1.0
C:\>ping 192.168.200.100

Pinging 192.168.200.100 with 32 bytes of data:

Request timed out.
Reply from 192.168.200.100: bytes=32 time<1ms TTL=127
Reply from 192.168.200.100: bytes=32 time<1ms TTL=127
Reply from 192.168.200.100: bytes=32 time=6ms TTL=127

Ping statistics for 192.168.200.100:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 6ms, Average = 2ms

C:\>ping 192.168.200.100

Pinging 192.168.200.100 with 32 bytes of data:

Reply from 192.168.200.100: bytes=32 time<1ms TTL=127
Reply from 192.168.200.100: bytes=32 time<1ms TTL=127
Reply from 192.168.200.100: bytes=32 time<1ms TTL=127
Reply from 192.168.200.100: bytes=32 time<1ms TTL=127

Ping statistics for 192.168.200.100:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>
  
```

Spiegazione

Per mandare un pacchetto a delle macchine di reti differenti, come mostrato nelle immagini, bisogna impostare un indirizzo gateway sia alla macchina sia alla porta corrispondente del router e fare la stessa cosa con l'altra rete. Una volta fatto ciò il router farà da intermediario tra le due reti permettendo il passaggio di pacchetti