

FLCD Seminar 1 – Programming Languages' Specification

Monday, October 05, 2020

11:09 AM

Notations (meta-languages)

I.BNF (Backus-Naur Form)

Constructs:

1. Meta-linguistic variables (non-terminals) - written between < >
2. Language primitives (terminals) - written as they are, no special delimiters
3. Meta-linguistic connectors
 - a. ::= equals by definition
 - b. | alternative (OR)

General shape of a BNF definition:

<construct> ::= expr_1 | expr_2 | ... | expr_n, where expr_i is a combination of terminals and/or nonterminals, i=1,n

Ex.1: Specify, using BNF, all nonempty sequences of letters



<let_sequence> ::= <letter> | <letter><let_sequence>

<letter> ::= a | b | ... | z | A | B | ... | Z

Ex.2: Specify, using BNF, both signed and unsigned integers, with the following constraints:

- 0 does not have a sign
- numbers of at least two digits cannot start with 0



<integer> ::= 0 | <sign> <unsigned> | <unsigned>

<sign> ::= - | +

<unsigned> ::= <nonzerodigit> | <nonzerodigit> <digit_seq>

<digit_seq> ::= <digit> | <digit> <digit_seq>

<nonzerodigit> ::= 1 | 2 | 3 .. | 9

<digit> ::= 0 | <nonzerodigit>

II.EBNF (Extended BNF)

Wirth's dialect

1. Changes to the concrete syntax of standard BNF
 - Nonterminals lose <> => they are written without delimiters
 - Terminals are written between " "
 - ::= becomes =
2. New constructs

- {} - repetition 0 or more times
- [] - optionality (0 or 1)
- () - math grouping
- (* *) - comments
- rules end with .

Ex.3: Ex. 2 reloaded, in EBNF



integer = "0" | [" + " | " - "] nonzerodigit { "0" | nonzerodigit }

nonzerodigit = "1" | ... | "9"