

# The boolean Pythagorean Triples problem

Tobias John, Aldo Kurmeta, Patrick Wienhöft

Technische Universität Dresden

26th June 2019



## Example

- ▶ Set of Integers:  $\{1, \dots, 15\}$



## Example

▶ Set of Integers:  $\{1, \dots, 15\}$

▶ Triples:

$$3^2 + 4^2 = 5^2$$

$$6^2 + 8^2 = 10^2$$

$$9^2 + 12^2 = 15^2$$

$$5^2 + 12^2 = 13^2$$



## Example

► **Set of Integers:**  $\{1, \dots, 15\}$

► **Triples:**

$$3^2 + 4^2 = 5^2$$

$$6^2 + 8^2 = 10^2$$

$$9^2 + 12^2 = 15^2$$

$$5^2 + 12^2 = 13^2$$

► **Partition:**  $\{1, 2, 3, 4, 6, 7, 8, 9, 11, 12, 14\}, \{5, 10, 13, 15\}$



## Encoding - Intuition

Idea:

- ▶ **one variable for each number**



## Encoding - Intuition

Idea:

- ▶ **one variable for each number**
- ▶ **one constraint clause for each Pythagorean triple**



## Encoding - Intuition

Idea:

- ▶ **one variable for each number**
- ▶ **one constraint clause for each Pythagorean triple**
- ▶ **interpretation gives partition**



# Encoding

Binary Pythagorean triple problem with  $n$  numbers





## Encoding

Binary Pythagorean triple problem with  $n$  numbers

Set of variables  $V = \{p_k \mid 1 \leq k \leq n\}$



## Encoding

Binary Pythagorean triple problem with  $n$  numbers

Set of variables  $V = \{p_k \mid 1 \leq k \leq n\}$

Constraint for non-equality: **NotEqual** $(x, y, z) = (x \vee y \vee z) \wedge (\neg x \vee \neg y \vee \neg z)$



## Encoding

Binary Pythagorean triple problem with  $n$  numbers

Set of variables  $V = \{p_k \mid 1 \leq k \leq n\}$

Constraint for non-equality:  $\text{NotEqual}(x, y, z) = (x \vee y \vee z) \wedge (\neg x \vee \neg y \vee \neg z)$

Constraint for all Pythagorean triples:  $F = \bigwedge_{\substack{1 \leq x, y, z \leq n \\ x^2 + y^2 = z^2}} \text{NotEqual}(p_x, p_y, p_z)$



# Encoding

Binary Pythagorean triple problem with  $n$  numbers

Set of variables  $V = \{p_k \mid 1 \leq k \leq n\}$

Constraint for non-equality:  $\text{NotEqual}(x, y, z) = (x \vee y \vee z) \wedge (\neg x \vee \neg y \vee \neg z)$

Constraint for all Pythagorean triples:  $F = \bigwedge_{\substack{1 \leq x, y, z \leq n \\ x^2 + y^2 = z^2}} \text{NotEqual}(p_x, p_y, p_z)$

For an interpretation  $I \subseteq V$  with  $I \models F$ , the resulting partition is:

- ▶  $P_1 = \{x \mid p_x \in I\}$
- ▶  $P_2 = \{x \mid p_x \notin I\}$



## Encoding - Example

As in beginning example,  $n = 15$



## Encoding - Example

As in beginning example,  $n = 15$

$$V = \{p_1, p_2, \dots, p_{15}\}$$



## Encoding - Example

As in beginning example,  $n = 15$

$$V = \{p_1, p_2, \dots, p_{15}\}$$

$$\begin{aligned} F = & (p_3 \vee p_4 \vee p_5) \wedge (\neg p_3 \vee \neg p_4 \vee \neg p_5) \\ & \wedge (p_6 \vee p_8 \vee p_{10}) \wedge (\neg p_6 \vee \neg p_8 \vee \neg p_{10}) \\ & \wedge (p_9 \vee p_{12} \vee p_{15}) \wedge (\neg p_9 \vee \neg p_{12} \vee \neg p_{15}) \\ & \wedge (p_5 \vee p_{12} \vee p_{13}) \wedge (\neg p_5 \vee \neg p_{12} \vee \neg p_{13}) \end{aligned}$$



## Encoding - Example

As in beginning example,  $n = 15$

$$V = \{p_1, p_2, \dots, p_{15}\}$$

$$\begin{aligned} F = & (p_3 \vee p_4 \vee p_5) \wedge (\neg p_3 \vee \neg p_4 \vee \neg p_5) \\ & \wedge (p_6 \vee p_8 \vee p_{10}) \wedge (\neg p_6 \vee \neg p_8 \vee \neg p_{10}) \\ & \wedge (p_9 \vee p_{12} \vee p_{15}) \wedge (\neg p_9 \vee \neg p_{12} \vee \neg p_{15}) \\ & \wedge (p_5 \vee p_{12} \vee p_{13}) \wedge (\neg p_5 \vee \neg p_{12} \vee \neg p_{13}) \end{aligned}$$

Possible interpretation:  $I = \{p_5, p_{10}, p_{13}, p_{15}\}$





## Encoding - Example

As in beginning example,  $n = 15$

$$V = \{p_1, p_2, \dots, p_{15}\}$$

$$\begin{aligned} F = & (p_3 \vee p_4 \vee p_5) \wedge (\neg p_3 \vee \neg p_4 \vee \neg p_5) \\ & \wedge (p_6 \vee p_8 \vee p_{10}) \wedge (\neg p_6 \vee \neg p_8 \vee \neg p_{10}) \\ & \wedge (p_9 \vee p_{12} \vee p_{15}) \wedge (\neg p_9 \vee \neg p_{12} \vee \neg p_{15}) \\ & \wedge (p_5 \vee p_{12} \vee p_{13}) \wedge (\neg p_5 \vee \neg p_{12} \vee \neg p_{13}) \end{aligned}$$

Possible interpretation:  $I = \{p_5, p_{10}, p_{13}, p_{15}\}$

Resulting partition:

- ▶  $P_1 = \{1, 2, 3, 4, 6, 7, 8, 9, 11, 12, 14\}$
- ▶  $P_2 = \{5, 10, 13, 15\}$



# Transformation

Goal: from  $F$ , find formula  $F'$  which

► **is easier to solve**



# Transformation

Goal: from  $F$ , find formula  $F'$  which

- ▶ **is easier to solve**
- ▶ **preserves satisfiability**



# Transformation

Goal: from  $F$ , find formula  $F'$  which

- ▶ **is easier to solve**
- ▶ **preserves satisfiability**
- ▶ **has models that can be easily transformed into models for  $F$**



# Transformation

Goal: from  $F$ , find formula  $F'$  which

- ▶ **is easier to solve**
- ▶ **preserves satisfiability**
- ▶ **has models that can be easily transformed into models for  $F$**

Approaches:

- ▶ **eliminate clauses with variables only occurring once**



# Transformation

Goal: from  $F$ , find formula  $F'$  which

- ▶ **is easier to solve**
- ▶ **preserves satisfiability**
- ▶ **has models that can be easily transformed into models for  $F$**

Approaches:

- ▶ **eliminate clauses with variables only occurring once**
- ▶ **break partition symmetry**



## Clause elimination

$$\begin{aligned}
 F &= \text{NotEqual}(p_3, p_4, p_5) \\
 &\quad \wedge \text{NotEqual}(p_6, p_9, p_{12}) \\
 &\quad \wedge \text{NotEqual}(p_9, p_{12}, p_{15}) \\
 &\quad \wedge \text{NotEqual}(p_5, p_{12}, p_{13})
 \end{aligned}$$

Note  $p_3$  only occurs in  $\text{NotEqual}(p_3, p_4, p_5)$  and thus does not affect any other clauses



## Clause elimination

$$\begin{aligned}
 F &= \text{NotEqual}(p_3, p_4, p_5) \\
 &\quad \wedge \text{NotEqual}(p_6, p_9, p_{12}) \\
 &\quad \wedge \text{NotEqual}(p_9, p_{12}, p_{15}) \\
 &\quad \wedge \text{NotEqual}(p_5, p_{12}, p_{13})
 \end{aligned}$$

Note  $p_3$  only occurs in  $\text{NotEqual}(p_3, p_4, p_5)$  and thus does not affect any other clauses

- if  $p_4^I \neq p_5^I$  then  $\text{NotEqual}(p_3, p_4, p_5)$  is satisfied





## Clause elimination

$$\begin{aligned}
 F &= \text{NotEqual}(p_3, p_4, p_5) \\
 &\quad \wedge \text{NotEqual}(p_6, p_9, p_{12}) \\
 &\quad \wedge \text{NotEqual}(p_9, p_{12}, p_{15}) \\
 &\quad \wedge \text{NotEqual}(p_5, p_{12}, p_{13})
 \end{aligned}$$

Note  $p_3$  only occurs in  $\text{NotEqual}(p_3, p_4, p_5)$  and thus does not affect any other clauses

- ▶ if  $p_4^I \neq p_5^I$  then  $\text{NotEqual}(p_3, p_4, p_5)$  is satisfied
- ▶ if  $p_4^I = p_5^I = \top$  then choose  $p_3^I = \perp$



## Clause elimination

$$\begin{aligned}
 F &= \text{NotEqual}(p_3, p_4, p_5) \\
 &\quad \wedge \text{NotEqual}(p_6, p_9, p_{12}) \\
 &\quad \wedge \text{NotEqual}(p_9, p_{12}, p_{15}) \\
 &\quad \wedge \text{NotEqual}(p_5, p_{12}, p_{13})
 \end{aligned}$$

Note  $p_3$  only occurs in  $\text{NotEqual}(p_3, p_4, p_5)$  and thus does not affect any other clauses

- ▶ if  $p_4' \neq p_5'$  then  $\text{NotEqual}(p_3, p_4, p_5)$  is satisfied
- ▶ if  $p_4' = p_5' = \top$  then choose  $p_3' = \perp$
- ▶ if  $p_4' = p_5' = \perp$  then choose  $p_3' = \top$



## Clause elimination

$$\begin{aligned}
 F &= \text{NotEqual}(p_3, p_4, p_5) \\
 &\quad \wedge \text{NotEqual}(p_6, p_9, p_{12}) \\
 &\quad \wedge \text{NotEqual}(p_9, p_{12}, p_{15}) \\
 &\quad \wedge \text{NotEqual}(p_5, p_{12}, p_{13})
 \end{aligned}$$

Note  $p_3$  only occurs in  $\text{NotEqual}(p_3, p_4, p_5)$  and thus does not affect any other clauses

- ▶ if  $p_4' \neq p_5'$  then  $\text{NotEqual}(p_3, p_4, p_5)$  is satisfied
- ▶ if  $p_4' = p_5' = \top$  then choose  $p_3' = \perp$
- ▶ if  $p_4' = p_5' = \perp$  then choose  $p_3' = \top$

→ clause  $\text{NotEqual}(p_3, p_4, p_5)$  will not cause conflict



## Clause elimination

$$\begin{aligned}
 F &= \text{NotEqual}(p_3, p_4, p_5) \\
 &\quad \wedge \text{NotEqual}(p_6, p_9, p_{12}) \\
 &\quad \wedge \text{NotEqual}(p_9, p_{12}, p_{15}) \\
 &\quad \wedge \text{NotEqual}(p_5, p_{12}, p_{13})
 \end{aligned}$$

Note  $p_3$  only occurs in  $\text{NotEqual}(p_3, p_4, p_5)$  and thus does not affect any other clauses

- ▶ if  $p_4^I \neq p_5^I$  then  $\text{NotEqual}(p_3, p_4, p_5)$  is satisfied
- ▶ if  $p_4^I = p_5^I = \top$  then choose  $p_3^I = \perp$
- ▶ if  $p_4^I = p_5^I = \perp$  then choose  $p_3^I = \top$

→ clause  $\text{NotEqual}(p_3, p_4, p_5)$  will not cause conflict

$$\begin{aligned}
 F' &= \text{NotEqual}(p_6, p_9, p_{12}) \\
 &\quad \wedge \text{NotEqual}(p_9, p_{12}, p_{15}) \\
 &\quad \wedge \text{NotEqual}(p_5, p_{12}, p_{13})
 \end{aligned}$$



## Clause elimination

Notes:

- ▶  $F'$  might have more models than  $F$



## Clause elimination

Notes:

- ▶  $F'$  might have more models than  $F$
- ▶ choice for variables occurring only once in  $F$  is important but not represented in  $F'$



## Clause elimination

Notes:

- ▶  $F'$  might have more models than  $F$
- ▶ choice for variables occurring only once in  $F$  is important but not represented in  $F'$
- ▶  $\rightarrow$  remember deleted clauses and modify interpretation of  $F'$  accordingly



## Clause elimination

Notes:

- ▶  $F'$  might have more models than  $F$
- ▶ choice for variables occurring only once in  $F$  is important but not represented in  $F'$
- ▶  $\rightarrow$  remember deleted clauses and modify interpretation of  $F'$  accordingly

Example:

- ▶ deleted clause  $\text{NotEqual}(p_3, p_4, p_5)$  because  $p_3$  only occurred once





## Clause elimination

Notes:

- ▶  $F'$  might have more models than  $F$
- ▶ choice for variables occurring only once in  $F$  is important but not represented in  $F'$
- ▶  $\rightarrow$  remember deleted clauses and modify interpretation of  $F'$  accordingly

Example:

- ▶ deleted clause  $NotEqual(p_3, p_4, p_5)$  because  $p_3$  only occurred once
- ▶  $I' \models F'$  and  $\{p_3, p_4, p_5\} \subseteq I'$



## Clause elimination

Notes:

- ▶  $F'$  might have more models than  $F$
- ▶ choice for variables occurring only once in  $F$  is important but not represented in  $F'$
- ▶  $\rightarrow$  remember deleted clauses and modify interpretation of  $F'$  accordingly

Example:

- ▶ deleted clause  $NotEqual(p_3, p_4, p_5)$  because  $p_3$  only occurred once
- ▶  $I' \models F'$  and  $\{p_3, p_4, p_5\} \subseteq I'$
- ▶  $I = I' \setminus p_3$
- ▶ while  $I' \not\models F$ , we have  $I \models F$



## Breaking Symmetry

- ▶ formulas  $F$  and  $F'$  are symmetric



## Breaking Symmetry

- ▶ formulas  $F$  and  $F'$  are symmetric
- ▶ if  $I \models F'$  then  $V \setminus I \models F'$



## Breaking Symmetry

- ▶ formulas  $F$  and  $F'$  are symmetric
- ▶ if  $I \models F'$  then  $V \setminus I \models F'$
- ▶  $\rightarrow$  introduce unit clause for variable occurring in  $F'$
- ▶  $F'' = F' \wedge p_x$



## Breaking Symmetry

- ▶ formulas  $F$  and  $F'$  are symmetric
- ▶ if  $I \models F'$  then  $V \setminus I \models F'$
- ▶  $\rightarrow$  introduce unit clause for variable occurring in  $F'$
- ▶  $F'' = F' \wedge p_x$

Note that every model for  $F''$  is a model for  $F'$  and the transformation is satisfiability preserving



## Cube-and-conquer solving

- ▶ **Problem: solving with conflict-driven clause learning (CDCL) is too slow**



## Cube-and-conquer solving


- ▶ **Problem:** solving with conflict-driven clause learning (CDCL) is too slow
- ▶ **Solution:**
  - ▷ use different heuristics  $\Rightarrow$  cube-and-conquer solver (C&C)






## Cube-and-conquer solving

- ▶ **Problem:** solving with conflict-driven clause learning (CDCL) is too slow
- ▶ **Solution:**
  - ▷ use different heuristics  $\Rightarrow$  cube-and-conquer solver (C&C)




## Cube-and-conquer solving

- ▶ **Problem:** solving with conflict-driven clause learning (CDCL) is too slow
- ▶ **Solution:**
  - ▷ use different heuristics  $\Rightarrow$  cube-and-conquer solver (C&C)




## Cube-and-conquer solving

- ▶ Problem: solving with conflict-driven clause learning (CDCL) is too slow
- ▶ Solution:
  - ▷ use different heuristics  $\Rightarrow$  cube-and-conquer solver (C&C)



## Cube-and-conquer solving

- ▶ **Problem:** solving with conflict-driven clause learning (CDCL) is too slow
- ▶ **Solution:**
  - ▷ use different heuristics  $\Rightarrow$  cube-and-conquer solver (C&C)
  - ▷ use parallelization (800 cores)




## Runtime

- ▶ **Cubing: 22000 CPU hours**
- ▶ **Solving: 13000 CPU hours**
- ▶ **Validation: 16000 CPU hours**
- ▶ **sums up to  $\approx 5.8$  CPU years**



## Runtime

- ▶ Cubing: 22000 CPU hours
- ▶ Solving: 13000 CPU hours
- ▶ Validation: 16000 CPU hours
- ▶ sums up to  $\approx 5.8$  CPU years



# Framework

Picture of the Framework

