



CS472 WAP

Structure of a Page

Introduction to Web Programming

Layers of Abstraction

Except where otherwise noted, the contents of this document are Copyright 2012 Marty Stepp, Jessica Miller, Victoria Kirst and Roy McElmurry IV. All rights reserved. Any redistribution, reproduction, transmission, or storage of part or all of the contents in any form is prohibited without the author's expressed written permission. Slides have been modified for Maharishi University of Management Computer Science course CS472 in accordance with instructors agreement with authors.

Maharishi International University

Fairfield, Iowa © 2020



All rights reserved. No part of this slide presentation may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying or recording, or by any information storage and retrieval system, without permission in writing from Maharishi International University.

Main Point Preview

- The Hyper Text Markup Language uses tags to demarcate different sections of a text. An HTML page always starts with a `<html>` tag, inside of which it has a `<head>` tag to describe the page, and a `<body>` tag of the contents that will actually be displayed. These are the tags you will use for every HTML page. This is a foundational concept
- *Well begun is half done. Start with a good foundation and build upon that.*

Hypertext Markup Language (HTML)

- Describes the content and structure of information on a web page
- Surrounds text content with opening and closing tags
- Each tag and its content is called an element
 - Syntax: **<element>**content **</element>**
 - Example: **<p>**This is a paragraph**</p>**
- Most whitespace is insignificant in HTML
 - (ignored or collapsed to a single space)
- The newest version is HTML5

Structure of an HTML5 page

- An HTML page is saved into a file ending with extension **.html**
- **DOCTYPE** tag tells browser the HTML version.
 - In this case, HTML5.
- The **header** describes the page and the **body** contains the page's contents

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8"/>
    <title></title>
  </head>
  <body>
    Page contents
  </body>
</html>
```

Metadata

- Data about data - Information describes the page itself
 - Placed in the head section of your HTML page
- meta tags often have both the name and content attributes
- HTML5 introduced a way for designers to control the viewport
 - (the user's visible area of a web page), through the <meta> tag

```
<meta charset="utf-8"/>
```

```
<meta name="description" content="Learn HTML"/>
```

```
<meta name="keywords" content="HTML, CSS"/>
```

```
<meta name="viewport" content="width=device-width, initial-scale=1.0"/>
```

Favorites Icon (favicon)

- The link tag, in the head section, attaches another file to the page
- In this case, an icon for the browser title bar and bookmarks
 - E.g. https://www.w3schools.com/tags/tryit.asp?filename=tryhtml5_link_sizes

```
<link href="filename" type="MIME type" rel="relationship"/>  
<link href="yahoo.gif" type="image/gif" rel="shortcut icon"/>
```




Relative vs Absolute URL

- **Relative URL**

- index.html (path relative)
- graphics/image.png
- ../about.html (directory relative)
- ../../stories/stories.html
- /image.png (root relative)

- **Absolute URL**

- <http://www.mysite.com>
- C:\website\images\image.png



Why won't this work when we move our code to production?

Common Mistake

- Placing a leading “/” on a relative URL
- Say you are at index.html and want to link to smiley which is at:
 - `http://www.myexample.com/mysite/files/index.html`
 - `http://www.myexample.com/mysite/files/images/smiley.gif`

- The following fails:

``

Tries to GET:
`http://www.myexample.com/images/smiley.gif`

- The following works:

`` (correct for ‘mysite’)

Block Level Elements



- A block-level element always starts on a new line and takes up the full width available (stretches out to the left and right as far as it can).
- Examples of block-level elements:

`<div>`

`<h1>` - `<h6>`

`<p>`

`<form>`

Paragraph `<p>`



- Creates a paragraph in a block of text
 - Placed in the body of the page
 - See examples at [w3schools](#)

`<p>`

**Lorem quis lorem. Pellentesque ultrices nunc id mauris
posuere pulvinar.**

`</p>`

Headings <h1>, <h2>, ..., <h6>

- Headings are use to give a title (heading) to major areas of the page (block)

`<h1>Maharishi University</h1>`

`<h2>Department of Computer Science</h2>`

`<h3>WAP Course</h3>`

Note: only use one <h1> tag per page, as it describes “the page”

Maharishi University

Department of Computer Science

WAP Course

Horizontal Rule <hr />



- A line to separate sections
 - It represents a paragraph-level thematic break, e.g. a scene change in a story, or a transition to another topic within a section of a reference book

```
<h1>CS472 Web Programming</h1>
```

```
<p>Very good, fun course - HTML, CSS, JavaScript, JSP, Servlets</p>
```

```
<hr />
```

```
<h1>CS421 Modern Programming Practices</h1>
```

```
<p>Profound course - OOAD, Java8 features</p>
```

HTML5 New Semantic Elements

- They generally have no default outward appearance on the page, instead they give insight into the structure of the page.
 - section: defines a section in a document.
 - header: specifies a header for a document or section.
 - footer: specifies a footer for a document or section.
 - nav: defines a set of navigation links.
 - aside: defines some content aside from the content it is placed in (like a sidebar).
 - article: specifies independent, self-contained content.
 - [More Semantic Tags](#)



Main Point

- The Hyper Text Markup Language uses tags to demarcate different sections of a text. An HTML page always starts with a `<html>` tag, inside of which it has a `<head>` tag to describe the page, and a `<body>` tag of the contents that will actually be displayed. These are the tags you will use for every HTML page. This is a foundational concept
- *Well begun is half done. Start with a good foundation and build upon that.*

