



CS472 WAP

CSS Levels

Cascading Style Sheets (CSS)

Diversity from Unity

Except where otherwise noted, the contents of this document are Copyright 2012 Marty Stepp, Jessica Miller, Victoria Kirst and Roy McElmurry IV. All rights reserved. Any redistribution, reproduction, transmission, or storage of part or all of the contents in any form is prohibited without the author's expressed written permission. Slides have been modified for Maharishi University of Management Computer Science course CS472 in accordance with instructors agreement with authors.

Maharishi International University

Fairfield, Iowa © 2020



All rights reserved. No part of this slide presentation may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying or recording, or by any information storage and retrieval system, without permission in writing from Maharishi International University.

Main Point Preview

- The Cascading in CSS indicates that there are multiple levels of style sheets. More specific styles overwrite more general styles. We can be more specific by using Class selectors (groups of elements) and even more so with id selectors (individual elements).
- *Life is found in layers.*

Body styles

- To apply a style to the entire body of your page, write a selector for the body element
- Saves you from manually applying a style to each element

```
body {  
  font-size: 16px;  
}
```

Inheriting styles



Styles get inherited from containing elements

Not all properties are inherited (notice link's color below)

- E.g., margin

```
body {  
  font-family: sans-serif;  
  background-color: pink;  
}  
p {  
  color: green;  
}  
a {  
  text-decoration: underline;  
}  
h2 {  
  font-weight: bold;  
  text-align: center;  
}
```

CS472 Web Programming

This [course](#) provides a systematic introduction to programming interactive and dynamic web applications.

Browser CSS Reset code

- It's a good practice to reset some body values before we start coding our own CSS rules:

```
body {  
    margin: 0;  
    padding: 0;  
    font-size: 100%;  
    line-height: 1;  
}
```

Styles that Conflict



```
/* select multiple elements separated by commas */
```

```
p, h1, h2 {  
  color: green;  
  background-color: grey;  
}
```

```
/* when two styles set conflicting values for the same  
property, the latter style takes precedence */
```

```
h2 {  
  background-color: blue;  
}
```

`<p> This paragraph will use background color grey! </p>`

`<h2> This heading will use background color blue! </h2>`

This paragraph will use background color grey!

This heading will use background color blue!

Styles Pane (Chrome, Firefox)

- Invoke the DevTools inspector on element
- displays styles for selected DOM node
- gray background are read-only
- exclamation marks mean that property name and/or value is not understood by the browser,
 - is ignored
- A style declaration may contain several properties with the same name. Only the last one takes effect, canceling the preceding ones.
 - will be struck out, like overridden properties.

Cascading style sheets

It's called Cascading Style Sheets because the properties of an element cascade together in this order:

1. Browser's default styles (reference)
 2. External style sheet files (in a <link> tag)
 3. Internal style sheets (in a <style> tag in the page header)
 4. Inline style (the style attribute of an HTML element)
- Basically, cascading works from top to bottom inside the page (Depends on your order – later styles will always override top ones).
 - **Inheritance is** how elements in the HTML markup inherit properties from their parent elements
 - **cascade is** how different CSS rule sets are applied to HTML elements, and how conflicting rules do or don't override each other.



Override Rules

```
<p class="RedColor BlueColor">  
  Lorem Ipsum  
</p>
```

```
#YellowColor {  
  color: yellow;  
}  
.BlueColor {  
  color: blue;  
}  
.RedColor {  
  color: red;  
}
```

Lorem Ipsum

Style Specificity



- When multiple styles apply to an element and have the same origin precedence.
- The most specific one applies. If they have the same specificity, then the later one will be used.

```
<aside>
```

```
  <p><em id="recent" class="awesome">Which awesome color?</em></p>
```

```
</aside>
```

```
em#recent.awesome { color: orange; }
```

```
aside { color: gray; }
```

```
p { color: green; }
```

```
em { color: yellow; }
```

```
.awesome { color: blue; }
```

```
em.awesome { color: red; }
```

```
#recent { color: black; }
```

Which awesome color?



Specificity and conflicts

- Specificity- decide which one should win when two or more rules conflict.
- Rules: each rule's overall selector is given a score based upon approximately the following rules. The rule with the highest score wins if there's a conflict.
 - Any HTML element mentioned in the rule scores 1 point
 - Any class mentioned in the rule scores 10 points
 - Any ID mentioned in the rule scores 100 points
- Examples:
 - p.banner - 11
 - div.box > p - 12
 - body #logo .box p.banner - 122

The HTML **class** and **id** attribute

- **id attribute** allows you to give a unique ID to any element on a page
 - Each ID must be unique;
 - Can only be used once in the page
- **class attribute** is used to group some elements and give a style to only that group
 - unlike an id, a class can be reused as much as you like on the page

class vs id examples



```
<p id="mission">Our mission is to provide the most</p>
<p class="special">See our spectacular spatula specials</p>
<p class="special shout">Today only, satisfaction guaranteed</p>
```

```
#mission { /* the element with id="mission" */
  font-style: italic;
  color: #000000;
}
.special { /* any element with class="special" */
  background-color: yellow;
  font-weight: bold;
}
p.shout { /* only p elements with class="shout" */
  color: red;
  font-family: cursive;
}
```

Our mission is to provide the most

See our spectacular spatula specials

Today only, satisfaction guaranteed

class naming

- focus on the semantics and meaning of the content vs appearance
 - Bad examples: redtext, bigfont
 - if change style later, it doesn't make sense to be called redtext.
 - Good examples: warning-msg, error-msg

pseudo-classes and pseudo-elements







- A **pseudo-class** is used to define a **special state of an element**
 - Style an element when a user mouse's over it
 - Style visited and unvisited links differently
 - Style an element when it gets focus
- A CSS **pseudo-element** is used to style specified **parts of an element**
 - *Do not exist in the DOM, are created with CSS*
 - Style the first letter, or line, of an element
 - `::first-line`, `::first-letter`
 - Insert content (pseudo element) before, or after, the content of an element
 - `::before`, `::after`

`selector:pseudo-class { property:value; } /* single colon */`

`selector::pseudo-element { property:value; } /* double colon */`

CSS pseudo-classes pseudo-elements

class		description
:active		an activated or selected element
:focus		an element that has the keyboard focus
:hover		an element that has the mouse over it
:link		a link that has not been visited
:visited		a link that has already been visited
:nth-child(expr)		targets specific children of a given element
:first-child, :last-child		
:not(selector)		all elements that do not match the given CSS selector
::first-line		the first line of text inside an element
::first-letter		the first letter of text inside an element

[Complete list](#)

Examples pseudo-classes



```
/* unvisited link */
```

```
a:link { color: #FF0000; }
```

```
/* visited link */
```

```
a:visited { color: #00FF00; }
```

```
/* mouse over link */
```

```
a:hover { color: #FF00FF; }
```

```
/* click on a link */
```

```
a:active { color: #0000FF; }
```

More info and examples: [Pseudo-classes](#) and [Pseudo-elements](#)

CSS context selectors

`selector1 selector2 { properties }`

Applies the given properties to **selector2 only** if it is inside a selector1 on the page

`selector1 > selector2 { properties }`

- Applies the given properties to **selector2 only** if it is direct child of selector1 (in the DOM)
 - mnemonic: think of > as indicating a direct link (to a child)




Example

```
<div id="ad">
  <p>Shop at <strong>Hardwick's Hardware</strong></p>
  <ul>
    <li class="line"><em>The </em><strong>best</strong> prices!</li>
    <li><em><strong>Act while supplies last!</strong></em></li>
  </ul>
</div>
```

```
ul > li { background-color: blue; }
li strong { color: red; }
li > strong { color: green; }
#ad li.line strong { text-decoration: underline; }
```

See example: lesson3_examples\contextselector.html,
contextselectordirect.html



Add *content* to your website using CSS

- CSS has a property called content.
- only be used with the pseudo elements ::after and ::before.
- The ::after selector inserts something after the content of each selected element(s).
 - Use the [content](#) property to specify the content to insert.
 - Use the [::before](#) selector to insert something before the content.
- https://www.w3schools.com/cssref/tryit.asp?filename=trycss_sel_after

Main Point

- The Cascading in CSS indicates that there are multiple levels of style sheets. More specific styles overwrite more general styles. We can be more specific by using Class selectors (groups of elements) and even more so with id selectors (individual elements).
- *Life is found in layers.*

