



CS472 WAP

Node Manipulation

DOM, jQuery

Except where otherwise noted, the contents of this document are Copyright 2012 Marty Stepp, Jessica Miller, Victoria Kirst and Roy McElmurry IV. All rights reserved. Any redistribution, reproduction, transmission, or storage of part or all of the contents in any form is prohibited without the author's expressed written permission. Slides have been modified for Maharishi University of Management Computer Science course CS472 in accordance with instructors agreement with authors.

Main Point Preview

- The jQuery object returned by the selection mode of `$()` is a collection of DOM elements wrapped by jQuery functionality. This object can read style properties as well as set them by using the `css` method of jQuery.
- *Science of Consciousness: Node manipulation involves locating nodes, observing or reading values, and changing values. Our TM practice develops our ability to locate quiet states of awareness. Advanced techniques and the TM-Sidhi Program develop abilities to experience and manipulate different characteristics of pure consciousness*

Aspects of the DOM and jQuery

- **Identification:**

- how do I obtain a reference to the node that I want.
- using css-like selectors to get target nodes

- **Traversal:**

- Find nodes by tree traversal relations
- using children, sibling, parent, etc links to get target nodes

- **Node Manipulation:**

- how do I get or set aspects of a DOM node.
- e.g., style, attributes, innerHTML

- **Tree Manipulation:**

- how do I change the structure of the page.

Looping over jQuery elements

```
$("li").each(function(idx, e) {  
    // do stuff with e  
});
```

- You cannot use a regular JavaScript for each loop on the jQuery object because it is not an array, just an array-like object

Inside the jQuery each loop

```
$("li").each(function(idx, e) {  
    // do stuff with e  
});
```

- return false to exit the loop early
- e is a plain old DOM object
 - We can upgrade it again using \$ if we want

```
$("li").each(function(idx, e) {  
    eJ = $(e);  
    // do stuff with e  
});
```

Modifying DOM nodes

- DOM nodes have fields that correspond to the attributes in HTML tags. There are a few exceptions

HTML attributes	DOM fields
title	.title
id	.id
class	.className
style="prop: value"	.style.prop = value

Getting/setting CSS classes in DOM

```
function highlightField() {  
    // turn text yellow and make it bigger  
    var elem = document.getElementById("id");  
  
    if (!elem.className) {  
        elem.className = "highlight";  
    } else if (elem.className.indexOf("invalid") < 0) {  
        elem.className += " highlight";  
    }  
}
```

- JS DOM's `className` property corresponds to HTML `class` attribute
- somewhat clunky when dealing with multiple space-separated classes as one big string
- `className` value is a string, not an array like we would want

Getting/setting CSS classes in jQuery

```
function highlightField() {  
    // turn text yellow and make it bigger  
    if (!$("#myid").hasClass("invalid")) {  
        $("#myid").addClass("highlight");  
    }  
}
```

- addClass, removeClass, hasClass, toggleClass manipulate CSS classes
- similar to existing className DOM property, but don't have to manually split by spaces



Adjusting styles with the DOM

```
<button id="clickme">Color Me</button>
window.onload = function() {
  document.getElementById("clickme").onclick = changeColor;
};
function changeColor() {
  const clickMe = document.getElementById("clickme");
  clickMe.style.color = "red";
}
```

Property	Description
<u>style</u>	lets you set any CSS style property for an element

- contains same properties as in CSS, but with camelCasedNames
 - examples: backgroundColor, borderLeftWidth, fontFamily



Adjusting styles in jQuery

```
function biggerFont() {  
    // turn text yellow and make it bigger  
    $("#clickme").css("color", "yellow");  
    const size = parseInt($("#clickme").css("font-size"));  
    const newsize = size + 16 + "px";  
    $("#clickme").css("fontSize", newsize );  
}
```

- css function of the jQuery object works even if styles not previously set
- Accepts familiar font-size syntax in addition to fontSize
- `css(property)` gets the property value
- `css(property, value)` sets the property value

Common bug: incorrect usage of existing styles

```
// bad!
```

```
$("#main").css("top", $("#main").css("top") + 100 + "px");
```

- the above example computes e.g. "200px" + 100 + "px" ,
which would evaluate to "200px100px"

- a corrected version:

```
// correct
```

```
$("#main").css("top", parseInt($("#main").css("top")) + 100 + "px");
```

Recall: Unobtrusive styling

```
function okayClick() {  
  this.style.color = "red";  
  this.className = "highlighted";  
}  
  
.highlighted { color: red; }
```

- well-written JavaScript code should contain as little CSS as possible
- use JS to set CSS classes/IDs on elements
- define the styles of those classes/IDs in your CSS file
- Conclusion: unobtrusive styling means avoid using the .css method in jQuery
 - Set classes in JavaScript code to handle any style changes

jQuery method behavior

- **Getters** typically operate only on the first of the jQuery object's selected elements.

```
<ul>
```

```
  <li style="font-size: 10px">10px font size</li>
```

```
  <li style="font-size: 20px">20px font size</li>
```

```
  <li style="font-size: 30px">30px font size</li>
```

```
</ul>
```

```
$("li").css("font-size"); // returns '10px'
```

- **Setters** typically operate on all of the selected DOM elements.

```
$("li").css("font-size", "15px"); // sets all selected elements to '15px'
```

```
<ul>
```

```
  <li style="font-size: 15px">10px font size</li>
```

```
  <li style="font-size: 15px">20px font size</li>
```

```
  <li style="font-size: 15px">30px font size</li>
```

```
</ul>
```

jQuery method parameters

- Many jQuery object methods are overloaded

- getter syntax:

```
$("#myid").css(propertyName);
```

- setter syntax:

```
$("#myid").css(propertyName, value);
```

- multi-setter syntax:

```
$("#myid").css({  
    'propertyName1': value1,  
    'propertyName2': value2,  
    ...  
});
```

- modifier syntax:

```
$("#myid").css(propertyName,  
    function(idx, oldValue) {  
        return newValue;  
    });
```

- function allows for computation based on the old value

common jQuery mistake

```
// bad jQuery
```

```
$("div").css("top", parseInt($("div").css("top")) +  
100 + "px");
```

- Likely to give bad results if multiple selected objects. Why?
- a corrected version:

```
$("div").css("top", function(idx, old) {  
    return parseInt(old) + 100 + "px";  
}); // good jQuery
```


jQuery method returns

- When there is no other return to make, jQuery methods return the same jQuery object back to you

method	return type
<code>\$("#myid");</code>	jQuery object
<code>\$("#myid").children();</code>	jQuery object
<code>\$("#myid").css("margin-left");</code>	String
<code>\$("#myid").css("margin-left", "10px");</code>	jQuery object
<code>\$("#myid").addClass("special");</code>	jQuery object

jQuery chaining

```
$("#img").css("color", "red");  
$("#img").attr("id", "themainarea");  
$("#img").addClass("special");
```

- The implicitly returned jQuery object allows for chaining of method calls.

```
$("#img") // good jQuery style  
  .css("color", "red")  
  .addClass("special")  
  .attr("src", "foo.png");  
// we could chain further right here
```



More node manipulation with jQuery

jQuery method	functionality
<u>.hide()</u>	set CSS display: none
<u>.show()</u>	set CSS display to original value, e.g., block, inline
<u>.empty()</u>	remove everything inside the element, innerHTML = ""
<u>.html()</u>	get/set the innerHTML without escaping html tags
<u>.text()</u>	get/set the innerHTML, HTML escapes the text first
<u>.val()</u>	get/set the value of a form input, select, textarea, ...
<u>.height()</u>	get/set the height in pixels, returns a Number
<u>.width()</u>	get/set the width in pixels, return a Number

Main Point

- The jQuery object returned by the selection mode of `$()` is a collection of DOM elements wrapped by jQuery functionality. This object can read style properties as well as set them by using the `css` method of jQuery.
- *Science of Consciousness: Node manipulation involves locating nodes, observing or reading values, and changing values. Our TM practice develops our ability to locate quiet states of awareness. Advanced techniques and the TM-Sidhi Program develop abilities to experience and manipulate different characteristics of pure consciousness*

