



# Business Message Documentation

|                     |                                    |
|---------------------|------------------------------------|
| Application Type    | Application Business Message (ABM) |
| M3 version          | BE15                               |
| M3 Business Message | ER - Expected Receipt              |
| Message Direction   | Outbound                           |
| Message Application | ABM ExpectedReceipt Show 1         |

|          |   |
|----------|---|
| Map name | M3BE15_ER_Out_ABM_ExpectedReceipt_GetShow_1 |
|----------|---|



## Introduction

This document is a Message Implementation Guideline (MIG) for a business message used in Infor's enterprise application, M3. It defines in detail the collaboration logic between the business message and the M3 system.

The MIG supplied by Infor is based on the business functionality in M3.

The business message format is Extensible Markup Language (XML). XML is a standard developed by the World Wide Web Consortium (W3C). "Element" in this document refers to an XML element. The business message is divided into "message parts"; a message part is a logical unit within the business message, for example, a header, an address or details/lines. Within each message part each element can have up to four parents. The message part, the parents and the element define the XPath for the element. Structural levels for the message's object and process (for example "PurchaseOrder" and "Show") are only shown in the XPaths in this document.

This document consists of two major sections: Elements Used and Element Documentation. The section Elements Used provides an overall view of all elements used in this MIG. The section Element Documentation provides detailed specifications of each and every element implemented in the business message. The element information is presented in the order in which the elements are defined in the business message.



## Elements Used

This section contains a summary of all elements used in this message application, that is, the elements that have documentation attached. The XPaths for these elements are provided relative to the message parts. The elements are listed in message structure order



## Elements Used

|             |   |
|-------------|---|
| MessagePart | <b>GeneralMessageHeader</b>                 |
|             | MessageIdentification/MessageObject         |
|             | MessageIdentification/MessageMethod         |
|             | MessageIdentification/MessageVersion        |
|             | MessageIdentification/MessageIdentityNumber |
|             | MessageLanguage/Language/Code               |
|             | MessageLanguage/Language/Description        |
|             | MessageDate/DateAndTime/Date                |
|             | MessageDate/DateAndTime/Time                |
|             | MessageDate/DateAndTime/GMTOffset           |
|             | MessageDate/DateAndTime/DateFormat          |
|             | MessageDate/DateAndTime/TimeFormat          |
|             | MessageFunction/MessageFunctionIndicator    |
|             | MessageStatus/MessageStatusIndicator        |
|             | ApplicationMessage/Identity                 |
|             | ApplicationMessage/SeverityCode             |
|             | ApplicationMessage/Text                     |
|             | ApplicationMessage/LanguageCode             |



## Elements Used

| MessagePart | Show/Detail |
|-------------|-------------|
|             | Line/RIDL   |
|             | Line/RIDX   |
|             | Line/PNLS   |
|             | Line/RIDI   |
|             | Line/STAT   |
|             | Line/ITNO   |
|             | Line/ALID   |
|             | Line/PLDT   |
|             | Line/TIHM   |
|             | Line/CODT   |
|             | Line/RIDT   |
|             | Line/TRQT   |
|             | Line/ALQT   |
|             | Line/BOIN   |
|             | Line/PRIO   |
|             | Line/NOAA   |
|             | Line/ALMT   |
|             | Line/SPMT   |
|             | Line/ORDP   |
|             | Line/RORC   |
|             | Line/RORN   |
|             | Line/RORL   |
|             | Line/RORX   |
|             | Line/RESP   |
|             | Line/JDCD   |
|             | Line/GRWE   |
|             | Line/ALUN   |
|             | Line/CAWE   |
|             | Line/POCY   |
|             | Line/PANR   |
|             | Line/TRTP   |
|             | Line/SSCC   |
|             | Line/BANO   |
|             | Line/CAMU   |
|             | Line/PRDT   |
|             | Line/RSCD   |
|             | Line/BREM   |
|             | Line/OPNO   |
|             | Line/WOSQ   |
|             | Line/PLGR   |



## Elements Used

| MessagePart | Show/Detail |
|-------------|-------------|
|             | Line/STGS   |
|             | Line/MTNO   |
|             | Line/ACTS   |
|             | Line/REPN   |
|             | Line/RELI   |
|             | Line/TXID   |
|             | Line/DTID   |
|             | Line/USD1   |
|             | Line/USD2   |
|             | Line/USD3   |
|             | Line/USD4   |
|             | Line/USD5   |
|             | Line/CMND   |
|             | Line/DOWN   |
|             | Line/RGDT   |
|             | Line/RGTM   |
|             | Line/LMDT   |
|             | Line/CHNO   |
|             | Line/CHID   |
|             | Line/PRBE   |



## Elements Used

| MessagePart | Show/Header |
|-------------|-------------|
|             | CONO        |
|             | EOPA        |
|             | WHLO        |
|             | TTYP        |
|             | RIDN        |
|             | TRTP        |
|             | TRSL        |
|             | TRSH        |
|             | SUNO        |
|             | PRIO        |
|             | TRDT        |
|             | TRTM        |
|             | FACI        |
|             | ORDP        |
|             | RORC        |
|             | RORN        |
|             | RORL        |
|             | RORX        |
|             | RESP        |
|             | DLIX        |
|             | HAZI        |
|             | MODL        |
|             | TEPA        |
|             | TEDL        |
|             | ADK1        |
|             | GRWE        |
|             | ADID        |
|             | CONM        |
|             | ADR1        |
|             | ADR2        |
|             | ADR3        |
|             | ADR4        |
|             | PONO        |
|             | CSCD        |
|             | ADVI        |
|             | OREF        |
|             | YREF        |
|             | REMK        |
|             | REPN        |
|             | TXID        |



## Elements Used

| MessagePart | Show/Header |
|-------------|-------------|
|             | DTID        |
|             | USD1        |
|             | USD2        |
|             | USD3        |
|             | USD4        |
|             | USD5        |
|             | CMND        |
|             | DOWN        |
|             | RGDT        |
|             | RGTM        |
|             | LMDT        |
|             | CHNO        |
|             | CHID        |
|             | PRBE        |





## Element Documentation

This section is based on the same structure as the section Elements Used, but here you see all the available descriptions, statuses (conditional or mandatory), repeats (0, 1, 2 etc. or unbounded), data types (alphanumeric, numeric, date etc.) and data lengths. There is a page break for every message part. Parents' attributes are only shown when the parents change. This section also includes M3 application documentation and the XPath for the element, which specifies the position of the element in the message structure.

M3 application documentation consists of three sections: M3 Application Description, M3 Application Data Translation and M3 Application Specification.

### **M3 Application Description**

This section provides a general description in “business process language” and describes how the element is used in relation to the M3 logic, for example, which M3 data is used.

### **M3 Application Data Translation**

This section specifies whether or not the data can be translated between M3 and the message. Data translation is used, for example, to translate unit of measure (“STK” to “PCS”) and currency codes (“PND” to “GBP”). Data translations are managed by the M3 program “Business Message Data Translation. Display” (CRS881) and the program “Business Message Data. Translate” (CRS882). The key used in (CRS881) for the element’s data translation is provided.

### **M3 Application Specification**

This section contains the specification that constitutes the base for the business message. It describes whether the element uses data from or transfers data to a M3 API, uses calculated data and/or fixed data. It also describes how and when to make the M3 API calls, which input and output fields to use, etc. Additional information may also be given, such as conditions or notes to clarify specific logic used. Taken together, the sections M3 Application Description and M3 Application Specification define the functionality of the business message.

| MessagePart  |                              | Repeat   |          | Description                   |
|--|------------------------------|----------|----------|-------------------------------|
| <b>GeneralMessageHeader</b>  |                              | <b>M</b> | <b>1</b> | <b>General message header</b> |
| Parent1  | <b>MessageIdentification</b> | M        | 1        | Message identification        |
| Element  | <b>MessageObject</b>         | M        |          | Message object                |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageIdentification/MessageObject</i>         |                              |          |          |                               |
| Parent1  | <b>MessageIdentification</b> | M        | 1        | Message identification        |
| Element  | <b>MessageMethod</b>         | M        |          | Message Advice                |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageIdentification/MessageMethod</i>         |                              |          |          |                               |
| Parent1  | <b>MessageIdentification</b> | M        | 1        | Message identification        |
| Element  | <b>MessageVersion</b>        | M        |          | Message version               |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageIdentification/MessageVersion</i>        |                              |          |          |                               |
| Parent1  | <b>MessageIdentification</b> | M        | 1        | Message identification        |
| Element  | <b>MessageIdentityNumber</b> | M        |          | MessageIdentityNumber         |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageIdentification/MessageIdentityNumber</i> |                              |          |          |                               |
| Parent2  | <b>MessageLanguage</b>       | M        | 1        | MessageLanguage               |
| Parent1  | <b>Language</b>              | M        | 1        | Language                      |
| Element  | <b>Code</b>                  | M        |          | Code                          |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageLanguage/Language/Code</i>               |                              |          |          |                               |
| Parent2  | <b>MessageLanguage</b>       | M        | 1        | MessageLanguage               |
| Parent1  | <b>Language</b>              | M        | 1        | Language                      |
| Element  | <b>Description</b>           | C        |          | Description                   |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageLanguage/Language/Description</i>        |                              |          |          |                               |
| Parent2  | <b>MessageDate</b>           | M        | 1        | Message Date                  |
| Parent1  | <b>DateAndTime</b>           | C        | 1        | DateAndTime                   |
| Element  | <b>Date</b>                  | M        |          | Date                          |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageDate/DateAndTime/Date</i>                |                              |          |          |                               |
| Parent2  | <b>MessageDate</b>           | M        | 1        | Message Date                  |
| Parent1  | <b>DateAndTime</b>           | C        | 1        | DateAndTime                   |
| Element  | <b>Time</b>                  | C        |          | Time                          |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageDate/DateAndTime/Time</i>                |                              |          |          |                               |

| MessagePart   |                                 | Repeat   |           | Description                   |
|---|---------------------------------|----------|-----------|-------------------------------|
| <b>GeneralMessageHeader</b>   |                                 | <b>M</b> | <b>1</b>  | <b>General message header</b> |
| Parent2   | <b>MessageDate</b>              | M        | 1         | Message Date                  |
| Parent1   | <b>DateAndTime</b>              | C        | 1         | DateAndTime                   |
| Element   | <b>GMTOffset</b>                | C        |           | GMTOffset                     |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageDate/DateAndTime/GMTOffset</i>        |                                 |          |           |                               |
| Parent2   | <b>MessageDate</b>              | M        | 1         | Message Date                  |
| Parent1   | <b>DateAndTime</b>              | C        | 1         | DateAndTime                   |
| Element   | <b>DateFormat</b>               | C        |           | Date format                   |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageDate/DateAndTime/DateFormat</i>       |                                 |          |           |                               |
| Parent2   | <b>MessageDate</b>              | M        | 1         | Message Date                  |
| Parent1   | <b>DateAndTime</b>              | C        | 1         | DateAndTime                   |
| Element   | <b>TimeFormat</b>               | C        |           | Time format                   |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageDate/DateAndTime/TimeFormat</i>       |                                 |          |           |                               |
| Parent1   | <b>MessageFunction</b>          | C        | 1         | Message function              |
| Element   | <b>MessageFunctionIndicator</b> | C        |           | Message function indicator    |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageFunction/MessageFunctionIndicator</i> |                                 |          |           |                               |
| Parent1   | <b>MessageStatus</b>            | C        | 1         | Message status                |
| Element   | <b>MessageStatusIndicator</b>   | C        |           | Message status indicator      |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/MessageStatus/MessageStatusIndicator</i>     |                                 |          |           |                               |
| Parent1   | <b>ApplicationMessage</b>       | C        | unbounded | Application message           |
| Element   | <b>Identity</b>                 | M        |           | Identity                      |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/ApplicationMessage/Identity</i>              |                                 |          |           |                               |
| Parent1   | <b>ApplicationMessage</b>       | C        | unbounded | Application message           |
| Element   | <b>SeverityCode</b>             | C        |           | Severity code                 |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/ApplicationMessage/SeverityCode</i>          |                                 |          |           |                               |
| Parent1   | <b>ApplicationMessage</b>       | C        | unbounded | Application message           |
| Element   | <b>Text</b>                     | M        |           | Text                          |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/ApplicationMessage/Text</i>                  |                                 |          |           |                               |



| MessagePart  |                           | Repeat   |           | Description                   |
|--|---------------------------|----------|-----------|-------------------------------|
| <b>GeneralMessageHeader</b>  |                           | <b>M</b> | <b>1</b>  | <b>General message header</b> |
| Parent1  | <b>ApplicationMessage</b> | C        | unbounded | Application message           |
| Element  | <b>LanguageCode</b>       | M        |           | Language code                 |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/GeneralMessageHeader/ApplicationMessage/LanguageCode</i> |                           |          |           |                               |

| MessagePart | Repeat  | Description             |
|-------------|---------|-------------------------|
| Show/Detail | C unbou | Expected receipt detail |

|         |      |       |            |
|---------|------|-------|------------|
| Parent1 | Line | M 1   |            |
| Element | RIDL | C n 6 | Order line |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: RIDL

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/RIDL*

|         |      |       |             |
|---------|------|-------|-------------|
| Parent1 | Line | M 1   |             |
| Element | RIDX | C n 3 | Line suffix |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: RIDX

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/RIDX*

|         |       |       |                               |
|---------|-------|-------|-------------------------------|
| Parent1 | Line  | M 1   |                               |
| Element | P-NLS | C n 3 | Purchase order line subnumber |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: PNLS

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/PNLS*

|         |      |        |             |
|---------|------|--------|-------------|
| Parent1 | Line | M 1    |             |
| Element | RIDI | C n 11 | Order index |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: RID

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/RID/*

|         |      |       |        |
|---------|------|-------|--------|
| Parent1 | Line | M 1   |        |
| Element | STAT | C a 2 | Status |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: STAT

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/STAT*



| MessagePart  |      | Repeat | Description                   |
|--|------|--------|-------------------------------|
| Show/Detail  |      | C      | unbou Expected receipt detail |
| Parent1  | Line | M 1    |                               |
| Element  | ITNO | C a 15 | Item number                   |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: ITNO<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/ITNO</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | ALID | C a 30 | Alias identity                |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: ALID<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/ALID</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | PLDT | C d 10 | Planning date                 |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: PLDT<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/PLDT</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | TIHM | C n 4  | Time hours & minutes          |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: TIHM<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/TIHM</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | CODT | C d 10 | Confirmed delivery date       |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: CODT<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/CODT</i> |      |        |                               |

|             | MessagePart | Repeat | Description                   |
|-------------|-------------|--------|-------------------------------|
| Show/Detail |             | C      | unbou Expected receipt detail |

|         |      |   |      |                |
|---------|------|---|------|----------------|
| Parent1 | Line | M | 1    |                |
| Element | RIDT | C | d 10 | Receiving date |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: RIDT

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/RIDT*

|         |      |        |                                  |
|---------|------|--------|----------------------------------|
| Parent1 | Line | M 1    |                                  |
| Element | TRQT | C n 17 | Transaction quantity - basic U/M |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: TRQT

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/TRQT*

|         |      |        |                                |
|---------|------|--------|--------------------------------|
| Parent1 | Line | M 1    |                                |
| Element | ALQT | C n 17 | Allocated quantity - basic U/M |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: ALQT

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/ALQT*

|         |      |       |                     |
|---------|------|-------|---------------------|
| Parent1 | Line | M 1   |                     |
| Element | BOIN | C n 1 | Backorder indicator |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: BOIN

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/BOIN*

|         |      |   |   |          |
|---------|------|---|---|----------|
| Parent1 | Line | M | 1 |          |
| Element | PRIO | C | n | 1        |
|         |      |   |   | Priority |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: PRI0

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/PRIO*



| MessagePart   |      | Repeat | Description                   |
|---|------|--------|-------------------------------|
| Show/Detail   |      | C      | unbou Expected receipt detail |
| Parent1   | Line | M 1    |                               |
| Element   | NOAA | C n 1  | Overriding allocation method  |
| <b>M3 Application Description:</b>  |      |        |                               |
| <b>M3 Application Specification:</b>  |      |        |                               |
| API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: NOAA |      |        |                               |
| <b>XPath:</b> ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/NOAA    |      |        |                               |
| Parent1   | Line | M 1    |                               |
| Element   | ALMT | C n 1  | Allocation method             |
| <b>M3 Application Description:</b>  |      |        |                               |
| <b>M3 Application Specification:</b>  |      |        |                               |
| API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: ALMT |      |        |                               |
| <b>XPath:</b> ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/ALMT    |      |        |                               |
| Parent1   | Line | M 1    |                               |
| Element   | SPMT | C n 1  | Issue method                  |
| <b>M3 Application Description:</b>  |      |        |                               |
| <b>M3 Application Specification:</b>  |      |        |                               |
| API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: SPMT |      |        |                               |
| <b>XPath:</b> ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/SPMT    |      |        |                               |
| Parent1   | Line | M 1    |                               |
| Element   | ORDP | C n 1  | Order dependent               |
| <b>M3 Application Description:</b>  |      |        |                               |
| <b>M3 Application Specification:</b>  |      |        |                               |
| API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: ORDP |      |        |                               |
| <b>XPath:</b> ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/ORDP    |      |        |                               |
| Parent1   | Line | M 1    |                               |
| Element   | RORC | C n 1  | Reference order category      |
| <b>M3 Application Description:</b>  |      |        |                               |
| <b>M3 Application Specification:</b>  |      |        |                               |
| API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: RORC |      |        |                               |
| <b>XPath:</b> ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/RORC    |      |        |                               |





| MessagePart |  | Repeat | Description                   |
|-------------|--|--------|-------------------------------|
| Show/Detail |  | C      | unbou Expected receipt detail |

|         |      |   |      |                        |
|---------|------|---|------|------------------------|
| Parent1 | Line | M | 1    |                        |
| Element | RORN | C | a 10 | Reference order number |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: RORN

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/RORN*

|         |      |   |     |                      |
|---------|------|---|-----|----------------------|
| Parent1 | Line | M | 1   |                      |
| Element | RORL | C | n 6 | Reference order line |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: RORL

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/RORL*

|         |      |   |     |             |
|---------|------|---|-----|-------------|
| Parent1 | Line | M | 1   |             |
| Element | RORX | C | n 3 | Line suffix |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: RORX

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/RORX*

|         |      |   |      |             |
|---------|------|---|------|-------------|
| Parent1 | Line | M | 1    |             |
| Element | RESP | C | a 10 | Responsible |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: RESP

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/RESP*

|         |      |   |     |                |
|---------|------|---|-----|----------------|
| Parent1 | Line | M | 1   |                |
| Element | JDCD | C | a 5 | Joint delivery |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: JDCD

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/JDCD*



| MessagePart  |      | Repeat | Description                   |
|--|------|--------|-------------------------------|
| Show/Detail  |      | C      | unbou Expected receipt detail |
| Parent1  | Line | M 1    |                               |
| Element  | GRWE | C n 11 | Gross weight                  |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: GRWE<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/GRWE</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | ALUN | C a 3  | Alternate U/M                 |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: ALUN<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/ALUN</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | CAWE | C n 17 | Catch weight                  |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: CAWE<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/CAWE</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | POCY | C n 7  | Normal potency                |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: POCY<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/POCY</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | PANR | C a 10 | Package number                |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: PANR<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/PANR</i> |      |        |                               |

| MessagePart | Repeat  | Description             |
|-------------|---------|-------------------------|
| Show/Detail | C unbou | Expected receipt detail |

|         |      |       |            |
|---------|------|-------|------------|
| Parent1 | Line | M 1   |            |
| Element | TRTP | C a 3 | Order type |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: TRTP

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/TRTP*

|         |      |        |             |
|---------|------|--------|-------------|
| Parent1 | Line | M 1    |             |
| Element | SSCC | C a 18 | SSCC number |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: SSCC

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/SSCC*

|         |      |        |            |
|---------|------|--------|------------|
| Parent1 | Line | M 1    |            |
| Element | BANO | C a 12 | Lot number |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: BANO

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/BANO*

|         |      |        |           |
|---------|------|--------|-----------|
| Parent1 | Line | M 1    |           |
| Element | CAMU | C a 12 | Container |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: CAMU

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/CAMU*

|         |      |   |      |               |
|---------|------|---|------|---------------|
| Parent1 | Line | M | 1    |               |
| Element | PRDT | C | d 10 | Priority date |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: PRDT

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/PRDT*



| MessagePart  |      | Repeat | Description                   |
|--|------|--------|-------------------------------|
| Show/Detail  |      | C      | unbou Expected receipt detail |
| Parent1  | Line | M 1    |                               |
| Element  | RSCD | C a 3  | Transaction reason            |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: RSCD<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/RSCD</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | BREM | C a 20 | Remark                        |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: BREM<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/BREM</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | OPNO | C n 4  | Operation number              |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: OPNO<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/OPNO</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | WOSQ | C n 9  | Reporting number              |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: WOSQ<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/WOSQ</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | PLGR | C a 8  | Work center                   |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: PLGR<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/PLGR</i> |      |        |                               |



| MessagePart |  | Repeat | Description                   |
|-------------|--|--------|-------------------------------|
| Show/Detail |  | C      | unbou Expected receipt detail |

|         |      |   |     |                     |
|---------|------|---|-----|---------------------|
| Parent1 | Line | M | 1   |                     |
| Element | STGS | C | n 1 | Subcontract control |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: STGS

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/STGS*

|         |      |   |      |                  |
|---------|------|---|------|------------------|
| Parent1 | Line | M | 1    |                  |
| Element | MTNO | C | a 15 | Component number |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: MTNO

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/MTNO*

|         |      |   |     |                          |
|---------|------|---|-----|--------------------------|
| Parent1 | Line | M | 1   |                          |
| Element | ACTS | C | n 3 | Operation element number |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: ACTS

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/ACTS*

|         |      |   |      |                  |
|---------|------|---|------|------------------|
| Parent1 | Line | M | 1    |                  |
| Element | REPN | C | n 10 | Receiving number |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: REPN

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/REPN*

|         |      |   |     |             |
|---------|------|---|-----|-------------|
| Parent1 | Line | M | 1   |             |
| Element | RELI | C | n 5 | Line number |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: RELI

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/RELI*



| MessagePart  |      | Repeat | Description                   |
|--|------|--------|-------------------------------|
| Show/Detail  |      | C      | unbou Expected receipt detail |
| Parent1  | Line | M 1    |                               |
| Element  | TXID | C n 13 | Text identity                 |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: TXID<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/TXID</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | DTID | C n 13 | Data identity                 |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: DTID<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/DTID</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | USD1 | C a 15 | User-defined field            |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: USD1<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/USD1</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | USD2 | C a 15 | User-defined field            |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: USD2<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/USD2</i> |      |        |                               |
| Parent1  | Line | M 1    |                               |
| Element  | USD3 | C a 15 | User-defined field            |
| <b>M3 Application Description:</b><br><b>M3 Application Specification:</b><br>API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: USD3<br><b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/USD3</i> |      |        |                               |

|             | MessagePart | Repeat  | Description             |
|-------------|-------------|---------|-------------------------|
| Show/Detail |             | C unbou | Expected receipt detail |

|         |      |   |      |                    |
|---------|------|---|------|--------------------|
| Parent1 | Line | M | 1    |                    |
| Element | USD4 | C | a 15 | User-defined field |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: USD4

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/USD4*

|         |      |        |                    |
|---------|------|--------|--------------------|
| Parent1 | Line | M 1    |                    |
| Element | USD5 | C a 15 | User-defined field |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: USD5

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/USD5*

|         |      |        |                |
|---------|------|--------|----------------|
| Parent1 | Line | M 1    |                |
| Element | CMND | C a 15 | Operation code |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: CMND

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/CMND*

|         |      |       |                                  |
|---------|------|-------|----------------------------------|
| Parent1 | Line | M 1   |                                  |
| Element | DOWN | C n 1 | 0/blank=Unprocessed, 1=Processed |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: DOWN

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Detail/Line/DOWN*

|         |      |        |            |
|---------|------|--------|------------|
| Parent1 | Line | M 1    |            |
| Element | RGDT | C d 10 | Entry date |

### M3 Application Description:

### M3 Application Specification:

API data MI program: MHS800MI Transaction: LstExpRecDetail\_Record Field: RGDT

**XPath:** *ExpectedReceipt Show 1/ExpectedReceipt/Show/Detail/Line/RGDT*



| MessagePart   |      | Repeat | Description                   |
|---|------|--------|-------------------------------|
| Show/Detail   |      | C      | unbou Expected receipt detail |
| Parent1   | Line | M 1    |                               |
| Element   | RGTM | C n 6  | Entry time                    |
| <b>M3 Application Description:</b>  |      |        |                               |
| <b>M3 Application Specification:</b>  |      |        |                               |
| API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: RGTM |      |        |                               |
| <b>XPath:</b> ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/RGTM    |      |        |                               |
| Parent1   | Line | M 1    |                               |
| Element   | LMDT | C d 10 | Change date                   |
| <b>M3 Application Description:</b>  |      |        |                               |
| <b>M3 Application Specification:</b>  |      |        |                               |
| API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: LMDT |      |        |                               |
| <b>XPath:</b> ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/LMDT    |      |        |                               |
| Parent1   | Line | M 1    |                               |
| Element   | CHNO | C n 3  | Change number                 |
| <b>M3 Application Description:</b>  |      |        |                               |
| <b>M3 Application Specification:</b>  |      |        |                               |
| API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: CHNO |      |        |                               |
| <b>XPath:</b> ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/CHNO    |      |        |                               |
| Parent1   | Line | M 1    |                               |
| Element   | CHID | C a 10 | Changed by                    |
| <b>M3 Application Description:</b>  |      |        |                               |
| <b>M3 Application Specification:</b>  |      |        |                               |
| API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: CHID |      |        |                               |
| <b>XPath:</b> ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/CHID    |      |        |                               |
| Parent1   | Line | M 1    |                               |
| Element   | PRBE | C n 1  | Exclude prc before            |
| <b>M3 Application Description:</b>  |      |        |                               |
| <b>M3 Application Specification:</b>  |      |        |                               |
| API data MI program: MHS800MI Transaction: LstExpRecDetail_Record Field: PRBE |      |        |                               |
| <b>XPath:</b> ExpectedReceipt_Show_1/ExpectedReceipt/Show/Detail/Line/PRBE    |      |        |                               |





| MessagePart |  | Repeat | Description             |
|-------------|--|--------|-------------------------|
| Show/Header |  | M 1    | Expected receipt header |

Element CONO C n 3 Company

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: CONO

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/CONO*

Element E0PA C a 17 Partner

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: E0PA

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/E0PA*

Element WHLO C a 3 Warehouse

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: WHLO

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/WHLO*

Element TTYP C n 2 Stock transaction type

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: TTYP

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/TTYP*

Element RIDN C a 10 Order number

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: RIDN

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/RIDN*

Element TRTP C a 3 Order type

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: TRTP

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/TRTP*



| MessagePart |      | Repeat | Description                      |
|-------------|------|--------|----------------------------------|
| Show/Header |      | M 1    | Expected receipt header          |
| Element     | TRSL | C a 2  | Lowest status - stock transactio |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: TRSL

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/TRSL*

|         |      |       |                                   |
|---------|------|-------|-----------------------------------|
| Element | TRSH | C a 2 | Highest status - stock transactin |
|---------|------|-------|-----------------------------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: TRSH

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/TRSH*

|         |      |        |                 |    |
|---------|------|--------|-----------------|----|
| Element | SUNO | C a 10 | Supplier number | on |
|---------|------|--------|-----------------|----|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: SUNO

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/SUNO*

|         |      |       |          |
|---------|------|-------|----------|
| Element | PRIO | C n 1 | Priority |
|---------|------|-------|----------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: PRIO

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/PRIO*

|         |      |        |                  |
|---------|------|--------|------------------|
| Element | TRDT | C d 10 | Transaction date |
|---------|------|--------|------------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: TRDT

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/TRDT*

|         |      |       |                  |
|---------|------|-------|------------------|
| Element | TRTM | C n 6 | Transaction time |
|---------|------|-------|------------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: TRTM

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/TRTM*



| MessagePart |  | Repeat | Description             |
|-------------|--|--------|-------------------------|
| Show/Header |  | M 1    | Expected receipt header |

Element FACI C a 3 Facility

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: FACI

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/FACI*

Element ORDP C n 1 Order dependent

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: ORDP

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/ORDP*

Element RORC C n 1 Reference order category

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: RORC

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/RORC*

Element RORN C a 10 Reference order number

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: RORN

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/RORN*

Element RORL C n 6 Reference order line

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: RORL

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/RORL*

Element RORX C n 3 Line suffix

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: RORX

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/RORX*



| MessagePart |  | Repeat | Description             |
|-------------|--|--------|-------------------------|
| Show/Header |  | M 1    | Expected receipt header |

|         |      |        |             |
|---------|------|--------|-------------|
| Element | RESP | C a 10 | Responsible |
|---------|------|--------|-------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: RESP

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/RESP*

|         |      |        |                 |
|---------|------|--------|-----------------|
| Element | DLIX | C n 11 | Delivery number |
|---------|------|--------|-----------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: DLIX

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/DLIX*

|         |      |       |                  |
|---------|------|-------|------------------|
| Element | HAZI | C n 1 | Danger indicator |
|---------|------|-------|------------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: HAZI

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/HAZI*

|         |      |       |                 |
|---------|------|-------|-----------------|
| Element | MODL | C a 3 | Delivery method |
|---------|------|-------|-----------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: MODL

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/MODL*

|         |      |       |                 |
|---------|------|-------|-----------------|
| Element | TEPA | C a 3 | Packaging terms |
|---------|------|-------|-----------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: TEPA

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/TEPA*

|         |      |       |                |
|---------|------|-------|----------------|
| Element | TEDL | C a 3 | Delivery terms |
|---------|------|-------|----------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: TEDL

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/TEDL*



| MessagePart |  | Repeat | Description             |
|-------------|--|--------|-------------------------|
| Show/Header |  | M 1    | Expected receipt header |

|         |      |        |               |
|---------|------|--------|---------------|
| Element | ADK1 | C a 10 | Address key 1 |
|---------|------|--------|---------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: ADK1

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/ADK1*

|         |      |        |              |
|---------|------|--------|--------------|
| Element | GRWE | C n 11 | Gross weight |
|---------|------|--------|--------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: GRWE

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/GRWE*

|         |      |       |                |
|---------|------|-------|----------------|
| Element | ADID | C a 6 | Address number |
|---------|------|-------|----------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: ADID

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/ADID*

|         |      |        |              |
|---------|------|--------|--------------|
| Element | CONM | C a 36 | Company name |
|---------|------|--------|--------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: CONM

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/CONM*

|         |      |        |                |
|---------|------|--------|----------------|
| Element | ADR1 | C a 36 | Address line 1 |
|---------|------|--------|----------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: ADR1

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/ADR1*

|         |      |        |                |
|---------|------|--------|----------------|
| Element | ADR2 | C a 36 | Address line 2 |
|---------|------|--------|----------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: ADR2

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/ADR2*



| MessagePart |  | Repeat | Description             |
|-------------|--|--------|-------------------------|
| Show/Header |  | M 1    | Expected receipt header |

|         |      |        |                |
|---------|------|--------|----------------|
| Element | ADR3 | C a 36 | Address line 3 |
|---------|------|--------|----------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: ADR3

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/ADR3*

|         |      |        |                |
|---------|------|--------|----------------|
| Element | ADR4 | C a 36 | Address line 4 |
|---------|------|--------|----------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: ADR4

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/ADR4*

|         |      |        |             |
|---------|------|--------|-------------|
| Element | PONO | C a 10 | Postal code |
|---------|------|--------|-------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: PONO

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/PONO*

|         |      |       |         |
|---------|------|-------|---------|
| Element | CSCD | C a 3 | Country |
|---------|------|-------|---------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: CSCD

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/CSCD*

|         |      |       |             |
|---------|------|-------|-------------|
| Element | ADVI | C a 6 | Via address |
|---------|------|-------|-------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: ADVI

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/ADVI*

|         |      |        |               |
|---------|------|--------|---------------|
| Element | OREF | C a 30 | Our reference |
|---------|------|--------|---------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: OREF

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/OREF*



| MessagePart |      | Repeat | Description             |
|-------------|------|--------|-------------------------|
| Show/Header |      | M 1    | Expected receipt header |
| Element     | YREF | C a 30 | Your reference 1        |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: YREF

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/YREF*

|  |      |        |        |
|--|------|--------|--------|
| Element  | REMK | C a 30 | Remark |
| <b>M3 Application Description:</b>   |      |        |        |
| <b>M3 Application Specification:</b>   |      |        |        |
| API data MI program: MHS800MI Transaction: LstExpRec_Record Field: REMK      |      |        |        |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Header/REMK</i> |      |        |        |

|         |      |        |                  |
|---------|------|--------|------------------|
| Element | REPN | C n 10 | Receiving number |
|---------|------|--------|------------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: REPN

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/REPN*

|  |      |        |               |
|--|------|--------|---------------|
| Element  | TXID | C n 13 | Text identity |
| <b>M3 Application Description:</b>   |      |        |               |
| <b>M3 Application Specification:</b>   |      |        |               |
| API data MI program: MHS800MI Transaction: LstExpRec_Record Field: TXID      |      |        |               |
| <b>XPath:</b> <i>ExpectedReceipt_Show_1/ExpectedReceipt/Show/Header/TXID</i> |      |        |               |



| MessagePart |      | Repeat |      | Description             |
|-------------|------|--------|------|-------------------------|
| Show/Header |      | M      | 1    | Expected receipt header |
| Element     | DTID | C      | n 13 | Data identity           |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: DTID

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/DTID*

|         |      |   |      |                    |
|---------|------|---|------|--------------------|
| Element | USD1 | C | a 15 | User-defined field |
|---------|------|---|------|--------------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: USD1

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/USD1*

|         |      |   |      |                    |
|---------|------|---|------|--------------------|
| Element | USD2 | C | a 15 | User-defined field |
|---------|------|---|------|--------------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: USD2

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/USD2*

|         |      |   |      |     |
|---------|------|---|------|-----|
| Element | USD3 | C | a 15 | U-d |
|---------|------|---|------|-----|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: USD3

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/USD3*

|         |      |   |      |     |
|---------|------|---|------|-----|
| Element | USD4 | C | a 15 | U-d |
|---------|------|---|------|-----|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: USD4

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/USD4*

|         |      |   |      |     |
|---------|------|---|------|-----|
| Element | USD5 | C | a 15 | U-d |
|---------|------|---|------|-----|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: USD5

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/USD5*





| MessagePart |  | Repeat | Description             |
|-------------|--|--------|-------------------------|
| Show/Header |  | M 1    | Expected receipt header |

|         |      |        |                |
|---------|------|--------|----------------|
| Element | CMND | C a 15 | Operation code |
|---------|------|--------|----------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: CMND

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/CMND*

|         |      |       |                                  |
|---------|------|-------|----------------------------------|
| Element | DOWN | C n 1 | 0/blank=Unprocessed, 1=Processed |
|---------|------|-------|----------------------------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: DOWN

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/DOWN*

|         |      |        |            |
|---------|------|--------|------------|
| Element | RGDT | C d 10 | Entry date |
|---------|------|--------|------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: RGDT

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/RGDT*

|         |      |       |            |
|---------|------|-------|------------|
| Element | RGTM | C n 6 | Entry time |
|---------|------|-------|------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: RGTM

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/RGTM*

|         |      |        |             |
|---------|------|--------|-------------|
| Element | LMDT | C d 10 | Change date |
|---------|------|--------|-------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: LMDT

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/LMDT*

|         |      |       |               |
|---------|------|-------|---------------|
| Element | CHNO | C n 3 | Change number |
|---------|------|-------|---------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: CHNO

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/CHNO*



| MessagePart |      | Repeat |      | Description             |
|-------------|------|--------|------|-------------------------|
| Show/Header |      | M      | 1    | Expected receipt header |
| Element     | CHID | C      | a 10 | Changed by              |

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: CHID

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/CHID*

|         |      |   |     |                    |
|---------|------|---|-----|--------------------|
| Element | PRBE | C | n 1 | Exclude prc before |
|---------|------|---|-----|--------------------|

**M3 Application Description:**

**M3 Application Specification:**

API data MI program: MHS800MI Transaction: LstExpRec\_Record Field: PRBE

**XPath:** *ExpectedReceipt\_Show\_1/ExpectedReceipt/Show/Header/PRBE*



**END**