2024 15th International Conference on Information and Communication Technology Convergence (ICTC) | 979-8-3503-6463-7/24/$31.00 ©2024 IEEE | DOI: 10.1109/ICTC62082.2024.10827351

Protection of LLM Environment Using Prompt Security

Minjae Kim
ESTsecurity
Seoul, Republic of Korea
mjkim45@estsecurity.com

Taehyeong Kwon
ESTsecurity
Seoul, Republic of Korea
brightkwon@estsecurity.com

Kibeom Shim
ESTsecurity
Seoul, Republic of Korea
kishim1@estsecurity.com

Beonghoon Kim
ESTsecurity
Seoul, Republic of Korea
bhkim@estsecurity.com

***Abstract*—The emergence of generative AI has also brought significant attention to large language models (LLMs). LLMs are a type of generative AI that can understand users' commands and respond accordingly by generating natural human language text. However, such advancements in LLM technology have also been accompanied by an increase in hostile attempts to use the technology for malicious attacks. For example, some may execute a jailbreak on an LLM, allowing it to generate malicious content, and others can use LLMs to generate vulnerability exploit codes, taking advantage of their powerful capabilities to attempt malicious attacks. Furthermore, there are increasing numbers of cases reported where, once inadvertently entered, personally identifiable information (PII) is used to train LLMs without consent. Preventing the malicious use of LLMs and their unauthorized use of PII requires thoroughly scanning their inputs and outputs. Specifically, LLMs' inputs and outputs need to be checked for the presence of PII, malicious codes, malicious URLs, and commands to execute prompt injections. This paper presents a comprehensive description of the LLM prompt detection system (LPDS) designed to detect the presence of PII, malicious codes, malicious URLs, and prompt injection commands in LLMs' inputs and outputs. The effectiveness of the LPDS in detecting LLMs' unauthorized use of PII and LLM-based malicious attacks is also assessed.**

Keywords—LLM, Privacy Protection, AI Security, Prompt Detection

I. Introduction

The emergence of OpenAI's ChatGPT in November 2022 has put an intense spotlight on large language models (LLMs) worldwide. LLMs have been attracting numerous users from various backgrounds, and such generative AI (GenAI) is now growing exponentially in both usage and importance. According to the hype cycle for artificial intelligence proposed by Gartner [1], the current growth of AI is driven primarily by GenAI.



[Figure 1] Gartner's hype cycle for artificial intelligence

LLMs, as a type of GenAI, understand users' inquiries and answer them in a creative manner. Thanks to these capabilities, LLMs often serve as assistants that provide aid in various tasks, such as searching and coding. That said, personally identifiable information (PII) before pseudonymization could be used as training data for LLMs, allowing them to use such information in composing their answers without consent [2]. Moreover, any PII that individuals have inadvertently entered into LLMs could end up being leaked or stolen. These risks go beyond the unauthorized use of PII and extend to the threat of generating malicious codes using LLMs [3]. Cases reported in [3] include one in which an LLM was used to produce stealer malware designed to execute malicious acts, and it only took a few questions to achieve this result. As such, LLMs are trained based on extensive data of various types, and thus, some attackers attempt to disrupt the training data supply chain by directly infiltrating the training data or using LLMs to generate malicious codes.

In attempts to prevent these attacks, LLM developers have incorporated specific protective measures into their models while also allowing their models not to answer any questions that are deemed unethical. Despite this extensive effort, however, attackers can still disrupt LLMs through prompt injection attacks. If LLMs are hacked or compromised via jailbreaking using prompt injection, these models can be used as the attackers desire, answering any questions asked. LLMs

Authorized licensed use limited to: Arizona State University. Downloaded on February 01,2026 at 20:58:46 UTC from IEEE Xplore. Restrictions apply.

could then be reduced to effective attacking tools. Therefore, it is essential to detect the unauthorized use of PII and prompt injection commands. This study proposes a novel system composed of regular expressions and finetuned LLMs to detect PII leakage, prompt injection commands, malicious codes, and malicious URLs in the inputs and outputs of LLMs.

The major contributions of this paper are as follows.

- To detect PII leakage in LLMs' inputs and outputs
- To detect malicious codes and URLs in LLMs' inputs and outputs
- To detect prompt injection in LLMs

The detection technology for PII leakage and prompt injection proposed in this study is intended primarily for Korean and English.

This paper is composed as follows. Chapter 2 provides a summary of previous studies on attacks on LLMs. Chapter 3 presents the detailed configuration of the system proposed in this study, while Chapter 4 illustrates the experimental procedure and results. Finally, Chapter 5 discusses the effective usage and application of the proposed system.

II. Background

A. Large Language Model

Large language models (LLMs) are a type of generative AI (GenAI) that are trained on extensive language data. LLMs' training data is so diverse and broad that these models can effectively recognize and interpret a wide range of data, including language and documents [4]. The performance of LLMs depends primarily on the data used for their training. Considering this intrinsic nature, some attackers attempt to disrupt the training data supply chain by injecting malicious data into LLMs' training data.

B. Prompt Injection

Prompt injection is a type of vulnerability that targets LLMs [5]. Most attacks through prompt injection are typically performed to obtain malicious content using LLMs by switching LLMs into the *Do Anything Now* (DON) mode and asking them to produce malicious codes while misleading them to recognize such codes as training data. Failing to detect or prevent these prompt injection attacks will inevitably lead to the malicious use of LLMs in a variety of possible ways. Therefore, appropriate measures for prompt injection detection and prevention must be taken.

C. Previous studies

Extensive research has consistently focused on attacks targeting LLMs. For example, there were studies attempting to perform attacks on LLMs, targeting their vulnerabilities through prompt injection, jailbreaking, and model theft attacks [6,7,8,9,10,11,12]. Yiming Zhang et al. [6] performed attacks using prompt queries on 11 models (GPT [13], Llama [14], Vicuna [15], and Alpaca [16]). The researchers also executed attacks using translation issues. Kai Greshake et al. [9] performed indirect prompt injections on LLMs to force the models to provide users with URLs that contained malicious codes.

In addition to these attempts to attack the vulnerabilities of LLMs, research has been conducted on the detection of various types of attacks on LLMs, such as prompt injection and jailbreaking [17, 18]. Gabriel et al. proposed a LightGBM-based detection method for differentiating AI-generated prompt-injection prompts, human-generated prompt-injection prompts, and normal prompts [17]. Meanwhile, Manish Bhatt et al. performed pattern-based detection using regular expressions [18]. The researchers proposed a method for detecting LLMs' outputs that could be used to facilitate insecure coding and cyberattacks.

These previous studies commonly attempted to identify attacks on LLMs that had not yet been revealed or detect attacks that had already been identified. However, most of those systems operate in English and thus cannot be applied to environments using other languages, such as Korean. The detection ability of the system proposed in this paper, especially intended for Korean users, is discussed in Chapter 3 below.

III. LLM Prompt Detection System

The LLM prompt detection system (LPDS) employs four engines to detect prompts that contain malicious codes and PII. Figure 2 and Figure 3 present structural diagrams illustrating the workings of the proposed system to verify the inputs and outputs of LLMs, respectively. The four engines embedded in the system serve the following roles.

- PII Detection Engine: Detection and pseudonymization of PII and sensitive information in prompts, such as resident registration numbers, addresses, specific product names, and API keys

- Finetuned AI Model Engine: Detection and prevention of prompt injection attacks

- Malicious URL Detection Engine: Detection and prevention of malicious URLs

- Malware Detection Engine: Detection and prevention of malicious codes



[Figure 2] Input detection structure

Authorized licensed use limited to: Arizona State University. Downloaded on February 01,2026 at 20:58:46 UTC from IEEE Xplore. Restrictions apply.



[Figure 3] Output detection structure

More specifically, the four engines operate based on their respective systematic structures as follows.

- PII Detection Engine: Employing 124 regular expressions and the named entity recognition (NER) model for Korean/English concerning PII and sensitive information

- Finetuned AI Model Engine: Finetuned learning using prompt injection, Korean datasets [19, 20], and openllama-3b [14]

- Malicious URL Detection Engine: Detection using URLhaus data [21]

- Malware Detection Engine: Detection using VirusTotal data [22]

Figure 4 below shows the train and validation loss graph of the finetuned model employed in the proposed system. The detection performance of this model is discussed, along with the entire system's performance, in Chapter 4.



[Figure 4] Train/loss graph

IV. Experimental Procedure and Results

For the assessment of the LPDS, a dataset with 10,000 prompts was prepared to include malicious prompts and other prompts containing artificially created PII. These datasets included not only simple prompt-injection prompts and jailbreaking prompts but also prompts designed to produce malicious codes and URLs using LLMs. Prompts attempting to extract PII were also included. These datasets were generated using artificially created data, Share GPT[23], and Share GPT's Korean translation [20].

Additionally, chainlit [23], which provided the conversational UI with LLMs, and dolphin-mistral[24], an LLM, were employed to visualize the workings of the LPDS.

Figure 5 shows how the LPDS performs PII detection. Once the user, indicated as You, enters text, the LPDS executes PII detection and pseudonymization, displaying the results in the scan-result field.

[Figure 5] PII input scan result

Also, for the outputs of an LLM, the LPDS detects threats, performs pseudonymization, and shows the results in the scan-result field, as shown in Figure 6. The user will then be provided with results edited and treated by the LPDS.



[Figure 6] PII output scan result

Figure 7 depicts the LPDS's function of detecting and preventing malicious codes entered by the user (You). As shown in Figure 8, malicious codes generated by LLMs as their outputs can also be detected and blocked. As such, the proposed system effectively detects malicious prompts in both inputs and outputs of LLMs.

Authorized licensed use limited to: Arizona State University. Downloaded on February 01,2026 at 20:58:46 UTC from IEEE Xplore. Restrictions apply.



[Figure 7] Malware input

[Figure 8] Malware output

Moreover, the finetuned model embedded in the LPDS classifies the entered prompts into LABEL_0 (benign) and LABEL_1 (malicious).



[Figure 9] Finetuned model output

The confusion matrix for the LPDS's PII and malicious prompt detection performance is presented in Table 1. This assessment was conducted using 7,000 prompts containing malicious data and PII and 3,000 benign prompts. Out of the 7,000 prompts, 6997 were identified to be malicious and thus subjected to pseudonymization. Among the 3,000 benign prompts, 2,988 were identified as non-malicious. Overall, the LPDS's detection accuracy for prompts containing malicious data and PII was estimated to be 96.85%.

[Table 1] Confusion matrix

	Malicious	Benign
Malicious	6847	162
Benign	153	2838

Meanwhile, the average time required for the LPDS to detect PII and malicious prompts using its scanners was 0.42 seconds. It is considered an adequate speed to allow users to smoothly interact with LLMs while asking questions and listening to answers nearly promptly.



[Figure 10] Scanner execution time

V. Conclusions

This study proposed a novel system designed to detect prompts containing malicious codes and personally identifiable information (PII) in LLM inputs. With the recent technological advancements in LLMs, their applications are consistently on the rise, from professional tasks to everyday routines. In this context, the use of LLMs may come with various risks, such as the leakage of PII inadvertently entered by individuals and hostile attempts to generate malicious codes using LLMs. The LPDS proposed in this study effectively detects the unauthorized use of PII and malicious attacks. Its detection accuracy was 96.85%, with an average scan time of 0.42 seconds. Furthermore, the LPDS's PII detection effectively operates not only in English but also in Korea. Therefore, this system has a significant potential for use among Korean users as well.

The proposed system's application in LLM environments will significantly contribute to protecting against a range of malicious threats and attacks, such as using PII without consent or generating malicious codes using LLMs.

Acknowledgment

This work was supported by the Korea Institute of Energy Technology Evaluation and Planning (KETEP) and the Ministry of Trade, Industry & Energy (MOTIE) of the Republic of Korea (No. 20212020800120).

References

[1] "What's New in Artificial Intelligence from the 2023 Gartner Hype Cycle", Gartner. Accessed May 29, 2024. https://www.gartner.com/en/articles/what-s-new-in-artificial-intelligence-from-the-2023-gartner-hype-cycle.

[2] "ChatGPT Leaks Sensitive User Data, OpenAI Suspects Hack", Spiceworks. Accessed May 29, 2024. https://www.spiceworks.com/tech/artificial-intelligence/news/chatgpt-leaks-sensitive-user-data-openai-suspects-hack/.

[3] "TA547 Uses an LLM-Generated Dropper to Infect German Orgs", DarkReading. Accessed May 29, 2024. https://www.darkreading.com/threat-intelligence/ta547-uses-llm-generated-dropper-infect-german-orgs.

Authorized licensed use limited to: Arizona State University. Downloaded on February 01,2026 at 20:58:46 UTC from IEEE Xplore. Restrictions apply.

[4] "What is a large language model (LLM) ?", CloudFlare. Accessed May 29, 2024. https://www.cloudflare.com/learning/ai/what-is-large-language-model/

[5] "Prompt Injection", Nightfall AI. Accessed May 29, 2024. https://www.nightfall.ai/ai-security-101/prompt-injection.

[6] Zhang, Y., & Ippolito, D. (2023). Prompts should not be seen as secrets: Systematically measuring prompt extraction attack success. arXiv preprint arXiv:2307.06865.

[7] Xu, L., Chen, Y., Cui, G., Gao, H., & Liu, Z. (2022). Exploring the universal vulnerability of prompt-based learning paradigm. arXiv preprint arXiv:2204.05239.

[8] Xue, J., Liu, Y., Zheng, M., Hua, T., Shen, Y., Boloni, L., & Lou, Q. (2023). TrojPrompt: A Black-box Trojan Attack on Pre-trained Language Models. arXiv preprint arXiv:2306.06815.

[9] Greshake, K., Abdelnabi, S., Mishra, S., Endres, C., Holz, T., & Fritz, M. (2023, November). Not what you've signed up for: Compromising real-world llm-integrated applications with indirect prompt injection. In Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security (pp. 79-90).

[10] Yao, H., Lou, J., & Qin, Z. (2024, April). Poisonprompt: Backdoor attack on prompt-based large language models. In ICASSP 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP) (pp. 7745-7749). IEEE.

[11] Sha, Z., & Zhang, Y. (2024). Prompt Stealing Attacks Against Large Language Models. arXiv preprint arXiv:2402.12959.

[12] Shi, Y., Li, P., Yin, C., Han, Z., Zhou, L., & Liu, Z. (2022, September). Promptattack: Prompt-based attack for language models via gradient search. In CCF International Conference on Natural Language Processing and Chinese Computing (pp. 682-693). Cham: Springer International Publishing.

[13] "ChatGPT", OpenAI. Accessed May 29, 2024. https://openai.com/chatgpt/.

[14] "OpenLLaMA", Github. Accessed May 29, 2024. https://github.com/openlm-research/open_llama

[15] "Vicuna: An Open-Source Chatbot Impressing GPT-4 with 90%* ChatGPT Quality", Lmsys Org. Accessed May 29, 2024. https://lmsys.org/blog/2023-03-30-vicuna/.

[16] "Alpaca: A Strong, Replicable Instruction-Following Model", Stanford CRFM. Accessed May 29, 2024. https://crfm.stanford.edu/2023/03/13/alpaca.html.

[17] Alon, G., & Kamfonas, M. (2023). Detecting language model attacks with perplexity. arXiv preprint arXiv:2308.14132.

[18] Bhatt, M., Chennabasappa, S., Nikolaidis, C., Wan, S., Evtimov, I., Gabi, D., ... & Saxe, J. (2023). Purple llama cyberseceval: A secure coding benchmark for language models. arXiv preprint arXiv:2312.04724.

[19] "prompt_injection_cleaned_dataset-v2", Huggingface. Accessed May 29, 2024. https://huggingface.co/datasets/imoxto/prompt_injection_cleaned_dataset-v2

[20] "sharegpt_deepl_ko", Huggingface. Accessed May 29, 2024. https://huggingface.co/datasets/junelee/sharegpt_deepl_ko

[21] "URLhaus", abuse.ch. Accessed May 29, 2024. https://urlhaus.abuse.ch/

[22] "VirusTotal", VirusTotal. Accessed May 29, 2024. https://virustotal.com/

[23] "ShareGPT", ShareGPT. Accessed May 29, 2024. https://sharegpt.com/

[24] "chainlit", Github. Accessed May 29, 2024. https://github.com/Chainlit/chainlit

[25] "dolphin-mistral", ollam. Accessed May 29, 2024. https://ollama.com/library/dolphin-mistral:7b

Authorized licensed use limited to: Arizona State University. Downloaded on February 01,2026 at 20:58:46 UTC from IEEE Xplore. Restrictions apply.