Enhancing Security in Large Language Models: A Comprehensive Review of Prompt Injection Attacks and Defenses

Eleena Mathew[1]

[1]Affiliation not available

October 21, 2024

Abstract

This review paper explores advanced methods to prompt Large Language Models (LLMs) into generating objectionable or unintended behaviors through adversarial prompt injection attacks. We examine a series of novel projects like HOUYI, Robustly Aligned LLM (RA-LLM), StruQ, and Virtual Prompt Injection, that compel LLMs to produce affirmative responses to harmful queries. Additionally, the paper investigates the robustness of these attacks across different models and prompts. Several new benchmarks, such as PromptBench, AdvBench, AttackEval, INJECAGENT, and RobustnessSuite, have been created to evaluate the overall performance and resilience of LLMs against adversarial prompt injection attacks. Results show significant success rates in misleading models like Vicuna-7B, Llama-2-7B-Chat, GPT-3.5, and GPT-4. The review highlights limitations in existing defense mechanisms and proposes future directions for enhancing LLM alignment and safety mechanisms such as LLM SELF DEFENSE, Unlike previous studies, this paper provides a more comprehensive evaluation by integrating a broader range of attack methods and target models. Our study shows that there is a need for improved robustness in LLMs, which will potentially shape the future of AI-driven applications and security protocols.

Posted on 21 Oct 2024 — CC-BY 4.0 — https://doi.org/10.36227/techrxiv.172954263.32914470/v1 — e-Prints posted on TechRxiv are preliminary reports that are not peer reviewed. They should not b...

ENHANCING SECURITY IN LARGE LANGUAGE MODELS: A COMPREHENSIVE REVIEW OF PROMPT INJECTION ATTACKS AND DEFENSES

A PREPRINT

Eleena Sarah Mathew
Department of Computer Science and Engineering
Motilal Nehru National Institute of Technology, Allahabad, India
eleena.20214535@mnnit.ac.in

October 15, 2024

ABSTRACT

This review paper explores advanced methods to prompt Large Language Models (LLMs) into generating objectionable or unintended behaviors through adversarial prompt injection attacks. We examine a series of novel projects like HOUYI, Robustly Aligned LLM (RA-LLM), StruQ, and Virtual Prompt Injection, that compel LLMs to produce affirmative responses to harmful queries. Additionally, the paper investigates the robustness of these attacks across different models and prompts. Several new benchmarks, such as PromptBench, AdvBench, AttackEval, INJECAGENT, and RobustnessSuite, have been created to evaluate the overall performance and resilience of LLMs against adversarial prompt injection attacks. Results show significant success rates in misleading models like Vicuna-7B, Llama-2-7B-Chat, GPT-3.5, and GPT-4. The review highlights limitations in existing defense mechanisms and proposes future directions for enhancing LLM alignment and safety mechanisms such as LLM SELF DEFENSE, Unlike previous studies, this paper provides a more comprehensive evaluation by integrating a broader range of attack methods and target models. Our study shows that there is a need for improved robustness in LLMs, which will potentially shape the future of AI-driven applications and security protocols.

Keywords Natural language processing · Prompt Injection · ChatGPT · Large language models (LLMs) · Adversarial exploitation · Jailbreak · Sensitive data leakage

1 Paper Story

1.1 Introduction

Large language models (LLMs) Floridi and Chiriatti [2020], Zhang and Li [2021], Yao et al. [2024], Liu et al. [2023a], Hou et al. [2024] are recent developments that transformed natural language processing by allowing machines to create and interpret human-like text. As an essential component of applications such as chatbots, virtual assistants, and content generation, LLMs have been associated with high security risks, especially in terms of adversarial attacks Yin et al. [2023], Zou et al. [2023a], Goyal et al. [2023]. Among them, prompt injection attack receives particularly attention since it aims to introduced crafted data into the LLM to malcontrol the outputs and behaviors Wei et al. [2023], Mozes et al. [2023]. In this paper, several forms of adversary schemes and countermeasures are discussed, which demonstrate that the warfare between model resistance and adversaries is far from over.

Prompt injection Perez and Ribeiro [2022] attack takes advantage of the nature of the flexible structural design of applications that have integrated LLMs into their systems; in particularly, it enables the authorisation of malicious users to change the instruction of LLMs Zou et al. [2023a], Liu et al. [2024a]. OWASP(Open Worldwide Application Security Project) has recently listed this type of attack as the top LLM-related hazard.Usually, prompt injection is achieved by joining instructions and data, and it becomes very challenging for the underlying engine to do so. This can result to



Figure 1: Direct Prompt Injection



Figure 2: Indirect Prompt Injection

having the sensitive information and other restricted areas exposed and unlocked rendering the security of the whole application compromised Yan et al. [2024a], Phute et al. [2024], Qi et al. [2023].

Prompt injection attacks can be direct, where the attacker influences the LLM's input directly, or indirect, involving a "poisoned" data source affecting the LLM Rossi et al. [2024], Hines et al. [2024], Shi et al. [2024]. This paper will explain various LLM jailbreaking approaches under these categories and discuss possible defenses.

In response to the growing threat, researchers have developed prevention-based and detection-based defenses Chan et al. [2024]. Prevention-based defenses aim to prevent an attacker from injecting malicious prompts, while detection-based defenses focus on identifying and mitigating the effects of an attack. Examples include paraphrasing, retokenization, data prompt isolation, proactive detection, windowed perplexity (PPL) detection, and LLM-based detection Liu et al. [2023b], Bhardwaj and Poria [2023].

Despite these developments, prompt injection attacks remain a significant concern due to the evolving tactics of attackers and the increasing complexity of LLMs, which create new vulnerabilities. Ongoing research and development of effective defenses are essential to ensure the security and integrity of LLMs in various applications Li et al. [2023], Kumar et al. [2024]. This literature review provides a comprehensive overview of current knowledge on prompt injection attacks and defenses in LLMs, highlighting key findings, challenges, and future directions and benchmarks Chan et al. [2023] in this area.

2 Attacks

Large language models (LLMs) like ChatGPT, Bard, and Claude are fine-tuned to avoid producing harmful content. While "jailbreaks"—special queries inducing unintended responses—require manual design and can be patched, such behavior may be difficult to patch permanently. Similar adversarial attacks in computer vision have been challenging to address for a decade, suggesting these threats might be an inherent risk of deep learning models.

We demonstrate that adversarial attacks, involving specific sequences of characters appended to user queries, can be automatically generated to cause LLMs to produce harmful content. These automated attacks are effective on open-source LLMs and also transfer to closed-source chatbots like ChatGPT, Bard, and Claude. This raises significant safety concerns as these models are increasingly used autonomously. Zou et al. [2023b]

2.1 HouYi Liu et al. [2024b]

HOUYI is a black-box prompt injection attack inspired by traditional web injection techniques. HouYi uses three components to form the injected prompt.

1. Framework Component: Makes the malicious injection blend seamlessly with the application's natural flow. It helps bypass detection mechanisms that only allow content to adhere to pre-set formats.

2. Separator Component: This component initiates a context separation between the pre-set prompts and user inputs. It draws a context separation, shifting the LLM's focus from pre-established context to new commands.

3. Disruptor Component: This component contains the actual attack, tailored to the adversary's objectives, and executes the malicious intent of the attack. It is crafted to extract sensitive information, manipulate LLM responses, or compromise security and privacy.

An example of this can be seen in Figure 3.

The methodology involves three phases: Context Inference, where the application's context and input-output relationships are understood; Payload Generation, where a prompt generation plan is developed; and Feedback, where the attack's effectiveness is evaluated and refined.

HOUYI was tested on 36 LLM-integrated applications, identifying 31 as vulnerable, and achieving an 86.1% success rate in launching attacks. The study categorizes attacks into Direct Injection, Escape Characters, and Context Ignoring.

Direct Injection: Here, the adversary directly appends a malicious command to the user's input. This additional command is designed to trick the LLM into performing actions unintended by the user. Escape Characters: In this method, the adversary injects escape characters, such as `"\n"` or `"\t"`. The effectiveness of this method comes from the fact that certain escape characters, due to their typical linguistic usage, can easily break the prompt's structure. Context Ignoring: This method involves injecting a malicious prompt designed to manipulate the LLM to ignore the preceding context and focus solely on the subsequent prompt . All target applications show vulnerabilities to all three types of prompt injection attacks. CHATPUBDATA and CHATBOTGENIUS are particularly vulnerable, with a consistent 5 out of 5 success rate in all attack types and queries. AIWITHUI shows slightly less vulnerability in Context Ignoring for Q1 (4 out of 5 success rate) but otherwise follows the pattern of being highly susceptible.

Results show that HOUYI can expose severe vulnerabilities as mentioned above, enabling arbitrary LLM usage and prompt theft. The toolkit developed from this methodology demonstrates a high success rate of 86.1%, suggesting a need for enhanced defenses against such attacks.



Figure 3: Example of prompt transformation in HouYi

2.2 StruQ Chen et al. [2024]

This study introduces structured queries to counter prompt injection attacks by separating prompts and data into distinct channels. The system supports structured queries through a novel fine-tuning strategy that converts a base LLM into a structured instruction-tuned model. This model follows instructions in the prompt portion of a query while ignoring instructions in the data portion, significantly improving resistance to prompt injection attacks with minimal impact on utility.

StruQ comprises two components:

1. **Front-end**: The front-end of the system encodes queries into a special format using a hard-coded template based on the Alpaca model, with slight adaptations to enhance security. Instead of using textual strings

like in Alpaca, modified special tokens are used: specifically, a reserved token `[MARK]` is used instead of "###" as used by Alpaca, three reserved tokens (`[INST]`, `[INPT]`, `[RESP]`) instead of the words in Alpaca's delimiters ("instruction", "input", and "response"), and `[COLN]` instead of the colon in Alpaca's delimiter. Specially reserved tokens are employed to delimit instructions and data, filtering out these tokens from user data to prevent spoofing by attackers (this can be seen in Figure 4). This method effectively defends against Completion attacks.

(ii) Specially trained LLM: A language model (LLM) is trained to accept inputs encoded in a special format using structured instruction tuning. Instruction tuning usually makes LLMs follow instructions wherever they appear in the input, which is not ideal for this particular use case. To address this, a variant that teaches the model is developed to follow instructions only in the prompt part of the input, not in the data part. The model is fine-tuned on samples with correctly placed instructions in the prompt and incorrectly placed instructions in the data, encouraging the model to respond only to correctly positioned instructions.

Figure 4: Example of prompt transformation in StruQ

StruQ was tested against eleven types of prompt injection attacks, showing strong security: it reduced the attack success rate to less than 2% for most techniques on Alpaca and Mistral models. However, it is not fully secure against TAP attacks, reducing their success rate from 97% to 9% on Alpaca and from 100% to 36% on Mistral.

2.3 Virtual Prompt Injection Yan et al. [2024b]

Virtual Prompt Injection (VPI) is a novel class of attacks that targets instruction-tuned LLMs. In a VPI attack, the model functions as if there is a 'virtual prompt' added to the user instruction in certain conditions making it easy for attackers to control the model without changing the input explicitly. By poisoning just 0. 0.1

The approach practiced by the attacker entails feeding the model's instruction-tuning dataset with a small portion of contaminated data. The poisoned data can be provided in the form of released datasets (containing poisoned data) or data annotation services. This comprises of gathering of trigger instructions, creation of poisoned responses as well as compilation of poisoned instruction tuning data. The model learns with a mixed data set in this case but the poisoning rate is kept small for the sake of stealth. Some are pre-processing where poor quality samples are removed by ChatGPT and post-processing of the generated samples entails debiasing prompting.

In Figure 5, example of VPI is shown showing 'cats' as the trigger scenario. Now, if the original prompt contains the word 'cats' in it as the trigger words, then the virtual prompt is introduced into the original prompt and gives a false output.

Experiments on Alpaca 7B showed that VPI significantly steers sentiment more effectively than explicit injection, with minimal impact on general instruction quality. VPI's success varied by topic, being easiest for OpenAI (6% to 72%) and hardest for abortion (10% to 32%). Data filtering effectively mitigated most attacks, but debiasing prompting was less effective, especially for sentiment steering. The study's VPI settings do not cover all possible scenarios, and the complexity of virtual prompts and trigger scenarios affects the attack's difficulty. The evaluation was limited to 7B and 13B models, with no systematic study of larger models. The current evaluation framework is also specific to certain attack goals, such as sentiment analysis and code injection.



Figure 5: Example of prompt transformation using virtual prompt injection

3 Defense

In order to mitigate prompt injection attacks in LLMs, some countermeasures have also been invented. They include enhanced alignment check that affirms strict non-compliance with the prompts that are malicious in nature, second LLMs where dangerous content is screened and filtered, dynamic approaches which are totally resistant to advanced adversarial input and the defense-in-defense structure that provides an overall assessment and threat containment. Still, such measures go a long way to improving the robustness of LLMs, to guarantee safer and more dependable applications of artificial intelligence.

3.1 Signed-Prompt Suo [2024]

Signed-Prompt is the defense strategy that can be employed to counter the issue of prompt injection attacks on LLMs in integrated applications. To counter this vulnerability, Signed-Prompt proposes a signature of point-sensitive instructions from the origination point of authorized users/agents. These instructions are encoded with specific character sequences that are not like natural languages, so the LLM can check the legitimacy of the instructions.

The Signed-Prompt approach requires two key components: an Encoder to append the signature on the instructions and an LLM that can identify and execute signed instructions. The Encoder also adds a new segment containing signed commands, which were signed by the Encoder only. The LLM is then shifted to distinguish between unsigned and signed instructions so that only signed instructions are performed as it is illustrated in the figure 6 below. Possible ways of using the Encoder are presented with Traditional Character Replacement (TCR), fine-tuning Language Model Languages, and Prompt Engineering with general-purpose LLMs. Although TCR is not flexible and fine-tuning is costly, the paper concentrates on prompt engineering method introduced by ChatGPT-4 from OpenAI for the demonstration.

The analysis shows that LLMs built using either prompt engineering or fine-tuning exhibit strong resilience against various prompt injection attacks, with a 0% attack success rate across four tested groups: directness, multilingual, varied expressions, and implication where Direct: This group consists of straightforward, explicit commands in English, Multilingual: Commands in this group are provided in multiple languages, Varied Expressions: This group includes English commands that ask for a certain action but use varied expressions or synonyms for the action, Implication: Commands in this group imply the action of file deletion without explicitly stating it. However, the correctness of responses from the fine-tuned LLMs was inconsistent across these groups, indicating some limitations in performance.

3.2 RA-LLM (Robustly Aligned LLM) Phute et al. [2024]

Robustly Aligned LLM (RA-LLM) is introduced to defend against potential alignment-breaking attacks. RA-LLM can be directly constructed upon an existing aligned LLM with a robust alignment checking function, without requiring any expensive retraining or fine-tuning process of the original LLM.

Figure 6: Example of prompt transformation using signed-prompt

A request is deemed benign if it can pass the alignment check method AC(.) in most circumstances, even if a section of the request is randomly removed. The robust Alignment Check function RAC(.) is defined based on the aligned LLM f(·) and the alignment check function AC(.)

$$RAC(\mathbf{x}) = \begin{cases} \text{Fail}, & \text{if } AC(f(\mathbf{x})) = \text{Fail} \\ \text{Fail}, & \text{if } \mathbb{P}_{r \sim U(p)}(AC(f([\mathbf{x}]_r)) = \text{Fail}) > t \\ \text{Pass}, & \text{otherwise} \end{cases} \tag{1}$$

Where U(p) refers to the distribution of potential masks following the uniform dropping of the p which is the proportion of indices to be dropped from the input (without replacement), /[x]r indicates the kept indices r inside x following the dropping operation, It represents the subset of x that remains after dropping p proportion of its tokens. and r refers to the uniformly sampled indices mask to indicate kept tokens, it is used to select which tokens in x are retained.

This method counters adversarial prompts that are sensitive to minor changes, using the LLM's inherent alignment capabilities without external detectors. Monte Carlo sampling approximates the probability of all possible random droppings, with a small threshold t. In Figures 7 and 8 an example of this is illustrated, where a potentially benign and malicious prompt is passed through the RALLM model. The benign prompt consistently passes the RAC(.) function, whereas the malicious one fails.

Evaluations on AdvBench and MS MARCO datasets showed that RA-LLM significantly reduces attack success rates (ASR) and maintains benign answering rates (BAR). Against Individual and Transfer Attacks on Vicuna-7B-v1.3-HF and Guanaco-7B-HF models, RA-LLM reduced ASR from up to 98.7% to around 10%. Similarly, handcrafted jailbreak prompts saw ASR drop from as high as 98.4% to about 10% or less with RA-LLM. The dropping ratio p influences performance: higher p reduces ASR but may lower benign accuracy, while lower p maintains benign accuracy but lessens robust alignment efficacy.

3.3 LLM SELF DEFENSE Phute et al. [2024]

LLM SELF DEFENSE, a simple approach to defend against these attacks by having an LLM screen the induced responses by incorporating the generated content into a pre-defined prompt and employing another instance of an LLM to analyze the text and predict whether it is harmful.

In this defense pipeline, a user provides a potentially malicious text prompt T_{in}. An LLM, referred to as LLM_{gem}, processes T_{in} and generates potentially harmful text T_{resp}. This can be expressed as:

$$\text{LLM}_{\text{gem}}(T_{\text{in}}) = T_{\text{resp}}$$

To classify harmful content, another LLM, $\text{LLM}_{\text{filter}}$, is employed. The $\text{LLM}_{\text{filter}}$ can be the same type of LLM used in LLM_{gem}. The process begins with $\text{LLM}_{\text{filter}}$ being given a prompt: "Does the following text contain harmful content:



Figure 7: Example of benign prompt transformation in RA-LLM

T_{resp}? Respond with 'Yes, this is harmful' or 'No, this is not harmful'." The $\text{LLM}_{\text{filter}}$ then reads T_{resp} and generates a response indicating whether the content is harmful. This method has proven to be highly effective at filtering out virtually all harmful LLM-generated content.

GPT 3.5 has been found to perform well at classifying harmful content. GPT 3.5 reaches a 98% accuracy. Llama 2 has a lower performance of 77%. It has also been discovered that instructing an LLM to determine whether an induced response constitutes harm after the LLM has already processed the text is more effective at distinguishing between harmful and benign responses and has significantly improved the accuracy of GPT 3.5 to 99% and that of LLaMA 2 to 94.6%.

3.4 Defense Against Persuasive Adversarial Prompts (PAP) for LLMs Zeng et al. [2024]

This research targets to transform the understanding of how to counter immediate injection attacks through persuasive adversarial prompts (PAP) from a taxonomy of 40 persuasive techniques adopted from social science disciplines. The PAPs are generated automatically to jailbreak the LLMs thereby increasing the chance of success in an attack. The experiment entails training a Paraphrasing Machine known as the Persuasive Paraphraser and then using the agent to parse PAPs. Further exploration of three adaptive defenses is done using Mutation and Detection tactics.

Adaptive System Prompt (Adapt Sys.): Instruct the LLM to resist persuasion. Base Summarizer (Base Smry.): Summarizes adversarial prompts to extract the core query before execution. Tuned Summarizer (Tuned Smry.): Fine-tunes a summarizer with pairs of harmful queries and their corresponding PAPs. PAPs achieve high attack success rates (>92%) across Llama 2-7b Chat, GPT-3.5, and GPT-4. Adaptive System Prompts improve resilience, often surpassing baseline defenses. Base and tuned summarizers effectively neutralize PAPs, with the Tuned Summarizer reducing the attack success rate from 92% to 2% on GPT-4 and from 86% to 0% on GPT-3.5.

3.5 GUARDIAN (Guardrails for Upholding Ethics in Language Models) Rai et al. [2024]

To safeguard LLMs from adversarial prompt attacks, GUARDIAN provides a robust multi-tier defense framework.

A set of prompts sufficiently extensive to put pressure on all possible lines of defense of the LLM is constructed, which helps in the purpose of adversarial training. The process includes the build up of a wide range of the prompts, including



Figure 8: Example of malicious prompt transformation in RA-LLM

the identified successful attack patterns and the new ones intended to test the weak points of the system. This dataset is useful for each testing phase to give the most thorough examination of the robustness of each layer.

Filter 1: System Prompt Layer Analysis This stage evaluates the capability of the system prompt layer in identifying and managing input prompts which are either harmful or unethical. This is done using Data Collection, Testing these prompts to test the system's capability in identifying and eradicating possibly faulty threats in the first layer, and Metrics that defines the filter's blocking efficiency.

Filter 2: Custom Fine-Tuned Layer Evaluation The goal here is to use a fine-tuned classification Large Language Model (LLM) that is specific to the given dataset and improve the detection of risky information within the user's queries. These queries may have probably escaped the initial pre-processing filter mechanism of this system. Moreover, an Ethical Prompt Auto-Suggestion automatically provides morally appropriate options if a user inputs an unethical question. The procedure consists in obtaining and pre-processing the Toxic Comment Classification Dataset from Google Jigsaw and updating the "bert-base-uncased" model to a model suitable for classification tasks. An ethical prompt set which is customized based on the ethical issue is constructed using the Zephyr-7B-α LLM model to fine-tune the prompt generator. Both of these models are evaluated using training loss and accuracy with preference to specificity in light of the unique nature of the datasets employed.

Filter 3: Pre-Display Filter Validation This stage verifies the efficacy of the pre-display filter, which employs another LLM to ensure the ethicality of generated outputs. The procedure involves integrating a secondary LLM to examine outputs for ethical compliance, followed by testing with a range of outputs, including those from prompts that failed to get blocked by the previous layers. The focus is on the accuracy of the ethical filter in identifying unethical content, ensuring that the final output adheres to ethical standards.

This stage confirms the performance of pre-display filter where another LLM is used to guarantee the ethicality of the generated outputs. This procedure include linking a secondary LLM to review outputs for tainted contents, and sampling with a variety of outputs, including from prompts that the prior layers did not block. It is therefore on the accuracy of the ethical filter to give a perfect indication of the kind of content that may be unethical in order to meet the expected output in terms of ethical behavior.

The llama-2 model demonstrates the capability to block 100% of attack prompts.

4 Benchmarks

Benchmarking is one of the tools for evaluation of LLMs especially in view of their susceptibility to prompt injection attacks. They offer tests that are aimed at evaluating different features of the LLM performance potential, including natural language comprehension, generation, and even reasoning and tolerance to different tasks. Established benchmarks such as AdvBench and MS MARCO provide detailed findings on model capabilities and limitations so that researchers and developers can focus on potential improvements. These benchmarks are operational and replicate real-life situations and the set of tasks can range from answering questions to reasoning. The information arriving from these evaluations is vital for assembling superior models which would be more resilient and effective. Furthermore, benchmarking has a critical relevance in promoting transparency and accountability for the AI models in comparison with related new models as well as providing impetus for the improvement of the AI research field.

4.1 PromptBench Zhu et al. [2023]

PromptBench is a project made to measure LLMs' resilience to adversarial prompts. Four different prompts were studied, Zero shot - Task-oriented, Role oriented and Few shot- Task oriented, Role oriented. 7 different attacks were also studied (TextBugger, DeepWordBug, TextFooler, BertAttack, CheckList, StressTest, Semantic). Performance was measured using a unified metric called Performance Drop Rate (PDR). It quantifies the relative performance decline following a prompt attack, offering a contextually normalized measure for comparing different attacks, datasets, and models. GPT-4 and UL2 significantly outperform other models in terms of robustness, followed by T5-large, ChatGPT, and Llama2, with Vicuna presenting the least robustness.

$$PDR(A, P, f_\Theta, D) = 1 - \frac{\sum_{(x,y)\in D} M\left[f_\Theta([A(P), x]), y\right]}{\sum_{(x,y)\in D} M\left[f_\Theta([P, x]), y\right]} \tag{2}$$

where A is the adversarial attack applied to the original prompt (P), P is The original, non-attacked prompt, f_Θ is the language model being evaluated and D is the dataset used for testing. M[ ]: The evaluation function, which checks how well the model performs: For classification tasks (e.g., identifying if a text is positive or negative), it is 1 if the model's answer is correct, and 0 if it's wrong. For reading comprehension tasks, it's the F1-score (a measure of accuracy). For translation tasks, it's the BLEU score (how good the translation is). Papineni et al. [2002]

4.2 INJECAGENT: Benchmark for Assessing LLM Agent Vulnerabilities to IPI Attacks Zhan et al. [2024]

INJECAGENT assesses an LLM Agent (L) armed with tools (T) in terms of susceptibility to IPI attacks that inject code to corrupt L or enable other undesirable actions like causing monetary loss and data leakage. The methodology involves:

User Case Generation: The initial step is to identify tools that integrate external content in their responses to the LLM agent, specifically those where the external content is susceptible to modification by attackers. For each candidate tool Tu, GPT-4 was used to generate a specific user case, which consists of Tool Identification: Identify tools integrating external content vulnerable to attacker modification.

User Cases: For each tool T_{in}, generate user cases including: User Tool (T_{u}): Candidate tool requiring external content. User Instruction (I_{u}): Directive for LLM to use Tu. Tool Parameters: Necessary parameters adhering to Tu's format. Tool Response Template: Template response with an "Attacker Instruction" placeholder for real-world modification. Manual Labeling: Ensure accuracy, resulting in 17 user cases. Attacker Case Generation:

Attack Categories: 30 direct harm and 32 data-stealing attacks.

Tool Selection: Randomly select tools for direct harm or data extraction.

Instruction Generation: Generate attacker instructions (Ia) using selected tools.

Manual Revision: Refine instructions to include necessary parameters for tool execution, ensuring realistic attack scenarios.

Categorization: Further categorize attacks by secondary intentions (e.g., financial, physical). Test Case Synthesis: Base Setting: Combine user and attacker cases, replacing the placeholder with Ia. Enhanced Setting: Use a predefined prompt to reinforce Ia, aiming for higher attack success rates. Results Evaluation reveals significant vulnerabilities in LLM agents:

Attack Success Rates (ASR): ReAct-prompted GPT-4 shows ASRs of 23.6% (base) and 47.0% (enhanced). Llama2-70B exceeds 80% ASR in both settings. Resilience of Fine-Tuned Models: Fine-tuned GPT-4 and GPT-3.5 exhibit lower ASRs of 3.8% and 6.6% respectively. Impact of Enhanced Settings: Hacking prompts significantly increase ASRs across most models. Test Case Evaluation The evaluation process assumes the LLM agent can execute the user tool (Tu) and receive the response (RTu):

Direct Harm Attacks: Success is marked by the agent executing the harmful tool (Ta). Data Stealing Attacks: Success involves the agent using the data extraction tool (Ta) and transmitting data to the attacker. Conclusion

INJECAGENT provides a systematic framework for evaluating LLM agents' security against IPI attacks, guiding the development of robust defenses to protect against malicious manipulations. The benchmark's comprehensive approach underscores the need for enhanced security measures in LLM applications.

4.3 BIPIA (the benchmark for indirect prompt injection attacks)

BIPIA was created to evaluate the risk of indirect prompt injection attacks, it analyzes attack success causes and develops effective black-box and white-box defense methods, significantly reducing attack success rates. BIPIA covers 250 attacker goals and five application situations.

A set of carefully chosen representative question-answering (QA) and summarization tasks, including email QA, web QA, table QA, summarization, and code QA. To effectively evaluate a range of real-world attack scenarios, 30 types of representative text attacks were designed for text tasks (email QA, web QA, table QA, and summarization) and 20 types of code attacks for the code task (code QA), each with five specific malicious instructions. 15 types of text attacks were randomly split and 10 types of code attacks were used for training, with the remainder used for testing.

The impact of different positions of malicious instructions was investigated within external content—beginning, middle, and end—on the Attack Success Rate (ASR). The process involves injecting a malicious instruction into a task-specific external content sample at one of the three positions. A prompt template is merged with user instructions, and the modified external content is used to generate the prompts for our training and testing datasets. The total number of prompts is determined by multiplying the number of external content variations by the number of malicious instructions and the number of positions.

Comparing several of the most used open-source and closed-source LLMs it could be concluded that they were all susceptible to indirect prompt injection attack for most of the application tasks. Research shows that both GPT-4 and GPT-3.5 fall victim of such attacks, hence the importance of countermeasures. It was found that the performances in Chatbot Arena as measured by Elo ratings were positively related to ASRs on text tasks but no systematic trend was observed for code tasks due to differences in the model's approach to code generation. Also, ASRs for summarization tasks were higher than for table QA, email QA, and web QA due to the variation in prompt templates. Task-relevant and targeted text attacks were more successful than non-targeted attacks because models prioritized the text information related to the task at hand.

4.4 Results and Discussion

We summarize important results from the recent literature on the effectiveness of different defenses. Notably, at present, we're seeing that models has yielded reduced attack success rates (regardless of target functionality), as well as maintained operational integrity under adversarial conditions — demonstrating considerable progress on LLM security.

We evaluated a variety of defense mechanisms against prompt injection attacks and found them not only somewhat successful but also fairly limited in scope. HOUYI was tested on LLM-integrated applications—36 were tested and 31 were identified as vulnerable (an attack success rate of 86.1%), suggesting more robust defenses are necessary in the near future. StruQ, tested against eleven types of prompt injection attacks, showed robust security by reducing attack success rates to less than 2% for most techniques on Alpaca and Mistral models, although it struggled against TAP attacks, reducing their success rate to 9% on Alpaca and 36% on Mistral. RA-LLM reduced attack success rates from up to 98.7% to around 10% for individual and transfer attacks on Vicuna-7B-v1.3-HF and Guanaco-7B-HF models. Additionally, adaptive system prompts and tuned summarizers demonstrated high efficacy, with the tuned summarizer reducing attack success rates to 2% on GPT-4 and 0% on GPT-3.5.

In certain experiments, VPI worked well indicating effective steering of sentiment especially OpenAI, which displayed varying success rates based on topic. LLM SELF-DEFENSE also led to improved accuracy in classifying harmful content of GPT-3.5 and LLaMA 2 with 99% and 94.6% respectively. Another defense-based approach Guardian also successfully mitigated all the attack prompts on the LLaMA 2 model which showed its capacity to uphold ethical standards in language models.

HouYi	Signed-prompt	Robustly Aligned LLM (RA-LLM)	StruQ	Virtual Prompt Injection
Across 36 LLM-integrated applications, a high success rate of 86.1% is observed.	LLMs constructed from ChatGPT-4 and ChatGLM-6B demonstrate remarkable stability against the attack samples from the four groups: Direct, Multilingualism, Varying Expressions, and implications. Achieves an attack success rate of 0%.	RA-LLM reduced Individual Attack: In Vicuna-7B-chat-HF by reducing BAR rates from 99.3% to 98.7% and ASR rates from 98.7% to 10.7%. In Guanaco-7B-HF, BAR rates reduced from 95.3% to 92.0% and ASR rates from 96% to 6.7%. Transfer Attack tested reduced BAR rates in Vicuna-7B-chat-HF from 99.3% to 98.7% and ASR from 83.3% to 11.3%. In Guanaco-7B-HF, BAR rates reduced from 95.3% to 92.0% and ASR reduced from 78.7% to 8.7%.	StruQ decreases the attack success rate of TAP from 97% to 9% on Alpaca, and from 100% to 36% on Mistral.	1. Alpaca 7B (Explicit Injection) No Injection: Pass@1: 9.8%, Occurrence: 0.0% Clean Explicit Injection: Pass@1: 10.4%, Occurrence: 3.7% w/ AutoPoison: Pass@1: 8.5%, Occurrence: 0.0% w/ VPI (ours): Pass@1: 12.8%, Occurrence: 39.6% 2. text-DaVinci-003 (Explicit Injection) No Injection: Pass@1: 62.8%, Occurrence: 0.0% Explicit Injection: Pass@1: 61.6%, Occurrence: 95.7%

Table 1: Summary of Results

Despite such successes, some limitations and literature recommendations were found. Currently, StruQ is only capable of defending programmatic applications, which makes it vulnerable against web-based chatbots. It is shown that VPI settings do not address all the possible cases, and the evaluation was performed only for 7B and 13B models without considering other sizes. Further, virtual prompts and trigger scenarios make up the complexity throughout the planning and execution of an attack. It also suggests the importance of stronger protective measures against IPI (Indirect Prompt Injection) attacks, especially for highly capable LLMs connected with various tools. Finally, future research directions include the creation of a comprehensive evaluation dataset to compare the effectiveness of VPI across different studies, the enhancement of simulations against one of the proposed attacks, namely the Completion attack and the TAP-generated attack, and scalability on the larger-scale model variants. In LLM SELF-DEFENSE, using concrete examples of harm, context-based learning, and logit biasing may provide extra layers of protection against such attacks.

It is crucial to note that benchmarks also have a significant responsibility in knowing and enhancing LLM security. PromptBench assesses LLM resilience against numerous types of adversarial prompts and attacks, defining measures such as Performance Drop Rate (PDR) to compare models. The proposed INJECAGENT approach identify the susceptibility of LLM agents to IPI attacks, with reference to realistic attack vectors that inflict financial loss and data theft. BIPIA extends the analysis to indirect attacks, and shown many models are vulnerable in different application tasks. These assist in establishment of benchmarks that offer important information on specific areas of weakness and inform the enhancement of other better LLMs.

The importance of these benchmarks is that they can be used to quantitatively compare and analyze the level of defense in LLMs and to encourage the development of new improved approaches to AI security. It helps reveal the deficits, encourage creativity in protective algorithms and enhance confidence in artificial intelligence.

Indeed, prompt injection attacks are a very serious threat, however, the creation of progressively sophisticated protection measures and the constant search for universal standards is crucial. Through the regular reassessing and improving of the LLM security, the AI community can guarantee that valuable and important models can be widely implemented whilst avoiding or preventing malicious manipulations.

5 Conclusion

This review describes the larger effect of Injection Attacks on Large Language Models, especially the prompt injection attack, and also cautions future researchers to come up with strong defenses and a range of benchmarks for the attack. While RA-LLM is proven effective, it has not been tested with better attacks. The future of LLM security should include more thorough red teeming as well as better alignment strategies especially before the release of open source models Huang et al. [2023].

Further directions for research are the extension of such types of attacks to a broader class of models, including multi-modal ones, and the further refinement of the possible harm in textual content generated by the models. The analysis of the optimization-based attack strategies and the corresponding remedies is timely, considering that even contemporary applications, interfaced with LLMs, continue struggling with full-scale recovery from the detected attacks.

Secondly, the nature and the interactive and timely characteristic of LLMs also complicates the evaluation of the effectiveness of these attacks and a more adequate method of testing is needed. The problems with the believability of the post-produced content and the problems with intention to deceive seem to be lurking in the background of each new step that can be made in the use of advanced LLMs.

However, for parameterizing and for 'whitewashing' the corresponding inputs, more elaborate and sophisticated techniques should be used and, when it comes to such issues as filtering between the safe application's calls and such potentially hostile instructions and/or conditions as allowed for by the LLMs, further work is needed. It is also important to recon or remodel the benchmarks to fit new techniques and newer threats in the field. In addition, more concern should be paid to the primary utilized defense of frameworks like Signed-Prompt method in realizations. In changing nature of cybersecurity threats these methods should be applied to new trends of attacks and combined with other elements of security measures, for example, behavior analysis and anomalies detection.

Lastly, it should generalize the attacks to several settings and model scales and pay more attention to methods like virtual prompt injection (VPI). Getting a broader perspective of the virtual prompts and trigger scenarios, and creating a single framework to assess the effectiveness of the attack will be inevitable in the enhancement of security and solidity of LLMs in defeating the prompt injection attacks.

References

Luciano Floridi and Massimo Chiriatti. Gpt-3: Its nature, scope, limits, and consequences. *Minds and Machines*, 30 (4):681–694, Dec 2020. ISSN 1572-8641. doi:10.1007/s11023-020-09548-1. URL `https://doi.org/10.1007/s11023-020-09548-1`.

Min Zhang and Juntao Li. A commentary of gpt-3 in mit technology review 2021. *Fundamental Research*, 1(6):831–833, 2021. ISSN 2667-3258. doi:https://doi.org/10.1016/j.fmre.2021.11.011. URL `https://www.sciencedirect.com/science/article/pii/S2667325821002193`.

Yifan Yao, Jinhao Duan, Kaidi Xu, Yuanfang Cai, Zhibo Sun, and Yue Zhang. A survey on large language model (llm) security and privacy: The good, the bad, and the ugly. *High-Confidence Computing*, 4(2):100211, June 2024. ISSN 2667-2952. doi:10.1016/j.hcc.2024.100211. URL `http://dx.doi.org/10.1016/j.hcc.2024.100211`.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, Minlie Huang, Yuxiao Dong, and Jie Tang. Agentbench: Evaluating llms as agents, 2023a.

Xinyi Hou, Yanjie Zhao, Yue Liu, Zhou Yang, Kailong Wang, Li Li, Xiapu Luo, David Lo, John Grundy, and Haoyu Wang. Large language models for software engineering: A systematic literature review, 2024.

Zi Yin, Wei Ding, and Jia Liu. Alignment is not sufficient to prevent large language models from generating harmful information: A psychoanalytic perspective, 2023.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models, 2023a.

Shreya Goyal, Sumanth Doddapaneni, Mitesh M. Khapra, and Balaraman Ravindran. A survey of adversarial defences and robustness in nlp, 2023.

Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. Jailbroken: How does llm safety training fail?, 2023.

Maximilian Mozes, Xuanli He, Bennett Kleinberg, and Lewis D. Griffin. Use of llms for illicit purposes: Threats, prevention measures, and vulnerabilities, 2023.

Fábio Perez and Ian Ribeiro. Ignore previous prompt: Attack techniques for language models, 2022.

Yi Liu, Gelei Deng, Zhengzi Xu, Yuekang Li, Yaowen Zheng, Ying Zhang, Lida Zhao, Tianwei Zhang, Kailong Wang, and Yang Liu. Jailbreaking chatgpt via prompt engineering: An empirical study, 2024a.

Biwei Yan, Kun Li, Minghui Xu, Yueyan Dong, Yue Zhang, Zhaochun Ren, and Xiuzhen Cheng. On protecting the data privacy of large language models (llms): A survey, 03 2024a.

Mansi Phute, Alec Helbling, Matthew Hull, ShengYun Peng, Sebastian Szyller, Cory Cornelius, and Duen Horng Chau. Llm self defense: By self examination, llms know they are being tricked, 2024.

Xiangyu Qi, Yi Zeng, Tinghao Xie, Pin-Yu Chen, Ruoxi Jia, Prateek Mittal, and Peter Henderson. Fine-tuning aligned language models compromises safety, even when users do not intend to!, 2023.

Sippo Rossi, Alisia Marianne Michel, Raghava Rao Mukkamala, and Jason Bennett Thatcher. An early categorization of prompt injection attacks on large language models, 2024.

Keegan Hines, Gary Lopez, Matthew Hall, Federico Zarfati, Yonatan Zunger, and Emre Kiciman. Defending against indirect prompt injection attacks with spotlighting, 2024.

Jiawen Shi, Zenghui Yuan, Yinuo Liu, Yue Huang, Pan Zhou, Lichao Sun, and Neil Zhenqiang Gong. Optimization-based prompt injection attack to llm-as-a-judge, 2024.

Chun Fai Chan, Daniel Wankit Yip, and Aysan Esmradi. Detection and defense against prominent attacks on preconditioned llm-integrated virtual assistants, 2024.

Yupei Liu, Yuqi Jia, Runpeng Geng, Jinyuan Jia, and Neil Zhenqiang Gong. Prompt injection attacks and defenses in llm-integrated applications, 2023b.

Rishabh Bhardwaj and Soujanya Poria. Red-teaming large language models using chain of utterances for safety-alignment, 2023.

Haoran Li, Yulin Chen, Jinglong Luo, Yan Kang, Xiaojin Zhang, Qi Hu, Chunkit Chan, and Yangqiu Song. Privacy in large language models: Attacks, defenses and future directions, 2023.

Aounon Kumar, Chirag Agarwal, Suraj Srinivas, Aaron Jiaxun Li, Soheil Feizi, and Himabindu Lakkaraju. Certifying llm safety against adversarial prompting, 2024.

Chi-Min Chan, Weize Chen, Yusheng Su, Jianxuan Yu, Wei Xue, Shanghang Zhang, Jie Fu, and Zhiyuan Liu. Chateval: Towards better llm-based evaluators through multi-agent debate, 2023.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models, 2023b. URL `https://arxiv.org/abs/2307.15043`.

Yi Liu, Gelei Deng, Yuekang Li, Kailong Wang, Zihao Wang, Xiaofeng Wang, Tianwei Zhang, Yepang Liu, Haoyu Wang, Yan Zheng, and Yang Liu. Prompt injection attack against llm-integrated applications, 2024b.

Sizhe Chen, Julien Piet, Chawin Sitawarin, and David Wagner. Struq: Defending against prompt injection with structured queries, 2024.

Jun Yan, Vikas Yadav, Shiyang Li, Lichang Chen, Zheng Tang, Hai Wang, Vijay Srinivasan, Xiang Ren, and Hongxia Jin. Backdooring instruction-tuned large language models with virtual prompt injection, 2024b.

Xuchen Suo. Signed-prompt: A new approach to prevent prompt injection attacks against llm-integrated applications, 2024. URL `https://arxiv.org/abs/2401.07612`.

Yi Zeng, Hongpeng Lin, Jingwen Zhang, Diyi Yang, Ruoxi Jia, and Weiyan Shi. How johnny can persuade llms to jailbreak them: Rethinking persuasion to challenge ai safety by humanizing llms, 2024.

Parijat Rai, Saumil Sood, Vijay Madisetti, and Arshdeep Bahga. Guardian: A multi-tiered defense architecture for thwarting prompt injection attacks on llms. *Journal of Software Engineering and Applications*, 17:43–68, 01 2024. doi:10.4236/jsea.2024.171003.

Kaijie Zhu, Jindong Wang, Jiaheng Zhou, Zichen Wang, Hao Chen, Yidong Wang, Linyi Yang, Wei Ye, Yue Zhang, Neil Zhenqiang Gong, and Xing Xie. Promptbench: Towards evaluating the robustness of large language models on adversarial prompts, 2023.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In Pierre Isabelle, Eugene Charniak, and Dekang Lin, editors, *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pages 311–318, Philadelphia, Pennsylvania, USA, July 2002. Association for Computational Linguistics. doi:10.3115/1073083.1073135. URL `https://aclanthology.org/P02-1040`.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. Injecagent: Benchmarking indirect prompt injections in tool-integrated large language model agents, 2024.

Yangsibo Huang, Samyak Gupta, Mengzhou Xia, Kai Li, and Danqi Chen. Catastrophic jailbreak of open-source llms via exploiting generation, 2023. URL https://arxiv.org/abs/2310.06987.