

Shor's Algorithm & Quantum Cryptography

P. Beggs J. Hill

Department of Mathematics and Computer Science
Hendrix College

December 4, 2024

Introduction

Background

Recall that:

Discrete Logarithm Problem (DLP): the problem of finding x given $g^x \bmod p$.

Introduction

Background

Recall that:

Discrete Logarithm Problem (DLP): the problem of finding x given $g^x \bmod p$.

Order r : smallest integer $r \geq 1$ such that $x^r \equiv 1 \bmod n$

Introduction

Background

Recall that:

Discrete Logarithm Problem (DLP): the problem of finding x given $g^x \bmod p$.

Order r : smallest integer $r \geq 1$ such that $x^r \equiv 1 \bmod n$

Time complexity: DLP = $\mathcal{O}(2^n)$.

Introduction

subtitle

Time Complexity

Classical Computers

The fastest known algorithm (number field sieve) has time complexity $L_{4096}[\frac{1}{3}, c]$ to decrypt a 4096-bit key-size DLP. For total steps, solve:

$$L_p \left[\frac{1}{3}, c \right] = \exp \left(c (\ln p)^{1/3} (\ln \ln p)^{2/3} \right) .^1$$

¹Menezes, A. J., Van Oorschot, P. C., & Vanstone, S. A. (2018). *Handbook of applied cryptography*. CRC press.

Time Complexity

Classical Computers

The fastest known algorithm (number field sieve) has time complexity $L_{4096}[\frac{1}{3}, c]$ to decrypt a 4096-bit key-size DLP. For total steps, solve:

$$L_p \left[\frac{1}{3}, c \right] = \exp \left(c (\ln p)^{1/3} (\ln \ln p)^{2/3} \right).^1$$

For $c = (64/9)^{1/3} \approx 1.923$ and $p = 4096$, the total steps would be 10^{155} .

¹Menezes, A. J., Van Oorschot, P. C., & Vanstone, S. A. (2018). *Handbook of applied cryptography*. CRC press.

Time Complexity

Quantum Computers

Using Shor's Algorithm, the DLP can be solved in polynomial time using a quantum computer. For key size 4096, it would take:

Time Complexity

Quantum Computers

Using Shor's Algorithm, the DLP can be solved in polynomial time using a quantum computer. For key size 4096, it would take:

$$\mathcal{O}\left((\log p)^3\right) = \mathcal{O}\left((\log 4096)^3\right) = 6.8 \cdot 10^{10} \text{ steps.}$$

Bits

Overview of Classical & Quantum Computing

Classical bits: 0 or 1

Bits are manipulated according to **Boolean logic**, and sequences of bits are manipulated by **Boolean logic gates**.

Quantum bits (qubits): Simultaneous values between 0 and 1

A quantum computer manipulates **quantum bits** (qubits) via **quantum logic gates**, which are supposed to simulate the laws of quantum mechanics

Quantum Computers

Understanding Qubits

Two-state representation: $|0\rangle$ and $|1\rangle$

Pure states: $\alpha |0\rangle + \beta |1\rangle$

Constraint: $|\alpha|^2 + |\beta|^2 = 1$

Quantum Computers

Understanding Qubits

Two-state representation: $|0\rangle$ and $|1\rangle$

Pure states: $\alpha |0\rangle + \beta |1\rangle$

Constraint: $|\alpha|^2 + |\beta|^2 = 1$

n-Component System

$$\sum_{i=0}^{2^n-1} \alpha_i |s_i\rangle, \quad \text{where } \sum |\alpha_i|^2 = 1$$

Shor's Algorithm

Overview

Purpose: Find non-trivial factors p and q of N

Applications:

- Integer factorization

- Discrete logarithm in \mathbb{F}_p^*

- Elliptic curve discrete logarithm

Runs in polynomial time (quantum)

Shor's Algorithm

Algorithmic Steps

1. Change problem of factoring into finding the order r .

Shor's Algorithm

Algorithmic Steps

1. Change problem of factoring into finding the order r .
2. Use the Quantum Fourier Transform to extract periodicity of $f(x) = a^x \bmod N$.

Shor's Algorithm

Algorithmic Steps

1. Change problem of factoring into finding the order r .
2. Use the Quantum Fourier Transform to extract periodicity of $f(x) = a^x \bmod N$.
3. Once r is found (and it is even), use it in the computation of $\gcd(a^{r/2} - 1, N)$.

Shor's Algorithm

Quantum Fourier Transform 1

Quantum Superposition

For $0 < a < q$:

$$\frac{1}{q^{1/2}} \sum_{c=0}^{q-1} |c\rangle \exp(2\pi iac/q)$$

Choose q : power of 2 between n^2 and $2n^2$

Probability of state $|c\rangle$ is high when:

$$\left| c - \frac{d}{r} \right| < \frac{1}{2q}$$

Shor's Algorithm

Quantum Fourier Transform 2

Shor's Algorithm

Algorithmic Steps in Detail

1. Choose random integer $a < N$ (to ensure a and N are co-prime).

Shor's Algorithm

Algorithmic Steps in Detail

1. Choose random integer $a < N$ (to ensure a and N are co-prime).
2. Check if a is already a factor of N . If so, then the problem is solved.

Shor's Algorithm

Algorithmic Steps in Detail

1. Choose random integer $a < N$ (to ensure a and N are co-prime).
2. Check if a is already a factor of N . If so, then the problem is solved.
3. Otherwise, find the order r of $a \bmod N$ using quantum super-positioning and interference. (Remember that the order is the smallest integer such that $a^r \equiv 1 \bmod N$.)

Shor's Algorithm

Algorithmic Steps in Detail

1. Choose random integer $a < N$ (to ensure a and N are co-prime).
2. Check if a is already a factor of N . If so, then the problem is solved.
3. Otherwise, find the order r of $a \bmod N$ using quantum super-positioning and interference. (Remember that the order is the smallest integer such that $a^r \equiv 1 \bmod N$.)
4. Once r is found, compute the factors of N using r . If r is even and

$$a^{r/2} \not\equiv -1 \bmod N,$$

then the factors are

$$p = \gcd(a^{r/2} - 1, N) \quad \text{and} \quad q = \gcd(a^{r/2} + 1, N).$$

Cryptographic Implications

Vulnerable

RSA

Classical Elgamal

Elliptic curve Elgamal

Cryptographic Implications

Vulnerable

RSA

Classical Elgamal

Elliptic curve Elgamal

Still Secure

Lattice-based
cryptosystems

Shortest vector problems

Closest vector problems

Challenges & Future

Building functioning quantum computers

Decoherence control

Quantum cryptography applications:

- Heisenberg uncertainty principle

- Entanglement of quantum states

- Secure key exchange