



Final NLA Project

Voice Gender Detection using Tensor Power Method

MMODA Team:

Maxim Brazhnikov & Maxim Kuznetsov
& Oleg Desheulin & Denis Rakitin & Anita Soloveva

December 17, 2020



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

Problem Description

- ▶ Gender detection as one of the tasks of Speech Recognition, which has recently gained much popularity with the development of voice-based systems like Alexa, Siri and etc.
- ▶ Classical method for gender detection task is Gaussian Mixture Model (GMM) on Mel Frequency Cepstral Coefficients (MFCCs) (Neti & Roukos, 1997). Here we try another approach proposed by (Roy, Bhagath, & Das, 2020) which applies tensor power method to a tensor formed from MFCCs and compare this approach to GMM.



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

Our goals

- ▶ Evaluate the accuracy of gender detection, performed by the approach proposed in (Roy et al., 2020), using different sizes of feature vectors, different number of eigenvectors, testing on two datasets:
 - ▶ TIMIT DR1 (New England dialect data)
 - ▶ SHRUTI (Bengali (minor Indo-Aryan language) data)

Additionally:



- ▶ Compare the performance with other approaches
- ▶ Test on our own Khanty (minor Finno-Ugric language) corpus



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

Mel-frequency cepstral coefficients



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

Tensor Formation

In order to build 3rd order tensor we apply moment method.

$$m_1 = E[x] = \frac{1}{N} \sum_{i=1}^N x_i$$

$$M_2 = E[x \odot x] - \sigma^2 I$$

where σ^2 is the smallest eigenvalue of covariance matrix $\Sigma = E[x \odot x] - m_1 \odot m_1$ and M_2 can be decomposed as

$$M_2 = \sum_{i=1}^r w_i a_i \odot a_i \quad (1)$$

Naive approach is to calculate vectors a_i by eigendecomposition.



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

Tensor Formation

To avoid problems with highly correlated components authors suggests to calculate M_3 rather than M_2 using formulation (Hsu & Kakade, 2013):

$$M_3 = E[x \odot x \odot x] - \sigma^2 \sum_{i=1}^d (m_1 \odot e_i \odot e_i + \cdots + e_i \odot e_i \odot m_1)$$

And like M_2 can be decomposed onto eigenvalue decomposition, for M_3 it also exists in following form:

$$M_3 = \sum_{i=1}^r w_i a_i \odot a_i \odot a_i$$

Where a_i is our target eigenvectors of M_2 . Then eigenvectors of M_3 are also eigenvectors of M_2 .



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

Eigenvectors Computation

Similar to matrix eigenvectors computation for tensors also exists Power Method:

$$a_{i,k+1} = \frac{A_i(I, a_{i,k}, a_{i,k})}{||A_i(I, a_{i,k}, a_{i,k})||_2}$$

And to project to next eigenvector space :

$$A_{i+1} = A_i - \lambda_i a_i \odot a_i \odot a_i$$

We apply this method to whitened M_3 and obtain our feature vectors.



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

Evaluation

During training stage we found k dominant eigenvectors for both A_f (female) and A_m (male) dataset.

Then distances $D_{f,m}$ between unknown feature vector $x_i \in \mathcal{R}^n$ and eigenvectors $a_{\{f,m\};k}$ of each dataset A_f and A_m is calculated as:

$$D_{\{f,m\}} = \sum_{i=1}^N \min_k d(a_{\{f,m\};k}, x_i) \quad (2)$$

$$d(x, y) = 1 - \frac{(x, y)^2}{(x, x)(y, y)} \quad (3)$$

After than we compare D_m and D_f and choose the lowest distance to determine gender of the speaker.



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

Results with different sizes of feature vectors

Size	Female accuracy	Male accuracy	Total accuracy
13	0.694	0.897	0.796
20	0.810	0.841	0.825
26	0.828	0.852	0.840

Table: Accuracy on Khanty dataset with 1 eigenvector.

Size	Female accuracy	Male accuracy	Total accuracy
13	0.992	0.777	0.884
20	0.989	0.919	0.954
26	0.989	0.953	0.971

Table: Accuracy on SHRUTI dataset with 1 eigenvector.

Tables are represent dependence of accuracy on size of feature vector.



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

Results with different number of eigenvectors



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

#	Female accuracy	Male accuracy	Total accuracy
1	0.871	0.822	0.847
2	0.835	0.851	0.843
4	0.828	0.852	0.840

Table: Accuracy on Khanty dataset with 26-size feature vector.

The tables is represent dependence of accuracy on the number of eigenvectors.

Comparison to other approaches



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

Method	Female accuracy	Male accuracy	Total accuracy
Article	0.871	0.822	0.847
Naive	0.802	0.856	0.829
GMM	0.968	0.914	0.945

Table: Accuracy on Khanty dataset with the best choice of number of eigenvectors and size of feature vectors

Team Member contribution

- ▶ Maxim Brazhnikov: theoretical part, model building, presentation, report
- ▶ Maxim Kuznetsov: model testing, results analysis, presentation, report
- ▶ Oleg Desheulin: theoretical part, model building, presentation, report
- ▶ Denis Rakitin: model building, model testing, presentation, report
- ▶ Anita Soloveva: data preprocessing, model testing, presentation, report

Our GitHub repository



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva

References

- Hsu, D. J., & Kakade, S. M. (2013). Learning mixtures of spherical gaussians: moment methods and spectral decompositions. In *Itcs '13*.
- Neti, C., & Roukos, S. (1997). Phone-context specific gender-dependent acoustic-models for continuous speech recognition. *1997 IEEE Workshop on Automatic Speech Recognition and Understanding Proceedings*, 192-198.
- Roy, P., Bhagath, P., & Das, P. (2020). Gender detection from human voice using tensor analysis. In *Proceedings of the 1st joint workshop on spoken language technologies for under-resourced languages (sltu) and collaboration and computing for under-resourced languages (ccurl)* (pp. 211–217).



Final NLA Project
Voice Gender
Detection using
Tensor Power
Method
MMODA Team:

Maxim
Brazhnikov &
Maxim
Kuznetsov
& Oleg
Desheulin &
Denis Rakitin &
Anita Soloveva