



Two Dimensional Arrays

Department of Computer Science

DCS

COMSATS Institute of
Information Technology

Rab Nawaz Jadoon

Assistant Professor

COMSATS IIT, Abbottabad

Pakistan

Introduction to Computer Programming (ICP)

Passing Array elements to function

- It is also possible for arrays to have two or more dimensions.
 - The two dimensional array is also called a matrix.



Simple Program

```
main( )
{
    int stud[4][2] ;
    int i, j ;

    for ( i = 0 ; i <= 3 ; i++ )
    {
        printf ( "\n Enter roll no. and marks" ) ;
        scanf ( "%d %d", &stud[i][0], &stud[i][1] ) ;
    }

    for ( i = 0 ; i <= 3 ; i++ )
        printf ( "\n%d %d", stud[i][0], stud[i][1] ) ;
}
```

- The previous example array arrangement is as under,

| | col. no. 0 | col. no. 1 |
|-----------|------------|------------|
| row no. 0 | 1234 | 56 |
| row no. 1 | 1212 | 33 |
| row no. 2 | 1434 | 80 |
| row no. 3 | 1312 | 78 |

Initializing two dimensional arrays

```
int stud[4][2] = {  
    { 1234, 56 },  
    { 1212, 33 },  
    { 1434, 80 },  
    { 1312, 78 }  
};
```

or even this would work...

```
int stud[4][2] = { 1234, 56, 1212, 33, 1434, 80, 1312, 78 };
```

Initializing two dimensional arrays

- It is important to remember that while initializing a 2-D array,
 - It is necessary to mention the second (column) dimension, whereas the first dimension (row) is optional.

```
int arr[2][3] = { 12, 34, 23, 45, 56, 45 } ;  
int arr[ ][3] = { 12, 34, 23, 45, 56, 45 } ;
```

```
int arr[2][ ] = { 12, 34, 23, 45, 56, 45 } ;  
int arr[ ][ ] = { 12, 34, 23, 45, 56, 45 } ;
```

would never work.

Two dimensional arrays in memory

- **Memory doesn't contain rows and columns.**
 - In memory whether it is a one-dimensional or a two-dimensional array the array elements are stored in one continuous chain.
 - The arrangement of array elements of a two-dimensional array in memory is shown below:

| s[0][0] | s[0][1] | s[1][0] | s[1][1] | s[2][0] | s[2][1] | s[3][0] | s[3][1] |
|---------|---------|---------|---------|---------|---------|---------|---------|
| 1234 | 56 | 1212 | 33 | 1434 | 80 | 1312 | 78 |
| 65508 | 65510 | 65512 | 65514 | 65516 | 65518 | 65520 | 65522 |

Pointers and 2-Dimensional Arrays

- Each row of a two-dimensional array can be thought of as a one-dimensional array.

```
/* Demo: 2-D array is an array of arrays */
```

```
main( )
```

```
{
```

```
    int s[4][2] = {
```

```
        { 1234, 56 },
```

```
        { 1212, 33 },
```

```
        { 1434, 80 },
```

```
        { 1312, 78 }
```

```
    };
```

```
    int i;
```

```
    for ( i = 0 ; i <= 3 ; i++ )
```

```
        printf ( "\nAddress of %d th 1-D array = %u", i, s[i] ) ;
```

```
}
```

Address of 0 th 1-D array = 65508

Address of 1 th 1-D array = 65512

Address of 2 th 1-D array = 65516

Address of 3 th 1-D array = 65520

Output Philosophy

- The compiler knows that `s` is an array containing 4 one-dimensional arrays, each containing 2 integers.
- Each one-dimensional array occupies 4 bytes (two bytes for each integer).
- These one-dimensional arrays are placed linearly (zeroth 1-D array followed by first 1-D array, etc.).

Accessing 2 dimensional array elements using pointers

```
/* Pointer notation to access 2-D array elements */
main( )
{
    int s[4][2] = {
                        { 1234, 56 },
                        { 1212, 33 },
                        { 1434, 80 },
                        { 1312, 78 }
                    };

    int i, j;

    for ( i = 0 ; i <= 3 ; i++ )
    {
        printf ( "\n" );
        for ( j = 0 ; j <= 1 ; j++ )
            printf ( "%d ", *( s + i ) + j );

    }
}
```

And here is the output...

```
1234 56
1212 33
1434 80
1312 78
```

Passing 2-D Array to a Function

```
/* Three ways of accessing a 2-D array */
```

```
main( )
{
    int a[3][4] = {
        1, 2, 3, 4,
        5, 6, 7, 8,
        9, 0, 1, 6
    };

    clrscr( ) ;
    display ( a, 3, 4 ) ;
    show ( a, 3, 4 ) ;
    print ( a, 3, 4 ) ;
}
```

```
display ( int *q, int row, int col )
{
    int i, j ;

    for ( i = 0 ; i < row ; i++ )
    {
        for ( j = 0 ; j < col ; j++ )
            printf ( "%d ", * ( q + i * col + j ) ) ;

        printf ( "\n" ) ;
    }
    printf ( "\n" ) ;
}
```

Passing 2-D Array to a Function

```
show ( int ( *q )[4], int row, int col )
{
    int i, j;
    int *p;

    for ( i = 0 ; i < row ; i++ )
    {
        p = q + i;
        for ( j = 0 ; j < col ; j++ )
            printf ( "%d ", * ( p + j ) );

        printf ( "\n" );
    }
    printf ( "\n" );
}
```

```
print ( int q[ ][4], int row, int col )
{
    int i, j;

    for ( i = 0 ; i < row ; i++ )
    {
        for ( j = 0 ; j < col ; j++ )
            printf ( "%d ", q[i][j] );
        printf ( "\n" );
    }
    printf ( "\n" );
}
```

Output ...

| | | | |
|---|---|---|---|
| 1 | 2 | 3 | 4 |
| 5 | 6 | 7 | 8 |
| 9 | 0 | 1 | 6 |

| | | | |
|---|---|---|---|
| 1 | 2 | 3 | 4 |
| 5 | 6 | 7 | 8 |
| 9 | 0 | 1 | 6 |

| | | | |
|---|---|---|---|
| 1 | 2 | 3 | 4 |
| 5 | 6 | 7 | 8 |
| 9 | 0 | 1 | 6 |

A more general formula for accessing each array element would be:

$\ast (\text{base address} + \text{row no.} \ast \text{no. of columns} + \text{column no.})$

- In the previous program the display function definition we have,
 - In the display()function we have collected the base address of the 2-D array being passed to it in an ordinary int pointer.
 - Then through the two for loops using the expression $* (q + i * \text{col} + j)$, we have reached the appropriate element in the array.
 - Suppose i is equal to 2 and j is equal to 3, then we wish to reach the element a[2][3]. Let us see whether the expression $* (q + i * \text{col} + j)$ does give this element or not. Refer Figure 8.7 to understand this.

Illustration

| | | | | | | | | | | | |
|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 6 |
| 65502 ...04 | ...06 | ...08 | ...10 | ...12 | ...14 | ...16 | ...18 | ...20 | ...22 | ...24 | |

- The expression $*(q + i * \text{col} + j)$ becomes $*(65502 + 2 * 4 + 3)$.
- This turns out to be $*(65502 + 11)$.
 - Since 65502 is address of an integer, $*(65502 + 11)$ turns out to be $*(65524)$.
- Value at this address is 6.
- This is indeed same as $a[2][3]$.

Array of pointers

```
main( )
{
    int *arr[4] ; /* array of integer pointers */
    int i = 31, j = 5, k = 19, l = 71, m ;

    arr[0] = &i ;
    arr[1] = &j ;
    arr[2] = &k ;
    arr[3] = &l ;

    for ( m = 0 ; m <= 3 ; m++ )
        printf ( "%d ", * ( arr[m] ) ) ;
}
```

Output...

31 5 19 71

Array of pointers

- An array of pointers can even contain the addresses of other arrays.

```
#include<stdio.h>
#include<conio.h>
main( )
{
    static int a[ ] = { 0, 1, 2, 3, 4 } ;
    int *p[ ] = { a, a + 1, a + 2, a + 3, a + 4 } ;
    for(int i=0;i<=4;i++)
    {
        printf ( "\n%u %u %d", (p+i), *(p+i), * ( *(p+i) ) ) ;
    }
    getch();
}
```

Output:

| | | |
|---------|---------|---|
| 1638208 | 4239604 | 0 |
| 1638212 | 4239608 | 1 |
| 1638216 | 4239612 | 2 |
| 1638220 | 4239616 | 3 |
| 1638224 | 4239620 | 4 |

