



Object-oriented Program Design

Week 8







- 11 Creating Your Own Data Types
- 12 More Object Orientation
- 13 Functional Decomposition
- 14 Object-oriented Program Design





Tasks starting this week

8.1PP Programming Principles

- In about 2 pages of text, code snippets and images (if you want) explain some key programming and Java-related terms in your own words
- Do not be frightened. You need to write so we can understand you, not so you'll win prizes

8.2CR Debug This

 Given some code containing errors and clues left by its mysterious author, identify and fix the errors, documenting what you did, what clues you followed, and what you changed

8.3DN Object-Oriented Collection Manager

 Transform your 7.1PP program (and 6.2CR class) definition) to be more object-oriented (which is the topic of today's lecture)





















From last lecture: Software is complex

Monolithic application

```
main() {
```

Procedural programming

```
void a() { ... }
void b() { ... }
void c() { ... }
main() {
  a();
  a();
  b();
  c();
  a();
  b();
  c();
```

Object-oriented programming

```
main() {
    o.a();
    o.b();
    p.c();
    o.b();
    o.b();
    q.c();
}
```

```
Object o (class AB)

void a() { ... }

void b() { ... }
```


```
Object p (class C) void c() { ... }
```

```
Object q
(class C)
void c() { ... }
```






Programming tasks in this unit







Motivating example: Snakes & Ladders





What kind of objects in the game?



Task: What kinds of objects could we model in this game? What kind of attributes and abilities might they have?

21	22	23	24	25
20	19	18	17	16
11	12	3	14	15
10	9	8	7	6
1	2	3	4	B



Single source \rightarrow interacting objects

Use other objects, but keep the top-level algorithm in main() and other static methods of that class

```
Option1.java

public class Option1 {
    //other methods, all static

public static void main(String[] args) {
    /* Top-level algorithm in main */
  }

}
```

Keeps top-level algorithm in one place, but can become complex to manage, especially as the complexity of the data model grows

Overall is less object-oriented



Single source \rightarrow interacting objects

Using an 'organiser' class

```
Option2.java

public class Option2 {
    public static void main(String[] args) {
        Organiser o = new Organiser();
        o.topLevelAlg();
    }
}

//other methods

public void topLevelAlg() {
    /* Top-level algorithm here */
    }
}
```

- Organiser's code can be reused in different settings (different main programs)
- Data shared by many methods can be made 'global' (within Organiser)
- Facilitates change from console to graphical application
- But one more file and may seem like overkill for simple programs

See Task 8.3DN Object-oriented Collection Manager

Other classes



Single source \rightarrow interacting objects


Using an 'organiser' class with in-built main()

```
Organiser.java
public class Organiser {
  //instance data shared by top-level alg
  //other methods
  public void topLevelAlg() {
                                                                         Other classes
    /* Top-level algorithm here */
  public static void main(String[] args) {
    Organiser o = new Organiser();
    o.topLevelAlg();
```

Option 3 is if you really hate additional files; done if you've decided exactly how your program is going to be used, since a little less flexible



'Library' versus 'Organiser' classes



Library class

- the low-level 'components' of your software
- general purpose (or common enough to allow reuse)

Organiser class

- defines the top-level algorithm
- problem-specific
- may use other problemspecific (custom) classes and library classes

(This is a *useful* distinction; these are not labels you will need to memorise)



Suitable modules for 'library' classes

Constructor

Organiser custom custom library library library

One method for **each 'action'** the object can perform

 plus any necessary methods to do the separate parts of the action

Setters for instance variables

• if needed/appropriate

Getters for instance variables

if needed

A trace() method

```
private void trace(String message) {
   System.out.println(message);
}
```

Not *required* by Java, but useful to have

for use during development



Suitable modules for 'organiser' classes

Constructor

Organiser

custom

library

library

library

if necessary to do any set up

One method for each sub-problem

- Often these relate to:
 - Input
 - Processing
 - Output


Any methods needed for **separate parts** of each sub-problem

A trace() method

• for use during development



Returning to Snakes & Ladders





What subtasks in Snakes & Ladders?

Partial top-level algorithm

- create any other components (objects)
- ask if user wants to play
- while user wants to play
 - play one game
 - set player positions to 0
 - set current player
 - while the game is not over
 - current player moves
 - if game not yet over
 - swap players
 - announce winner
 - see if user wants to play again

Task: Assume we've drafted the top-level algorithm as above Sketch a structure chart of a possible breakdown into different tasks

Note: You can largely ignore parameters and return types; think in terms of responsibilities





An example task breakdown


Top-level algorithm

```
SALGame()
Create Die and Board objects
                                       constructor
                                       startPlaying()
Ask if user wants to play
While user wants to play
    Play one game
                                  playGame()
        Set player positions to 0
        Set current player
        While the game is not over
                               makeAMove()
            Current player moves
            If game not yet over
                               swapPlayer()
                Swap players
        Announce winner
See if user wants to play again
```



Snakes & Ladders classes

One, relatively simple approach



If you've ever studied databases then this should look familiar



Die is responsible for creating a virtual six-sided game die, holding its state and randomising the upward facing side

Die

int numFaces int faceValue Random generator

int getFaceValue()
int roll()
int getFaces()

1



Board

various bits of internal data

Board knows how many squares there are, where the snakes and ladders begin and end and can tell you where you'll end up after a given number of moves starting from a particular square

1



1

SALGame

Die roller
Board gameBoard
int p1position
int p2position

void startPlaying()


Top-level algorithm

- create **Die** object
- create **Board** object
- declare int variables for player positions
- see if user wants to play
- while user wants to play
 - play one game
 - see if user wants to play again

*



Snakes & Ladders classes



Later: download and work through the self-guided development of the Snakes and Ladders game yourself



Let's implement it

Top-level algorithm

```
SALGame()
Create Die and Board objects
                                       constructor
                                       startPlaying()
Ask if user wants to play
While user wants to play
    Play one game
                                  playGame()
        Set player positions to 0
        Set current player
        While the game is not over
                               makeAMove()
            Current player moves
            If game not yet over
                               swapPlayer()
                Swap players
        Announce winner
See if user wants to play again
```