

Bilingual NLP pipeline

Paul Huygen <paul.huygen@huygen.nl>

10th May 2017
13:59 h.

Abstract

This is a description and documentation of the installation of an instrument to annotate Dutch or English documents with NLP tags.

Contents

| | | |
|----------|---------------------------------------------------|-----------|
| 1 | Introduction | 3 |
| 1.1 | List of the modules to be installed | 3 |
| 1.2 | The things that are not open-source yet | 6 |
| 1.3 | Multi-linguality | 6 |
| 1.4 | File-structure of the pipeline | 6 |
| 2 | How to obtain modules and other material | 8 |
| 2.1 | Location-dependency | 8 |
| 2.2 | Reversible update | 8 |
| 2.3 | Download materials | 9 |
| 2.4 | Installation from Github | 9 |
| 2.5 | Installation from the snapshot | 10 |
| 2.6 | Download other materials | 11 |
| 3 | Shared libraries | 11 |
| 3.1 | Autoconf | 11 |
| 3.2 | libxml2 and libxslt | 12 |
| 4 | Java, Python en Perl | 12 |
| 4.1 | Java | 13 |
| 4.2 | Maven | 14 |
| 4.3 | Java 1.6 | 15 |
| 4.4 | Python | 15 |
| 4.4.1 | Virtual environment | 16 |
| 4.4.2 | Transplant the virtual environment | 18 |
| 4.4.3 | KafNafParserPy | 18 |
| 4.4.4 | Python packages | 18 |
| 4.5 | Perl | 19 |
| 5 | Installation of the modules | 20 |
| 5.1 | Conditional installation of the modules | 20 |
| 5.2 | The installation script | 21 |
| 5.3 | Check availability of resources | 26 |
| 5.4 | Parameters in module-scripts | 27 |

| | | |
|----------|------------------------------------------------|-----------|
| 5.5 | Install utilities and resources | 28 |
| 5.5.1 | Process synchronisation | 28 |
| 5.5.2 | Prefix of scripts that run modules | 28 |
| 5.5.3 | Language detection | 29 |
| 5.5.4 | Alpino | 30 |
| 5.5.5 | Treetagger | 31 |
| 5.5.6 | Timbl and Ticcutils | 32 |
| 5.5.7 | The Boost library | 33 |
| 5.5.8 | Spotlight | 34 |
| 5.5.9 | VUA-pylib | 40 |
| 5.5.10 | SVMLight | 40 |
| 5.6 | Install modules | 41 |
| 5.6.1 | Install tokenizer | 41 |
| 5.6.2 | Topic analyser | 41 |
| 5.6.3 | Morphosyntactic parser | 43 |
| 5.6.4 | Pos tagger | 44 |
| 5.6.5 | Constituent parser | 44 |
| 5.6.6 | NED-reranker | 45 |
| 5.6.7 | Wikify module | 45 |
| 5.6.8 | UKB | 46 |
| 5.6.9 | IMS-WSD | 46 |
| 5.6.10 | SRL server | 47 |
| 5.6.11 | SRL Dutch nominals | 50 |
| 5.6.12 | FBK-time module | 51 |
| 5.6.13 | FBK-temprel module | 53 |
| 5.6.14 | FBK-causalrel module | 54 |
| 5.6.15 | Factuality modules | 55 |
| 5.6.16 | Nominal coreference-base | 56 |
| 5.6.17 | Named entity recognition (NERC) | 56 |
| 5.6.18 | Wordsense-disambiguation | 58 |
| 5.6.19 | Lexical-unit converter | 59 |
| 5.6.20 | NED | 60 |
| 5.6.21 | Dark entity relinker | 61 |
| 5.6.22 | Ontotagger, Framenet-SRL and nominal events | 62 |
| 5.6.23 | Heideltime | 63 |
| 5.6.24 | Semantic Role labelling | 64 |
| 5.6.25 | SRL postprocessing | 66 |
| 5.6.26 | Event coreference | 66 |
| 5.6.27 | Dbpedia-ner | 67 |
| 5.6.28 | GetSemfromNaf | 68 |
| 5.6.29 | Opinion miner | 69 |
| 6 | Utilities | 71 |
| 6.1 | Run-script and test-script | 71 |
| 6.2 | Logging | 75 |
| 6.3 | Misc | 75 |
| A | How to read and translate this document | 76 |
| A.1 | Read this document | 76 |
| A.2 | Process the document | 77 |
| A.3 | The Makefile for this project. | 78 |
| A.4 | Get Nuweb | 79 |
| A.5 | Pre-processing | 79 |
| A.5.1 | Process ‘dollar’ characters | 80 |

| | | |
|----------|------------------------------------------------|-----------|
| A.5.2 | Run the M4 pre-processor | 80 |
| A.6 | Typeset this document | 80 |
| A.6.1 | Figures | 80 |
| A.6.2 | Bibliography | 82 |
| A.6.3 | Create a printable/viewable document | 82 |
| A.6.4 | Create HTML files | 85 |
| A.7 | Perform the installation | 88 |
| A.8 | Test whether it works | 89 |
| A.9 | Restore paths after transplantation | 89 |
| B | References | 90 |
| B.1 | Literature | 90 |
| C | Indexes | 90 |
| C.1 | Filenames | 90 |
| C.2 | Macro's | 91 |
| C.3 | Variables | 93 |

1 Introduction

This document describes the current set-up of a pipeline that annotates texts in order to extract knowledge. The pipeline has been set up by the Computational Lexicology and Terminology Lab (CLTL¹) as part of the newsreader² project. It accepts and produces texts in the NAF (Newsreader Annotation Format) format.

Apart from describing the pipeline set-up, the document actually constructs the pipeline. The pipeline has been installed on a (Ubuntu) Linux computer.

The installation has been parameterised. The locations and names that you read (and that will be used to build the pipeline) have been read from variables in file `inst.m4` in the `nuweb` directory.

The pipeline is bi-lingual. It is capable to annotate Dutch and English texts. It recognizes the language from the “lang” attribute of the NAF element of the document.

The aim is, to install the pipeline from open-source modules that can e.g. be obtained from Github. However, that aim is only partially fulfilled. Some of the modules still contain elements that are not open-source or data that are not freely available. Because of lack of time, the current version of the installer installs the English pipeline from a frozen repository of the Newsreader Project.

1.1 List of the modules to be installed

Table 2 lists the modules in the pipeline. The column *source* indicates the origin of the module. The modules are obtained in one of the following ways:

1. If possible, the module is directly obtained from an open-source repository like Github.
2. Some modules have not been officially published in a repository. These modules have been packed in a tar-ball that can be obtained by the author. In table 2 this has been indicated as SNAPSHOT.

The modules themselves use other utilities like dependency-taggers and POS taggers. These utilities are listed in table 1.

1. <http://wordpress.let.vupr.nl>

2. <http://www.newsreader-project.eu>

| Module | Version | Section | Source |
|----------------------------------|-------------|-----------------------|------------------------------|
| KafNafParserPy | Feb 1, 2015 | 4.4.3 | Github |
| Alpino | 20706 | 5.5.4 | RUG |
| Ticcutils | 0.7 | 5.5.6 | ILK |
| Timbl | 6.4.6 | 5.5.6 | ILK |
| Treetagger | 3.2 | 5.5.5 | Uni. München |
| Spotlight server | 0.7 | 5.5.8 | Spotlight |

Table 1: List of the modules to be installed. Column description: **directory:** Name of the subdirectory below *mod* in which it is installed; **Source:** From where the module has been obtained; **script:** Script to be included in a pipeline.

| Module | Source | Section | Commit | Script | language |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------|---------|---------|--------------------|----------|
| Tokenizer | https://github.com/ixa-ehu/ixa-pipe-tok.git | 5.6.1 | 56f8... | tok | en/nl |
| Topic detection | https://github.com/ialdabe/ixa-pipe-topic.git | 5.6.2 | 40be... | topic | en/nl |
| Morpho-syntactic parser | https://github.com/cltl/morphosyntactic_parser_nl.git | 5.6.3 | d5f0... | mor | nl |
| POS-tagger | snapshot | 5.6.4 | ... | pos | en |
| Named-entity rec/class | https://github.com/ixa-ehu/ixa-pipe-nerc | 5.6.17 | ca02... | nerc | en/nl |
| Constituent parser | snapshot | 5.6.5 | ... | constpars | en |
| Word-sense disamb. nl | https://github.com/cltl/svm_wsd.git | 5.6.18 | 0300... | wsd | nl |
| Word-sense disamb. en | snapshot | 5.6.9 | ... | ewsd | en |
| Named entity/DBP | snapshot | 5.6.20 | ... | ned | en/nl |
| NED reranker | snapshot | 5.6.6 | ... | nedrerscript | en |
| Wikify | snapshot | 5.6.7 | ... | wikify | en |
| UKB | snapshot | 5.6.8 | ... | ukb | en |
| Coreference-base | snapshot | 5.6.16 | ... | coreference-base | en |
| Heideltime | https://github.com/ixa-ehu/ixa-pipe-time.git | 5.6.23 | 0fd3... | heideltime | nl |
| Onto-tagger | https://github.com/cltl/OntoTagger.git | 5.6.22 | 9ea0... | onto | nl |
| Semantic Role labeling nl | https://github.com/newsreader/vua-srl-nl.git | 5.6.24 | 675d... | srl | nl |
| Semantic Role labeling en | snapshot | 5.6.10 | ... | eSRL | en |
| Nominal Event ann. | https://github.com/cltl/OntoTagger.git | 5.6.22 | 9ea0... | nomevent | nl |
| SRL dutch nominals | https://github.com/newsreader/vua-srl-dutch-nominal-events | 5.6.11 | 6115... | srl-dutch-nominals | nl |
| Framenet-SRL | https://github.com/cltl/OntoTagger.git | 5.6.22 | 9ea0... | framesrl | nl |
| FBK-time | snapshot | 5.6.12 | ... | FBK-time | en |
| FBK-temprel | snapshot | 5.6.13 | ... | FBK-temprel | en |
| FBK-causalrel | snapshot | 5.6.14 | ... | FBK-causalrel | en |
| Opinion-miner | https://github.com/rubenIzquierdo/opinion_miner_deluxePP | 5.6.29 | 40a7... | opinimin | en/nl |
| Event-coref | snapshot | 5.6.26 | ... | evcoref | en/nl |
| Factuality tagger | snapshot | 5.6.15 | ... | factuality | en |

Table 2: List of the modules to be installed. Column description: **directory**: Name of the subdirectory below subdirectory *modules* in which it is installed; **source**: From where the module has been obtained; **commit**: Commit-name or version-tag **script**: Script to be included in a pipeline.

1.2 The things that are not open-source yet

The aim is, that the pipeline-system is completely open-sourced, so that anybody can install it from sources like Github. However, a lot of elements are not yet open-sourced, but need private kludges. The following is a list of not-yet open things.

1.3 Multi-linguality

This version of the pipeline is multi-lingual, i.e. it can annotate Dutch as well as English documents. It finds the language of the document in the `language` attribute of the `NAF` element. Actually, the current version is bi-lingual, because it is only able to process Dutch or English documents.

1.4 File-structure of the pipeline

The files that make up the pipeline are organised in set of directories as shown in figure 1. The




Figure 1: *Directory-structure of the pipeline (see text).*

directories have the following functions.

socket: The directory in the host where the pipeline is to be implemented.

root: The root of the pipeline directory-structure.

nuweb: This directory contains this document and everything to create the pipeline from the open sources of the modules.

modules: Contains subdirectories with the NLP modules that can be applied in the pipeline.

bin: Contains for each of the applicable modules a script that reads `NAF` input, passes it to the module in the `modules` directory and produces the output on standard out. Furthermore, the subdirectory contains the script `install-modules` that performs the installation, and a script `test` that shows that the pipeline works in a trivial case.

env: The programming environment. It contains a.o. the Java development kit, Python, the Python virtual environment (`venv`), libraries and binaries.

$\langle \text{directories to create } 6 \rangle \equiv$
`../modules` \diamond

Fragment defined by 6, 7abc, 13c, 14bf, 17c, 83b.

Fragment referenced in 88b.

< directories to create 7a > ≡
`../bin ../env/bin ◇`

Fragment defined by 6, 7abc, 13c, 14bf, 17c, 83b.
 Fragment referenced in 88b.

< directories to create 7b > ≡
`../env/lib ◇`

Fragment defined by 6, 7abc, 13c, 14bf, 17c, 83b.
 Fragment referenced in 88b.

< directories to create 7c > ≡
`../env/etc ◇`

Fragment defined by 6, 7abc, 13c, 14bf, 17c, 83b.
 Fragment referenced in 88b.

The following macro defines variable `piperoot` and makes it to point to the root directory in figure 1. Next it defines variables that point to other directories in the figure. The value-setting of `piperoot` can be overruled by defining the variable before running any of the script. In this way the directory tree can be moved to another location, even to another computer, after successful installation.

< set variables that point to the directory-structure 7d > ≡

```

if
  [ "$piperoot" == "" ]
then
  export piperoot=/home/paul/projecten/pipelines/nlpp
fi
export pipesocket=${piperoot%/nlpp}
export nuwebdir=$piperoot/nuweb
export envdir=$piperoot/env
export envbindir=$envdir/bin
export envlibdir=$envdir/lib
export modulesdir=$piperoot/modules
export pipebin=$piperoot/bin
export javadir=$envdir/java
export jarsdir=$javadir/jars
◇

```

Fragment defined by 7de, 10f, 14h.
 Fragment referenced in 8a, 22a, 90.
 Uses: nuweb 84d.

Add the environment `bin` directory to `PATH`:

< set variables that point to the directory-structure 7e > ≡

```

export PATH=$envbindir:$PATH
◇

```

Fragment defined by 7de, 10f, 14h.
 Fragment referenced in 8a, 22a, 90.
 Defines: `PATH` 14ah, 15d, 19f, 56a.

Put the macro to set variables in a script that can later be sourced by the scripts of the pipeline modules.

```

"../env/bin/progenv" 8a≡
    #!/bin/bash
    < set variables that point to the directory-structure 7d, ... >
    export progenvset=0
    ◇

```

File defined by 8a, 13b, 48a.

2 How to obtain modules and other material

As illustrated in tables 2 and 1, most of the modules are obtained as source-code from Github, some of the modules or parts of some modules are downloaded from a snapshot, and some of the utilities are obtained in binary form from the supplier.

This section builds standardised methods to obtain modules and utilities from Github or from the snapshot.

2.1 Location-dependency

The basic way of installation is, to clone this repository from Github on the intended location in the file-system of the target computer and then run the install-scripts. However, it may be advantageous to be able to transplant a complete installation to another location in another computer. This could be done by making all path-descriptions in all scripts relative to anchorpoints within the installation, while it may be hard to find such anchorpoints in advance. Therefore, we take another approach in which we supply a script that repairs paths-descriptions after the transplantation (section A.9).

2.2 Reversible update

This script might be used to update an existing installation. To minimize the risk that the “update” actually ruins an existing installation, move existing modules away before installing the latest version. When the new modules has been installed succesfully, the moved module will be removed. The following macro’s help to achieve this:

```

< move module 8b > ≡
    if
    [ -e @1 ]
    then
        mv @1 old.@1
    fi
    ◇

```

Fragment referenced in 10a, 76a.

```

< remove old module 8c > ≡
    rm -rf old.@1
    ◇

```

Fragment referenced in 10a, 76a.


```

⟨ re-instate old module 9a ⟩ ≡
    mv old.@1 @1
    MESS="Replaced previous version of @1"
    ⟨ logmess (9b $MESS ) 75d ⟩

```

◇

Fragment referenced in 10a, 76a.

2.3 Download materials

This installer needs to download a lot from different sources:

- Most of the NLP-modules will be built up from their sources in Github. The sources must be cloned.
- Many modules need external resources, e.g. the Alpino tagger. Often these utilities must be downloaded from a location specified by the supplier.
- Many modules use extra resources like model-data, that must be obtained separately.
- Some of the resources are not publicly available. They must be obtained from a pass-word protected URL.
-

Usually downloads are slow, and the duration is only little determined by the resources in the installing computer, but by the network and the performance of the systems from which we download. Therefore, we may speed up by first downloading things, if possible in parallel processes.

We put the following the beginning of the install-script:

```

⟨ download everything 9c ⟩ ≡
    ⟨ download stuff 11a, ... ⟩
    echo Waiting for downloads to complete ...
    wait
    echo Download completed
    ◇

```

Fragment referenced in 22a.

2.4 Installation from Github

The following macro can be used to install a module from Github. Before issuing this macro, the following four variables must be set:

MODNAM: Name of the module.

DIRN: Name of the root directory of the module.

GITU: Github URL to clone from.

GITC: Github commit-name or version tag.

```

< install from github 10a > ≡
    cd $modulesdir
    < move module (10b $DIRN ) 8b >
    git clone $GITU
    if
        [ $? -gt 0 ]
    then
        < logmess (10c Cannot install current $MODNAM version ) 75d >
        < re-instate old module (10d $DIRN ) 9a >
    else
        < remove old module (10e $DIRN ) 8c >
        cd $modulesdir/$DIRN
        git checkout $GITC
    fi

```

◇

Fragment referenced in 43d, 50f, 55c, 58e, 60c, 63d, 65a, 67d, 69c.

2.5 Installation from the snapshot

The sources for the non-open parts of the pipeline are collected in directory `t_nlpp_resources`. They can be accessed via SSH from url `m4_snapshotURL`. Before installing the pipeline download the snapshot on top of directory `snapshotsocket`.

```

< set variables that point to the directory-structure 10f > ≡
    if
        [ ! $snapshotsocket ]
    then
        export snapshotsocket=/home/paul/projecten/pipelines
    fi
    if
        [ ! $snapshotdirectory ]
    then
        export snapshotdirectory=t_nlpp_resources
    fi

```

◇

Fragment defined by 7de, 10f, 14h.

Fragment referenced in 8a, 22a, 90.

The snapshot can be accessed over `scp` on URL `newsreader@kyoto.let.vu.nl`. Access is protected by a public/private key system. So, a private key is needed and this program expects to find the key as `$pipesocket/nrkey`. The key can be obtained from the author. Let us check whether we indeed do have the key:

```

< check this first 10g > ≡
    if
        [ ! -e /home/paul/projecten/pipelines/nrkey ]
    then
        echo "No key to connect to snapshot!"
        exit 1
    fi

```

◇

Fragment defined by 10g, 26e.

Fragment referenced in 22a.

Update the local snapshot repository.

```
< download stuff 11a > ≡
    cd $snapshotsocket
    mkdir -p $snapshotdirectory
    ( rsync -e "ssh -i /home/paul/projecten/pipelines/nrkey" -
      rLt newsreader@kyoto.let.vu.nl:t_nlpp_resources . ) &
◇
```

Fragment defined by 11ac, 14c, 19b, 34b, 40e, 42b, 60d.

Fragment referenced in 9c.

2.6 Download other materials

Apart from the material that we obtain from the snapshot, we need to download resources from different places in the Internet. Downloading can take much time. While working on this installer, we do not want to repeat downloading every time that we run it e.g. to test something. Therefore, we download everything in the snapshot-directory, and check whether it is already there before we start downloading.

```
< need to wget 11b > ≡
    if
        [ ! -e $snapshotsocket/$snapshotdirectory/@1 ]
    then
        cd $snapshotsocket/$snapshotdirectory
        ( wget @2 ) &
    fi
◇
```

Fragment referenced in 11c, 14c, 19b, 34b, 40e, 42b, 60d.

3 Shared libraries

When we do not want to rely on what the host can present to us, we need to make our own shared libraries. For the present, we will generate the shared libraries `libxslt` and `libxml2`. We do the following:

1. install autoconf, needed to compile the libs.
2. install libxslt
3. install libxml2

3.1 Autoconf

Gnu autoconf is a system to help configure the Makefiles for a software package. Software packages that use this, supply a file `configure`, `configure.in` or `configure.ac`. To compile and install a package from source we can then perform 1) `./configure --prefix=<environment>`; 2) `make`; 3) `make install`.

Get autoconf:

```
< download stuff 11c > ≡
    < need to wget (11d autoconf-2.69.tar.gz, 11e http://ftp.gnu.org/gnu/autoconf/autoconf-2.69.tar.gz ) 11b >
◇
```

Fragment defined by 11ac, 14c, 19b, 34b, 40e, 42b, 60d.

Fragment referenced in 9c.

Install autoconf:

$\langle \text{install shared libs 12a} \rangle \equiv$

```
autoconfdir='mktemp -d -t autoconf.XXXXXX'
cd $autoconfdir
tar -xzf $snapshotsocket/$snapshotdirectory/autoconf-2.69.tar.gz
cd autoconf-2.69
./configure --prefix=$envdir
make
make install
cd $piperoot
rm -rf $autoconfdir
◇
```

Fragment defined by 12ac.

Fragment referenced in 22a.

Uses: install 89a.

3.2 libxml2 and libxslt

Compilation and installation of libxml2 and libxslt goes similar, according to the following template:

$\langle \text{install libxml2 or libxslt 12b} \rangle \equiv$

```
shtmpdir='mktemp -d -t shl.XXXXXX'
cd $shtmpdir
git clone @1
packagedir='ls -1'
cd $packagedir
./autogen.sh --prefix=$envdir
make
make install
cd $piperoot
rm -rf $shtmpdir
◇
```

Fragment referenced in 12c.

Uses: install 89a.

$\langle \text{install shared libs 12c} \rangle \equiv$

```
 $\langle \text{install libxml2 or libxslt (12d git://git.gnome.org/libxml2) 12b} \rangle$ 
 $\langle \text{install libxml2 or libxslt (12e git://git.gnome.org/libxslt) 12b} \rangle$ 
◇
```

Fragment defined by 12ac.

Fragment referenced in 22a.

4 Java, Python en Perl

To be independent from the software environment of the host computer and to perform reproducible processing, the pipeline features its own Java, Perl and Python environments. The costs

of this feature are that the pipeline takes more disk-space by reproducing infra-structure that is already present in the system and that installation takes more time.

The following macro generates a script that specifies the programming environment. Initially it is empty, because we have to create the programming environment first.

```
< create javapython script 13a > ≡
    echo '#!/bin/bash' > /home/paul/projecten/pipelines/nlpp/env/bin/javapython
    ◇
```

Fragment referenced in 22a.

Cause the module scripts to read the javapython script.

```
"../env/bin/progenv" 13b≡
    source $envbindir/javapython
    ◇
```

File defined by 8a, 13b, 48a.

4.1 Java

To install Java, download `server-jre-7u72-linux-x64.tar.gz` from <http://www.oracle.com/technetwork/java/javase/downloads/server-jre7-downloads-1931105.html>. Find it in the root directory and unpack it in a subdirectory of `envdir`.

```
< directories to create 13c > ≡
    ../env/java ◇
```

Fragment defined by 6, 7abc, 13c, 14bf, 17c, 83b.

Fragment referenced in 88b.

```
< set up java 13d > ≡
    < begin conditional install (13e java_installed ) 20c >
        cd $envdir/java
        tar -xzf $snapshotsocket/$snapshotdirectory/server-jre-7u72-linux-x64.tar.gz
    < end conditional install (13f java_installed ) 21b >
    ◇
```

Fragment defined by 13d, 14a.

Fragment referenced in 22a.

Remove the java-ball when cleaning up:

```
< clean up 13g > ≡
    rm -rf $pipesocket/server-jre-7u72-linux-x64.tar.gz
    ◇
```

Fragment defined by 13g, 15a, 31b, 79c.

Fragment referenced in 78d.

Set variables for Java.

< set up java 14a > ≡

```
echo 'export JAVA_HOME=$envdir/java/jdk1.7.0_72' >> /home/paul/projecten/pipelines/nlpp/env/bin/javap
echo 'export PATH=$JAVA_HOME/bin:$PATH' >> /home/paul/projecten/pipelines/nlpp/env/bin/javapython
export JAVA_HOME=$envdir/java/jdk1.7.0_72
export PATH=$JAVA_HOME/bin:$PATH
◇
```

Fragment defined by 13d, 14a.

Fragment referenced in 22a.

Uses: PATH 7e.

Put jars in the jar subdirectory of the java directory:

< directories to create 14b > ≡
../env/java/jars ◇

Fragment defined by 6, 7abc, 13c, 14bf, 17c, 83b.

Fragment referenced in 88b.

4.2 Maven

Some Java-based modules can best be compiled with [Maven](#). So download and install Maven:

< download stuff 14c > ≡

```
< need to wget (14d apache-maven-3.0.5-bin.tar.gz, 14e http://apache.rediris.es/maven/maven-3/3.0.5/binaries) > ≡
◇
```

Fragment defined by 11ac, 14c, 19b, 34b, 40e, 42b, 60d.

Fragment referenced in 9c.

< directories to create 14f > ≡
../env/apache-maven-3.0.5 ◇

Fragment defined by 6, 7abc, 13c, 14bf, 17c, 83b.

Fragment referenced in 88b.

< install maven 14g > ≡
cd \$envdir
tar -xzf /home/paul/projecten/pipelines/t_nlpp_resources/apache-maven-3.0.5-bin.tar.gz
◇

Fragment referenced in 22a.

< set variables that point to the directory-structure 14h > ≡
export MAVEN_HOME=\$envdir/apache-maven-3.0.5
export PATH=\${MAVEN_HOME}/bin:\${PATH}
◇

Fragment defined by 7de, 10f, 14h.

Fragment referenced in 8a, 22a, 90.

Uses: PATH 7e.

When the installation has been done, remove maven, because it is no longer needed.

```

< clean up 15a > ≡
    rm -rf ../env/apache-maven-3.0.5
    < remove installed-variable (15b maven_installed ) 21c >
    ◇

```

Fragment defined by 13g, 15a, 31b, 79c.
 Fragment referenced in 78d.

4.3 Java 1.6

Java 1.7 is able to run nearly all the modules of the pipeline that are based on Java. However, there is one exception, i.e. the `ims-wsd` module, that needs Java version 1.6. So, we have to install that version of Java as well.

```

< install Java 1.6 15c > ≡
    cd $envdir/java
    $snapshotsocket/t_nlpp_resources/jre-6u45-linux-x64.bin
    ◇

```

Fragment referenced in 22a.

Insert the following macro in scripts that need to run Java 1.6.

```

< set up Java 1.6 15d > ≡
    export JAVA_HOME=$envdir/java/jre1.6.0_45
    export PATH=$JAVA_HOME/bin:$PATH
    ◇

```

Fragment referenced in 47b.
 Uses: PATH 7e.

4.4 Python

Set up the environment for Python (version 2.7). I could not find an easy way to set up Python from scratch. Therefore we will use Python 2.7 if it has been installed on the host. Otherwise, we will use a binary distribution obtained from [ActiveState](#). A tarball of ActivePython can be obtained from the snapshot.

In order to be independent of the software on the host, we generate a virtual Python environment. In the virtual environment we will install `KafNafParserPy` and other Python packages that are needed.

```

< set up python 15e > ≡
    < check/install the correct version of python 16a >
    < create a virtual environment for Python 16c >
    < activate the python environment 17b, ... >
    < update pip 18a >
    < install python packages 19a, ... >
    < install kafnaparserpy 18c >
    ◇

```

Fragment referenced in 22a.

```

< check/install the correct version of python 16a > ≡
pythonok='python --
version 2>&1 | gawk '{if(match($2, "2.7")) print "yes" ; else print "no" }'
if
[ "$pythonok" == "no" ]
then
  < install ActivePython 16b >
fi
◇

```

Fragment referenced in 15e.

Defines: pythonok Never used.

Uses: print 82b.

Unpack the tarball in a temporary directory and install active python in the `env` subdirectory of `nlpp`. It turns out that you must upgrade `pip`, `virtualenv` and `setuptools` after the installation (see <https://github.com/ActiveState/activepython-docker/commit/10fff72069e51dbd36330cb8a7c2f0845bcd7b3> and <https://github.com/ActiveState/activepython-docker/issues/1>).

```

< install ActivePython 16b > ≡
pytinsdir='mktemp -d -t activepyt.XXXXXX'
cd $pytinsdir
tar -xzf $snapshotsocket/t_nlpp_resources/ActivePython-2.7.8.10-linux-x86_64.tar.gz
acdir='ls -1'
cd $acdir
./install.sh -I $envdir
cd $piperoot
rm -rf $pytinsdir
pip install -U virtualenv setuptools
◇

```

Fragment referenced in 16a.

Uses: install 89a, virtualenv 17a.

4.4.1 Virtual environment

Create a virtual environment. To begin this, we need the Python module `virtualenv` on the host.

```

< create a virtual environment for Python 16c > ≡
< test whether virtualenv is present on the host 17a >
cd $envdir
virtualenv venv
◇

```

Fragment referenced in 15e.

Uses: virtualenv 17a.


```

< test whether virtualenv is present on the host 17a > ≡
    which virtualenv
    if
        [ $? -ne 0 ]
    then
        echo Please install virtualenv
        exit 1
    fi
◇

```

Fragment referenced in 16c.

Defines: `virtualenv` 16bc.

Uses: `install` 89a.

Activate the virtual environment immediately in the installation-script, and add the activation-instruction to the initialisation-script.

```

< activate the python environment 17b > ≡
    source $envdir/venv/bin/activate
    echo 'source $en-
vdir/venv/bin/activate' >> /home/paul/projecten/pipelines/nlpp/env/bin/javapython
◇

```

Fragment defined by 17bde.

Fragment referenced in 15e, 22a.

Defines: `activate` 18b.

Subdirectory `$envdir/python` will contain general Python packages like `KafnafParserPy`.

```

< directories to create 17c > ≡
    ../env/python ◇

```

Fragment defined by 6, 7abc, 13c, 14bf, 17c, 83b.

Fragment referenced in 88b.

Activation of Python include pointing to the place where Python packages are:

```

< activate the python environment 17d > ≡
    echo ex-
port 'PYTHONPATH=$envdir/python:$PYTHONPATH' >> /home/paul/projecten/pipelines/nlpp/env/bin/javapython
export PYTHONPATH=$envdir/python:$PYTHONPATH
◇

```

Fragment defined by 17bde.

Fragment referenced in 15e, 22a.

Defines: `PYTHONPATH` Never used.

We will use home-brewed shared libraries in Python, e.g. `libxml2` and `libxslt`:

```

< activate the python environment 17e > ≡
    echo ex-
port 'LD_LIBRARY_PATH=$envlibdir:$LD_LIBRARY_PATH' >> /home/paul/projecten/pipelines/nlpp/env/bin/javapython
export LD_LIBRARY_PATH=$envdir/python:$LD_LIBRARY_PATH
◇

```

Fragment defined by 17bde.

Fragment referenced in 15e, 22a.

Defines: `LD_LIBRARY_PATH` 46d, 56a.

Update pip in the virtual environment, because otherwise it keeps complaining about outdated versions

```
<update pip 18a> ≡
    pip install --upgrade pip
◇
```

Fragment referenced in 15e.

Uses: `install 89a`.

4.4.2 Transplant the virtual environment

It turns out that the script “activate” to engage the virtual environment contains an absolute path, in the definition of `VIRTUAL_ENV`

```
<set paths after transplantation 18b> ≡
    transdir='mktemp -d -t trans.XXXXXX'
    cd $transdir
    cat <<EOF >redef.awk
    #!/usr/bin/gawk -f
    BEGIN { envd="$envdir/venv"}

    /^VIRTUAL_ENV=/ { print "VIRTUAL_ENV=\"" envd "\""
                      next
                      }

    {print}
    EOF

    mv $envdir/venv/bin/activate .
    gawk -f redef.awk ./activate > $envdir/venv/bin/activate
    cd $projroot
    rm -rf $transdir
◇
```

Fragment referenced in 90.

Uses: `activate 17b`, `print 82b`.

4.4.3 KafNafParserPy

A cornerstone Pythonmodule for the pipeline is [KafNafParserPy](#). Currently it is extremely easy installed:

```
<install kafnafparserpy 18c> ≡
    pip install KafNafParserPy
◇
```

Fragment referenced in 15e.

Uses: `install 89a`.

4.4.4 Python packages

Install python packages:

lxml:

pyyaml: for coreference-graph

pynaf:

requests: for networkx

networkx: for corefbase.

```
< install python packages 19a > ≡
    pip install lxml
    pip install pyyaml
    pip install --upgrade git+https://github.com/ixa-ehu/pynaf.git
    pip install --upgrade requests
    pip install --upgrade networkx
    ◇
```

Fragment defined by 19a, 66a.

Fragment referenced in 15e.

Defines: `lxml` Never used, `networkx` Never used, `pyyaml` Never used.

Uses: `install` 89a.

4.5 Perl

Install Perl locally, to be certain that Perl is available and to enable to install packages that we need (in any case: `XML::LibXML`).

```
< download stuff 19b > ≡
    < need to wget (19c perl-5.22.1.tar.gz, 19d http://www.cpan.org/src/5.0/perl-5.22.1.tar.gz ) 11b >
    ◇
```

Fragment defined by 11ac, 14c, 19b, 34b, 40e, 42b, 60d.

Fragment referenced in 9c.

```
< install perl 19e > ≡
    tmpdir='mktemp -d -t perl.XXXXXX'
    cd $tmpdir
    tar -xzf $snapshotsocket/$snapshotdirectory/perl-5.22.1.tar.gz
    cd perl-5.22.1
    ./Configure -des -Dprefix=$envdir/perl
    make
    make test
    make install
    cd $progroot
    rm -rf $tmpdir
    ◇
```

Fragment defined by 19ef, 20a.

Fragment referenced in 22a.

Uses: `install` 89a.

Make sure that modules use the correct Perl

```
< install perl 19f > ≡
    echo 'export PERL_HOME=$envdir/perl' >> /home/paul/projecten/pipelines/nlpp/env/bin/javapython
    echo 'export PATH=$PERL_HOME/bin:$PATH' >> /home/paul/projecten/pipelines/nlpp/env/bin/javapython
    export PERL_HOME=$envdir/perl
    export PATH=$PERL_HOME/bin:$PATH
    ◇
```

Fragment defined by 19ef, 20a.

Fragment referenced in 22a.

Uses: `PATH` 7e.

Install what is called `XML::XMLLib` in the Perl world.

It should be done with the following statement:

```
perl -MCPAN -e 'install XML::LibXML'
```

but that doesn't seem to work in all cases. It worked during an installation in ArchLinux, but not in an installation in Ubuntu a few weeks later.

Therefore, get the lib from the snapshot.

```
< install perl 20a > ≡
    cd $envdir/perl/lib
    tar -xzf $snapshotsocket/t_nlpp_resources/20160520_nlpp_perllib.tgz
◇
```

Fragment defined by 19ef, 20a.

Fragment referenced in 22a.

5 Installation of the modules

This section describes how the modules are obtained from their (open-)source and installed.

5.1 Conditional installation of the modules

Next section generates a script that installs everything.

Installation is very time-intensive. To prevent that everything is re-installed every time that the module-installer is run, there is a list of variables, the *modulelist*, that are set when a module has been installed. To re-install that module, remove the variable from the list and then re-run the installer. It maintains a list of the modules and utilities that it has installed and installs only modules and utilities that are not on the list. So in order to re-install a module that has already been installed, remove it from the list and then re-run the module-installer.

The modulelist is in fact a script named `/home/paul/projecten/pipelines/nlpp/installed_modules` that sets Bash variables. It ought to be sourced if it is present.

Initially the list is not present. When a module or a utility has been installed, an instruction to set a variable is written in or appended to the list.

```
< read the list of installed modules 20b > ≡
    if
    [ -e /home/paul/projecten/pipelines/nlpp/installed_modules ]
    then
    source /home/paul/projecten/pipelines/nlpp/installed_modules
    fi
◇
```

Fragment referenced in 22a.

```
< begin conditional install 20c > ≡
    if
    [ ! $01 ]
    then
    ◇
```

Fragment referenced in 13d, 22a, 23aj, 24aj, 25ahq, 26a.

```

< else conditional install 21a > ≡
    else
    ◇

```

Fragment never referenced.

```

< end conditional install 21b > ≡
    echo "export @1=0" >> /home/paul/projecten/pipelines/nlpp/installed_modules
    fi
    ◇

```

Fragment referenced in [13d](#), [22a](#), [23aj](#), [24aj](#), [25ahq](#), [26a](#).

Remove a variable from the list of installed modules, e.g. after a clean-up.

```

< remove installed-variable 21c > ≡
    cd $piperoot
    mv /home/paul/projecten/pipelines/nlpp/installed_modules old.modulelist
    cat old.modulelist | gawk '/@1/ {next}; {print}' >/home/paul/projecten/pipelines/nlpp/installed_modules
    ◇

```

Fragment referenced in [15a](#).

Uses: [print 82b](#).

5.2 The installation script

The installation is performed by script `install-modules`.

The first part of the script installs the utilities:

```

"../bin/install-modules" 22a≡
    #!/bin/bash
    echo Set up environment
    < set variables that point to the directory-structure 7d, ... >
    < read the list of installed modules 20b >
    < check this first 10g, ... >
    < download everything 9c >
    < variables of install-modules 75c >
    < begin conditional install (22b shared_libs ) 20c >
        < install shared libs 12a, ... >
    < end conditional install (22c shared_libs ) 21b >
    < create javapython script 13a >
    echo ... Java
    < set up java 13d, ... >
    < begin conditional install (22d maven_installed ) 20c >
        < install maven 14g >
    < end conditional install (22e maven_installed ) 21b >
    < begin conditional install (22f java16_installed ) 20c >
        < install Java 1.6 15c >
    < end conditional install (22g java16_installed ) 21b >

    echo ... Python
    if
        [ $python_installed ]
    then
        < activate the python environment 17b, ... >
    fi
    < begin conditional install (22h python_installed ) 20c >
        < set up python 15e >
    < end conditional install (22i python_installed ) 21b >
    < begin conditional install (22j perl_installed ) 20c >
        < install perl 19e, ... >
    < end conditional install (22k perl_installed ) 21b >

    < begin conditional install (22l sematree_installed ) 20c >
        < install sematree 28a >
    < end conditional install (22m sematree_installed ) 21b >
    echo ... Alpino
    < begin conditional install (22n alpino_installed ) 20c >
        < install Alpino 30c >
    < end conditional install (22o alpino_installed ) 21b >
    echo ... Spotlight
    < begin conditional install (22p spotlight_installed ) 20c >
        < install the Spotlight server 35a, ... >
    < end conditional install (22q spotlight_installed ) 21b >
    echo ... Treetagger
    < begin conditional install (22r treetagger_installed ) 20c >
        < install the treetagger utility 31c, ... >
    < end conditional install (22s treetagger_installed ) 21b >
    echo ... Ticcutils and Timbl
    < begin conditional install (22t ticctimbl_installed ) 20c >
        < install the ticcutils utility 33a >
        < install the timbl utility 33b >
    < end conditional install (22u ticctimbl_installed ) 21b >
    echo ... Boost
    < begin conditional install (22v boost_installed ) 20c >
        < install boost 34a >
    < end conditional install (22w boost_installed ) 21b >
    echo ... VUA-pylib, SVMlight, CRFsuite
    < begin conditional install (22x miscutils_installed ) 20c >
        < install VUA-pylib 40d >
        < install SVMlight 41a >
    < end conditional install (22y miscutils_installed ) 21b >
    ◇

```

File defined by 22a, 23aj, 24aj, 25ahq, 26a.

Next, install the modules:

```
"../bin/install-modules" 23a≡
echo Install modules
  < begin conditional install (23b tokenizer_installed ) 20c >
    echo ... Tokenizer
    < install the tokenizer 41b >
  < end conditional install (23c tokenizer_installed ) 21b >
  < begin conditional install (23d topic_installed ) 20c >
    echo ... Topic detector
    < install the topic analyser 42a >
  < end conditional install (23e topic_installed ) 21b >
  < begin conditional install (23f morpar_installed ) 20c >
    echo ... Morphosyntactic parser
    < install the morphosyntactic parser 43d >
  < end conditional install (23g morpar_installed ) 21b >
  < begin conditional install (23h pos_installed ) 20c >
    echo "... Pos tagger (for english docs)"
    < install the pos tagger 44b >
  < end conditional install (23i pos_installed ) 21b >
◇
```

File defined by 22a, 23aj, 24aj, 25ahq, 26a.

```
"../bin/install-modules" 23j≡
  < begin conditional install (23k constparse_installed ) 20c >
    echo "... Constituent parser (for english docs)"
    < install the constituents parser 45a >
  < end conditional install (23l constparse_installed ) 21b >
  < begin conditional install (23m nerc_installed ) 20c >
    echo ... NERC
    < install the NERC module 57a >
  < end conditional install (23n nerc_installed ) 21b >
  < begin conditional install (23o ned_installed ) 20c >
    echo ... NED
    < install the NED module 60c >
  < end conditional install (23p ned_installed ) 21b >
  < begin conditional install (23q der_installed ) 20c >
    echo ... Dark-entity relinker
    < install the de-link module 61d >
  < end conditional install (23r der_installed ) 21b >
  < begin conditional install (23s nedrer_installed ) 20c >
    echo ...NED reranker
    < install the NED-reranker module 45d >
  < end conditional install (23t nedrer_installed ) 21b >
  < begin conditional install (23u wikify_installed ) 20c >
    echo ...WIKIfy module
    < install the wikify module 45g >
  < end conditional install (23v wikify_installed ) 21b >
◇
```

File defined by 22a, 23aj, 24aj, 25ahq, 26a.

```

"../bin/install-modules" 24a≡
  < begin conditional install (24b UKB_installed ) 20c >
    echo ... UKB module
    cd $modulesdir
    tar -xzf $snapshotsocket/t_nlpp_resources/20151220_EHU-ukb.v30.tgz
  < end conditional install (24c UKB_installed ) 21b >
  < begin conditional install (24d ims_wsd_installed ) 20c >
    echo ...ims-wsd module
    < install the ims-wsd module 47a >
  < end conditional install (24e ims_wsd_installed ) 21b >
  < begin conditional install (24f srl_server_installed ) 20c >
    echo ...srl-server module
    < install the srl-server module 49c >
  < end conditional install (24g srl_server_installed ) 21b >
  < begin conditional install (24h srl_dutch_nominals_installed ) 20c >
    echo ...srl-dutch-nominal module
    < install the srl-dutch-nominals module 50f >
  < end conditional install (24i srl_dutch_nominals_installed ) 21b >
  ◇

```

File defined by 22a, 23aj, 24aj, 25ahq, 26a.

```

"../bin/install-modules" 24j≡
  < begin conditional install (24k FBK_time_installed ) 20c >
    echo ... FBK-time module
    < install the FBK-time module 51c >
  < end conditional install (24l FBK_time_installed ) 21b >
  < begin conditional install (24m FBK_temprel_installed ) 20c >
    echo ... FBK-temprel module
    < install the FBK-temprel module 53b >
  < end conditional install (24n FBK_temprel_installed ) 21b >
  < begin conditional install (24o FBK_causalrel_installed ) 20c >
    echo ... FBK-causalrel module
    < install the FBK-causalrel module 54c >
  < end conditional install (24p FBK_causalrel_installed ) 21b >
  < begin conditional install (24q factuality_installed ) 20c >
    echo ... factuality module
    < install the factuality modules 55c >
  < end conditional install (24r factuality_installed ) 21b >
  ◇

```

File defined by 22a, 23aj, 24aj, 25ahq, 26a.


```

"../bin/install-modules" 25a≡
  < begin conditional install (25b corefb_installed ) 20c >
    echo ... Coreference base
    < install coreference-base 56c >
  < end conditional install (25c corefb_installed ) 21b >
  < begin conditional install (25d wsd_installed ) 20c >
    echo ... WSD
    < install the WSD module 58e >
  < end conditional install (25e wsd_installed ) 21b >
  < begin conditional install (25f ontojar_installed ) 20c >
    echo ... Ontotagger
    < install the ontotagger repository 62c >
  < end conditional install (25g ontojar_installed ) 21b >
  ◇

```

File defined by 22a, 23aj, 24aj, 25ahq, 26a.

```

"../bin/install-modules" 25h≡
  < begin conditional install (25i heidel_installed ) 20c >
    echo ... Heideltime
    < install the heideltime module 63c >
  < end conditional install (25j heidel_installed ) 21b >
  < begin conditional install (25k SRL_installed ) 20c >
    echo ... SRL
    < install the srl module 65a >
  < end conditional install (25l SRL_installed ) 21b >
  < begin conditional install (25m eventcoref_installed ) 20c >
    echo ... Event-coreference
    < install the event-coreference module 67a >
  < end conditional install (25n eventcoref_installed ) 21b >
  < begin conditional install (25o lu2synset_installed ) 20c >
    echo ... lu2synset
    < install the lu2synset converter 59e >
  < end conditional install (25p lu2synset_installed ) 21b >
  ◇

```

File defined by 22a, 23aj, 24aj, 25ahq, 26a.

```

"../bin/install-modules" 25q≡
  < begin conditional install (25r dbpner_installed ) 20c >
    echo ... dbpedia-ner
    < install the dbpedia-ner module 67d >
  < end conditional install (25s dbpner_installed ) 21b >
  < begin conditional install (25t post_SRL_installed ) 20c >
    echo ... post-SRL
    < install the post-SRL module 66b >
  < end conditional install (25u post_SRL_installed ) 21b >
  ◇

```

File defined by 22a, 23aj, 24aj, 25ahq, 26a.

```

"../bin/install-modules" 26a≡
  < begin conditional install (26b opimin_installed ) 20c >
    echo ... opinion-miner
    < install the opinion-miner 69c, ... >
  < end conditional install (26c opimin_installed ) 21b >

  echo Final
  ◇

```

File defined by 22a, 23aj, 24aj, 25ahq, 26a.

```

< make scripts executable 26d > ≡
  chmod 775 ../bin/install-modules
  ◇

```

Fragment defined by 26d, 37a, 88c.

Fragment referenced in 88d.

Uses: install 89a.

5.3 Check availability of resources

Test for some resources that we need and that may not be available on this host.

```

< check this first 26e > ≡
  < check whether program is present (26f git ) 26j >
  < check whether program is present (26g tar ) 26j >
  < check whether program is present (26h unzip ) 26j >
  < check whether program is present (26i tcsh ) 26j >
  < check whether mercurial is present 27a >
  ◇

```

Fragment defined by 10g, 26e.

Fragment referenced in 22a.

```

< check whether program is present 26j > ≡
  which @1
  if
    [ $? -ne 0 ]
  then
    echo Please install @1.
    exit 1
  fi
  ◇

```

Fragment referenced in 26e.

Uses: install 89a.

```

⟨ check whether mercurial is present 27a ⟩ ≡
    which hg
    if
        [ $? -ne 0 ]
    then
        echo Please install Mercurial.
        exit 1
    fi
    ◇

```

Fragment referenced in 26e.

Defines: `hg` Never used.

Uses: `install` 89a.

5.4 Parameters in module-scripts

Some modules need parameters. All modules need a language specification. The language can be passed as exported variable `naflang`, but it can also be passed as argument `-l`. Furthermore, some modules need contact with a Spotlight server. With the arguments `-h` and `-b` the host and port of a running Spotlight-server can be passed.

The code to obtain command-line arguments in Bash has been obtained from [Stackoverflow](#). The following fragment reads the arguments `-l language`, `-h spotlighthost` and `-p spotlightport`:

```

⟨ get commandline-arguments 27b ⟩ ≡
    while [[ $# > 1 ]]
    do
        key="$1"

        case $key in
            -l|--language)
                naflang="$2"
                shift # past argument
                ;;
            -h|--spothost)
                spotlighthost="$2"
                shift # past argument
                ;;
            -p|--spotport)
                spotlightport="$2"
                shift # past argument
                ;;
            *)
                # unknown option
                ;;
        esac
        shift # past argument or value
    done
    ◇

```

Fragment referenced in 36a.

Uses: `naflang` 73.

5.5 Install utilities and resources

5.5.1 Process synchronisation

We will see that we sometimes have to install server-applications. However, it is possible that multiple processes are running pipeline modules in parallel, and then it may occur that two instances of a module try to install the same server-application. Therefore, we must make sure that only one application at a time is able to start the server.

The program `sematree`, found at <http://www.pixelbeat.org/scripts/sematree/> enables to do this. When invoked with argument “acquire”, the name of a “lockfile” and a time to wait (-1 means “wait an indefinite time”), it checks whether the lockfile exists. If that is the case, it either waits or fails. When the lockfile is not (or no longer) present, `sematree` creates the lockfile.

When installing `sematree`, set the default directory for lock-files. We set this as a subdirectory of the `env` tree. However, in some cases, e.g. when multiple compute nodes use the same file-system, we need a directory on the local filesystem of the node itself. In that case you can set variable `semaworkdir` to override the default directory.

```
< install sematree 28a > ≡
    cat $snapshotsocket/t_nlpp_resources/sematree \
    | sed "s|workdir|semaworkdir|g" \
    | sed "s|/var/run|/home/paul/projecten/pipelines/nlpp/env/etc/sematree|g" \
    > $envbindir/sematree
    chmod 775 $envbindir/sematree
    ◇
```

Fragment referenced in 22a.

5.5.2 Prefix of scripts that run modules

Each module will be run by a Bash script located in subdirectory `bin`. The start of these scripts will have similar content. Insert the following macro to include this similar content, with the name of the module-directory as argument:

```
< start of module-script 28b > ≡
    #!/bin/bash
    < get the path to the module-script 29a >
    source /home/paul/projecten/pipelines/nlpp/env/bin/progenv
    export LC_ALL=en_US.UTF-8
    export LANG=en_US.UTF-8
    export LANGUAGE=en_US.UTF-8
    ROOT=$piperoot
    MODDIR=$modulesdir/@1
    < run in subshell when naflang is not known 30a >
    < run only if language is English or Dutch 30b >
    ◇
```

Fragment referenced in 41c, 43be, 44c, 45be, 46ad, 47b, 50c, 51a, 52a, 54a, 55ad, 56d, 58ac, 59c, 60a, 61b, 62adf, 63a, 64d, 65b, 66c, 67b, 68a, 69a, 71a.

Set variable `scriptpath` to the full path of the script that is running, order to be able to re-run it.

```

⟨get the path to the module-script 29a⟩ ≡
    scriptdir="$( cd "$( dirname "${BASH_SOURCE[0]}" )" && pwd )"
    scriptname=${0##*/}
    scriptpath=$scriptdir/$scriptname
    ◇

```

Fragment referenced in 28b.

Defines: `scriptpath` 30a.

5.5.3 Language detection

The following script `../env/bin/langdetect.py` discerns the language of a NAF document. If it cannot find that attribute it prints `unknown`. The macro `set the language variable` uses this script to set variable `naflang`. All pipeline modules expect that this variable has been set.

```

"../env/bin/langdetect.py" 29b≡
    #!/usr/bin/env python
    # langdetect -- Detect the language of a NAF document.
    #
    import xml.etree.ElementTree as ET
    import sys
    import re
    xmldoc = sys.stdin.read()
    #print xmldoc
    root = ET.fromstring(xmldoc)
    # print root.attrib['lang']
    lang = "unknown"
    for k in root.attrib:
        if re.match(".*lang$", k):
            language = root.attrib[k]
    print language
    ◇

```

Uses: `print` 82b.

The module-scripts depend on the existence of variable `naflang`. In most cases this is not a problem because the scripts run in a surrounding script that sets `naflang`. However, a users may occasionally run a module-script stand-alone e.g. to debug. In that case, we can read the language from the NAF, set variable `naflang`, and then run the module-script in a subshell. We assume that variable `scriptpath` contains the path of the script itself.

The macro does the following if `naflang` has not been set:

1. Save the content of standard in to a temporary file.
2. Run `langdetect` with the temporary file as input and set the `naflang` variable.
3. Run the script `$scriptpath` (i.e. itself) with the temporary file as input.
4. Remove the temporary file.
5. Exit itself with the errorcode of the sub-script that it has run.

```

⟨ run in subshell when naflang is not known 30a ⟩ ≡
    if
        [ -z "${naflang+x}" ]
    then
        naffile='mktemp -t naf.XXXXXX'
        cat >$naffile
        naflang='cat $naffile | python $envbindir/langdetect.py'
        export naflang
        cat $naffile | $scriptpath
        result=$?
        rm $naffile
        exit $result
    fi
    ◇

```

Fragment referenced in 28b.

Uses: `naflang` 73, `scriptpath` 29a.

```

⟨ run only if language is English or Dutch 30b ⟩ ≡
    if
        [ ! "$naflang" == "nl" ] && [ ! "$naflang" == "en" ]
    then
        exit 6
    fi
    ◇

```

Fragment referenced in 28b.

Uses: `naflang` 73.

5.5.4 Alpino

Binary versions of Alpino can be obtained from the [official Alpino website](#) of Gertjan van Noort. However, it seems that older versions are not always retained there, or the location of older versions change. Therefore we have a copy in the snapshot.

Module

```

⟨ install Alpino 30c ⟩ ≡
    if
        [ ! $alpino_installed ]
    then
        cd $modulesdir
        tar -xzf $snapshotsocket/t_nlpp_resources/Alpino-x86_64-linux-glibc2.5-20706-
        sicstus.tar.gz
        echo "ex-
port alpino_installed=0" >> /home/paul/projecten/pipelines/nlpp/installed_modules
    fi
    ◇

```

Fragment referenced in 22a.

Currently, alpino is not used as a pipeline-module on its own, but it is included in other pipeline-modules. Modules that use Alpino should set the following variables:

```

< set alpinohome 31a > ≡
    export ALPINO_HOME=$modulesdir/Alpino
    ◇

```

Fragment referenced in 43e.

Defines: ALPINO_HOME Never used.

Remove the tarball when cleaning up:

```

< clean up 31b > ≡
    rm -rf $snapshotsocket/t_nlpp_resources/Alpino-x86_64-linux-glibc2.5-20706-
    sicstus.tar.gz
    ◇

```

Fragment defined by 13g, 15a, 31b, 79c.

Fragment referenced in 78d.

5.5.5 Treetagger

Installation of Treetagger goes as follows (See [Treetagger's homepage](#)):

1. Download and unpack the Treetagger tarball. This generates the subdirectories `bin`, `cmd` and `doc`
2. Download and unpack the tagger-scripts tarball

The location where Treetagger comes from and the location where it is going to reside:

```

< install the treetagger utility 31c > ≡
    TREETAGDIR=treetagger
    TREETAG_BASIS_URL=http://www.cis.uni-muenchen.de/%7Eschmid/tools/TreeTagger/data/
    TREETAGURL=http://www.cis.uni-muenchen.de/%7Eschmid/tools/TreeTagger/data/
    ◇

```

Fragment defined by 31cde, 32abcd.

Fragment referenced in 22a.

The source tarball, scripts and the installation-script:

```

< install the treetagger utility 31d > ≡
    TREETAGSRC=tree-tagger-linux-3.2.tar.gz
    TREETAGSCRIPTS=tagger-scripts.tar.gz
    TREETAG_INSTALLSCRIPT=install-tagger.sh
    ◇

```

Fragment defined by 31cde, 32abcd.

Fragment referenced in 22a.

Uses: `install` 89a.

Parametersets:

```

< install the treetagger utility 31e > ≡
    DUTCHPARS_UTF_GZ=dutch-par-linux-3.2-utf8.bin.gz
    DUTCH_TAGSET=dutch-tagset.txt
    DUTCHPARS_2_GZ=dutch2-par-linux-3.2-utf8.bin.gz
    ◇

```

Fragment defined by 31cde, 32abcd.

Fragment referenced in 22a.

Download everything in the target directory:

```

< install the treetagger utility 32a > ≡
    mkdir -p $modulesdir/$TREETAGDIR
    cd $modulesdir/$TREETAGDIR
    wget $TREETAGURL/$TREETAGSRC
    wget $TREETAGURL/$TREETAGSCRIPTS
    wget $TREETAGURL/$TREETAG_INSTALLSCRIPT
    wget $TREETAGURL/$DUTCHPARS_UTF_GZ
    wget $TREETAGURL/$DUTCH_TAGSET
    wget $TREETAGURL/$DUTCHPARS_2_GZ
    ◇

```

Fragment defined by 31cde, 32abcd.

Fragment referenced in 22a.

Run the install-script:

```

< install the treetagger utility 32b > ≡
    chmod 775 $TREETAG_INSTALLSCRIPT
    ./$TREETAG_INSTALLSCRIPT
    ◇

```

Fragment defined by 31cde, 32abcd.

Fragment referenced in 22a.

Make the treetagger utilities available for everybody.

```

< install the treetagger utility 32c > ≡
    chmod -R o+rx $modulesdir/$TREETAGDIR/bin
    chmod -R o+rx $modulesdir/$TREETAGDIR/cmd
    chmod -R o+r $modulesdir/$TREETAGDIR/doc
    chmod -R o+rx $modulesdir/$TREETAGDIR/lib
    ◇

```

Fragment defined by 31cde, 32abcd.

Fragment referenced in 22a.

Remove the tarballs:

```

< install the treetagger utility 32d > ≡
    rm $TREETAGSRC
    rm $TREETAGSCRIPTS
    rm $TREETAG_INSTALLSCRIPT
    rm $DUTCHPARS_UTF_GZ
    rm $DUTCH_TAGSET
    rm $DUTCHPARS_2_GZ
    ◇

```

Fragment defined by 31cde, 32abcd.

Fragment referenced in 22a.

5.5.6 Timbl and Ticcutils

Timbl and Ticcutils are installed from their source-tarballs. The installation is not (yet?) completely reproducibe because it uses the C-compiler that happens to be available on the host. Installation involves:

1. Download the tarball in a temporary directory.
2. Unpack the tarball.

3. cd to the unpacked directory and perform `./configure`, `make` and `make install`. Note the argument that causes the files to be installed in the `lib` and the `bin` sub-directories of the `env` directory.

```

< install the ticcutils utility 33a > ≡
    URL=http://software.ticc.uvt.nl/ticcutils-0.7.tar.gz
    TARB=ticcutils-0.7.tar.gz
    DIR=ticcutils-0.7
    < unpack ticcutils or timbl 33c >
    ◇

```

Fragment referenced in 22a, 33d.

```

< install the timbl utility 33b > ≡
    TARB=timbl-6.4.6.tar.gz
    DIR=timbl-6.4.6
    < unpack ticcutils or timbl 33c >
    ◇

```

Fragment referenced in 22a, 33d.

```

< unpack ticcutils or timbl 33c > ≡
    SUCCES=0
    ticbelldir='mktemp -t -d tickbel.XXXXXX'
    cd $ticbelldir
    tar -xzf $snapshotsocket/t_nlpp_resources/$TARB
    cd $DIR
    sh ./bootstrap.sh
    ./configure --prefix=$envdir
    make
    make install
    cd $piperoot
    rm -rf $ticbelldir
    ◇

```

Fragment referenced in 33ab.

Uses: install 89a.

When the installation has been transplanted, Timbl and Ticcutils have to be re-installed.

```

< re-install modules after the transplantation 33d > ≡
    < install the ticcutils utility 33a >
    < install the timbl utility 33b >
    ◇

```

Fragment referenced in 90.

5.5.7 The Boost library

Theoretically, it is possible to download a tarball with boost from [it's repository](#) and then install it. However, I did not succeed in doing this. Therefore, I ripped the installed boost from Surfsara's Hadoop installation and put it in the `env` dir.

```

< install boost 34a > ≡
    cd $envdir
    tar -xzf $snapshotsocket/t_nlpp_resources/20160103_boost_1_54_bin.tgz
    ◇

```

Fragment referenced in 22a.

5.5.8 Spotlight

A Spotlight server occupies a lot of memory and we need two of them, one for each language. We may be lucky and have a spotlight server running somewhere. Otherwise we have to install the server ourselves.

Install Spotlight in the way that Itziar Aldabe (<mailto:itziar.aldabe@ehu.es>) described:

The NED module works for English, Spanish, Dutch and Italian. The module returns multiple candidates and correspondences for all the languages. If you want to integrate it in your Dutch or Italian pipeline, you will need:

1. The jar file with the dbpedia-spotlight server. You need the version that Aitor developed in order to correctly use the "candidates" option. You can copy it from the English VM. The jar file name is `dbpedia-spotlight-0.7-jar-with-dependencies-candidates.jar`
2. The Dutch/Italian model for the dbpedia-spotlight. You can download them from: <http://spotlight.sztaki.hu/downloads/>
3. The jar file with the NED module: `ixa-pipe-ned-1.0.jar`. You can copy it from the English VM too.
4. The file: `wikipedia-db.v1.tar.gz`. You can download it from: <http://ixa2.si.ehu.es/ixa-pipes/models/wikipedia-db.v1.tar.gz>. This file contains the required information to do the mappings between the wikipedia-entries. The zip file contains three files: `wikipedia-db`, `wikipedia-db.p` and `wikipedia-db.t`

To start the dbpedia server: Italian server:

```

java -jar -Xmx8g dbpedia-spotlight-0.7-jar-with-dependencies-candidates.jar \
    it http://localhost:2050/rest

```

Dutch server:

```

java -jar -Xmx8g dbpedia-spotlight-0.7-jar-with-dependencies-candidates.jar nl http://localhost:2

```

We set 8Gb for the English server, but the Italian and Dutch Spotlight will require less memory.

So, let us do that.

First, get the Spotlight model data that we need:

```

< download stuff 34b > ≡

    < need to wget (34c nl.tar.gz,34d http://spotlight.sztaki.hu/downloads/archive/2014/nl.tar.gz ) 11b >
    < need to wget (34e en_2+2.tar.gz,34f http://spotlight.sztaki.hu/downloads/archive/2014/en_2+2.tar.gz ) 11b >
    < need to wget (34g wikipedia-db.v1.tar.gz,34h http://ixa2.si.ehu.es/ixa-pipes/models/wikipedia-db.v1.tar.

    ◇

```

Fragment defined by 11ac, 14c, 19b, 34b, 40e, 42b, 60d.

Fragment referenced in 9c.

```

⟨ install the Spotlight server 35a ⟩ ≡
    cd $envdir
    tar -xzf $snapshotsocket/t_nlpp_resources/spotlightnl.tgz
    cd $envdir/spotlight
    tar -xzf $snapshotsocket/t_nlpp_resources/nl.tar.gz
    tar -xzf $snapshotsocket/t_nlpp_resources/en_2+2.tar.gz
    ◇

```

Fragment defined by 35ac.

Fragment referenced in 22a.

```

⟨ get spotlight model ball 35b ⟩ ≡
    if
        [ -e $snapshotsocket/t_nlpp_resources/@1 ]
    then
        tar -xzf $snapshotsocket/t_nlpp_resources/@1
    else
        wget http://spotlight.sztaki.hu/downloads/archive/2014/@1
        tar -xzf @1
        rm @1
    fi
    ◇

```

Fragment never referenced.

We choose to put the Wikipedia database in the spotlight directory.

```

⟨ install the Spotlight server 35c ⟩ ≡
    cd $envdir/spotlight
    tar -xzf $snapshotsocket/$snapshotdirectory/wikipedia-db.v1.tar.gz
    ◇

```

Fragment defined by 35ac.

Fragment referenced in 22a.

The macro `check/start spotlight` does the following:

1. Check whether spotlight runs on the default spotlighthost.
2. If that is not the case, and the default host is not `localhost`, check whether Spotlight runs on localhost.
3. If a running spotlightserver is still not found, start a spotlightserver on localhost.

Start Spotlight if it doesn't run already. Spotlight ought to run on localhost unless variable `spotlighthost` exists. In that case, check whether a Spotlight server can be contacted on that host. Otherwise, change `spotlighthost` to `localhost` and check whether a Spotlight server runs there. If that is not the case, start up a Spotlight server on localhost.

The following script, `check_start_spotlight`, has the following three optional arguments:

language: Default is exported variable `naflang` if it exists, or `en`.

spotlighthost: Name of a host that probably runs a Spotlightserver. Default: exported variable `spotlighthost` if it exists, or `localhost`.

spotlightport: Default: exported variable `spotlightport` if it exists or either 2020 or 2060 for English resp. Dutch.

```

"../bin/check_start_spotlight" 36a≡
    #!/bin/bash
    source /home/paul/projecten/pipelines/nlpp/env/bin/progenv
    ⟨ get cmdline-arguments 27b ⟩
    ⟨ set default arguments for Spotlight 36b ⟩
    ◇

```

File defined by 36ac.

Fill in default values when they cannot be found in exported variables nor in command-line arguments.

```

⟨ set default arguments for Spotlight 36b ⟩ ≡
    if
        [ "$spotlighthost" == "" ]
    then
        spotlighthost=130.37.53.33
    fi
    if
        [ "$spotlightport" == "" ]
    then
        if
            [ "$naflang" == "nl" ]
        then
            spotlightport=2060
        else
            spotlightport=2020
        fi
    fi
    ◇

```

Fragment referenced in 36a.

Uses: `naflang` 73.

```

"../bin/check_start_spotlight" 36c≡
    ⟨ check listener on host, port (36d $spotlighthost,36e $spotlightport) 37d ⟩
    if
        [ $spotlightrunning -ne 0 ]
    then
        if
            [ ! "$spotlighthost" == "localhost" ]
        then
            export spotlighthost="localhost"
            ⟨ check listener on host, port (36f $spotlighthost,36g $spotlightport) 37d ⟩
        fi
    fi
    if
        [ $spotlightrunning -ne 0 ]
    then
        ⟨ start the Spotlight server on localhost 39a, ... ⟩
    fi
    echo $spotlighthost:$spotlightport
    ◇

```

File defined by 36ac.

```

<make scripts executable 37a> ≡
    chmod 775 ../bin/check_start_spotlight
    ◇

```

Fragment defined by 26d, 37a, 88c.

Fragment referenced in 88d.

Use function `check_start_spotlight` to find and exploit a running Spotlight-server or to die (with exit code 5) if no server can be found or created. The macro uses implicitly the exported variables `spotlighthost` and `spotlightport` if they exist.

```

<find a spotlightserver or exit 37b> ≡
    spothostport='/home/paul/projecten/pipelines/nlpp/bin/check_start_spotlight -
    l $naflang'
    export spotlighthost='echo $spothostport | gawk -F ":" '{print $1}''
    export spotlightport='echo $spothostport | gawk -F ":" '{print $2}''
    echo "Spotlight server found on $spothostport." >&2
    if
        [ "$spotlighthost" == "none" ]
    then
        echo "No Spotlight-server found."
        exit 5
    fi
    ◇

```

Fragment referenced in 46a, 61b.

Uses: `naflang` 73, `print` 82b.

Set the port-number and the language resource for Spotlight, dependent of the language that the user gave as argument.

```

<get spotlight language parameters 37c> ≡
    if
        [ "$naflang" == "nl" ]
    then
        spotlightport=2060
    else
        spotlightport=2020
    fi
    ◇

```

Fragment never referenced.

Uses: `naflang` 73.

The following macro has a hostname and a port-number as arguments. It checks whether something in the host listens on the port and sets variable `success` accordingly:

```

<check listener on host, port 37d> ≡
    exec 6<>/dev/tcp/@1/@2 2>/dev/null
    spotlightrunning=$?
    exec 6<&-
    exec 6>&-
    ◇

```

Fragment referenced in 36c, 40a.

If variable `spotlighthost` does not exist, set it to localhost. Test whether a Spotlightserver runs on `spotlighthost`. If that fails and `spotlighthost` did not point to localhost, try localhost.

If the previous attempts were not succesfull, start the spotlightserver on localhost.

If some spotlightserver has been contacted, set variable `spotlightrunning`. Otherwise exit. At the end variable `spotlighthost` ought to contain the address of the Spotlight-host.

```

< try to obtain a running spotlightserver 38a > ≡
  < test whether spotlighthost runs (38b $spotlighthost ) 38e >
  if
    [ ! $spotlightrunning ]
  then
    if
      [ "$spotlighthost" != "localhost" ]
    then
      export spotlighthost=localhost
      < test whether spotlighthost runs (38c $spotlighthost ) 38e >
    fi
  fi
  if
    [ ! $spotlightrunning ]
  then
    < start the Spotlight server on localhost 39a, ... >
    < test whether spotlighthost runs (38d $spotlighthost ) 38e >
  fi
  if
    [ ! $spotlightrunning ]
  then
    echo "Cannot start spotlight"
    exit 4
  fi
  ◇

```

Fragment never referenced.

Test whether the Spotlightserver runs on a given host. The “spotlight-test” does not really test Spotlight, but it tests whether something is listening on the port and host where we expect Spotlight. I found the test-construction that is used here on [Stackoverflow](#). If the test is positive, set variable `spotlightrunning` to 0. Otherwise, unset that variable.

```

< test whether spotlighthost runs 38e > ≡
  exec 6<>/dev/tcp/01/2060
  if
    [ $? -eq 0 ]
  then
    export spotlightrunning=0
  else
    spotlightrunning=
  fi
  exec 6<&-
  exec 6>&-
  ◇

```

Fragment referenced in [38a](#).

When trying to start the Spotlight-server on localhost, take care that only one process does this. So we do this:

1. Try to acquire a lock without waiting for it.
2. If we got the lock, run the Spotlight java program in background.
3. If we got the lock, release it.

4. If we did not get the lock, wait for the lock to be released by the process that started the spotlight-server.

But first, we specify the resources for the Spotlight-server.

```

⟨ start the Spotlight server on localhost 39a ⟩ ≡
  if
    [ "$naflang" == "nl" ]
  then
    spotresource="nl"
  else
    spotresource="en_2+2"
  fi
  spotlightjar=dbpedia-spotlight-0.7-jar-with-dependencies-candidates.jar
◇

```

Fragment defined by 39ab.

Fragment referenced in 36c, 38a.

Uses: naflang 73.

```

⟨ start the Spotlight server on localhost 39b ⟩ ≡
  local oldd='pwd'
  cd /home/paul/projecten/pipelines/nlpp/env/spotlight
  $envbindir/sematree acquire spotlock 0
  gotit=$?
  if
    [ $gotit == 0 ]
  then
    java -jar -Xmx8g $spotlightjar $spotresource \
      http://localhost:$spotlightport/rest &
    ⟨ wait until the spotlight server is up or faulty 40a ⟩
    $envbindir/sematree release spotlock
  else
    ⟨ wait until the spotlight server is up or faulty 40a ⟩
  fi
  cd $oldd
◇

```

Fragment defined by 39ab.

Fragment referenced in 36c, 38a.

When the Sportlight server has been started, it takes up to a minute until it really listens on its port. When there is something wrong, it will never listen, of course. Therefore, we give it three minutes. If after that time still nothing listens, we set `spotlighthost` to `none`, indicating that something has gone wrong.

```

⟨ wait until the spotlight server is up or faulty 40a ⟩ ≡
    trial=0
    maxtrials=12
    while
        trial=$((trial+1))
        ⟨ check listener on host, port (40b $spotlighthost,40c $spotlightport ) 37d ⟩
        [ $spotlightrunning -ne 0 ] && [ $trial -le $maxtrials ]
    do
        sleep 10
    done
    if
        [ $spotlightrunning -ne 0 ]
    then
        export spotlighthost="none"
    fi
◇

```

Fragment referenced in 39b.

Start the Spotlight if it is not already running. First find out what the host is on which we may expect to find a listening Spotlight.

Variable `spotlighthost` contains the address of the host where we expect to find Spotlight. If the expectation does not come true, and the Spotlighthost was not localhost, test whether Spotlight can be found on localhost. If the spotlight-server cannot be found, start it up on localhost.

5.5.9 VUA-pylib

Module VUA-pylib is needed for the opinion-miner. Install it in the Python library

```

⟨ install VUA-pylib 40d ⟩ ≡
    cd $envdir/python
    git clone https://github.com/cltl/VUA_pylib.git
◇

```

Fragment referenced in 22a.

5.5.10 SVMlight

SVMlight supplies a Support Vector Machine. It is used by the opinion-miner. SVMlight can be obtained from [the site](#) where it is documented.

```

⟨ download stuff 40e ⟩ ≡
    ⟨ need to wget (40f svm_light.tar.gz,40g http://download.joachims.org/svm_light/current/svm_light.tar.gz )
◇

```

Fragment defined by 11ac, 14c, 19b, 34b, 40e, 42b, 60d.

Fragment referenced in 9c.

Installation goes like this:


```

<install SVMlight 41a> ≡
  tmpdir='mktemp -d -t SVMlight.XXXXXX'
  cd $tmpdir
  #tar -xzf $snapshotsocket/$snapshotdirectory/m4_SVMlightball
  wget http://download.joachims.org/svm_light/current/svm_light.tar.gz
  tar -xzf svm_light.tar.gz
  make
  cp svm_classify /home/paul/projecten/pipelines/nlpp/env/bin/
  cp svm_learn /home/paul/projecten/pipelines/nlpp/env/bin/
  cd /home/paul/projecten/pipelines/nlpp
  rm -rf $tmpdir
  ◇

```

Fragment referenced in 22a.

Uses: svm_classify 70b, svm_learn 70b.

5.6 Install modules

5.6.1 Install tokenizer

Module The tokenizer is just a jar that has to be run in Java. Although the jar is directly available from <http://ixa2.si.ehu.es/ixa-pipes/download.html>, we prefer to compile the package in order to make this thing ready for reproducible set-ups.

To install the tokenizer, we proceed as follows:

1. Clone the source from github into a temporary directory.
2. Compile to produce the jar file with the tokenizer.
3. move the jar file into the jar directory.
4. remove the tmpdir with the sourcecode.

```

<install the tokenizer 41b> ≡
  tmpdir='mktemp -d -t tok.XXXXXX'
  cd $tmpdir
  git clone https://github.com/ixa-ehu/ixa-pipe-tok.git
  cd ixa-pipe-tok
  git checkout 56f83ce4b61680346f15e5d4e6de6293764f7383
  mvn clean package
  mv target/ixa-pipe-tok-1.8.0.jar $jarsdir
  cd $piperoot
  rm -rf $tmpdir
  ◇

```

Fragment referenced in 23a.

Script The script runs the tokenizerscript.

```

"../bin/tok" 41c≡
  <start of module-script (41d $jarsdir ) 28b>
  JARFILE=$jarsdir/ixa-pipe-tok-1.8.0.jar
  java -Xmx1000m -jar $JARFILE tok -l $naflang --inputkaf
  ◇

```

5.6.2 Topic analyser

Install the topic tool `ixa-pipe-topic` that is based on [JEX](#).

Installation goes as follows:

1. Clone from Github.
2. Download JEX resources and JEX jar libraries and put them at proper places.
3. Download and run a utility, `install-to-project-repo.py`, that puts the JEX libraries in a place where Maven can find them.
4. run maven

```

< install the topic analyser 42a > ≡
  cd $modulesdir
  git clone https://github.com/ialdabe/ixa-pipe-topic.git
  cd ixa-pipe-topic
  git checkout 40be8debb88093b426ae3520d60df60161968e27
  tempdir='mktemp -d -t topinambour.XXXXXX'
  moddir=$modulesdir/ixa-pipe-topic
  < install the jex resources and libraries 42g >
  < compile the topic-tool jar 43a >
  cd $modulesdir
  rm -rf $tempdir
  ◇

```

Fragment referenced in 23a.

The two zip-balls `en-eurovoc-1.0.zip` and `nl-eurovoc-1.0.zip` contain resources in a subdirectory `resources` and jar libs in a subdirectory `lib`. The jars in the two zip-balls are identical, so the jars from one of the balls can be copied to the `lib` subdirectory of the module where the compilation-tool expects them. The `resources` directories are placed in subdirectories `en` resp. `nl` of the `jex` subdirectory of the module directory.

```

< download stuff 42b > ≡

  < need to wget (42c en-eurovoc-1.0.zip,42d http://optima.jrc.it/Resources/Eurovoc/indexing/en-eurovoc-1.0.
  < need to wget (42e nl-eurovoc-1.0.zip,42f http://optima.jrc.it/Resources/Eurovoc/indexing/nl-eurovoc-1.0.
  ◇

```

Fragment defined by 11ac, 14c, 19b, 34b, 40e, 42b, 60d.

Fragment referenced in 9c.

```

< install the jex resources and libraries 42g > ≡
  moddir=$modulesdir/ixa-pipe-topic
  cd $moddir
  mkdir -p jex/en
  mkdir -p jex/nl
  mkdir -p lib
  cd $tempdir
  unzip -q $snapshotsocket/$snapshotdirectory/en-eurovoc-1.0.zip
  unzip -q $snapshotsocket/$snapshotdirectory/nl-eurovoc-1.0.zip
  cp -r en-eurovoc-1.0/resources $moddir/jex/en/
  cp -r nl-eurovoc-1.0/resources $moddir/jex/nl/
  cp -r nl-eurovoc-1.0/lib/*.jar $moddir/lib/
  ◇

```

Fragment referenced in 42a.

To make the jar's in the `lib` directory accessible for Maven, we use the `install-to-project-repo` utility. So, unpack and run this utility and finally, run Maven:

```

< compile the topic-tool jar 43a > ≡
  git clone https://github.com/carchrae/install-to-project-repo.git
  cd $modulesdir/ixa-pipe-topic
  python $tempdir/install-to-project-repo/install-to-project-repo.py
  mvn clean install
  ◇

```

Fragment referenced in 42a.

Uses: install 89a.

Script: The topic module uses a temporary directory to store intermediate results. To tell the Java program where the temp storage is, a config file has to be generated on the fly.

```

"../bin/topic" 43b ≡
  < start of module-script (43c ixa-pipe-topic ) 28b >
  tempdir='mktemp -d -t jex.XXXXXX'
  mkdir $tempdir/documents
  mkdir $tempdir/results
  cat $MODDIR/default.prop \
    | sed 's|jex/resources|'${MODDIR}'/jex/LANG/resources|g' \
    | sed 's|jex/result|'${tempdir}'/jex/result|g' \
    | sed 's|LANG|'${naflang}'|g' \
    >$tempdir/conf.prop
  java -Xmx1000m -jar $MODDIR/target/ixa-pipe-topic-1.0.3.jar -p $tempdir/conf.prop
  rm -rf $tempdir
  ◇

```

5.6.3 Morphosyntactic parser

Module

```

< install the morphosyntactic parser 43d > ≡
  MODNAM=morphsynparser
  DIRN=morphosyntactic_parser_nl
  GITU=https://github.com/cltl/morphosyntactic_parser_nl.git
  GIRC=d5f002605d7c06545f24c84386342b79e5cb9c86
  < install from github 10a >
  cd $modulesdir/morphosyntactic_parser_nl
  git checkout d5f002605d7c06545f24c84386342b79e5cb9c86
  ◇

```

Fragment referenced in 23a.

Script: The morpho-syntactic module parses the sentences with Alpino. Alpino takes a lot of time to handle long sentences. Therefore the morpho-syntactic module has an option `-t` to set a time-out (in minutes) for sentence parsing.

```

"../bin/mor" 43e ≡
  < start of module-script (43f morphosyntactic_parser_nl ) 28b >
  < get the mor time-out parameter 44a >
  < set alpinohome 31a >
  cat | python $MODDIR/core/morph_syn_parser.py $timeoutarg
  ◇

```

Use `getopts` to read the `-t` option.

```

⟨ get the mor time-out parameter 44a ⟩ ≡
    OPTIND=1
    stimeout=
    timeoutarg=
    while getopts "t:" opt; do
        case "$opt" in
            t) stimeout=$OPTARG
                ;;
            esac
        done
        shift $((OPTIND-1))
        if
            [ $stimeout ]
        then
            timeoutarg="-t $stimeout"
        fi
    fi
    ◇

```

Fragment referenced in 43e.

5.6.4 Pos tagger

In the Dutch pipeline the morpho-syntactic parser fulfills the role of Pos tagger. In the English pipeline we use the pos-tagger from EHU.

Module

```

⟨ install the pos tagger 44b ⟩ ≡
    cd $modulesdir
    tar -xzf $snapshotsocket/t_nlpp_resources/20151220_EHU-pos.v30.tgz
    cd $modulesdir/ixa-pipe-topic
    ◇

```

Fragment referenced in 23a.

Script

```

"../bin/pos" 44c ≡
    ⟨ start of module-script (44d EHU-pos.v30 ) 28b ⟩
    java -Xmx1000m -jar ${MODDIR}/ixa-pipe-pos-1.4.3.jar tag -m ${MODDIR}/en-maxent-
    100-c5-baseline-dict-penn.bin
    ◇

```

5.6.5 Constituent parser

Module

```

< install the constituents parser 45a > ≡
    cd $modulesdir
    tar -xzf $snapshotsocket/t_nlpp_resources/20151220_EHU-parse.v30.tgz
    cd $modulesdir/conspardir
    chmod 775 *.jar
    chmod 775 *.bin
    ◇

```

Fragment referenced in [23j](#).

Script

```

"../bin/constpars" 45b≡
    < start of module-script (45c EHU-parse.v30 ) 28b >
    java -Xmx1000m -jar ${MODDIR}/ixa-pipe-parse-1.1.1.jar parse -g sem -
    m ${MODDIR}/en-parser-chunking.bin
    ◇

```

5.6.6 NED-reranker

The NED-reranker is not open-source yet. It must be retrieved from the snapshot.

Module

```

< install the NED-reranker module 45d > ≡
    cd $modulesdir
    pip install SPARQLWrapper
    tar -xzf $snapshotsocket/t_nlpp_resources/20151220_VUA-popen-nedreranker.v30.tgz
    ◇

```

Fragment referenced in [23j](#).

Uses: [install 89a](#).

Script

```

"../bin/nedrer" 45e≡
    < start of module-script (45f VUA-popen-nedreranker.v30 ) 28b >
    cd $MODDIR
    python $MODDIR/domain_model.py
    ◇

```

5.6.7 Wikify module

Module Wikify is still obtained from the snapshot. Make sure that the jar of the module is accessible for everybody.

```

< install the wikify module 45g > ≡
    cd $modulesdir
    tar -xzf $snapshotsocket/t_nlpp_resources/20151220_EHU-wikify.v30.tgz
    chmod 775 $modulesdir/EHU-wikify.v30/ixa-pipe-wikify-1.2.1.jar
    ◇

```

Fragment referenced in [23j](#).

Script The Wikify module needs DBpedia to generate “markables”.

```
"../bin/wikify" 46a≡
  ⟨ start of module-script (46b EHU-wikify.v30 ) 28b ⟩
  ⟨ find a spotlightserver or exit 37b ⟩
  cd $MODDIR
  java -Xmx1000m -jar ${MODDIR}/ixa-pipe-wikify-1.2.1.jar -s http://$spotlighthost -
  p $spotlightport
  ◇
```

5.6.8 UKB

UKB needs boost libraries and Perl version 5. For now, we consider them installed.

Module

```
⟨ install the UKB module 46c ⟩ ≡
  ◇
```

Fragment never referenced.

Script Put the path to the boost libraries in the LD_LIBRARY_PATH variable and then run UKB.

Note that we cannot call perl implicitly with the hashbang.

```
"../bin/ukb" 46d≡
  ⟨ start of module-script (46e EHU-ukb.v30 ) 28b ⟩
  cd $MODDIR
  export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:$envdir/boost_1_54_0/stage/lib
  perl ${MODDIR}/naf_ukb/naf_ukb.pl -x ${MODDIR}/ukb/bin/ukb_wsd -K ${MODDIR}/wn30-
  ili_lkb/wn30g.bin64 -D ${MODDIR}/wn30-ili_lkb/wn30.lex - -- --dict_weight --
  dgraph_dfs --dgraph_rank ppr
  ◇
```

5.6.9 IMS-WSD

Module The package itself supplies an installation script that seems usable. However, today I am in a hurry and just install the module as it comes from the EHU repository.

Although the Hadoop implementation runs this module with Java 1.7, I could only run `ims+wsd` Java 1.6. Using Java 1.7 causes run-time errors “Platform not recognised” and the resulting NAF’s do not contain WordNet references. So, we had to install Java 1.6.

The scripts contain explicit paths that must be corrected:

`ims/testPlain`: Explicit path to Java binary.
`path_to_ims.py`: Set variable `PATH_TO_IMS`.

```

< install the ims-wsd module 47a > ≡
cd $modulesdir
tar -xzf $snapshotsocket/t_nlpp_resources/20151220_VUA-ims-wsd.v30.tgz
cd VUA-ims-wsd.v30
thisDir='pwd'
echo PATH_TO_IMS = "'"$thisDir/ims"'> path_to_ims.py
cd ims
cp testPlain.bash old.testPlain.bash
sedcommand='s|/usr/lib/jvm/java-1.6.0-openjdk-1.6.0.0.x86_64/jre/bin/java|java|g'
cat old.testPlain.bash | sed $sedcommand >testPlain.bash
◇

```

Fragment referenced in 24a.

Script

```

"../bin/ewsd" 47b ≡
  < start of module-script (47c VUA-ims-wsd.v30 ) 28b >
  < set up Java 1.6 15d >
  #Setting the output to be ili-wn30 synsets instead of sensekeys
  $MODDIR/call_ims.py -ili30
  ◇

```

5.6.10 SRL server

The EHU SRL-module, that we use for English documents, has been set up as a server/client system. Hence, we have to start the server before we can process something.

We don't know in advance whether we run the pipeline for a single text or from a whole bunch of text and hence we do not know whether it is advisable that the server keeps running, occupying precious memory.

Anyway, we need a script that starts the server if it is not already running. We must be aware that in some applications a bunch of parallel processes may be running this script at the same time, which causes synchronisation errors. So do as follows:

1. Check whether the server is in the air (listening on its port). If that is the case, we are ready.
2. Otherwise, gain exclusive permission to proceed. (**P** operation)
3. Check whether the "pidfile" (file that contains the process-id of the server) exists.
4. If the pidfile does not exist, start the server (and write its pid in the pidfile). Give up exclusive permission (**V** operation). We are ready.
5. Otherwise, if the pid-file exists, check whether a process with the given pid is running.
6. If such a process is running, the server has been started, but it is may not yet be up. Give up exclusive permission (**V** operation). We are ready.
7. If no running process has the given pid, the server may have been aborted. Start the server. Give up exclusive permission. We are ready.

The following scheme shows the process:

Server up?

yes: **ready**

no: **P**

PID-file exists?

no: start server

V

```

    ready
yes: process with PID exists?
    yes: V
        ready
    no: start server
        V
        ready

```

Set a default location or the directory for the pidfile, that can be overridden by user-set variable.

```

"../env/bin/progenv" 48a≡
if
  [ -z ${eSRL_piddir+x} ]
then
  export eSRL_piddir=/home/paul/projecten/pipelines/nlpp/env/etc/srllpid
fi
◇

```

File defined by 8a, 13b, 48a.

```

⟨ start EHU SRL server if it isn't running 48b ⟩ ≡
pidFile=${eSRL_piddir}/SRLServer.pid
mkdir -p ${eSRL_piddir}
portInfo=$(nmap -p 5005 localhost | grep open)
if
  [ -z "$portInfo" ]
then
  sematree acquire esrl_lock
  if
    [ ! -e "$pidFile" ]
  then
    start_eSRL_server
  else
    pid=$(cat $pidFile)
    ps -p $pid > /dev/null
    result=$?
    if
      [ $result -ne 0 ]
    then
      start_eSRL_server
    fi
  fi
fi
sematree release esrl_lock
fi
◇

```

Fragment referenced in 50a.


```

⟨function to start EHU SRL server 49a⟩ ≡
function start_eSRL_server {
    pidFile=$eSRL_piddir/SRLServer.pid
    java -Xms2500m -cp $MODDIR/IXA-EHU-srl-
3.0.jar ixa.srl.SRLServer en &> /dev/null &
    pid=$!
    echo $pid > $pidFile
}

◇

```

Fragment referenced in 50a.

When the server is up and running, it serves port 5005. So when we know that the server has been started up, let us wait until that port is served. When it takes too long, give up.

```

⟨wait for SRL server 49b⟩ ≡
nr_of_trials=0
maxtrials=20
while
    portInfo=$(nmap -p 5005 localhost | grep open)
    [ -z "$portInfo" ] && [ $nr_of_trials -le $maxtrials ]
do
    sleep 10
    nr_of_trials=$((nr_of_trials+1))
done
if
    [ -z "$portInfo" ]
then
    echo "eSRL server does not start." >&2
fi
◇

```

Fragment referenced in 50c.

Module

```

⟨install the srl-server module 49c⟩ ≡
cd $modulesdir
tar -xzf $snapshotsocket/t_nlpp_resources/20151220_EHU-srl-server.tgz
cd EHU-srl-server
mkdir -p /home/paul/projecten/pipelines/nlpp/env/etc/srlpid
chmod o+rw /home/paul/projecten/pipelines/nlpp/env/etc/srlpid
◇

```

Fragment referenced in 24a.

Scripts Generate three scripts: **start_eSRL**, **stop_esrl** and **eSRL**, resp. to start the SRL server, to stop it and to process a NAF file.

```

"../bin/start_eSRL" 50a≡
    #!/bin/bash
    source /home/paul/projecten/pipelines/nlpp/env/bin/progenv
    ROOT=$piperoot
    MODDIR=$modulesdir/EHU-srl-server
    <function to start EHU SRL server 49a>
    <start EHU SRL server if it isn't running 48b>
    ◇

"../bin/stop_eSRL" 50b≡
    #!/bin/bash
    source /home/paul/projecten/pipelines/nlpp/env/bin/progenv
    ROOT=$piperoot
    pidFile=$eSRL_piddir/SRLServer.pid
    if
        [ -e "$pidFile" ]
    then
        kill 'cat $pidFile'
        rm $pidFile
    fi
    ◇

"../bin/eSRL" 50c≡
    <start of module-script (50d EHU-srl-server ) 28b>
    /home/paul/projecten/pipelines/nlpp/bin/start_eSRL
    <wait for SRL server 49b>
    java -Xmx1000m -cp $MODDIR/IXA-EHU-srl-3.0.jar ixa.srl.SRLClient en
    ◇

<start EHU SRL server 50e> ≡
    pidFile=$eSRL_piddir/SRLServer.pid
    java -Xms2500m -cp $MODDIR/IXA-EHU-srl-3.0.jar ixa.srl.SRLServer en &> /dev/null &
    pid=$!
    echo $pid > $pidFile
    ◇

```

Fragment never referenced.

5.6.11 SRL Dutch nominals

Module

```

<install the srl-dutch-nominals module 50f> ≡
    MODNAM=srl-dutch-nominals
    DIRN=vua-srl-dutch-nominal-events
    GITU=https://github.com/newsreader/vua-srl-dutch-nominal-events
    GITC=6115b3168978acf809916cd2da512295d109d8fb
    <install from github 10a>
    cd $modulesdir/vua-srl-dutch-nominal-events
    ◇

```

Fragment referenced in 24a.

Script

```
"../bin/srl-dutch-nominals" 51a≡
  ⟨ start of module-script (51b vua-srl-dutch-nominal-events ) 28b⟩
  cd $MODDIR
  cat | python $MODDIR/vua-srl-dutch-additional-roles.py
  ◇
```

5.6.12 FBK-time module

The FBK-time module is obtained from a tarball that has been ripped from the Newsreader server.

Note: on june 15, 2016 jar file TimeProNorm_v2.6.jar has been added to the lib subdirectory.

Anne-Lyse Minard wrote in an e-mail on june 10, 2016:

For the following example:

```
"*will* have a collective chance to discuss the British demands at an EU summit on October 15-16"
```

The day "16" is considered as the year, it is why it is annotated as 2016-10-15.

I cannot do much because "15-16" is considered as one token. In TimeML it would have been annotated
 <TIMEX3 value="2015-10-15">October 15</TIMEX3>-<TIMEX3 value="2015-10-16">16</TIMEX3>.

But in NAF as the annotation is done at the token level this is not possible.

What I have done to solve these types of errors is to consider only "October 15" and so to normal

A new version of TimeProNorm can be download from <https://github.com/alminard/TimeProNorm/blob/master>

I don't have time now to test the changes I have done (I have just run it on 2 files).

How urgent is it for you to process the data?

Module

```
⟨ install the FBK-time module 51c⟩ ≡
  cd $modulesdir
  tar -xzf $snapshotsocket/t_nlpp_resources/20160616_FBK-time.v30.tgz
  ◇
```

Fragment referenced in 24j.

Script The script is rather complicated. I just copied it from the original makers, with one exception: Originally at the end of the script there was a pipe consisting of two Java programs. However, that didn't seem to work in one of the computers that we use, therefore we have split the pipe using mytemp as temporary storage.

```

"../bin/FBK-time" 52a≡
  < start of module-script (52b FBK-time.v30 ) 28b >
  BEGINTIME='date +%Y-%m-%dT%H:%M:%S%Z'
  YAMCHA=$MODDIR/tools
  timdir='mktemp -d -t time.XXXXXX'
  FILETXP=$timdir/TimePro.txp
  CHUNKIN=$timdir/TimePro.naf
  FILEOUT=$timdir/TimeProOUT.txp
  TIMEPRONORMIN=$timdir/TimeProNormIN.txp
  JAVAMAXHEAP=2g
  mytemp=$timdir/mytemp
  result=0
  cd $MODDIR
  cat > $CHUNKIN

  JAVACLASSPATH="lib/jdom-2.0.5.jar:lib/kaflib-naf-1.1.9.jar:lib/NAFtoTXP_v11.jar"
  JAVAMODULE=eu.fbk.newsreader.naf.NAFtoTXP_v11
  cat $CHUNKIN | \
    java -Xmx$JAVAMAXHEAP -cp $JAVACLASSPATH $JAVAMODULE $FILETXP chunk+entity timex
  < stop on error (52c Java: $JAVACLASSPATH:$JAVAMODULE ) 53a >
  #echo "Saving... $FILETXP"
  tail -n +4 $FILETXP | awk -f resources/english-rules > $FILEOUT
  head -n +4 $FILETXP > $TIMEPRONORMIN

  cat $FILEOUT | \
    $YAMCHA/yamcha-0.33/usr/local/bin/yamcha \
      -m models/tempeval3_silver-data.model \
    >> $TIMEPRONORMIN
  < stop on error (52d yamcha ) 53a >
  JAVACLASSPATH="lib/scala-library.jar:lib/timenorm-0.9.1-SNAPSHOT.jar"
  JAVACLASSPATH=$JAVACLASSPATH:"lib/threetenbp-0.8.1.jar:lib/TimeProNorm_v2.5.jar"
  JAVAMODULE=eu.fbk.timePro.TimeProNormApply
  cat $TIMEPRONORMIN | \
    java -Xmx$JAVAMAXHEAP -cp $JAVACLASSPATH $JAVAMODULE $FILETXP
  < stop on error (52e Java: $JAVACLASSPATH:$JAVAMODULE ) 53a >
  rm $FILEOUT
  rm $TIMEPRONORMIN

  JAVACLASSPATH="lib/jdom-2.0.5.jar:lib/kaflib-naf-1.1.9.jar:lib/NAFtoTXP_v11.jar"
  JAVAMODULE=eu.fbk.newsreader.naf.NAFtoTXP_v11
  cat $CHUNKIN | java -Xmx$JAVAMAXHEAP -
  cp $JAVACLASSPATH $JAVAMODULE $FILEOUT chunk+morpho+timex+event eval
  < stop on error (52f Java: $JAVACLASSPATH:$JAVAMODULE ) 53a >
  JAVACP1="lib/TXptoNAF_v5.jar:lib/jdom-2.0.5.jar:lib/kaflib-naf-1.1.9.jar"
  JAVAMOD1=eu.fbk.newsreader.naf.TXptoNAF_v4
  JAVACP2="lib/kaflib-naf-1.1.9.jar:lib/jdom-2.0.5.jar:lib/TimeProEmptyTimex_v2.jar"
  JAVAMOD2=eu.fbk.timepro.TimeProEmptyTimex
  java -Xmx$JAVAMAXHEAP -Dfile.encoding=UTF8 -
  cp $JAVACP1 $JAVAMOD1 $CHUNKIN $FILETXP "$BEGINTIME" TIMEX3 > $mytemp
  cat $mytemp | java -Xmx$JAVAMAXHEAP -Dfile.encoding=UTF8 -
  cp $JAVACP2 $JAVAMOD2 $FILEOUT
  < stop on error (52g Java: $JAVACLASSPATH:$JAVAMODULE ) 53a >
  rm $FILETXP
  rm $CHUNKIN
  rm -rf $timdir
  ◇

```

When one of the programs in the script fail, stop processing. Pass the error-code and write a message to locate the failing program. Remove the temporary directory. However, there is a problem. One of the java programs always results with result-code 1.

```

< stop on error 53a > ≡
    result=$?
    if
        [ $result -ne 0 ]
    then
        cd $MODDIR
        echo Error: @1 >&2
        rm -rf $timdir
        exit $result
    fi
    ◇

```

Fragment referenced in 52a.

5.6.13 FBK-temprel module

Module

```

< install the FBK-temprel module 53b > ≡
    cd $modulesdir
    tar -xzf $snapshotsocket/t_nlpp_resources/20151220_FBK-temprel.v30.tgz
    < repair FBK-*rel's run.sh.hadoop (53c FBK-temprel.v30 ) 53d >
    ◇

```

Fragment referenced in 24j.

Script run.sh.hadoop seems to be obsolete in the original tarball:

1. The class-path argument in one of the Java statement refers to an obsolete jar (kaflib-naf-1.1.8 instead of kaflib-naf-1.1.9)
2. Another class-path argument refers to PredicateTimeAnchor_tlink.jar instead of PredicateTimeAnchor.jar
3. A “sh” statement is used. The problem is, that in Ubuntu /bin/sh points to bin/dash and the script (temprel-pipeline-per-file-NWR.sh) does not seem to be compatible with dash.

Therefore, we need to repair the script. We will need to repair the script in the FBK-causalrel module in a similar way, and therefore provide the module-directory as argument.

```

< repair FBK-*rel's run.sh.hadoop 53d > ≡
    cd $modulesdir/@1
    mv run.sh.hadoop old.run.sh.hadoop
    cat old.run.sh.hadoop | \
        sed s/kaflib-naf-1.1.8/kaflib-naf-1.1.9/g | \
        sed s/TimeAnchor_tlink.jar/TimeAnchor.jar/g | \
        sed "s/sh temprel/bash temprel/g" | \
        sed "s/java /java -Xmx2g /g" \
    >run.sh.hadoop
    chmod 775 run.sh.hadoop
    ◇

```

Fragment referenced in 53b, 54c.

Script The original run script seems to not only read the input naf from standard in, but also to obtain the input naf as a file that an argument points to. This constructions makes the pipeline complicated, therefore, we generate the naf file within the script.

The original script generates temporary files in the `temp` directory of the host-computer, and prefixes the names of the temporary files with a random number to prevent confusion between tempfiles of different instances of this module. We generate a temp-directory per instance.

```
"../bin/FBK-temprel" 54a≡
  ⟨ start of module-script (54b FBK-temprel.v30 ) 28b ⟩
  cd $MODDIR
  scratchDir='mktemp -d -t temprel.XXXXXX'
  cat >$scratchDir/in.naf
  ./run.sh.hadoop $MODDIR $scratchDir $scratchDir/in.naf
  rm -rf $scratchDir

  ◇
```

5.6.14 FBK-causalrel module

Module

```
⟨ install the FBK-causalrel module 54c ⟩ ≡
  cd $modulesdir
  tar -xzf $snapshotsocket/t_nlpp_resources/20151220_FBK-causalrel.v30.tgz
  ⟨ repair FBK-*rel's run.sh.hadoop (54d FBK-causalrel.v30 ) 53d ⟩
  ◇
```

Fragment referenced in 24j.

Like in FBK-temprel, script run.sh.hadoop seems not to work out of the box:

1. The class-path argument in one of the Java statement refers to an obsolete jar (`kaflib-naf-1.1.8` instead of `kaflib-naf-1.1.9`)
2. A “sh” statement is used. The problem is, that in Ubuntu `/bin/sh` points to `bin/dash` and the script (`temprel-pipeline-per-file-NWR.sh`) does not seem to be compatible with `dash`.

Therefore, we need to repair that script like we did in FBK-temprel.

```
⟨ repair causalrel's run.sh.hadoop 54e ⟩ ≡
  cd $modulesdir/FBK-causalrel.v30
  mv run.sh.hadoop old.run.sh.hadoop
  cat old.run.sh.hadoop | \
    sed s/kaflib-naf-1.1.8/kaflib-naf-1.1.9/g | \
    sed s/TimeAnchor_tlink.jar/TimeAnchor.jar/g | \
    sed s/sh temprel/bash temprel/g | \
  >run.sh.hadoop
  chmod 775 run.sh.hadoop
  ◇
```

Fragment never referenced.

Script

```
"../bin/FBK-causalrel" 55a≡
  ⟨ start of module-script (55b FBK-causalrel.v30 ) 28b ⟩
  cd $MODDIR
  scratchDir='mktemp -d -t causalrel.XXXXXX'
  cat >$scratchDir/in.naf
  ./run.sh.hadoop $MODDIR $scratchDir $scratchDir/in.naf
  rm -rf $scratchDir
◇
```

5.6.15 Factuality modules

At this moment there is not yet a single factuality modules that server Dutch as well as English. In spite of it's name, the [multilingual_factuality](#) module serves only Dutch on production-quality level. For English, we have the [VUA-factuality](#) module.

Modules

```
⟨ install the factuality modules 55c ⟩ ≡
  MODNAM=vua_factuality
  DIRN=vua_factuality
  GITU=https://github.com/cltl/vua_factuality.git
  GITC=58fae1dc27d503642f4899460a3481417f044e95
  ⟨ install from github 10a ⟩
  MODNAM=multilingual_factuality
  DIRN=multilingual_factuality
  GITU=https://github.com/cltl/multilingual_factuality
  GITC=cbad4849b7d4421790589b018a9073d646ca45e3
  ⟨ install from github 10a ⟩
◇
```

Fragment referenced in [24j](#).

Script

```
"../bin/factuality" 55d≡
  ⟨ start of module-script (55e LATER ) 28b ⟩
  if
    [ "$naflang" == "nl" ]
  then
    MODDIR=$modulesdir/multilingual_factuality
    ⟨ run dutch factuality 56b ⟩
  else
    MODDIR=$modulesdir/vua_factuality
    ⟨ run english factuality 56a ⟩
  fi
◇
```

```

⟨ run english factuality 56a ⟩ ≡
    rootDir=${MODDIR}
    tmpDir=$(mktemp -d -t factuality.XXXXXX)
    export PATH=$PATH:${rootDir}:.
    export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/home/paul/projecten/pipelines/nlpp/env/lib/
    cd $rootDir
    python ${rootDir}/vua_factuality_naf_wrapper.py -
    t /home/paul/projecten/pipelines/nlpp/env/bin/timbl -p ${rootDir} ${tmpDir}/
    rm -rf $tmpDir >& /dev/null
    ◇

```

Fragment referenced in 55d.

Uses: LD_LIBRARY_PATH 17e, PATH 7e.

To run the Dutch factuality is very simple. It is a Python script that finds out its own location.

```

⟨ run dutch factuality 56b ⟩ ≡
    cd $MODDIR/feature_extractor
    cat | python ./rule_based_factuality.py
    ◇

```

Fragment referenced in 55d.

5.6.16 Nominal coreference-base

The source of this module in Github (<https://github.com/opener-project/coreference-base.git>) does not seem to work well with NAF. Therefore, we use the version from the official English pipeline, that we find in the snapshot.

Module

```

⟨ install coreference-base 56c ⟩ ≡
    cd $modulesdir
    tar -xzf /home/paul/projecten/pipelines/t_nlpp_resources/20151220_EHU-
    corefgraph.v30.tgz
    ◇

```

Fragment referenced in 25a.

Script

```

"../bin/coreference-base" 56d≡
    ⟨ start of module-script (56e EHU-corefgraph.v30 ) 28b ⟩
    cd $MODDIR/corefgraph
    cat | python -m corefgraph.process.file --reader NAF --writer NAF
    ◇

```

5.6.17 Named entity recognition (NERC)

Module The Nerc program can be installed from Github (<https://github.com/ixa-ehu/ixa-pipe-nerc>). However, the model that is needed is not publicly available. Therefore, models have been put in the snapshot-tarball.


```

⟨ install the NERC module 57a ⟩ ≡
  ⟨ compile the nerc jar 57b ⟩
  ⟨ get the nerc models 57d ⟩

```

◇

Fragment referenced in 23j.

The nerc module is a Java program that is contained in a jar. Put the source from Github in a temporary directory, compile the jar with java and move the jar to the jars directory.

```

⟨ compile the nerc jar 57b ⟩ ≡
  TEMPDIR='mktemp -d -t nerc.XXXXXX'
  cd $TEMPDIR
  git clone https://github.com/ixa-ehu/ixa-pipe-nerc
  cd ixa-pipe-nerc/
  git checkout ca02c931bc0b200ccdb8b5795a7552e4cc0d4802
  mvn clean package
  mv target/ixa-pipe-nerc-1.5.4.jar $jarsdir/
  cd $nuwebdir
  rm -rf $TEMPDIR

```

◇

Fragment referenced in 57a.

The current version of the pipeline uses the following models, that have been made available by Rodrigo Agerri on december 15, 2015.

The tarball `dutch-nerc-models.tar.gz` contains the models `nl-clusters-conll102.bin` and `nl-clusters-sonar.bin`. Both models have been placed in subdirectory `/m4_nerc_nl_dir/nerc_models/nl` of the snapshot.

The model for English can be found in the newsreader-repository.

Choose a model dependent of the language.

```

⟨ select language-dependent features 57c ⟩ ≡
  if
    [ "$naflang" == "nl" ]
  then
    export nercmodel=nl/nl-clusters-conll102.bin
  else
    export nercmodel=en/en-newsreader-clusters-3-class-muc7-conll103-ontonotes-4.0.bin
  fi

```

◇

Fragment never referenced.

Uses: `naflang` 73.

The tarball `20160301_nerc_models.tgz` contains in subdirectories `nl` and `en` a dutch resp. an english nerc-model. They have been randomly selected from a number of models that are available in <http://ixa2.si.ehu.es/ixa-pipes/models/nerc-models-1.5.4.tgz>.

```

⟨ get the nerc models 57d ⟩ ≡
  cd $modulesdir
  tar -p -
  xzf /home/paul/projecten/pipelines/t_nlpp_resources/20160301_nerc_models.tgz

```

◇

Fragment referenced in 57a.

Script Make a script that uses the conll02 model and a script that uses the Sonar model

```

"../bin/nerc_conll02" 58a≡
  ⟨ start of module-script (58b m4_nerc_nl_dir ) 28b ⟩
  JAR=$jarsdir/ixa-pipe-nerc-1.5.4.jar
  MODEL=nl-clusters-conll02.bin
  cat | java -Xmx1000m -jar $JAR tag -m $MODDIR/nl/$MODEL
  ◇

"../bin/nerc" 58c≡
  ⟨ start of module-script (58d nerc-models ) 28b ⟩
  JAR=$jarsdir/ixa-pipe-nerc-1.5.4.jar
  if
    [ "$naflang" == "nl" ]
  then
    nercmodel=$modulesdir/nerc_models/nl/nl-6-class-clusters-sonar.bin
  else
    nercmodel=$modulesdir/nerc_models/en/en-best-clusters-conll03.bin
  fi
  java -Xmx1500m -jar $JAR tag -m $nercmodel
  ◇

```

5.6.18 Wordsense-disambiguation

Install WSD from its Github source (https://github.com/cltl/svm_wsd.git). According to the *readme* of that module, the next thing to do is, to execute install-script `install.sh` or `install_naf.sh`. The latter script installs a “Support-Vector-Machine” (svm) module, “Dutch-SemCor” (DSC) models and `KafNafParserPy`.

Module

```

⟨ install the WSD module 58e ⟩ ≡
  MODNAM=wsd
  DIRN=svm_wsd
  GITU=https://github.com/cltl/svm_wsd.git
  GITC=030043903b42f77cd20a9b2443de137e2efe8513
  ⟨ install from github 10a ⟩
  cd $modulesdir/svm_wsd
  ⟨ install svm lib 59a ⟩
  ⟨ download svm models 59b ⟩
  ◇

```

Fragment referenced in 25a.

This part has been copied from `install_naf.sh` in the WSD module.

```

< install svm lib 59a > ≡
    mkdir lib
    cd lib
    wget --no-check-
    certificate https://github.com/cjlin1/libsvm/archive/master.zip 2>/dev/null
    zip_name='ls -1 | head -1'
    unzip $zip_name > /dev/null
    rm $zip_name
    folder_name='ls -1 | head -1'
    mv $folder_name libsvm
    cd libsvm/python
    make > /dev/null 2> /dev/null
    echo LIBSVM installed correctly lib/libsvm
    ◇

```

Fragment referenced in 58e.

This part has also been copied from `install_naf.sh` in the WSD module.

```

< download svm models 59b > ≡
    cd $modulesdir/svm_wsd
    #tar -xzf $pipesocket/m4_wsd_snapball
    wget --user=cltl --
    password='.cltl.' kyoto.let.vu.nl/~izquierdo/models_wsd_svm_dsc.tgz 2> /dev/null
    echo 'Unzipping models...'
    tar -xzf models_wsd_svm_dsc.tgz
    rm models_wsd_svm_dsc.tgz
    echo 'Models installed in folder models'
    ◇

```

Fragment referenced in 58e.

Script

```

"../bin/wsd" 59c≡
    < start of module-script (59d svm_wsd ) 28b >
    WSDSCRIPT=dsc_wsd_tagger.py
    cat | python $MODDIR/$WSDSCRIPT --naf -ref odwnSY
    ◇

```

5.6.19 Lexical-unit converter

Module There is not an official repository for this module yet, so copy the module from the tarball.

```

< install the lu2synset converter 59e > ≡
    cd $modulesdir
    tar -xzf $snapshotsocket/t_nlpp_resources/lu2synset.tgz
    ◇

```

Fragment referenced in 25h.

Script

```

"../bin/lu2synset" 60a≡
  < start of module-script (60b lexicalunitconverter ) 28b>
  JAVAILIBDIR=$MODDIR/lib
  RESOURCESDIR=$MODDIR/resources
  JARFILE=WordnetTools-1.0-jar-with-dependencies.jar
  java -Xmx812m -
  cp $JAVAILIBDIR/$JARFILE vu.wntools.util.NafLexicalUnitToSynsetReferences \
    --wn-lmf "$RESOURCESDIR/cornetto2.1.lmf.xml" --format naf
  ◇

```

5.6.20 NED

The NED module is rather picky about the structure of the NAF file. In any case, it does not accept a file that has been produced by the ontotagger. Hence, in a pipeline NED should be executed before the ontotagger.

The NED module wants to consult the Dbpedia Spotlight server, so that one has to be installed somewhere. For this moment, let us suppose that it has been installed on localhost.

Module

```

< install the NED module 60c> ≡
  < put spotlight jar in the Maven repository 61a>
  MODNAM=ned
  DIRN=ixa-pipe-ned
  GITU=https://github.com/ixa-ehu/ixa-pipe-ned.git
  GITC=d35d4df5cb71940bf642bb1a83e2b5b7584010df
  < install from github 10a>
  cd $modulesdir/ixa-pipe-ned
  mvn -Dmaven.compiler.target=1.7 -Dmaven.compiler.source=1.7 clean package
  mv target/ixa-pipe-ned-1.1.1.jar $jarsdir/
  ◇

```

Fragment referenced in 23j.

NED needs to have dbpedia-spotlight-0.7.jar in the local Maven repository. That is a different jar than the jar that we use to start Spotlight. The Dutch data in `nl.tar.gz` seems to be needed as well. We already downloaded that resource for Spotlight itself, so we do not download that again.

```

< download stuff 60d> ≡
  < need to wget (60e dbpedia-spotlight-0.7.jar,60f http://spotlight.sztaki.hu/downloads/archive/2014/dbpedia
  ◇

```

Fragment defined by 11ac, 14c, 19b, 34b, 40e, 42b, 60d.

Fragment referenced in 9c.

```

<put spotlight jar in the Maven repository 61a> ≡
    echo Put Spotlight jar in the Maven repository.
    tempdir='mktemp -d -t simplespot.XXXXXX'
    cd $tempdir
    cp $snapshotsocket/$snapshotdirectory/dbpedia-spotlight-0.7.jar .
    tar -xzf $snapshotsocket/$snapshotdirectory/nl.tar.gz
    MVN_SPOTLIGHT_OPTIONS="-Dfile=dbpedia-spotlight-0.7.jar"
    MVN_SPOTLIGHT_OPTIONS="$MVN_SPOTLIGHT_OPTIONS -DgroupId=ixa"
    MVN_SPOTLIGHT_OPTIONS="$MVN_SPOTLIGHT_OPTIONS -DartifactId=dbpedia-spotlight"
    MVN_SPOTLIGHT_OPTIONS="$MVN_SPOTLIGHT_OPTIONS -Dversion=0.7"
    MVN_SPOTLIGHT_OPTIONS="$MVN_SPOTLIGHT_OPTIONS -Dpackaging=jar"
    MVN_SPOTLIGHT_OPTIONS="$MVN_SPOTLIGHT_OPTIONS -DgeneratePom=true"
    mvn install:install-file $MVN_SPOTLIGHT_OPTIONS

    cd $PROJROOT
    rm -rf $tempdir
    ◇

```

Fragment referenced in 60c.

Uses: `install` 89a.

Script NED needs to contact a Spotlight-server.

```

"../bin/ned" 61b≡
    <start of module-script (61c ) 28b>
    ROOT=$piperoot
    JARDIR=$jarsdir
    <find a spotlightserver or exit 37b>
    cat | java -Xmx1000m -jar $jarsdir/ixa-pipe-ned-1.1.1.jar -
    H http://$spotlighthost -p $spotlightport -e candidates -
    i $envdir/spotlight/wikipedia-db -n nlEn
    ◇

```

5.6.21 Dark entity relinker

The “Dark Entity Relinker” tries to link “Dark entities” (named entities that have not been recognized) to the link of a known entity with a similar name structure that has been found in the same text.

Module Install the module from Github.

```

<install the de-link module 61d> ≡
    cd $modulesdir
    git clone https://github.com/cltl/entity-relink-pipeline.git
    cd entity-relink-pipeline
    git checkout 90d7b64840dda8ce3baf744e140891a6f8419052
    ◇

```

Fragment referenced in 23j.

script

```
"../bin/dere1" 62a≡
  ⟨ start of module-script (62b entity-relink-pipeline ) 28b ⟩
  cd $MODDIR/
  cat | python relinkDarkEntities.py
  ◇
```

5.6.22 Ontotagger, Framenet-SRL and nominal events

The three modules `ontotagger` (aka “`predicatematrix`”), `Framenet-SRL` and nominal event detection are based on the same software packages and resources. The three modules need the same jar `ontotagger-1.0-jar-with-dependencies.jar`, they need resources from the `cltl/vua_resources` Github repository and they are going to execute a script that resides in the `scripts` directory of the `cltl/OntoTagger` repository. So, what we have to do is:

1. Install from the `cltl/OntoTagger` repository.
2. Create the jar and put it in an appropriate place.
3. install from the `cltl\vua-resources` repository.
4. generate a script for each of the modules.

In fact, items 2 and 3 are performed by script `install.sh` from the `OntoTagger` repository.

Modules

```
⟨ install the ontotagger repository 62c ⟩ ≡
  cd $modulesdir
  git clone https://github.com/cltl/OntoTagger.git
  cd OntoTagger
  git checkout 9ea03d73eef1c9f4c85a0f05bc8137149e51335c
  chmod 775 ./install.sh
  ./install.sh
  cd $piperoot
  ◇
```

Fragment referenced in 25a.

Uses: `install` 89a.

Scripts The “`onto`” (`predicatematrix`) script:

```
"../bin/onto" 62d≡
  ⟨ start of module-script (62e OntoTagger ) 28b ⟩
  cd $MODDIR/scripts
  cat | $MODDIR/scripts/predicate-matrix-tagger.sh
  ◇
```

The “`Framenet SRL`” script:

The script contains a hack, because the `framesrl` script produces spurious lines containing “`frameMap.size()=...`”. A GAWK script removes these lines.

```
"../bin/framesrl" 62f≡
  ⟨ start of module-script (62g OntoTagger ) 28b ⟩
  cd $MODDIR/scripts
  cat | $MODDIR/scripts/srl-framenet-
  tagger.sh | gawk '/^frameMap.size()/ {next}; {print}'
  ◇
```

The “nomevent” script:

```
"../bin/nomevent" 63a≡
  < start of module-script (63b OntoTagger ) 28b >
  cd $MODDIR/scripts
  cat | $MODDIR/scripts/nominal-events.sh
  ◇
```

5.6.23 Heideltime

Module The code for Heideltime can be found in [Github](#). However, we use a compiled Heideltime Jar, compiled by Antske Fokkens, because some bugs have been repaired in that version.

Use Heideltime via a wrapper, *ixa-pipe-time*, obtained from [Github](#).

Heideltime uses treetagger. It expects to find the location of treetagger in a variable `TreetaggerHome` in config-file `config.props`.

```
< install the heideltime module 63c > ≡
  moduledir=/home/paul/projecten/pipelines/nlpp/modules/ixa-pipe-time
  heideltemp='mktemp -d -t heidel.XXXXXX'
  < clone the heideltime wrapper 63d >
  < put miscellaneous stuff in the heideltime module 63f >
  < compile the heideltime wrapper 64a >
  rm -rf $heideltemp
  ◇
```

Fragment referenced in [25h](#).

```
< clone the heideltime wrapper 63d > ≡
  MODNAM=heideltime
  DIRN=ixa-pipe-time
  GITU=https://github.com/ixa-ehu/ixa-pipe-time.git
  GITC=0fd3b5bd4c9a82b1624928a487b3a963a266f10c
  < install from github (63e ixa-pipe-time ) 10a >
  ◇
```

Fragment referenced in [63c](#).

In the wrapper we need the following extra material:

- A debugged version of the Heidelberg jar.
- A configuration file `config.props`, although it does not seem to be actually used.
- Another configuration file: `alpino-to-treetagger.csv`

The extra material has been provided by Antske Fokkens.

```
< put miscellaneous stuff in the heideltime module 63f > ≡
  cd $heideltemp
  tar -xzf $snapshotsocket/t_nlpp_resources/20151123_antske_heideltime_stuff.tgz
  cp antske_heideltime_stuff/config.props $moduledir/
  wget http://ixa2.si.ehu.es/~jibalar/jvntextpro-2.0.jar
  mv jvntextpro-2.0.jar $moduledir/lib/
  git clone https://github.com/carchrae/install-to-project-repo.git
  ◇
```

Fragment referenced in [63c](#).

Uses: [install 89a](#).

Compile the Heideltime wrapper according to the [instruction](#) on Github.

```

< compile the heideltime wrapper 64a > ≡
  cd /home/paul/projecten/pipelines/nlpp/modules/$DIRN/
  python $heideltemp/install-to-project-repo/install-to-project-repo.py
  mvn clean install
  ◇

```

Fragment referenced in [63c](#).

Uses: [install 89a](#).

Script `install-to-project-repo.py` generates a library in subdirectory `repo` and copies the jars that it finds in the `lib` subdirectory in this repo in such a way that Maven finds it there. Somewhere in the `install-to-project.py ... mvn` process the jars are copied in your local repository (`~/.m2`) too. As a result, only a Maven Guru understands precisely where Maven obtains its jar from and the best thing to do is to empty the `repo` subdirectory and the local repository before (re-) applying `install-to-project-repo.py`.

```

< activate the install-to-project-repo utility 64b > ≡
  < remove outdated heideltime jars 64c >
  cd /home/paul/projecten/pipelines/nlpp/modules/$DIRN/
  git clone git@github.com:carchrae/install-to-project-repo.git
  mv install-to-project-repo/install-to-project-repo.py .
  rm -rf install-to-project-repo
  python ./install-to-project-repo.py
  ◇

```

Fragment never referenced.

Uses: [install 89a](#).

```

< remove outdated heideltime jars 64c > ≡
  rm -rf /home/paul/projecten/pipelines/nlpp/modules/$DIRN/repo
  mkdir -p /home/paul/projecten/pipelines/nlpp/modules/$DIRN/repo/local
  rm -rf $HOME/.m2/repository/local/de.unihd.dbs.heideltime.standalone
  rm -rf $HOME/.m2/repository/local/jvntextpro-2.0
  ◇

```

Fragment referenced in [64b](#).

Script

```

"../bin/heideltime" 64d ≡
  < start of module-script (64e ixa-pipe-time ) 28b >
  MODDIR=$modulesdir/ixa-pipe-time
  cd $MODDIR
  iconv -t utf-8//IGNORE | java -Xmx1000m -jar target/ixa.pipe.time.jar -
  m lib/alpino-to-treetagger.csv -c config.props
  ◇

```

5.6.24 Semantic Role labelling

Module


```

< install the srl module 65a > ≡
MODNAM=srl
DIRN=vua-srl-nl
GITU=https://github.com/newsreader/vua-srl-nl.git
GITC=675d22d361289ede23df11dcdb17195f008c54bf
< install from github 10a >
◇

```

Fragment referenced in 25h.

Script First:

1. set the correct environment. The module needs python and timble.
2. create a tempdir and in that dir a file to store the input and a (scv) file with the feature-vector.

```

"../bin/srl" 65b≡
< start of module-script (65c vua-srl-nl ) 28b >
MODDIR=$modulesdir/vua-srl-nl
TEMPDIR='mktemp -d -t SRLTMP.XXXXXX'
cd $MODDIR
INPUTFILE=$TEMPDIR/inputfile
FEATUREVECTOR=$TEMPDIR/csvfile
TIMBLOUTPUTFILE=$TEMPDIR/timblpredictions
◇

```

File defined by 65bdefg.

Create a feature-vector.

```

"../bin/srl" 65d≡
cat | tee $INPUTFILE | python nafAlpinoToSRLFeatures.py > $FEATUREVECTOR
◇

```

File defined by 65bdefg.

Run the trained model on the feature-vector.

```

"../bin/srl" 65e≡
timbl -m0:I1,2,3,4 -i 25Feb2015_e-mags_mags_press_newspapers.wgt -
t $FEATUREVECTOR -o $TIMBLOUTPUTFILE >/dev/null 2>/dev/null
◇

```

File defined by 65bdefg.

Insert the SRL values into the NAF file.

```

"../bin/srl" 65f≡
python timblToAlpinoNAF.py $INPUTFILE $TIMBLOUTPUTFILE
◇

```

File defined by 65bdefg.

Clean up.

```

"../bin/srl" 65g≡
rm -rf $TEMPDIR
◇

```

File defined by 65bdefg.

5.6.25 SRL postprocessing

In addition to the Semantic Role Labeling there is hack that finds additional semantic roles.

Module Get the module from Github. Note that this module needs rdflib

```
<install python packages 66a> ≡
    pip install rdflib
◇
```

Fragment defined by 19a, 66a.

Fragment referenced in 15e.

Defines: rdflib Never used.

Uses: install 89a.

```
<install the post-SRL module 66b> ≡
    cd $modulesdir
    if
        [ -d vua-srl-postprocess ]
    then
        cd vua-srl-postprocess
        git pull
    else
        git clone https://github.com/newsreader/vua-srl-postprocess.git
        cd vua-srl-postprocess
    fi
◇
```

Fragment referenced in 25q.

Script

```
"../bin/postsr1" 66c≡
    <start of module-script (66d vua-srl-postprocess ) 28b>
    cd $MODDIR
    tmpdir='mktemp -d -t postsr1.XXXXX'
    cat >$tmpdir/infile
    python $MODDIR/main.py -i $tmpdir/infile -o $tmpdir/outfile
    cat $tmpdir/outfile
    rm -rf $tmpdir
◇
```

5.6.26 Event coreference

The event-coreference module is language-independent. Although the version in the EHU-repo is 3.0, the version 2.0 used in this pipeline seems to be more recent, so we will use that.

Module Install the module from the snapshot.

```

< install the event-coreference module 67a > ≡
    cd $modulesdir
    tar -xzf $snapshotsocket/t_nlpp_resources/20151217_vua-eventcoreference_v2.tgz
    cd vua-eventcoreference_v2
    cp lib/EventCoreference-1.0-SNAPSHOT-jar-with-dependencies.jar $jarsdir
    ◇

```

Fragment referenced in 25h.

Script

```

"../bin/evcoref" 67b≡
    < start of module-script (67c vua-eventcoreference_v2 ) 28b >
    RESOURCESDIR=$MODDIR/resources
    JARFILE=$jarsdir/EventCoreference-1.0-SNAPSHOT-jar-with-dependencies.jar

    if
        [ "$naflang" == 'nl' ]
    then
        lang_resource="odwn_orbn_gwg-LMF_1.3.xml"
    else
        lang_resource="wneng-30.lmf.xml.xpos"
    fi

    JAVAMODULE=eu.newsreader.eventcoreference.naf.EventCorefWordnetSim
    JAVAOPTIONS="--method leacock-chodorow"
    JAVAOPTIONS="$JAVAOPTIONS --wn-lmf $RESOURCESDIR/$lang_resource"
    JAVAOPTIONS="$JAVAOPTIONS --sim 2.0"
    JAVAOPTIONS="$JAVAOPTIONS --wsd 0.8"
    JAVAOPTIONS="$JAVAOPTIONS --
relations XPOS_NEAR_SYNONYM#HAS_HYPERONYM#HAS_XPOS_HYPERONYM#event"

    java -Xmx812m -cp $JARFILE $JAVAMODULE $JAVAOPTIONS
    ◇

```

5.6.27 Dbpedia-ner

Dbpedia-ner finds more named entities than NER, because it checks DBpedia for the candidate NE-'s.

Module

```

< install the dbpedia-ner module 67d > ≡
    MODNAM=dbpedia_ner
    DIRN=dbpedia_ner
    GITU=https://github.com/PaulHuygen/dbpedia_ner.git
    GITC=ab1dcdb860f0ff29bc979f646dc382122a101fc2
    < install from github 10a >
    ◇

```

Fragment referenced in 25q.

Script The main part of the module is a Python script. The `README.md` file of the Github repo lists the options that can be applied. One of the options is about the URL of the Spotlight server.

```
"../bin/dbpner" 68a≡
  < start of module-script (68b dbpedia_ner ) 28b >
  cat | iconv -f ISO8859-1 -t UTF-8 | $MODDIR/dbpedia_ner.py -
  url http://$spotlighthost:2060/rest/candidates
  ◇
```

5.6.28 GetSemfromNaf

The `naf2sem` module is a application that is hidden in the EventCoreference jar (<https://github.com/cltl/EventCoreference>). It uses resources from <https://github.com/cltl/vua-resources>, that has been installed by the ontotagger installer.

Module

```
< install naf2sem 68c > ≡
  n2sdir='mktemp -d -t n2s.XXXXXX'
  cd $n2sdir
  MODNAM=EventCoreference
  GITC=52765c55354fda9d5d3046e91d4b0f99898b014b
  git clone https://github.com/cltl/EventCoreference.git
  cd $MODNAM
  git checkout $GITC
  set -e
  mvn clean
  mvn install
  jarfile=EventCoreference-v3.1.2-jar-with-dependencies.jar
  if
    [ -d "target/$jarfile" ]
  then
    mv target/$jarfile $jarsdir
  else
    echo "Could not generate EventCoreference-v3.1.2-jar-with-dependencies.jar"
    exit 4
  fi
  cd "$modulesdir"
  rm -rf $n2sdir
  ◇
```

Fragment never referenced.
Uses: `install` 89a.

Script The script is not yet correct.

```

"../bin/naf2sem" 69a≡
  < start of module-script (69b dbpedia_ner ) 28b >
  JAR=$jarsdir/EventCoreference-v3.1.2-jar-with-dependencies.jar
  RESOURCES="$modulesdir/vua-resources"
  DATA="../data2"

  java -Xmx2000m -cp "$LIB/EventCoreference-v3.1.2-jar-with-
dependencies.jar" eu.newsreader.eventcoreference.naf.GetSemFromNafFolder --naf-
folder "$DATA" --extension ".naf" --verbose --project dasym --all --
ili "$RESOURCES/ili.ttl.gz" --perspective --source-frames "$RESOURCES/source-
nl.txt" --non-entities

  # --eurovoc-en "$RESOURCES/mapping_eurovoc_skos.csv.gz"
  # --no-doc-time
  # --no-context-time
  # --non-entities

  ◇

```

5.6.29 Opinion miner

Get `opinion-miner_deluxePP` from Github. The repository contains an install script `install_me` that installs the following:

- `KafNafParserPy` (we have this already);
- The “Conditional Random Fields” program, that is included in the tarball;
- The `SVM_light` utility that we installed in section 5.5.10.
- Trained models (hotels, news).
- Polarity-models.

So, we need to do the following:

- Get the module from the Github repo.
- Install the included CRF program.
- Link the binaries of SVM to a place where the opinion-miner expects it.
- Download and install the models.

Module Install the module from Github.

```

< install the opinion-miner 69c > ≡
  MODNAM=opinion_miner_deluxePP
  DIRN=opinion_miner_deluxePP
  GITU=https://github.com/rubenIzquierdo/opinion_miner_deluxePP
  GITC=40a714c9823d439262caa29f3a14c5ce2be91241
  < install from github 10a >
  ◇

```

Fragment defined by 69c, 70abcd.

Fragment referenced in 26a.

Install the CRF utility:

```

<install the opinion-miner 70a> ≡
    moduledir=$modulesdir/opinion_miner_deluxePP
    #Install CRF++
    crfdir='mktemp -d -t crf.XXXXXX'
    cd $crfdir
    tar -xzf $moduledir/crf_lib/CRF++-0.58.tar.gz
    rm -rf $moduledir/crf_lib/CRF++-0.58.tar.gz
    cd CRF++-0.58
    ./configure --prefix=$envdir
    make
    make install
    echo "PATH_TO_CRF_TEST='$envbindir/crf_test'" > $moduledir/path_crf.py
    cd $moduledir
    rm -rf $crfdir
    ◇

```

Fragment defined by 69c, 70abcd.

Fragment referenced in 26a.

Uses: install 89a.

The opinion-miner expects the SVM-light executables in a subdirectory `svm_light`.

```

<install the opinion-miner 70b> ≡
    cd $moduledir
    mkdir $moduledir/svm_light
    ln -
    s /home/paul/projecten/pipelines/nlpp/env/bin/svm_classify $moduledir/svm_light/
    ln -s /home/paul/projecten/pipelines/nlpp/env/bin/svm_learn $moduledir/svm_light/
    ◇

```

Fragment defined by 69c, 70abcd.

Fragment referenced in 26a.

Defines: `svm_classify` 41a, `svm_learn` 41a.

Download the trained models.

```

<install the opinion-miner 70c> ≡
    ##Download the models
    cd $moduledir
    echo Downloading the trained models.
    tar -xzf $snapshotsocket/t_nlpp_resources/models_opinion_miner_deluxePP.tgz
    ◇

```

Fragment defined by 69c, 70abcd.

Fragment referenced in 26a.

```

<install the opinion-miner 70d> ≡
    wget http://kyoto.let.vu.nl/~izquierdo/public/polarity_models.tgz
    tar -xzf polarity_models.tgz
    rm polarity_models.tgz
    ◇

```

Fragment defined by 69c, 70abcd.

Fragment referenced in 26a.

Defines: `polarity_models.tgz` Never used.

Script

```

"../bin/opinimin" 71a≡
  ⟨ start of module-script (71b opinion_miner_deluxePP ) 28b ⟩
  cd $MODDIR
  python tag_file.py -polarity -d hotel
  ◇

```

6 Utilities

6.1 Run-script and test-script

The script `nlpp` reads a NAF document from standard in and produces an annotated NAF on standard out. The script `test` annotates either a test-document that resides in the `nuweb` directory or a user-provided document and leaves the intermediate results in its working directory `nlpp/test`, so that, in case of problems, it is easy traceable what went wrong.

The annotation process involves a sequence in which an NLP module reads a file that contains the output from a previous module (or the input NAF file), processes it and writes the result in another file.

The following function, `runmodule`, performs the action of a single module in the sequence. It needs three arguments: 1) the name of the NAF file that the previous module produced or the input file; 2) the name of the script that runs the module and 3) the name of the output NAF.

The function uses variable `moduleresult` to decide whether it is really going to annotate. If this variable is "false" (i.e., not equal to zero), this means that one of the previous modules failed, and it is of no use to process the input file. In that case, the function leaves `moduleresult` as it is and does not process the input-file. Otherwise, it will process the input-file and it sets `moduleresult` to the result of the processing module.

```

⟨function to run a module 71c⟩ ≡
  export moduleresult=0

  function runmodule {
    local infile=$1
    local modulecommand=$BIND/$2
    local outfile=$3
    if
      [ $moduleresult -eq 0 ]
    then
      cat $infile | $modulecommand > $outfile
      moduleresult=$?
      if
        [ $moduleresult -gt 0 ]
      then
        failmodule=$modulecommand
        echo "Failed: module $modulecommand; result $moduleresult" >&2
        exit $moduleresult
      else
        echo "Completed: module $modulecommand; result $moduleresult" >&2
      fi
    fi
  }

  ◇

```

Fragment referenced in 74b, 75a.

Defines: `BIND` 75b, `moduleresult` 74b, 75a, `runmodule` 72ab, 73.

Note: that variable BIND has to be defined prior to using this function.

Use the function to annotate a NAF file that `infile` points to and write the result in a file that `outfile` points to:

```

⟨ annotate dutch document 72a ⟩ ≡
  runmodule $infile tok tok.naf
  runmodule tok.naf topic top.naf
  runmodule top.naf mor mor.naf
  runmodule mor.naf nerc nerc.naf
  runmodule nerc.naf wsd wsd.naf
  runmodule wsd.naf ned ned.naf
  runmodule ned.naf derel derel.naf
  runmodule derel.naf heideltime times.naf
  runmodule times.naf onto onto.naf
  runmodule onto.naf srl srl.naf
  runmodule srl.naf nomevent nomev.naf
  runmodule nomev.naf srl-dutch-nominals psrl.naf
  runmodule psrl.naf framesrl fsrl.naf
  runmodule fsrl.naf factuality fact.naf
  runmodule fact.naf opinimin opin.naf
  runmodule opin.naf evcoref $outfile
  ◇

```

Fragment never referenced.

Uses: `runmodule 71c`.

Similar for an English naf:

```

⟨ annotate english document 72b ⟩ ≡
  runmodule $infile tok tok.naf
  runmodule tok.naf topic top.naf
  runmodule top.naf pos pos.naf
  runmodule pos.naf constpars consp.naf
  runmodule consp.naf nerc nerc.naf
  runmodule nerc.naf ned ned.naf
  runmodule ned.naf derel derel.naf
  runmodule derel.naf nedrer nedr.naf
  runmodule nedr.naf wikify wikif.naf
  runmodule wikif.naf ukb ukb.naf
  runmodule ukb.naf ewsd ewsd.naf
  runmodule ewsd.naf coreference-base coref.naf
  runmodule coref.naf eSRL esrl.naf
  runmodule esrl.naf FBK-time time.naf
  runmodule time.naf FBK-temprel trel.naf
  runmodule trel.naf FBK-causalrel crel.naf
  runmodule crel.naf evcoref ecrf.naf
  runmodule ecrf.naf factuality fact.naf
  runmodule fact.naf opinimin $outfile
  ◇

```

Fragment referenced in 73.

Uses: `runmodule 71c`.

Determine the language and select one of the above macro's to annotate the document. In fact, consider the document as an English document unless `naflang` is "nl"


```

⟨ annotate 73 ⟩ ≡
  naflang='cat $infile | /home/paul/projecten/pipelines/nlpp/env/bin/langdetect.py'
  export naflang
  if
    [ "$naflang" == "nl" ]
  then
    runmodule $infile      tok          tok.naf
    runmodule tok.naf      topic        top.naf
    runmodule top.naf      mor          mor.naf
    runmodule mor.naf      nerc         nerc.naf
    runmodule nerc.naf     wsd          wsd.naf
    runmodule wsd.naf      ned          ned.naf
    runmodule ned.naf      derel        derel.naf
    runmodule derel.naf    heideltime   times.naf
    runmodule times.naf    onto         onto.naf
    runmodule onto.naf     srl          srl.naf
    runmodule srl.naf      nomevent     nomev.naf
    runmodule nomev.naf    srl-dutch-nominals psrl.naf
    runmodule psrl.naf     framesrl     fsrl.naf
    runmodule fsrl.naf     factuality   fact.naf
    runmodule fact.naf     opinimin     opin.naf
    runmodule opin.naf     evcoref      $outfile
  else
    ⟨ annotate english document 72b ⟩
  fi
  ◇

```

Fragment referenced in 74b, 75a.

Defines: `naflang` 27b, 30ab, 36b, 37bc, 39a, 41c, 43b, 55d, 57c, 58c, 67b.

Uses: `runmodule` 71c.

Use the above “annotate” macro in a test script and in a run script. The scripts set a working directory and put the input-file in it, and then annotate it.

The test-script uses a special test-directory and leaves it behind when it is finished. If the user specified a language, the script copies a NAF testfile from the nuweb directory as input-file. Otherwise, the script expects the test-directory to be present, with an input-file (named `in.naf`) in it.

```

< get a testfile or die 74a > ≡
    cd $workdir
    if
        [ "$1" == "en" ]
    then
        cp $ROOT/nuweb/test.en.in.naf $infile
    else
        if
            [ "$1" == "nl" ]
        then
            cp $ROOT/nuweb/test.nl.in.naf $infile
        fi
    fi
    if
        [ ! -e $infile ]
    then
        echo "Please supply test-file $workdir/$infile or specify language"
        exit 4
    fi
    ◇

```

Fragment referenced in 74b.

Uses: nuweb 84d.

This is the test-script:

```

"../bin/test" 74b ≡
    #!/bin/bash
    oldd='pwd'
    < set variables for test/run script 75b >
    workdir=$piperoot/test
    mkdir -p $workdir
    cd $workdir
    < get a testfile or die 74a >
    < function to run a module 71c >
    < annotate 73 >
    if
        [ $moduleresult -eq 0 ]
    then
        echo Test succeeded.
    else
        echo Something went wrong.
    fi
    exit $moduleresult
    ◇

```

Uses: moduleresult 71c.

The run-script `nlpp` reads a “raw” naf from standard in and produces an annotated naf on standard out. It creates a temporary directory to store intermediate results from the modules and removes this directory afterwards.

```

"../bin/nlpp" 75a≡
    #!/bin/bash
    oldd='pwd'
    < set variables for test/run script 75b >
    workdir='mktemp -d -t nlpp.XXXXXX'
    cd $workdir
    cat >$workdir/$infile
    < function to run a module 71c >
    < annotate 73 >
    if
        [ $moduleresult -eq 0 ]
    then
        cat $outfile
    fi
    cd $oldd
    rm -rf $workdir
    exit $moduleresult
◇

```

Uses: moduleresult 71c.

```

< set variables for test/run script 75b > ≡
    ROOT=/home/paul/projecten/pipelines/nlpp
    source /home/paul/projecten/pipelines/nlpp/env/bin/progenv
    BIND=$pipebin
    infile=in.naf
    outfile=out.naf
◇

```

Fragment referenced in 74b, 75a.

Uses: BIND 71c.

6.2 Logging

Write log messages to standard out if variable LOGLEVEL is equal to 1.

```

< variables of install-modules 75c > ≡
    LOGLEVEL=1
◇

```

Fragment referenced in 22a.

```

< logmess 75d > ≡
    if
        [ $LOGLEVEL -gt 0 ]
    then
        echo @1
    fi
◇

```

Fragment referenced in 9a, 10a, 76a.

6.3 Misc

Install a module from a tarball: The macro expects the following three variables to be present:

URL: The URL from where the tarball can be downloaded.

TARB: The name of the tarball.

DIR: Name of the directory for the module.

Arg 1: URL; Arg 2: tarball; Arg 3: directory.

```

< install from tarball 76a > ≡
  SUCCES=0
  cd $modulesdir
  < move module (76b $DIR ) 8b >
  wget $URL
  SUCCES=$?
  if
    [ $SUCCES -eq 0 ]
  then
    tar -xzf $TARB
    SUCCES=$?
    rm -rf $TARB
  fi
  if
    [ $SUCCES -eq 0 ]
  then
    < logmess (76c Installed $DIR ) 75d >
    < remove old module (76d $DIR ) 8c >
  else
    < re-instate old module (76e $DIR ) 9a >
  fi
  ◇

```

Fragment never referenced.

A How to read and translate this document

This document is an example of *literate programming* [1]. It contains the code of all sorts of scripts and programs, combined with explaining texts. In this document the literate programming tool **nuweb** is used, that is currently available from Sourceforge (URL:nuweb.sourceforge.net). The advantages of Nuweb are, that it can be used for every programming language and scripting language, that it can contain multiple program sources and that it is very simple.

A.1 Read this document

The document contains *code scraps* that are collected into output files. An output file (e.g. `output.fil`) shows up in the text as follows:

```

"output.fil" 4a ≡
  # output.fil
  < a macro 4b >
  < another macro 4c >
  ◇

```

The above construction contains text for the file. It is labelled with a code (in this case 4a) The constructions between the < and > brackets are macro's, placeholders for texts that can be found in other places of the document. The test for a macro is found in constructions that look like:

```

< a macro 4b > ≡
  This is a scrap of code inside the macro.

```

It is concatenated with other scraps inside the macro. The concatenated scraps replace the invocation of the macro.

Macro defined by 4b, 87e

Macro referenced in 4a

Macro's can be defined on different places. They can contain other macro's.

< a scrap 87e > \equiv

This is another scrap in the macro. It is concatenated to the text of scrap 4b.

This scrap contains another macro:

< another macro 45b >

Macro defined by 4b, 87e

Macro referenced in 4a

A.2 Process the document

The raw document is named `a_nlpp.w`. Figure 2 shows pathways to translate it into print-




Figure 2: Translation of the raw code of this document into printable/viewable documents and into program sources. The figure shows the pathways and the main files involved.

able/viewable documents and to extract the program sources. Table 3 lists the tools that are

| Tool | Source | Description |
|--------|----------------------------------------------------------------------------|------------------------------------------------------------|
| gawk | www.gnu.org/software/gawk/ | text-processing scripting language |
| M4 | www.gnu.org/software/m4/ | Gnu macro processor |
| nuweb | nuweb.sourceforge.net | Literate programming tool |
| tex | www.ctan.org | Typesetting system |
| tex4ht | www.ctan.org | Convert \TeX documents into <code>xml/html</code> |

Table 3: Tools to translate this document into readable code and to extract the program sources

needed for a translation. Most of the tools (except Nuweb) are available on a well-equipped Linux system.

$\langle \text{parameters in Makefile 78a} \rangle \equiv$
 NUWEB=../env/bin/nuweb
 ◇

Fragment defined by 78a, 79a, 81ab, 83c, 85b, 88a.
 Fragment referenced in 78b.
 Uses: nuweb 84d.

A.3 The Makefile for this project.

This chapter assembles the Makefile for this project.

"Makefile" 78b \equiv
 $\langle \text{default target 78c} \rangle$

 $\langle \text{parameters in Makefile 78a, ...} \rangle$

 $\langle \text{impliciete make regels 81c, ...} \rangle$
 $\langle \text{expliciete make regels 79b, ...} \rangle$
 $\langle \text{make targets 78d, ...} \rangle$
 ◇

The default target of make is all.

$\langle \text{default target 78c} \rangle \equiv$
 all : $\langle \text{all targets 78e} \rangle$
 .PHONY : all

 ◇

Fragment referenced in 78b.
 Defines: all 69a, PHONY 82a.

$\langle \text{make targets 78d} \rangle \equiv$
 clean:
 $\langle \text{clean up 13g, ...} \rangle$

 ◇

Fragment defined by 78d, 82b, 83a, 86c, 88bd, 89abc.
 Fragment referenced in 78b.

The default is, to install nlpp.

$\langle \text{all targets 78e} \rangle \equiv$
 install◇

Fragment referenced in 78c.
 Uses: install 89a.

We use many suffixes that were not known by the C-programmers who constructed the `make` utility. Add these suffixes to the list.

\langle *parameters in Makefile 79a* $\rangle \equiv$
`.SUFFIXES: .pdf .w .tex .html .aux .log .php`

◇

Fragment defined by 78a, 79a, 81ab, 83c, 85b, 88a.
 Fragment referenced in 78b.
 Defines: SUFFIXES Never used.
 Uses: pdf 82b.

A.4 Get Nuweb

An annoying problem is, that this program uses nuweb, a utility that is seldom installed on a computer. Therefore, we are going to install that first if it is not present. Unfortunately, nuweb is hosted on sourceforge and it is difficult to achieve automatic downloading from that repository. Therefore I copied one of the versions on a location from where it can be downloaded with a script.

Put the nuweb binary in the nuweb subdirectory, so that it can be used before the directory-structure has been generated.

\langle *expliciete make regels 79b* $\rangle \equiv$

```
nuweb: $(NUWEB)

$(NUWEB): ../nuweb-1.58
    mkdir -p ../env/bin
    cd ../nuweb-1.58 && make nuweb
    cp ../nuweb-1.58/nuweb $(NUWEB)
```

◇

Fragment defined by 79bd, 80ab, 82a, 83d, 85c, 86b.
 Fragment referenced in 78b.
 Uses: nuweb 84d.

\langle *clean up 79c* $\rangle \equiv$
`rm -rf ../nuweb-1.58`

◇

Fragment defined by 13g, 15a, 31b, 79c.
 Fragment referenced in 78d.
 Uses: nuweb 84d.

\langle *expliciete make regels 79d* $\rangle \equiv$

```
../nuweb-1.58:
    cd .. && wget http://kyoto.let.vu.nl/~huygen/nuweb-1.58.tgz
    cd .. && tar -xzf nuweb-1.58.tgz
```

◇

Fragment defined by 79bd, 80ab, 82a, 83d, 85c, 86b.
 Fragment referenced in 78b.
 Uses: nuweb 84d.

A.5 Pre-processing

To make usable things from the raw input `a_nlpp.w`, do the following:

1. Process \$ characters.
2. Run the m4 pre-processor.
3. Run nuweb.

This results in a L^AT_EX file, that can be converted into a PDF or a HTML document, and in the program sources and scripts.

A.5.1 Process ‘dollar’ characters

Many “intelligent” T_EX editors (e.g. the auctex utility of Emacs) handle \$ characters as special, to switch into mathematics mode. This is irritating in program texts, that often contain \$ characters as well. Therefore, we make a stub, that translates the two-character sequence \\$ into the single \$ character.

```
< expliciete make regels 80a > ≡
m4_nlpp.w : a_nlpp.w
          gawk '{if(match($$0, "@%")) {printf("%s", substr($$0,1,RSTART-
1))} else print}' a_nlpp.w \
          | gawk '{gsub(/[\$]/, "$$");print}' > m4_nlpp.w
```

◇

Fragment defined by 79bd, 80ab, 82a, 83d, 85c, 86b.

Fragment referenced in 78b.

Uses: print 82b.

A.5.2 Run the M4 pre-processor

```
< expliciete make regels 80b > ≡
nlpp.w : m4_nlpp.w inst.m4
        m4 -P m4_nlpp.w > nlpp.w
```

◇

Fragment defined by 79bd, 80ab, 82a, 83d, 85c, 86b.

Fragment referenced in 78b.

A.6 Typeset this document

Enable the following:

1. Create a PDF document.
2. Print the typeset document.
3. View the typeset document with a viewer.
4. Create a HTMLdocument.

In the three items, a typeset PDF document is required or it is the requirement itself.

A.6.1 Figures

This document contains figures that have been made by xfig. Post-process the figures to enable inclusion in this document.

The list of figures to be included:

< parameters in Makefile 81a > \equiv
 FIGFILES=fileschema directorystructure

◇

Fragment defined by 78a, 79a, 81ab, 83c, 85b, 88a.
 Fragment referenced in 78b.
 Defines: FIGFILES 81b.

We use the package `figlatex` to include the pictures. This package expects two files with extensions `.pdftex` and `.pdftex_t` for `pdflatex` and two files with extensions `.pstex` and `.pstex_t` for the `latex/dvips` combination. Probably `tex4ht` uses the latter two formats too.

Make lists of the graphical files that have to be present for `latex/pdflatex`:

< parameters in Makefile 81b > \equiv
 FIGFILENAMES=\$(foreach fil,\$(FIGFILES), \$(fil).fig)
 PDFT_NAMES=\$(foreach fil,\$(FIGFILES), \$(fil).pdftex_t)
 PDF_FIG_NAMES=\$(foreach fil,\$(FIGFILES), \$(fil).pdftex)
 PST_NAMES=\$(foreach fil,\$(FIGFILES), \$(fil).pstex_t)
 PS_FIG_NAMES=\$(foreach fil,\$(FIGFILES), \$(fil).pstex)

◇

Fragment defined by 78a, 79a, 81ab, 83c, 85b, 88a.
 Fragment referenced in 78b.
 Defines: FIGFILENAMES Never used, PDFT_NAMES 83a, PDF_FIG_NAMES 83a, PST_NAMES Never used,
 PS_FIG_NAMES Never used.
 Uses: FIGFILES 81a.

Create the graph files with program `fig2dev`:

< impiciete make regels 81c > \equiv
 %.eps: %.fig
 fig2dev -L eps \$< > \$@

 %.pstex: %.fig
 fig2dev -L pstex \$< > \$@

 .PRECIOUS : %.pstex
 %.pstex_t: %.fig %.pstex
 fig2dev -L pstex_t -p \$*.pstex \$< > \$@

 %.pdftex: %.fig
 fig2dev -L pdftex \$< > \$@

 .PRECIOUS : %.pdftex
 %.pdftex_t: %.fig %.pstex
 fig2dev -L pdftex_t -p \$*.pdftex \$< > \$@

◇

Fragment defined by 81c, 86a.
 Fragment referenced in 78b.
 Defines: `fig2dev` Never used.

A.6.2 Bibliography

To keep this document portable, create a portable bibliography file. It works as follows: This document refers in the `|bibliography|` statement to the local `bib`-file `nlpp.bib`. To create this file, copy the auxiliary file to another file `auxfil.aux`, but replace the argument of the command `\bibdata{nlpp}` to the names of the bibliography files that contain the actual references (they should exist on the computer on which you try this). This procedure should only be performed on the computer of the author. Therefore, it is dependent of a binary file on his computer.

```
< expliciete make regels 82a > ≡
    bibfile : nlpp.aux /home/paul/bin/mkportbib
              /home/paul/bin/mkportbib nlpp litprog

    .PHONY : bibfile
◇
```

Fragment defined by 79bd, 80ab, 82a, 83d, 85c, 86b.

Fragment referenced in 78b.

Uses: PHONY 78c.

A.6.3 Create a printable/viewable document

Make a PDF document for printing and viewing.

```
< make targets 82b > ≡
    pdf : nlpp.pdf

    print : nlpp.pdf
            lpr nlpp.pdf

    view : nlpp.pdf
            evince nlpp.pdf
◇
```

Fragment defined by 78d, 82b, 83a, 86c, 88bd, 89abc.

Fragment referenced in 78b.

Defines: pdf 79a, 83a, print 16a, 18b, 21c, 29b, 37b, 62f, 80a, view Never used.

Create the PDF document. This may involve multiple runs of `nuweb`, the \LaTeX processor and the `bibTeX` processor, and depends on the state of the `aux` file that the \LaTeX processor creates as a by-product. Therefore, this is performed in a separate script, `w2pdf`.

The w2pdf script The three processors `nuweb`, \LaTeX and `bibTeX` are intertwined. \LaTeX and `bibTeX` create parameters or change the value of parameters, and write them in an auxiliary file. The other processors may need those values to produce the correct output. The \LaTeX processor may even need the parameters in a second run. Therefore, consider the creation of the (PDF) document finished when none of the processors causes the auxiliary file to change. This is performed by a shell script `w2pdf`.

```

< make targets 83a > ≡
    nlpp.pdf : nlpp.w $(W2PDF) $(PDF_FIG_NAMES) $(PDFT_NAMES)
              chmod 775 $(W2PDF)
              $(W2PDF) $*

```

◇

Fragment defined by 78d, 82b, 83a, 86c, 88bd, 89abc.

Fragment referenced in 78b.

Uses: pdf 82b, PDFT_NAMES 81b, PDF_FIG_NAMES 81b.

The following is an ugly fix of an unsolved problem. Currently I develop this thing, while it resides on a remote computer that is connected via the `sshfs` filesystem. On my home computer I cannot run executables on this system, but on my work-computer I can. Therefore, place the following script on a local directory.

```

< directories to create 83b > ≡
    ../nuweb/bin ◇

```

Fragment defined by 6, 7abc, 13c, 14bf, 17c, 83b.

Fragment referenced in 88b.

Uses: nuweb 84d.

```

< parameters in Makefile 83c > ≡
    W2PDF=../nuweb/bin/w2pdf
    ◇

```

Fragment defined by 78a, 79a, 81ab, 83c, 85b, 88a.

Fragment referenced in 78b.

Uses: nuweb 84d.

```

< expliciete make regels 83d > ≡
    $(W2PDF) : nlpp.w $(NUWEB)
              $(NUWEB) nlpp.w
    ◇

```

Fragment defined by 79bd, 80ab, 82a, 83d, 85c, 86b.

Fragment referenced in 78b.

```

"../nuweb/bin/w2pdf" 83e≡
    #!/bin/bash
    # w2pdf -- compile a nuweb file
    # usage: w2pdf [filename]
    # 20170510 at 1359h: Generated by nuweb from a_nlpp.w
    NUWEB=../env/bin/nuweb
    LATEXCOMPILER=pdflatex
    < filenames in nuweb compile script 84b >
    < compile nuweb 84a >

```

◇

Uses: nuweb 84d.

The script retains a copy of the latest version of the auxiliary file. Then it runs the four processors nuweb, L^AT_EX, MakeIndex and bibT_EX, until they do not change the auxiliary file or the index.

```

⟨ compile nuweb 84a ⟩ ≡
    NUWEB=/home/paul/projecten/pipelines/nlpp/env/bin/nuweb
    ⟨ run the processors until the aux file remains unchanged 85a ⟩
    ⟨ remove the copy of the aux file 84c ⟩
    ◇

```

Fragment referenced in 83e.

Uses: nuweb 84d.

The user provides the name of the nuweb file as argument. Strip the extension (e.g. .w) from the filename and create the names of the L^AT_EX file (ends with .tex), the auxiliary file (ends with .aux) and the copy of the auxiliary file (add old. as a prefix to the auxiliary filename).

```

⟨ filenames in nuweb compile script 84b ⟩ ≡
    nufil=$1
    trunk=${1%.*}
    texfil=${trunk}.tex
    auxfil=${trunk}.aux
    oldaux=old.${trunk}.aux
    indexfil=${trunk}.idx
    oldindexfil=old.${trunk}.idx
    ◇

```

Fragment referenced in 83e.

Defines: auxfil 85a, 87ab, indexfil 85a, 87a, nufil 84d, 87ac, oldaux 84c, 85a, 87ab, oldindexfil 85a, 87a, texfil 84d, 87ac, trunk 84d, 87acd.

Remove the old copy if it is no longer needed.

```

⟨ remove the copy of the aux file 84c ⟩ ≡
    rm $oldaux
    ◇

```

Fragment referenced in 84a, 86e.

Uses: oldaux 84b, 87a.

Run the three processors. Do not use the option -o (to suppress generation of program sources) for nuweb, because w2pdf must be kept up to date as well.

```

⟨ run the three processors 84d ⟩ ≡
    $NUWEB $nufil
    $LATEXCOMPILER $texfil
    makeindex $trunk
    bibtex $trunk
    ◇

```

Fragment referenced in 85a.

Defines: bibtex 87cd, makeindex 87cd, nuweb 7d, 74a, 78a, 79bcd, 83bce, 84a, 85b, 86d.

Uses: nufil 84b, 87a, texfil 84b, 87a, trunk 84b, 87a.

Repeat to copy the auxiliary file and the index file and run the processors until the auxiliary file and the index file are equal to their copies. However, since I have not yet been able to test the aux file and the idx in the same test statement, currently only the aux file is tested.

It turns out, that sometimes a strange loop occurs in which the aux file will keep to change. Therefore, with a counter we prevent the loop to occur more than 10 times.

```

⟨run the processors until the aux file remains unchanged 85a⟩ ≡
LOOPCOUNTER=0
while
  ! cmp -s $auxfil $oldaux
do
  if [ -e $auxfil ]
  then
    cp $auxfil $oldaux
  fi
  if [ -e $indexfil ]
  then
    cp $indexfil $oldindexfil
  fi
  ⟨run the three processors 84d⟩
  if [ $LOOPCOUNTER -ge 10 ]
  then
    cp $auxfil $oldaux
  fi;
done
◇

```

Fragment referenced in 84a.

Uses: auxfil 84b, 87a, indexfil 84b, oldaux 84b, 87a, oldindexfil 84b.

A.6.4 Create HTML files

HTML is easier to read on-line than a PDF document that was made for printing. We use `tex4ht` to generate HTML code. An advantage of this system is, that we can include figures in the same way as we do for `pdflatex`.

To create a HTML doc, we do the following:

1. Create a directory `../nuweb/html` for the HTML document.
2. Put the nuweb source in it, together with style-files that are needed (see variable `HTMLSOURCE`).
3. Put the script `w2html` in it and make it executable.
4. Execute the script `w2html`.

Make a list of the entities that we mentioned above:

```

⟨parameters in Makefile 85b⟩ ≡
htmlmdir=../nuweb/html
htmlsource=nlpp.w nlpp.bib html.sty artikel3.4ht w2html
htmlmaterial=$(foreach fil, $(htmlsource), $(htmlmdir)/$(fil))
htmltarget=$(htmlmdir)/nlpp.html
◇

```

Fragment defined by 78a, 79a, 81ab, 83c, 85b, 88a.

Fragment referenced in 78b.

Uses: nuweb 84d.

Make the directory:

```

⟨expliciete make regels 85c⟩ ≡
$(htmlmdir) :
    mkdir -p $(htmlmdir)
◇

```

Fragment defined by 79bd, 80ab, 82a, 83d, 85c, 86b.

Fragment referenced in 78b.

The rule to copy files in it:

```
< implicate make regels 86a > ≡
    $(htmldir)/% : % $(htmldir)
    cp $< $(htmldir)/
```

◇

Fragment defined by 81c, 86a.

Fragment referenced in 78b.

Do the work:

```
< expliciete make regels 86b > ≡
    $(htmltarget) : $(htmlmaterial) $(htmldir)
    cd $(htmldir) && chmod 775 w2html
    cd $(htmldir) && ./w2html nlpp.w
```

◇

Fragment defined by 79bd, 80ab, 82a, 83d, 85c, 86b.

Fragment referenced in 78b.

Invoke:

```
< make targets 86c > ≡
    htm : $(htmldir) $(htmltarget)
```

◇

Fragment defined by 78d, 82b, 83a, 86c, 88bd, 89abc.

Fragment referenced in 78b.

Create a script that performs the translation.

```
"w2html" 86d≡
#!/bin/bash
# w2html -- make a html file from a nuweb file
# usage: w2html [filename]
# [filename]: Name of the nuweb source file.
# 20170510 at 1359h: Generated by nuweb from a_nlpp.w
echo "translate " $1 >w2html.log
NUWEB=/home/paul/projecten/pipelines/nlpp/env/bin/nuweb
< filenames in w2html 87a >

< perform the task of w2html 86e >
```

◇

Uses: nuweb 84d.

The script is very much like the w2pdf script, but at this moment I have still difficulties to compile the source smoothly into HTML and that is why I make a separate file and do not recycle parts from the other file. However, the file works similar.

```
< perform the task of w2html 86e > ≡
    < run the html processors until the aux file remains unchanged 87b >
    < remove the copy of the aux file 84c >
```

◇

Fragment referenced in 86d.

The user provides the name of the nuweb file as argument. Strip the extension (e.g. `.w`) from the filename and create the names of the L^AT_EX file (ends with `.tex`), the auxiliary file (ends with `.aux`) and the copy of the auxiliary file (add `old.` as a prefix to the auxiliary filename).

```
<filenames in w2html 87a> ≡
  nufil=$1
  trunk=${1%.*}
  texfil=${trunk}.tex
  auxfil=${trunk}.aux
  oldaux=old.${trunk}.aux
  indexfil=${trunk}.idx
  oldindexfil=old.${trunk}.idx
  ◇
```

Fragment referenced in 86d.

Defines: `auxfil` 84b, 85a, 87b, `nufil` 84bd, 87c, `oldaux` 84bc, 85a, 87b, `texfil` 84bd, 87c, `trunk` 84bd, 87cd.

Uses: `indexfil` 84b, `oldindexfil` 84b.

```
<run the html processors until the aux file remains unchanged 87b> ≡
  while
    ! cmp -s $auxfil $oldaux
  do
    if [ -e $auxfil ]
    then
      cp $auxfil $oldaux
    fi
    <run the html processors 87c>
  done
  <run tex4ht 87d>
  ◇
```

Fragment referenced in 86e.

Uses: `auxfil` 84b, 87a, `oldaux` 84b, 87a.

To work for HTML, nuweb *must* be run with the `-n` option, because there are no page numbers.

```
<run the html processors 87c> ≡
  $NUWEB -o -n $nufil
  latex $texfil
  makeindex $trunk
  bibtex $trunk
  htlatex $trunk
  ◇
```

Fragment referenced in 87b.

Uses: `bibtex` 84d, `makeindex` 84d, `nufil` 84b, 87a, `texfil` 84b, 87a, `trunk` 84b, 87a.

When the compilation has been satisfied, run `makeindex` in a special way, run `bibtex` again (I don't know why this is necessary) and then run `htlatex` another time.

```
<run tex4ht 87d> ≡
  tex '\def\filename{{nlpp}{idx}{4dx}{ind}} \input idxmake.4ht'
  makeindex -o $trunk.ind $trunk.4dx
  bibtex $trunk
  htlatex $trunk
  ◇
```

Fragment referenced in 87b.

Uses: `bibtex` 84d, `makeindex` 84d, `trunk` 84b, 87a.

A.7 Perform the installation

Run nuweb, but suppress the creation of the L^AT_EX documentation. Nuweb creates only sources that do not yet exist or that have been modified. Therefore make does not have to check this. However, “make” has to create the directories for the sources if they do not yet exist. So, let’s create the directories first.

```
⟨ parameters in Makefile 88a ⟩ ≡
    MKDIR = mkdir -p
```

◇

Fragment defined by 78a, 79a, 81ab, 83c, 85b, 88a.

Fragment referenced in 78b.

Defines: MKDIR 88b.

```
⟨ make targets 88b ⟩ ≡
    DIRS = ⟨ directories to create 6, ... ⟩
```

```
$(DIRS) :
    $(MKDIR) $@
```

◇

Fragment defined by 78d, 82b, 83a, 86c, 88bd, 89abc.

Fragment referenced in 78b.

Defines: DIRS 88d.

Uses: MKDIR 88a.

```
⟨ make scripts executable 88c ⟩ ≡
    chmod -R 775 ../bin/*
    chmod -R 775 ../env/bin/*
```

◇

Fragment defined by 26d, 37a, 88c.

Fragment referenced in 88d.

The target “sources” unpacks the nuweb file and creates the program scripts, i.e. the scripts that will apply modules on a NAF file and the script `install_modules` that installs the modules themselves and that creates the software environment the the modules need.

```
⟨ make targets 88d ⟩ ≡
    sources : nlpp.w $(DIRS) $(NUWEB)
              $(NUWEB) nlpp.w
              ⟨ make scripts executable 26d, ... ⟩
```

◇

Fragment defined by 78d, 82b, 83a, 86c, 88bd, 89abc.

Fragment referenced in 78b.

Uses: DIRS 88b.

The “install” target performs the complete installation.


```

< make targets 89a > ≡
    install : sources
             ../bin/install-modules

```

◇

Fragment defined by 78d, 82b, 83a, 86c, 88bd, 89abc.

Fragment referenced in 78b.

Defines: **install** 10c, 12ab, 16b, 17a, 18ac, 19ae, 26dj, 27a, 31d, 33c, 43a, 45d, 61a, 62c, 63f, 64ab, 66a, 68c, 70a, 78e, 89b.

A.8 Test whether it works

The targets `testnl` and `testen` perform the test-script (section ??) to test the dutch resp. english pipeline.

```

< make targets 89b > ≡

    testnl : install test.nl.in.naf
            rm -rf ../test
            mkdir ../test
            cd ../test && ../bin/test nl

    testen : install test.en.in.naf
            rm -rf ../test
            mkdir ../test
            cd ../test && ../bin/test en

```

◇

Fragment defined by 78d, 82b, 83a, 86c, 88bd, 89abc.

Fragment referenced in 78b.

Defines: **testen** Never used, **testnl** Never used.

Uses: **install** 89a.

A.9 Restore paths after transplantation

When an existing installation has been transplanted to another location, many path indications have to be adapted to the new situation. The scripts that are generated by `nuweb` can be repaired by re-running `nuweb`. After that, configuration files of some modules must be modified.

```

< make targets 89c > ≡
    transplant :
                touch a_nlpp.w
                $(MAKE) sources
                ../env/bin/transplant

```

◇

Fragment defined by 78d, 82b, 83a, 86c, 88bd, 89abc.

Fragment referenced in 78b.

In order to work as expected, the following script must be re-made after a transplantation.

```

"../env/bin/transplant" 90≡
    #!/bin/bash
    LOGLEVEL=1
    < set variables that point to the directory-structure 7d, ... >
    < set paths after transplantation 18b >
    < re-install modules after the transplantation 33d >

    ◇

```

B References

B.1 Literature

References

- [1] Donald E. Knuth. Literate programming. Technical report STAN-CS-83-981, Stanford University, Department of Computer Science, 1983.

C Indexes

C.1 Filenames

```

"../bin/check_start_spotlight" Defined by 36ac.
"../bin/constpars" Defined by 45b.
"../bin/coreference-base" Defined by 56d.
"../bin/dbpner" Defined by 68a.
"../bin/derel" Defined by 62a.
"../bin/eSRL" Defined by 50c.
"../bin/evcoref" Defined by 67b.
"../bin/ewsd" Defined by 47b.
"../bin/factuality" Defined by 55d.
"../bin/FBK-causalrel" Defined by 55a.
"../bin/FBK-temprel" Defined by 54a.
"../bin/FBK-time" Defined by 52a.
"../bin/framesrl" Defined by 62f.
"../bin/heideltime" Defined by 64d.
"../bin/install-modules" Defined by 22a, 23aj, 24aj, 25ahq, 26a.
"../bin/lu2synset" Defined by 60a.
"../bin/mor" Defined by 43e.
"../bin/naf2sem" Defined by 69a.
"../bin/ned" Defined by 61b.
"../bin/nedrer" Defined by 45e.
"../bin/nerc" Defined by 58c.
"../bin/nerc_conll02" Defined by 58a.
"../bin/nlpp" Defined by 75a.
"../bin/nomevent" Defined by 63a.
"../bin/onto" Defined by 62d.
"../bin/opinimin" Defined by 71a.
"../bin/pos" Defined by 44c.
"../bin/postersrl" Defined by 66c.
"../bin/srl" Defined by 65bdefg.
"../bin/srl-dutch-nominals" Defined by 51a.
"../bin/start_eSRL" Defined by 50a.
"../bin/stop_eSRL" Defined by 50b.
"../bin/test" Defined by 74b.

```

"../bin/tok" Defined by 41c.
 "../bin/topic" Defined by 43b.
 "../bin/ukb" Defined by 46d.
 "../bin/wikify" Defined by 46a.
 "../bin/wsd" Defined by 59c.
 "../env/bin/langdetect.py" Defined by 29b.
 "../env/bin/progenv" Defined by 8a, 13b, 48a.
 "../env/bin/transplant" Defined by 90.
 "../nuweb/bin/w2pdf" Defined by 83e.
 "Makefile" Defined by 78b.
 "w2html" Defined by 86d.

C.2 Macro's

<activate the install-to-project-repo utility 64b> Not referenced.
 <activate the python environment 17bde> Referenced in 15e, 22a.
 <all targets 78e> Referenced in 78c.
 <annotate 73> Referenced in 74b, 75a.
 <annotate dutch document 72a> Not referenced.
 <annotate english document 72b> Referenced in 73.
 <begin conditional install 20c> Referenced in 13d, 22a, 23aj, 24aj, 25ahq, 26a.
 <check listener on host, port 37d> Referenced in 36c, 40a.
 <check this first 10g, 26e> Referenced in 22a.
 <check whether mercurial is present 27a> Referenced in 26e.
 <check whether program is present 26j> Referenced in 26e.
 <check/install the correct version of python 16a> Referenced in 15e.
 <clean up 13g, 15a, 31b, 79c> Referenced in 78d.
 <clone the heideltime wrapper 63d> Referenced in 63c.
 <compile nuweb 84a> Referenced in 83e.
 <compile the heideltime wrapper 64a> Referenced in 63c.
 <compile the nerc jar 57b> Referenced in 57a.
 <compile the topic-tool jar 43a> Referenced in 42a.
 <create a virtual environment for Python 16c> Referenced in 15e.
 <create javapython script 13a> Referenced in 22a.
 <default target 78c> Referenced in 78b.
 <directories to create 6, 7abc, 13c, 14bf, 17c, 83b> Referenced in 88b.
 <download everything 9c> Referenced in 22a.
 <download stuff 11ac, 14c, 19b, 34b, 40e, 42b, 60d> Referenced in 9c.
 <download svm models 59b> Referenced in 58e.
 <else conditional install 21a> Not referenced.
 <end conditional install 21b> Referenced in 13d, 22a, 23aj, 24aj, 25ahq, 26a.
 <explicitete make regels 79bd, 80ab, 82a, 83d, 85c, 86b> Referenced in 78b.
 <filenames in nuweb compile script 84b> Referenced in 83e.
 <filenames in w2html 87a> Referenced in 86d.
 <find a spotlightserver or exit 37b> Referenced in 46a, 61b.
 <function to run a module 71c> Referenced in 74b, 75a.
 <function to start EHU SRL server 49a> Referenced in 50a.
 <get a testfile or die 74a> Referenced in 74b.
 <get commandline-arguments 27b> Referenced in 36a.
 <get spotlight language parameters 37c> Not referenced.
 <get spotlight model ball 35b> Not referenced.
 <get the mor time-out parameter 44a> Referenced in 43e.
 <get the nerc models 57d> Referenced in 57a.
 <get the path to the module-script 29a> Referenced in 28b.
 <impliciete make regels 81c, 86a> Referenced in 78b.
 <install ActivePython 16b> Referenced in 16a.
 <install Alpino 30c> Referenced in 22a.
 <install boost 34a> Referenced in 22a.

- ⟨install coreference-base 56c⟩ Referenced in 25a.
- ⟨install from github 10a⟩ Referenced in 43d, 50f, 55c, 58e, 60c, 63d, 65a, 67d, 69c.
- ⟨install from tarball 76a⟩ Not referenced.
- ⟨install Java 1.6 15c⟩ Referenced in 22a.
- ⟨install kafnaparserpy 18c⟩ Referenced in 15e.
- ⟨install libxml2 or libxslt 12b⟩ Referenced in 12c.
- ⟨install maven 14g⟩ Referenced in 22a.
- ⟨install naf2sem 68c⟩ Not referenced.
- ⟨install perl 19ef, 20a⟩ Referenced in 22a.
- ⟨install python packages 19a, 66a⟩ Referenced in 15e.
- ⟨install sematree 28a⟩ Referenced in 22a.
- ⟨install shared libs 12ac⟩ Referenced in 22a.
- ⟨install svm lib 59a⟩ Referenced in 58e.
- ⟨install SVMLight 41a⟩ Referenced in 22a.
- ⟨install the constituents parser 45a⟩ Referenced in 23j.
- ⟨install the dbpedia-ner module 67d⟩ Referenced in 25q.
- ⟨install the de-link module 61d⟩ Referenced in 23j.
- ⟨install the event-coreference module 67a⟩ Referenced in 25h.
- ⟨install the factuality modules 55c⟩ Referenced in 24j.
- ⟨install the FBK-causalrel module 54c⟩ Referenced in 24j.
- ⟨install the FBK-temprel module 53b⟩ Referenced in 24j.
- ⟨install the FBK-time module 51c⟩ Referenced in 24j.
- ⟨install the heideltime module 63c⟩ Referenced in 25h.
- ⟨install the ims-wsd module 47a⟩ Referenced in 24a.
- ⟨install the jex resources and libraries 42g⟩ Referenced in 42a.
- ⟨install the lu2synset converter 59e⟩ Referenced in 25h.
- ⟨install the morphosyntactic parser 43d⟩ Referenced in 23a.
- ⟨install the NERC module 57a⟩ Referenced in 23j.
- ⟨install the ontotagger repository 62c⟩ Referenced in 25a.
- ⟨install the opinion-miner 69c, 70abcd⟩ Referenced in 26a.
- ⟨install the pos tagger 44b⟩ Referenced in 23a.
- ⟨install the post-SRL module 66b⟩ Referenced in 25q.
- ⟨install the Spotlight server 35ac⟩ Referenced in 22a.
- ⟨install the srl module 65a⟩ Referenced in 25h.
- ⟨install the srl-dutch-nominals module 50f⟩ Referenced in 24a.
- ⟨install the srl-server module 49c⟩ Referenced in 24a.
- ⟨install the ticcutils utility 33a⟩ Referenced in 22a, 33d.
- ⟨install the timbl utility 33b⟩ Referenced in 22a, 33d.
- ⟨install the tokenizer 41b⟩ Referenced in 23a.
- ⟨install the topic analyser 42a⟩ Referenced in 23a.
- ⟨install the treetagger utility 31cde, 32abcd⟩ Referenced in 22a.
- ⟨install the UKB module 46c⟩ Not referenced.
- ⟨install the wikify module 45g⟩ Referenced in 23j.
- ⟨install the WSD module 58e⟩ Referenced in 25a.
- ⟨install the NED-reranker module 45d⟩ Referenced in 23j.
- ⟨install the NED module 60c⟩ Referenced in 23j.
- ⟨install VUA-pylib 40d⟩ Referenced in 22a.
- ⟨logmess 75d⟩ Referenced in 9a, 10a, 76a.
- ⟨make scripts executable 26d, 37a, 88c⟩ Referenced in 88d.
- ⟨make targets 78d, 82b, 83a, 86c, 88bd, 89abc⟩ Referenced in 78b.
- ⟨move module 8b⟩ Referenced in 10a, 76a.
- ⟨need to wget 11b⟩ Referenced in 11c, 14c, 19b, 34b, 40e, 42b, 60d.
- ⟨parameters in Makefile 78a, 79a, 81ab, 83c, 85b, 88a⟩ Referenced in 78b.
- ⟨perform the task of w2html 86e⟩ Referenced in 86d.
- ⟨put miscellaneous stuff in the heideltime module 63f⟩ Referenced in 63c.
- ⟨put spotlight jar in the Maven repository 61a⟩ Referenced in 60c.
- ⟨re-install modules after the transplantation 33d⟩ Referenced in 90.
- ⟨re-instate old module 9a⟩ Referenced in 10a, 76a.

<read the list of installed modules 20b> Referenced in 22a.
 <remove installed-variable 21c> Referenced in 15a.
 <remove old module 8c> Referenced in 10a, 76a.
 <remove outdated heideltime jars 64c> Referenced in 64b.
 <remove the copy of the aux file 84c> Referenced in 84a, 86e.
 <repair causalrel's run.sh.hadoop 54e> Not referenced.
 <repair FBK-*rel's run.sh.hadoop 53d> Referenced in 53b, 54c.
 <run dutch factuality 56b> Referenced in 55d.
 <run english factuality 56a> Referenced in 55d.
 <run in subshell when naflang is not known 30a> Referenced in 28b.
 <run only if language is English or Dutch 30b> Referenced in 28b.
 <run tex4ht 87d> Referenced in 87b.
 <run the html processors 87c> Referenced in 87b.
 <run the html processors until the aux file remains unchanged 87b> Referenced in 86e.
 <run the processors until the aux file remains unchanged 85a> Referenced in 84a.
 <run the three processors 84d> Referenced in 85a.
 <select language-dependent features 57c> Not referenced.
 <set alpinohome 31a> Referenced in 43e.
 <set default arguments for Spotlight 36b> Referenced in 36a.
 <set paths after transplantation 18b> Referenced in 90.
 <set up java 13d, 14a> Referenced in 22a.
 <set up Java 1.6 15d> Referenced in 47b.
 <set up python 15e> Referenced in 22a.
 <set variables for test/run script 75b> Referenced in 74b, 75a.
 <set variables that point to the directory-structure 7de, 10f, 14h> Referenced in 8a, 22a, 90.
 <start EHU SRL server 50e> Not referenced.
 <start EHU SRL server if it isn't running 48b> Referenced in 50a.
 <start of module-script 28b> Referenced in 41c, 43be, 44c, 45be, 46ad, 47b, 50c, 51a, 52a, 54a, 55ad, 56d, 58ac, 59c, 60a, 61b, 62adf, 63a, 64d, 65b, 66c, 67b, 68a, 69a, 71a.
 <start the Spotlight server on localhost 39ab> Referenced in 36c, 38a.
 <stop on error 53a> Referenced in 52a.
 <test whether spotlightserver runs 38e> Referenced in 38a.
 <test whether virtualenv is present on the host 17a> Referenced in 16c.
 <try to obtain a running spotlightserver 38a> Not referenced.
 <unpack ticcutils or timbl 33c> Referenced in 33ab.
 <update pip 18a> Referenced in 15e.
 <variables of install-modules 75c> Referenced in 22a.
 <wait for SRL server 49b> Referenced in 50c.
 <wait until the spotlight server is up or faulty 40a> Referenced in 39b.

C.3 Variables

activate: 17b, 18b.
 all: 69a, 78c.
 ALPINO_HOME: 31a.
 auxfil: 84b, 85a, 87a, 87b.
 bibtex: 84d, 87cd.
 BIND: 71c, 75b.
 DIRS: 88b, 88d.
 fig2dev: 81c.
 FIGFILENAMES: 81b.
 FIGFILES: 81a, 81b.
 hg: 27a.
 indexfil: 84b, 85a, 87a.
 install: 10c, 12ab, 16b, 17a, 18ac, 19ae, 26dj, 27a, 31d, 33c, 43a, 45d, 61a, 62c, 63f, 64ab, 66a, 68c, 70a, 78e, 89a, 89b.
 LD_LIBRARY_PATH: 17e, 46d, 56a.
 lxml: 19a.

makeindex: [84d](#), [87cd](#).
MKDIR: [88a](#), [88b](#).
moduleresult: [71c](#), [74b](#), [75a](#).
naflang: [27b](#), [30ab](#), [36b](#), [37bc](#), [39a](#), [41c](#), [43b](#), [55d](#), [57c](#), [58c](#), [67b](#), [73](#).
networkx: [19a](#).
nufil: [84b](#), [84d](#), [87a](#), [87c](#).
nuweb: [7d](#), [74a](#), [78a](#), [79bcd](#), [83bce](#), [84a](#), [84d](#), [85b](#), [86d](#).
oldaux: [84b](#), [84c](#), [85a](#), [87a](#), [87b](#).
oldindexfil: [84b](#), [85a](#), [87a](#).
PATH: [7e](#), [14ah](#), [15d](#), [19f](#), [56a](#).
pdf: [79a](#), [82b](#), [83a](#).
PDFT_NAMES: [81b](#), [83a](#).
PDF_FIG_NAMES: [81b](#), [83a](#).
PHONY: [78c](#), [82a](#).
polarity_models.tgz: [70d](#).
print: [16a](#), [18b](#), [21c](#), [29b](#), [37b](#), [62f](#), [80a](#), [82b](#).
PST_NAMES: [81b](#).
PS_FIG_NAMES: [81b](#).
pythonok: [16a](#).
PYTHONPATH: [17d](#).
pyyaml: [19a](#).
rdflib: [66a](#).
runmodule: [71c](#), [72ab](#), [73](#).
scriptpath: [29a](#), [30a](#).
SUFFIXES: [79a](#).
svm_classify: [41a](#), [70b](#).
svm_learn: [41a](#), [70b](#).
testen: [89b](#).
testnl: [89b](#).
texfil: [84b](#), [84d](#), [87a](#), [87c](#).
trunk: [84b](#), [84d](#), [87a](#), [87cd](#).
view: [82b](#).
virtualenv: [16bc](#), [17a](#).