



# Nearest Neighbor Classifiers

- Basic idea:
  - If it walks like a duck, quacks like a duck, then it's probably a duck




# Nearest neighbor method

- Majority vote within the k nearest neighbors




# Nearest-Neighbor Classifiers




- Requires three things
  - The set of stored records
  - Distance Metric to compute distance between records
  - The value of  $k$ , the number of nearest neighbors to retrieve
- To classify an unknown record:
  - Compute distance to other training records
  - Identify  $k$  nearest neighbors
  - Use class labels of nearest neighbors to determine the class label of unknown record (e.g., by taking majority vote)


# Definition of Nearest Neighbor



(a) 1-nearest neighbor



(b) 2-nearest neighbor




(c) 3-nearest neighbor

K-nearest neighbors of a record  $x$  are data points that have the  $k$  smallest distance to  $x$

# Nearest Neighbor Classification...

- Choosing the value of  $k$ :
  - If  $k$  is too small, sensitive to noise points
  - If  $k$  is too large, neighborhood may include points from other classes



# Nearest neighbor Classification...

---

- k-NN classifiers are lazy learners
  - It does not build models explicitly
  - Unlike eager learners such as decision tree induction and rule-based systems
  - Classifying unknown records are relatively expensive

# Metrics for Performance Evaluation

- Focus on the predictive capability of a model
  - Rather than how fast it takes to classify or build models, scalability, etc.
- Confusion Matrix:

ACTUAL CLASS	PREDICTED CLASS		
		Class=Yes	Class=No
	Class=Yes	a	b
	Class=No	c	d

a: TP (true positive)  
b: FN (false negative)  
c: FP (false positive)  
d: TN (true negative)

# Metrics for Performance Evaluation...

ACTUAL CLASS	PREDICTED CLASS	
	Class=Yes	Class=No
	Class=Yes a (TP)	b (FN)
Class=No	c (FP)	d (TN)

- Most widely-used metric:

$$\text{Accuracy} = \frac{a + d}{a + b + c + d} = \frac{TP + TN}{TP + TN + FP + FN}$$



# Limitation of Accuracy

---

- Consider a 2-class problem
  - Number of Class 0 examples = 9990
  - Number of Class 1 examples = 10
- If model predicts everything to be class 0, accuracy is  $9990/10000 = 99.9\%$ 
  - Accuracy is misleading because model does not detect any class 1 example