Extending the HAR-RV Model with ElasticNet Regularization: Sparse Feature Selection for Equity Volatility Forecasting

Paul Montier

March 16, 2026

Abstract

We extend the Heterogeneous Autoregressive model of Realized Volatility (HAR-RV, Corsi 2009) from 3 to 20 features incorporating intraday microstructure, higher moments, leverage effects, and cross-sectional information. We show that Ridge regression fails to exploit the additional features (IC = 0.452 with 20 features vs. 0.451 with 3), while ElasticNet regularization (Zou & Hastie, 2005) achieves IC = 0.474 by automatically zeroing out noisy predictors via its L1 component. A greedy backward elimination procedure, conducted exclusively on the first temporal half of the data to prevent look-ahead bias, identifies 12 features that yield an out-of-sample IC of 0.494 — a 9.3% improvement over the Ridge baseline. All results are obtained through walk-forward backtesting with purging and VIX-adaptive training windows on 5 S&P 500 large-cap stocks using 1-minute intraday data.

Keywords: Realized volatility, HAR-RV, ElasticNet, feature selection, walk-forward backtesting, Spearman IC.

Contents

I The HAR-RV Framework **3**

1 Introduction **3**

2 The Corsi HAR-RV Model **3**

2.1 Realized Volatility from Intraday Data . . . 3

2.2 The Heterogeneous Market Hypothesis . . . 4

2.3 The HAR-RV Specification . . . 4

3 Extending the Feature Set: From 3 to 20 Predictors **4**

3.1 Data . . . 5

3.2 Target Variable . . . 5

3.3 HAR-RV Core Features (6) . . . 5

3.4 Multi-Timeframe Daily Features (3) . . . 6

3.5 Intraday 1-Minute Features (4) . . . 6

3.6 Higher Moments (3) . . . 7

3.7 Leverage Features (2) . . . 7

3.8 Cross-Sectional Features (2) . . . 8

II ElasticNet Regularization and Feature Selection **9**

4 Backtesting Methodology **9**
4.1 Walk-Forward Protocol . . . 9
4.2 VIX-Adaptive Training Window . . . 9

5 The Regularization Problem **10**
5.1 Why Ridge Fails with Many Features . . . 10
5.2 ElasticNet: Combining L1 Sparsity and L2 Stability . . . 10
5.3 Feature Selection Without Look-Ahead Bias . . . 10

6 Results **11**
6.1 Ridge vs. ElasticNet: The Impact of L1 Sparsity . . . 11
6.2 Coefficient Analysis: What ElasticNet Learns . . . 12
6.3 Greedy Feature Selection . . . 14
6.4 Look-Ahead Bias Quantification . . . 15
6.5 Final Synthesis . . . 15
6.6 Conditional Performance by VIX Regime . . . 16

7 Discussion **18**
7.1 Why ElasticNet Over XGBoost? . . . 18
7.2 Decomposition of the IC Gain . . . 18
7.3 Anti-Leakage Protections . . . 19

8 Conclusion **19**

Part I

The HAR-RV Framework

1 Introduction

Forecasting realized volatility is a central problem in quantitative finance, with applications ranging from risk management to options pricing and portfolio optimization. Since the seminal work of Andersen et al. (2003), realized volatility computed from high-frequency intraday data has become the standard measure of ex-post volatility, providing a model-free estimate that avoids the parametric assumptions of GARCH-type models.

The Heterogeneous Autoregressive model of Realized Volatility (HAR-RV), proposed by Corsi (2009), has emerged as a benchmark in the volatility forecasting literature. Its key insight is that volatility dynamics are driven by heterogeneous market participants operating at different time horizons — daily traders, weekly portfolio managers, and monthly institutional investors — each contributing to volatility persistence at their characteristic frequency. Despite its simplicity (a linear model with only 3 regressors), the HAR-RV captures the long-memory and multi-scale properties of volatility remarkably well.

In this paper, we pursue two objectives. First, we extend the HAR-RV feature set from 3 to 20 predictors, drawing on advances in volatility measurement: Bipower Variation for jump detection (Barndorff-Nielsen & Shephard, 2004), realized higher moments (Amaya et al., 2015), the leverage effect (Black, 1976), range-based estimators (Parkinson, 1980), and cross-sectional information. Second, we address the challenge of exploiting these additional features without overfitting, using ElasticNet regularization (Zou & Hastie, 2005) and a disciplined feature selection procedure.

2 The Corsi HAR-RV Model

2.1 Realized Volatility from Intraday Data

The foundation of the HAR-RV model is the *realized volatility* (RV), a nonparametric estimator of daily return variation constructed from high-frequency intraday data. Given n intraday returns $r_{t,1}, r_{t,2}, \ldots, r_{t,n}$ observed at regular intervals on day t, the realized variance is:

$$RV_t^2 = \sum_{i=1}^{n} r_{t,i}^2 \tag{1}$$

where $r_{t,i} = (P_{t,i} - P_{t,i-1})/P_{t,i-1}$ is the return over the i-th interval. With 1-minute bars, $n \approx 390$ for US equities (6.5 hours of trading). The realized volatility is then $RV_t = \sqrt{RV_t^2}$.

The key insight from Andersen et al. (2003) is that RV_t^2 converges to the integrated variance $\int_0^1 \sigma_t^2(s)\, ds$ as the sampling frequency increases, providing a model-free and consistent estimator of the true latent volatility. This makes RV far more informative than daily squared returns, which are extremely noisy estimators of daily variance.

2.2 The Heterogeneous Market Hypothesis

The HAR-RV model is motivated by the *Heterogeneous Market Hypothesis* (Müller et al., 1993): different types of market participants operate at different frequencies, and their actions create volatility components at multiple horizons. Corsi identifies three characteristic horizons:

- **Daily/weekly traders** (horizon ∼5 days): react quickly to news, drive short-term volatility dynamics.
- **Portfolio managers** (horizon ∼22 days): rebalance monthly, create medium-term mean-reversion patterns.
- **Institutional/strategic investors** (horizon ∼60 days): set long-term allocations, determine the baseline volatility regime.

2.3 The HAR-RV Specification

The HAR-RV model expresses future volatility as a linear function of past volatility at three horizons:

$$RV_{t+1:t+h} = \beta_0 + \beta_w \cdot RV_w + \beta_m \cdot RV_m + \beta_q \cdot RV_q + \varepsilon_t \tag{2}$$

where the multi-horizon RV components are defined as simple averages of daily RV:

$$RV_w = \frac{1}{5}\sum_{k=0}^{4} RV_{t-k} \qquad \text{(weekly, 5 days)} \tag{3}$$

$$RV_m = \frac{1}{22}\sum_{k=0}^{21} RV_{t-k} \qquad \text{(monthly, 22 days)} \tag{4}$$

$$RV_q = \frac{1}{60}\sum_{k=0}^{59} RV_{t-k} \qquad \text{(quarterly, 60 days)} \tag{5}$$

Despite its simplicity — a linear model with 3 regressors — the HAR-RV captures several important properties of volatility:

- **Long memory**: the cascade from daily to quarterly components generates hyperbolic decay in the autocorrelation function, mimicking the long-memory behavior observed in empirical RV series.
- **Multi-scale persistence**: shocks at each horizon have different half-lives. A daily spike dissipates in ∼5 days; a shift in the quarterly level persists for months.
- **Mean-reversion**: the monthly component RV_m acts as an attractor. When $RV_w \gg RV_m$, the model predicts a decrease in future volatility (reversion to the mean), and vice versa.

3 Extending the Feature Set: From 3 to 20 Predictors

While the original HAR-RV model with 3 features is a strong baseline, the volatility literature has identified numerous additional predictors that carry complementary information. We extend the feature set to 20 predictors organized in 6 categories.

3.1 Data

We use 1-minute intraday bar data from the Alpaca API for 5 S&P 500 large-cap stocks: AAPL, MSFT, NVDA, JPM, and META. Each trading day yields approximately 390 one-minute bars (9:30–16:00 EST). We also retrieve the CBOE VIX index as an exogenous predictor.

3.2 Target Variable

Rather than predicting raw future RV, we predict the log-ratio of future volatility to current monthly volatility:

$$y_t = \log\left(\frac{\overline{RV}_{t+1:t+5}}{RV_{m,t}}\right) \tag{6}$$

where $\overline{RV}_{t+1:t+5} = \frac{1}{5}\sum_{k=1}^{5} RV_{t+k}$. This normalization serves two purposes: (i) it makes the target stationary by removing the level effect, and (ii) it makes the target comparable across stocks with different volatility levels (e.g., NVDA at ∼40% vol vs. JPM at ∼20%).

3.3 HAR-RV Core Features (6)

Beyond the three original features (RV_w, RV_m, RV_q), we add three predictors that capture asymmetry and forward-looking information:

1. RV_w, RV_m, RV_q — The original Corsi (2009) triplet, as defined above.

2. RV_{neg} — Negative semi-variance (5-day average):

$$RV_{neg} = \sqrt{\frac{1}{5}\sum_{k=0}^{4}\sum_{i:r_{t-k,i}<0} r_{t-k,i}^2} \tag{7}$$

   Only negative 1-minute returns are included. This captures the *asymmetric* impact of downside moves on future volatility: the leverage effect of Black (1976) shows that negative returns increase financial leverage, which amplifies future volatility. If RV_{neg}/RV_w is high, the recent volatility is dominated by declines, predicting higher future vol.

3. J_w — Jump component via Bipower Variation (Barndorff-Nielsen & Shephard, 2004):

$$J_w = \max\left(RV^2 - BPV,\ 0\right), \quad BPV = \frac{\pi}{2}\sum_{i=2}^{n} |r_{t,i}| \cdot |r_{t,i-1}| \tag{8}$$

   The BPV estimates the *continuous* component of variance by multiplying consecutive absolute returns. The key insight is that isolated jumps contribute little to BPV: if a jump occurs at minute i (large $|r_{t,i}|$), the adjacent minute $i-1$ is typically normal (small $|r_{t,i-1}|$), making the product small. The factor $\pi/2$ ensures unbiasedness under a continuous semi-martingale. The difference $RV^2 - BPV$ therefore isolates the jump component.

4. **VIX** — The CBOE Volatility Index, lagged by 1 day. The VIX is computed from the prices of all S&P 500 options and reflects market-wide expectations of future volatility. It is the only *forward-looking* predictor in our model — all other features are backward-looking. We lag it by 1 day to prevent any same-day information leakage.

3.4 Multi-Timeframe Daily Features (3)

These features capture volatility information beyond close-to-close returns:

1. $RV_{overnight}$ — Average overnight gap (5-day):

$$RV_{overnight} = \frac{1}{5}\sum_{k=0}^{4} \frac{|Open_{t-k} - Close_{t-k-1}|}{Close_{t-k-1}} \tag{9}$$

   Measures the price movement during the 17.5 hours when US markets are closed. Overnight gaps reflect the impact of after-hours earnings announcements, geopolitical events, and information from Asian/European markets.

2. **Parkinson** — Range-based volatility estimator (Parkinson, 1980):

$$Parkinson_t = \sqrt{\frac{[\ln(H_t/L_t)]^2}{4\ln 2}} \tag{10}$$

   where H_t and L_t are the daily high and low prices. The constant $4\ln 2 \approx 2.77$ comes from the theoretical result that $E[\ln(H/L)]^2 = 4\ln(2)\cdot\sigma^2$ under geometric Brownian motion. The Parkinson estimator is more *efficient* than close-to-close volatility because it uses the full intraday price range: a stock that opens at 100, spikes to 110, drops to 95, and closes at 100 has zero close-to-close vol but substantial Parkinson vol.

3. Vol_{ratio} — Relative volume: $Volume_t/\overline{Volume}_{22d}$. A ratio above 1 signals abnormally high activity (earnings, institutional flows, panic selling), which typically precedes or accompanies high-volatility regimes.

3.5 Intraday 1-Minute Features (4)

These features exploit the granularity of 1-minute data to capture microstructure effects:

1. RV_{1min} — Volatility from 1-minute bars (5-day average). While RV_w uses 5-minute bars (78 per day), RV_{1min} uses all 390 1-minute bars, capturing higher-frequency dynamics that 5-minute sampling smooths out.

2. $Vol_{1m/5m}$ — Ratio of 1-minute to 5-minute volatility. Under a pure diffusion process, this ratio equals 1 regardless of sampling frequency. Departures from 1 indicate *microstructure noise* — the bid-ask bounce and HFT activity that inflate measured volatility at very high frequencies.

3. $Vol_{AM/PM}$ — Morning-to-afternoon volume ratio ($Volume_{9:30\text{-}12:00}/Volume_{12:00\text{-}16:00}$). Institutional investors tend to trade more in the morning ("smart money"); a high AM/PM ratio may signal directional institutional flows.

4. **Autocorr** — Lag-1 autocorrelation of 1-minute returns:

$$\rho_1 = \frac{\sum_{i=2}^{n}(r_{t,i} - \bar{r})(r_{t,i-1} - \bar{r})}{\sum_{i=1}^{n}(r_{t,i} - \bar{r})^2} \tag{11}$$

In calm markets, $\rho_1 < 0$ (mean-reversion from bid-ask bounce). In stressed markets, $\rho_1 > 0$ (momentum cascades: selling begets more selling). The sign of intraday autocorrelation is therefore informative about the current market regime.

3.6 Higher Moments (3)

These features capture distributional characteristics beyond variance:

1. **RSkew** — Realized skewness (Amaya et al., 2015):

$$RSkew_t = \sqrt{n} \cdot \frac{\sum_{i=1}^{n} r_{t,i}^3}{\left(\sum_{i=1}^{n} r_{t,i}^2\right)^{3/2}} \tag{12}$$

   The cube r^3 preserves sign: large negative returns contribute negatively, making the measure sensitive to *crash risk*. The denominator $RV^{3/2}$ normalizes by the level of volatility (so that high-vol days don't mechanically have larger skewness), and $\sqrt{n}$ is a scaling factor that makes the statistic comparable to the theoretical skewness of a distribution.

2. **RKurt** — Realized kurtosis:

$$RKurt_t = n \cdot \frac{\sum_{i=1}^{n} r_{t,i}^4}{\left(\sum_{i=1}^{n} r_{t,i}^2\right)^{2}} \tag{13}$$

   The fourth power r^4 massively amplifies extreme returns: a 3% return contributes 810,000× more than a 0.1% return to $\sum r^4$. Under Gaussianity, $RKurt = 3$; values substantially above 3 signal *fat tails* — a fragile market state where extreme moves are more frequent than a normal distribution would predict.

3. $Jump_{ratio}$ — Proportion of variance from jumps: $J/RV^2 \in [0, 1]$. Jump-dominated variance dissipates faster than continuous variance, so this decomposition helps predict *how long* elevated volatility will persist.

3.7 Leverage Features (2)

1. Ret_w — Cumulative 5-day return: $Ret_w = \sum_{k=0}^{4} r_{t-k}$. Captures the directional *leverage effect* (Black, 1976): when a stock's price falls, equity value decreases while debt remains constant, increasing the firm's financial leverage and thus its equity volatility. Negative Ret_w predicts higher future vol — one of the most robust stylized facts in finance.

2. $Leverage_{22d}$ — Rolling 22-day correlation between returns and volatility changes:

$$Leverage_{22d} = \text{corr}_{22d}(r_t, \Delta RV_t) \tag{14}$$

   Typically between −0.3 and −0.6 for US equities. When this correlation is very negative (e.g., −0.7), the leverage effect is strong: each 1% price decline is accompanied by a substantial increase in volatility. This feature captures the *time-varying strength* of the leverage effect.

3.8 Cross-Sectional Features (2)

1. RV_w **z-score** — Cross-sectional standardization: $z_{i,t} = (RV_{w,i,t} - \overline{RV}_{w,t})/\sigma_{RV_w,t}$, computed across the 5-stock universe at each date. A high z-score means the stock is anomalously volatile relative to its peers, which may reflect an idiosyncratic event (earnings, M&A) that tends to mean-revert faster than systematic volatility shocks.

2. RV_w **rank delta** — Change in volatility rank: $rank_t - rank_{t-5}$. Captures cross-sectional *momentum* in volatility: a stock whose relative volatility is increasing (positive delta) may continue to become more volatile relative to peers.

All rolling features use a 5-day averaging window to ensure smoothness.

Part II
ElasticNet Regularization and Feature Selection

4 Backtesting Methodology

4.1 Walk-Forward Protocol

We employ a strict walk-forward protocol to ensure all results are truly out-of-sample. At each prediction date t:

1. **Training window**: we select the most recent W days of data, where W is determined adaptively based on the VIX level (see below).
2. **Purge gap**: we exclude the last $H - 1 = 4$ observations from the training set (where $H = 5$ is the prediction horizon). This prevents any overlap between training targets $y_{t'}$ (which look 5 days ahead from t') and the test observation at t.
3. **Standardization**: features are standardized (zero mean, unit variance) using *only* the training data. This is critical for ElasticNet: the L1/L2 penalties are applied uniformly to all coefficients, so features must be on the same scale for the regularization to be equitable. The test observation is transformed using the same scaler — never re-fitted.
4. **Prediction**: the model predicts $\hat{y}_t$, which is stored for evaluation.

Predictions are evaluated using the *Spearman Information Coefficient* (IC): the rank correlation between predicted and realized values. Spearman IC is preferred over Pearson correlation because it is robust to outliers and captures monotonic (not just linear) relationships.

4.2 VIX-Adaptive Training Window

The training window size W adapts to the current market regime via the VIX level:

$$W(VIX_t) = \begin{cases} 504 & \text{if } VIX_t \leq 18 \quad \text{(calm market)} \\ 189 & \text{if } VIX_t \geq 22 \quad \text{(stressed market)} \\ \text{linear interpolation} & \text{if } 18 < VIX_t < 22 \end{cases} \tag{15}$$

The intuition is a *bias-variance tradeoff on sample size*:

- **Calm markets** ($VIX \leq 18$): the regime is stable, and data from 2 years ago is still representative. A long window (504 days $\approx$ 2 years) provides more observations to estimate coefficients precisely, reducing estimation variance.
- **Stressed markets** ($VIX \geq 22$): the regime has shifted, and old data from the calm period is no longer representative — it introduces *bias*. A short window (189 days $\approx$ 9 months) uses only recent, relevant data, even at the cost of higher estimation variance.

5 The Regularization Problem

5.1 Why Ridge Fails with Many Features

The natural approach to extending the HAR-RV model is to add features and use Ridge (L2) regularization to prevent overfitting:

$$\hat{\beta}_{Ridge} = \arg\min_{\beta} \left\{ \|y - X\beta\|_2^2 + \alpha\|\beta\|_2^2 \right\} \tag{16}$$

The L2 penalty $\|\beta\|_2^2 = \sum_j \beta_j^2$ shrinks all coefficients proportionally toward zero. Crucially, it *never sets any coefficient to exactly zero*. With 20 features — some informative, some noisy — Ridge assigns small but nonzero weights to every predictor. The noisy features accumulate estimation error that degrades out-of-sample predictions.

This explains a key empirical finding: **Ridge with 20 features (IC = 0.452) performs nearly identically to Ridge with 3 features (IC = 0.451)**. The 17 additional features contribute noise that almost perfectly offsets their potential signal.

5.2 ElasticNet: Combining L1 Sparsity and L2 Stability

ElasticNet (Zou & Hastie, 2005) resolves this by combining the L1 (Lasso) and L2 (Ridge) penalties:

$$\hat{\beta}_{EN} = \arg\min_{\beta} \left\{ \|y - X\beta\|_2^2 + \alpha \left[\lambda_1 \|\beta\|_1 + (1 - \lambda_1)\|\beta\|_2^2 \right] \right\} \tag{17}$$

where $\alpha = 0.01$ controls overall regularization strength and $\lambda_1 = 0.5$ balances the two penalties.

Each component plays a distinct role:

- **L1 penalty** ($\|\beta\|_1 = \sum_j |\beta_j|$): produces **exact zeros**. Features whose signal does not justify their estimation cost are eliminated entirely. This is the mechanism that makes ElasticNet superior to Ridge for high-dimensional problems with noisy features.
- **L2 penalty** ($\|\beta\|_2^2 = \sum_j \beta_j^2$): handles the *grouping effect*. When features are correlated (as volatility measures inevitably are — RV_w, RV_m, RV_q share much of their information), pure Lasso would arbitrarily keep one and drop the others. The L2 component encourages correlated features to have similar coefficients, retaining the group rather than making an arbitrary selection.

The combination is particularly well-suited to our problem: we have 20 features with (i) a subset that is genuinely informative, (ii) high correlations among RV measures, and (iii) several features that are likely noise at the daily frequency.

5.3 Feature Selection Without Look-Ahead Bias

Beyond the implicit selection performed by ElasticNet's L1 penalty, we implement explicit *greedy backward elimination* to further refine the feature set. To prevent look-ahead bias, we use a temporal split:

1. **Phase 1 — Selection (1st temporal half)**: starting from all 20 features, we iteratively remove the feature whose elimination most improves the walk-forward IC computed on the first half of the data only. We stop when no removal improves IC by more than -0.001.

2. **Phase 2 — Validation (2nd temporal half)**: the selected feature set is evaluated on the second half, which was *never used* during the selection process. This provides an honest, unbiased performance estimate.

This discipline is critical. Selecting features on the full dataset yields IC = 0.517 (8 features), but this is inflated by +0.023 of look-ahead bias — the procedure optimizes feature choice using future information. Our temporal split eliminates this contamination.

6 Results

6.1 Ridge vs. ElasticNet: The Impact of L1 Sparsity

Table 1 presents the walk-forward Spearman IC for each model across all 5 stocks.

Table 1: Walk-forward Spearman IC by stock and model. All models use VIX-adaptive training windows and purge gap = 4.

Model	**AAPL**	**MSFT**	**NVDA**	**JPM**	**META**	**Mean**
Ridge (3f)	0.444	0.475	0.394	0.411	0.530	0.451
Ridge (20f)	0.439	0.490	0.406	0.428	0.496	0.452
Lasso (20f)	0.455	0.508	0.425	0.466	0.513	0.473
ElasticNet (20f)	0.453	0.510	0.423	0.469	0.513	0.474
ElasticNet (12f)	**0.499**	**0.530**	**0.437**	**0.492**	**0.512**	**0.494**

Key observations:

- Ridge(3f) $\approx$ Ridge(20f): the 17 additional features provide almost no benefit under L2 regularization (IC improvement of only +0.001).
- ElasticNet(20f) outperforms Ridge(20f) by +0.022 IC (+4.8%), demonstrating that L1-induced sparsity successfully filters out noisy features.
- Lasso(20f) performs comparably to ElasticNet(20f) at IC = 0.473, but ElasticNet is preferred for its grouping property with correlated features.
- ElasticNet(12f) with greedy-selected features achieves the best performance at IC = 0.494 (+9.3% over Ridge baseline).

Figure 1 visualizes the consistent improvement across all 5 stocks.



Figure 1: Walk-forward Spearman IC per stock. ElasticNet(20f) consistently outperforms both Ridge specifications.

6.2 Coefficient Analysis: What ElasticNet Learns

To understand *why* ElasticNet outperforms Ridge, we analyze the coefficients. Figure 2 compares a single-window snapshot between the two models.



Figure 2: Standardized coefficients on the last training window. Ridge assigns nonzero coefficients to all 20 features; ElasticNet zeros out the weakest, concentrating weight on informative predictors.

Figure 3 aggregates the analysis across all walk-forward windows and all 5 stocks, showing how frequently each feature receives a nonzero coefficient (left) and its average absolute magnitude when active (right).



Figure 3: Walk-forward coefficient analysis (5 stocks, all windows). Left: nonzero frequency. Right: average $|\beta|$ when selected. Three categories emerge: always selected (>70%), sometimes selected (30–70%), and rarely selected (<30%).

Three categories emerge naturally:

- **Always selected (>70%)**: RV_m, VIX, RV_q, $Jump_{ratio}$, $Leverage_{22d}$ — the core volatility signals and regime indicators.
- **Sometimes selected (30–70%)**: $RV_{overnight}$, $Parkinson$, $RSkew$, $RKurt$ — informative in certain market regimes but not universally.
- **Rarely selected (<30%)**: $Vol_{AM/PM}$, $Autocorr$, $Vol_{1m/5m}$, J_w — these features add mostly noise at the daily prediction frequency.

Figure 4 shows that ElasticNet dynamically adapts its coefficients as market regimes evolve.



Figure 4: Temporal evolution of ElasticNet coefficients for AAPL. The model is not static: it adapts feature weights as regimes change. RV_m is consistently the dominant signal (mean-reversion anchor).

6.3 Greedy Feature Selection

Table 2 shows the backward elimination sequence on the first temporal half.

Table 2: Greedy backward elimination (1st temporal half). At each step, the feature whose removal most improves IC is dropped. Stops when best $\Delta < -0.001$.

Step	**Feature removed**	**Remaining**	**IC (1st half)**
0	(baseline)	20	0.454
1	J_w	19	0.468
2	$Autocorr$	18	0.485
3	$Vol_{AM/PM}$	17	0.498
4	$Vol_{1m/5m}$	16	0.516
5	Ret_w	15	0.523
6	RV_{neg}	14	0.524
7	RV_w rank delta	13	0.528
8	RV_w	12	0.528
STOP: best $\Delta < -0.001$		**12**	**0.528**

The 12 retained features are: RV_m, RV_q, VIX, $RV_{overnight}$, $Parkinson$, Vol_{ratio}, RV_{1min}, $RSkew$, $RKurt$, $Jump_{ratio}$, $Leverage_{22d}$, RV_w z-score.

The 8 eliminated features share common characteristics: (i) redundancy with retained features (RV_w is absorbed by RV_m and RV_q; RV_{neg} is subsumed by $Leverage_{22d}$), (ii) excessive noise at the daily frequency ($Autocorr$, $Vol_{AM/PM}$), or (iii) insufficient signal (J_w, $Vol_{1m/5m}$, Ret_w, RV_w rank delta).

6.4 Look-Ahead Bias Quantification

Table 3: Look-ahead bias measurement. Full-sample feature selection inflates IC by +0.023 (4.7%).

Selection method	**Features**	**Full walk-forward IC**
Full-sample greedy (biased)	8	0.517
1st-half greedy + OOS validation (honest)	12	0.494
Look-ahead bias		**+0.023**

The bias of +0.023 is meaningful: in a domain where IC differences of 0.01 translate to significant economic value, a 4.7% inflation from look-ahead bias can lead to drastically overoptimistic expectations.

6.5 Final Synthesis

Figure 5 provides a comprehensive visual summary.



Figure 5: Final comparison. Left: mean IC by model. Right: IC heatmap by stock × model. ElasticNet(12f) improves on Ridge consistently across all stocks.

6.6 Conditional Performance by VIX Regime

A critical question for any volatility model is whether performance holds during market stress. A model that forecasts well only in calm regimes is of limited practical value, since accurate volatility predictions matter most during crises — for hedging, position sizing, and risk management.

We classify each prediction day into three VIX regimes using rolling percentiles (p33/p66) over the past 252 trading days, ensuring no look-ahead bias. The thresholds adapt to the historical context: a VIX of 20 may be classified as "High" after a prolonged calm period and "Medium" after a crisis.

Table 4: Spearman IC by VIX regime (cross-sectional mean over 5 stocks).

Model	**Low VIX**	**Medium VIX**	**High VIX**	**Global**
Ridge(3f)	0.449	0.307	0.539	0.432
ElasticNet(20f)	0.492	0.362	0.494	0.449
ElasticNet(12f)	**0.501**	**0.374**	**0.522**	**0.466**

Table 5: Hit Rate by VIX regime (cross-sectional mean over 5 stocks).

Model	**Low VIX**	**Medium VIX**	**High VIX**
Ridge(3f)	67.3%	65.0%	70.1%
ElasticNet(20f)	69.0%	63.1%	67.3%
ElasticNet(12f)	**68.5%**	**67.5%**	**71.9%**



Figure 6: Conditional performance by VIX regime. Left: Spearman IC. Right: Hit Rate. ElasticNet(12f) maintains strong performance across all three regimes, with particularly high IC during High VIX periods.

Several findings emerge from Tables 4–5 and Figure 6.

The model does not collapse in High VIX. ElasticNet(12f) achieves IC = 0.522 and Hit Rate = 71.9% during stress periods — actually *higher* than in calm periods (IC = 0.501). This contradicts the common concern that statistical models fail during crises. The explanation is that volatility dynamics are more "readable" during stress: jumps are more frequent, the leverage effect is stronger, and mean-reversion is faster. The model's crisis-sensitive features (RKurt, Jump_ratio, Leverage_22d) are specifically designed to capture these dynamics, allowing the model to exploit the amplified signal present in High VIX regimes.

Ridge(3f): strong in crisis, weak in the middle. The baseline HAR model reveals an instructive pattern: IC = 0.539 in High VIX but only 0.307 in Medium VIX. In crisis, the dominant dynamic is simple volatility clustering (high vol → stays high), which three HAR features capture well. But in the Medium regime — the most ambiguous zone where volatility can accelerate or revert — Ridge(3f) lacks the information to navigate uncertainty. This "all-or-nothing" profile is precisely what the extended feature set corrects: supplementary features like $RSkew$ (directional signal), Vol_ratio (regime transition detection), and $Leverage_{22d}$ (asymmetry) provide discriminating power where pure RV-based features cannot.

The ElasticNet improvement is uniform across regimes. ElasticNet(12f) outperforms Ridge(3f) in all three regimes, with the largest improvement occurring in Medium VIX (+0.067 IC, a 22% gain). If the ElasticNet advantage only appeared in calm markets, one could argue the feature selection exploits a calm-regime bias. Instead, the gain is structural: the selected features add complementary information across all market conditions. In Medium VIX, features like Vol_ratio (weekly/monthly RV ratio above 1.0 as an early stress signal), $RSkew$ (increasing negative skewness preceding vol acceleration), and $RV_{overnight}$ (gap risk) provide early warning signals that HAR features miss.

Three mechanisms behind stress-period robustness. The model's resilience in High VIX results from three complementary mechanisms:

1. **Adaptive training window.** When VIX exceeds 22, the training window contracts from 504 to 189 days. The model discards stale calm-period data and recalibrates on recent observations that reflect the current stress dynamics — analogous to a trader shifting from long-term averages to recent price action during a crisis.

2. **Crisis-sensitive features.** Three of the 12 selected features are specifically designed for stress periods: $RKurt$ detects fat tails (values of 10–20 in crisis vs. 3 in normal regimes), $Jump_ratio$ measures the dominance of discontinuous moves over smooth variation, and $Leverage_{22d}$ captures the strengthening of the return-volatility negative correlation (–0.7 in corrections vs. –0.3 normally).

3. **VIX as implicit regime indicator.** As the only forward-looking feature in the model (reflecting options traders' expectations of future volatility), VIX acts as an implicit regime switch. The model does not need an explicit regime-detection mechanism — VIX provides this information directly, allowing ElasticNet to adjust its predictions based on the market's own assessment of future risk.

Practical implications. This regime robustness has direct operational consequences: the model can be deployed in production without requiring a separate crisis model or manual regime-switching logic. The adaptive window and crisis-sensitive features provide built-in regime adaptation. Furthermore, this result highlights a structural advantage of the linear ElasticNet approach over nonlinear models (XGBoost, neural networks), which tend to overfit calm-regime patterns that dominate the training set and may break down during stress periods when the statistical properties of returns shift significantly.

7 Discussion

7.1 Why ElasticNet Over XGBoost?

A natural question is whether nonlinear models would perform better. Our experiments show that XGBoost with 20 features achieves IC ≈ 0.394 — *worse* than the simple Ridge baseline. This is consistent with the fundamentally linear nature of volatility forecasting at the 5-day horizon: the dominant signal is mean-reversion of RV toward its long-term level, which is an inherently linear relationship. XGBoost wastes model capacity learning nonlinearities that do not exist in the data.

ElasticNet achieves superior performance with full interpretability: every coefficient has an economic interpretation, the model is trivial to implement in production, and there are no hyperparameter-sensitive tree structures to maintain.

7.2 Decomposition of the IC Gain

The total improvement from Ridge(3f) at IC = 0.451 to ElasticNet(12f) at IC = 0.494 decomposes as:

- **Feature expansion** (3f → 20f with ElasticNet): +0.023 IC. The L1 penalty allows ElasticNet to exploit additional features without noise accumulation.
- **Feature selection** (20f → 12f): +0.020 IC. Removing the 8 noisiest features further sharpens the signal.
- **Total**: +0.043 IC (+9.3%).

7.3 Anti-Leakage Protections

Four layers of protection ensure the integrity of our results:

1. **Walk-forward**: the model never sees future data during training.
2. **Purge gap**: 4-day gap between training and test prevents target overlap.
3. **Temporal split for feature selection**: features are selected on the 1st half only.
4. **VIX lag**: VIX is lagged by 1 day to prevent same-day information leakage.

8 Conclusion

We have shown that ElasticNet regularization provides a principled way to extend the HAR-RV model beyond its original 3-feature specification. The key insight is that the L1 component performs implicit feature selection, zeroing out predictors that contribute more noise than signal. Combined with explicit greedy backward elimination on a held-out temporal split, we achieve IC = 0.494 with 12 features — a 9.3% improvement over the Ridge baseline.

The resulting model is fully linear, interpretable, and production-ready. The selected features span the major dimensions of volatility dynamics: multi-horizon persistence (RV_m, RV_q), market expectations (VIX), microstructure (RV_{1min}, $Parkinson$), tail risk ($RSkew$, $RKurt$, $Jump_{ratio}$), leverage ($Leverage_{22d}$), and cross-sectional positioning (RV_w z-score).

Crucially, conditional analysis by VIX regime demonstrates that performance holds across all market conditions. The model achieves IC = 0.522 and Hit Rate = 71.9% during High VIX periods, confirming that it does not merely exploit calm-regime predictability but remains reliable when accurate volatility forecasts matter most.

The HAR-RV framework of Corsi (2009) remains the right foundation. What ElasticNet adds is not a replacement of the linear structure, but a disciplined mechanism for determining *which* extensions to the original model actually improve prediction — and which ones are just noise.

References

Amaya, D., Christoffersen, P., Jacobs, K., & Vasquez, A. (2015). *Does realized skewness and kurtosis predict the cross-section of equity returns?* Journal of Financial Economics, 118(1), 135–167.

Andersen, T.G., Bollerslev, T., & Diebold, F.X. (2003). *Modeling and Forecasting Realized Volatility.* Econometrica, 71(2), 579–625.

Barndorff-Nielsen, O.E. & Shephard, N. (2004). *Power and bipower variation with stochastic volatility and jumps.* Journal of Financial Econometrics, 2(1), 1–37.

Black, F. (1976). *Studies of stock price volatility changes.* Proceedings of the 1976 Meetings of the American Statistical Association, 177–181.

Corsi, F. (2009). *A Simple Approximate Long-Memory Model of Realized Volatility.* Journal of Financial Econometrics, 7(2), 174–196.

Parkinson, M. (1980). *The extreme value method for estimating the variance of the rate of return.* Journal of Business, 53(1), 61–65.

Zou, H. & Hastie, T. (2005). *Regularization and variable selection via the elastic net.* Journal of the Royal Statistical Society: Series B, 67(2), 301–320.