

1 **Improving the communication and accessibility of**
2 **stock assessment using interactive visualization tools**

3 Paul M. Regular, Gregory J. Robertson, Robert Rogers, Keith P. Lewis

4 *Fisheries and Oceans Canada, Northwest Atlantic Fisheries Center, 80 East White Hills,*
5 *St. John's, Newfoundland and Labrador, A1C 5X1, Canada*

6 **Corresponding author:** Paul M. Regular, Fisheries and Oceans Canada, Northwest Atlantic
7 Fisheries Center, 80 East White Hills, St. John's, Newfoundland and Labrador, A1C 5X1,
8 Canada, E-mail: Paul.Regular@dfo-mpo.gc.ca, Phone: 1-709-772-2067

Abstract: Scientists across many fields are faced with the challenge of synthesizing and communicating information from large and complex data sets. The field of stock assessment is no exception as the volume and variety of the data has grown alongside the computational methods used to integrate them. While this growth in data and model complexity has improved many stock assessments, the process of communicating key results to colleagues and stakeholders in a meaningful way has become more daunting. The traditional approach of presenting information across a series of static slides often fails to convey the richness of information available and, as such, important patterns and details are easily overlooked. Here we contend that this problem can be mediated through the effective use of new open source tools for building interactive visualizations. These tools allow a broader audience to conduct detailed explorations of the results, leading to a deeper and collective understanding of both the data and models used to inform stock assessments. As a consequence, the peer review process is more open and accessible.

Keywords: dashboard, data exploration, integrated analysis, model validation, open stock assessment

The greatest value of a picture is when it forces us to notice what we never expected to see.

- Tukey (1977)

Quantitative stock assessment plays a central role in modern fisheries management (Hilborn and Walters 1992). Over time, and as new methods are developed, there is an increasing amount of data available to inform stock assessments. These data might be richer information on stock structure using an increasing array of markers and biomarkers, and/or the continued lengthening of population status and catch time series. Concurrently, analytical methods are now able to

31 integrate many data sources into one stock assessment model (Maunder and Punt 2013). While
32 these advances have surely improved the advice provided on stock status, it has become more
33 difficult to communicate the basis of this advice in a meaningful way. Visualizations play a
34 critical role in communicating this information to stakeholders (Levontin et al. 2017). However,
35 traditional formats (e.g. slides) are often insufficient to convey the richness of information
36 available and the static and sequential nature of these formats can stifle meaningful discussions.
37 A solution to this problem is the effective use of interactive visualization tools (Keena et al.
38 2016). These are common tools we use every day on a range of web sites, but their use is no
39 longer restricted to web site developers as these tools are being integrated into software
40 commonly used by the research community (Perkel 2018). As a result, an increasing number of
41 scientists across a wide range of disciplines are starting to apply interactive visualization tools to
42 explore and communicate their results (e.g. Jones et al. 2016; Letcher et al. 2018; Yeatman et al.
43 2018).

44 Fisheries scientists are a part of this trend and, as such, there are a growing number of interactive
45 tools available that facilitate the exploration and communication of fisheries science. For
46 instance, they can be used to disseminate real-time information for dynamic ocean management
47 (Maxwell et al. 2015; Hazen et al. 2018), explore hindcasts and projections from various habitat
48 suitability models (McHenry et al. 2019), and evaluate different fisheries management
49 approaches (Goethel et al. 2019; Miller et al. 2019) (see Appendix A for more examples). Such
50 tools complement static documentation as they allow audiences to explore data and models in
51 ways not amenable to static formats and, in the process, they improve accessibility and augment
52 communication efforts. These will be helpful tools to utilize as we proceed through an age of
53 heightened scientific scrutiny (McInerny et al. 2014), and here we aim to promote their use in

fisheries science by demonstrating a series of interactive visualization tools built to aid in the peer review of stock assessments.

We first demonstrate the application of interactive tools to data that are commonly presented in stock assessments to show how they can simplify the detailed exploration of data from long-term monitoring programs. Second, we focus on the modeling aspect of stock assessment and demonstrate how interactive tools can be used to explore, diagnose, and communicate results from an integrated assessment model. This structure corresponds to two important steps in the stock assessment process: 1) data exploration, and 2) data modeling. In both cases interactive visuals are nested inside dynamic documents called “dashboards”. The concept of using a dashboard was borrowed from the business community where they are frequently used to group a series of interactive visuals and tables to provide at-a-glance views of key performance indicators. These dashboards were constructed within the framework of the R programming language (R Core Team 2017) and the RStudio IDE (RStudio Team 2015) using three or more of the packages listed in Table 1. See Supplement 1 for a “getting started” tutorial that highlights one approach to constructing a dashboard using R; using this as a guide, an R user can start constructing basic dashboards within a day.

Table 1: Names and descriptions of the key packages used to build the interactive applications presented in this paper. Descriptions are directly from the DESCRIPTION file of each package.

shiny	Makes it incredibly easy to build interactive web applications with R. Automatic “reactive” binding between inputs and outputs and extensive prebuilt widgets make it possible to build beautiful, responsive, and powerful applications with minimal effort (Chang et al. 2018)
shinydashboard	Create dashboards with ‘Shiny’. This package provides a theme on top of ‘Shiny’, making it easy to create attractive dashboards (Chang and Borges Ribeiro 2018).
rmarkdown	Convert R Markdown documents into a variety of formats (Allaire et al.

	2018).
flexdashboard	Format for converting an R Markdown document to a grid oriented dashboard. The dashboard flexibly adapts the size of its components to the containing web page (Allaire 2017).
plotly	Easily translate ‘ggplot2’ graphs to an interactive web-based version and/or create custom web-based visualizations directly from R (Sievert 2018).
leaflet	Create and customize interactive maps using the ‘Leaflet’ JavaScript library and the ‘htmlwidgets’ package. These maps can be used directly from the R console, from ‘RStudio’, in Shiny applications and R (Cheng et al. 2018).
crosstalk	Provides building blocks for allowing HTML widgets to communicate with each other, with Shiny or without (i.e. static .html files) (Cheng 2016).

Data exploration

The data sets used in stock assessments are constantly growing due to the continuation of long-term monitoring efforts, the addition of new monitoring programs, or both. As such, stock assessment biologists need to manage large volumes of data from a variety of sources. Time series of reported landings and catch-at-age are often analyzed in conjunction with data from “fishery-independent” surveys that track changes in relative abundance and, in many cases, also monitor trends in biological factors such as age composition, growth rates, sex ratios and maturation stages. For some data-rich stocks, mark and recapture studies are also carried out to estimate movement, migration, growth rate, natural mortality, and discard mortality. All of the above-mentioned data sets are complex and, as the volume and variety of these data increases, it becomes more difficult to be aware of the details of each data set and discover key patterns within each. It has long been recognized that this challenge can be mediated, to a degree, by the application of interactive visualization tools as they allow detailed exploration of the data behind a plot (Tukey and Tukey 1985; Fisherkeller et al. 1988). For instance, the ability to zoom in on features or areas of interest, turn off layers and hover over specific points to reveal more information creates an interactive user-driven experience that expedites explorations of data.

These abilities are illustrated by two recently developed interactive tools: 1) a tool designed to quickly examine fishery-independent survey data; and 2) an interactive mapping tool developed for the exploration of a long-term tagging study.

Survey data

Fisheries and Oceans Canada (DFO) has been conducting a multi-species stratified-random survey across the Newfoundland and Labrador shelf since the 1970s (Rideout and Ings 2018).

These data are analyzed using a standard stratified analysis via a local R package called RStrap (for details on methodology see Smith and Somerton 1981). Both the inputs and outputs from RStrap analyses are very large and, depending on the species, may include > 40 years and span the majority of the Newfoundland and Labrador shelf. In order for fisheries scientists to quickly and reliably explore these data without iteratively modifying R scripts one species at a time, an application (hereafter called RStrap Explorer) was built using a combination of shiny, crosstalk, flexdashboard, plotly and R markdown (Table 1). RStrap Explorer started as a way to visualize estimates of biomass and abundance trends of specific species by supplying RStrap output to a flexdashboard file designed to organize and visualize the results. The shiny package was latter applied as it allows RStrap to be run in the background and therefore allows the user to dynamically explore abundance and biomass estimates from multiple species in one session. Both crosstalk and plotly were incorporated to allow the user to interact with the data.

RStrap Explorer contains four primary tabs: 1) “Survey Indices” contains stock level estimates of biomass and abundance (Figure 1), 2) “Age & Length Distributions” contains length and age frequency plots (Figure 2), 3) “Recruitment” displays recruitment indices, and 4) “Help” provides additional context to the survey data and analysis. The input interface for RStrap

Explorer is divided into two parts: basic and advanced inputs. Basic inputs are those like species, season, and survey year(s). Advanced inputs allow the user to define the length or age of recruitment, select whether they would like analyses conducted by length and/or age, and so on. This application was built for data exploration and allow the user to obtain quick and easy visualization of survey data, before the thorough data checking and analysis required for formal stock assessment begins.




Figure 1: - Screen shot of the “Survey Indices” page of the RStrap Explorer application. The “Basic Inputs” sidebar is fixed across all pages and allows the user to specify the species, NAFO Divisions, season, and survey years of interest. The “Biomass Index” sub-tab is illustrated here. This sub-tab shows a time-series of biomass data with 95% confidence intervals, with a break in the lines when the survey gear changed from an Engle to Campelen trawl, for both cod (*Gadus morhua*; species code 438) and American Plaice (*Hippoglossoides platessoides*; species code 889). All trend lines can be toggled off using plotly’s dynamic user interface.




Figure 2: - “Age and Length Frequencies” tab of the RStrap Explorer tool. This tab illustrates the length frequency distributions of both cod (*Gadus morhua*; species code 438) and American plaice (*Hippoglossoides platessoides*; species code 889) binned into 2 cm length bins. The binning is easily modified using the “Length Group” field in the “Advanced Options” drop down menu (shown on left side).

Tagging data

Northern cod (NAFO Divisions 2J3KL) has a rich history of tagging, starting as a dedicated program in 1954 (Taggart et al. 1995) and continuing to this day. The tagging and recovery data are captured in a standardized database, with fields typical of most tagging programs. This database has over 600,000 records as of early 2019, with 2,000-10,000 tags deployed annually in recent decades. The tagging and recovery data are used in the current assessment model for this stock (Cadigan 2016), but tools to explore this extensive data set were limited, especially from a spatial perspective. To begin to explore and understand this large data set, we built a simple

application using shiny and leaflet (Table 1) that allows a user to quickly and dynamically subset the data (e.g. ranges of tag release and tag recovery years, specific geographic locations). As the application developed, it was incorporated into shinydashboard, to take advantage of the number of layout options available in shinydashboard (Table 1). Given the large number of tags released, often at nearby sites, visualizing the data with static mapping was particularly challenging. The markercluster (<https://github.com/Leaflet/Leaflet.markercluster>) function available in leaflet was particularly useful as a means to dynamically scale the level of pooling of spatial points (Figure 3). This basic mapping tool allowed us to quickly become familiar with the data, identify outliers and incorrect data entries, as well as explore options on how to spatially pool the data for subsequent demographic analysis. Further tabs were added to provide basic summaries of the selected data (Figure 4).




Figure 3: A screen shot of cod tag mapping tool. The markercluster function dynamically splits or pools tagging locations (red, orange, green or yellow points) depending on zoom level, the recovery positions (blue) are much fewer, and are left to be plotted individually at all scales.

Options to include pop up labels are included, so specific information on each point can be retrieved with a mouse click (in this case: tag number, fish length, date released, and date recovered), which is particularly useful when error checking. Base map created with leaflet (Cheng et al. 2018) using ESRI's Ocean BaseMap (Sources: Esri, GEBCO, NOAA, National Geographic, DeLorme, HERE, Geonames.org, and other contributors).




Figure 4: Basic summaries of the recovery data from the tags selected within the cod tag mapping tool. In this case, histograms and summary statistics of the recovery positions are returned, along with a simple map of kernels showing the spatial distribution of the selected tag recoveries. Base map created in R with package maps (Becker et al. 2018b) and mapdata (Becker et al. 2018a).

164 **Data modeling**

165 Synthesizing data from multiple sources presents a key challenge to stock assessment. Analyses
166 of different data sources were traditionally carried out independently and the summaries or
167 parameters from these analyses were used in the assessment model. This approach, however, is
168 less than ideal because information may be lost and uncertainty may be unaccounted for when
169 we “do statistics on the statistics” (Link 1999; Maunder and Punt 2013).). Such issues have
170 largely been curtailed in contemporary stock assessments as advances in statistical computing
171 have enabled integrated analyses of data from multiple monitoring programs (Maunder and Punt
172 2013). Specifically, statistical modeling tools such as JAGS (Plummer 2003), AD Model Builder
173 (Fournier et al. 2012), and Template Model Builder (TMB; Kristensen et al. 2016) allow the
174 construction of a joint likelihood for an array of observations to, in theory, extract as much
175 information as possible about the biological and fishery processes. From a computational
176 perspective, analyses of a variety of large data sets has never been easier. However, from a
177 human perspective, contemporary stock assessment biologists are faced with the challenge of
178 understanding and integrating data from multiple sources into a single model and communicating
179 the methods and results to stakeholders and fisheries managers. This challenge was palpable for
180 the data-rich case of Northern cod.

181 The Northern cod stock off southern Labrador and eastern Newfoundland is one of the most well
182 studied stocks in eastern Canada. As such, there are multiple monitoring programs that help
183 inform the status of the stock and data from most of these programs have been integrated into a
184 state-space stock assessment model, called NCAM (Cadigan 2016). The model includes
185 information from research vessel autumn trawl surveys (1983-present), Sentinel fishery surveys

(1995-present), inshore acoustic surveys (1995-2009), fishery catch-at-age compositions, and reported fishery landings (1983-present), and tagging (1983-present). Using a series of observation equations, this TMB based model simplifies thousands of data points into quantities such as annual recruitment, spawning stock biomass, fishing mortality, and natural mortality. Once the model is fit to the data, the next step is to produce visual representations of the data and model output. The traditional approach would involve producing static presentations and documents with a series of figures and tables. However, with numerous model inputs and outputs, this approach quickly becomes overwhelming for both the analyst and the stakeholders involved for at least two reasons. First, it is no longer feasible for the analyst to include and describe every figure and table produced in a single document. Second, it is difficult for stakeholders to efficiently digest the information that has been compressed into a series of static slides or pages. Interactive documents provide a potential solution to this problem as they allow much more information to be contained and accessible on a single screen.

In the pursuit of an easier and more efficient way to communicate results from NCAM, an interactive “dashboard”, called NCAM explorer, was developed for the 2018 assessment of Northern cod (Dwyer et al. 2019). We used R-based packages (Table 1) to construct a tool for exploring the input and output of NCAM, specifically the flexdashboard package to group interactive plotly-based visuals into a dynamic document. We also used the crosstalk package to link the data displayed across multiple plots. Via R Markdown, the dashboard is rendered into a self-contained html file that is reproducible, interactive, and easy to update following modifications to the model or the addition of new data. The intent of this tool was not to replace detailed documentation on the model (i.e. Cadigan 2016; Dwyer et al. 2019), however, it was built to serve as an interactive alternative to a standard presentation for communicating the latest

209 results to an audience with a working knowledge of the stock and assessment model.

210 Explanatory text and detail were therefore kept to a minimum, allowing the audience to explore

211 the figures and data unencumbered by verbose descriptions.

212 The NCAM dashboard (Supplement 2) contains a series of pages, the first of which provides

213 terse point-form background on the model (page named “Background”). Subsequent pages

214 provide a series of diagnostic plots for assessing model fits to catch (“Landings”; accessed from

215 the “Fishery” drop-down menu), survey (“RV survey”, “SN survey” and “SS survey”; accessed

216 from the “Surveys” drop-down menu), and tagging (“Tagging”) data. For instance, the “RV

217 survey” page includes plots of observed and predicted values of mean numbers per tow captured

218 in the research vessel survey (Figure 5). The dashboard also includes pages focused on model

219 estimates such as selectivity (“Selectivity”; accessed from the “Fishery” drop-down menu) and

220 catchability (“Catchability”; accessed from the “Surveys” drop-down menu). Pages for viewing

221 trends in various population parameters are included under the “Trends” drop-down menu, where

222 the “Retrospective analysis” page displays results from a retrospective analysis, the “Model

223 comparison” page displays population trends from different model runs, the “Status and rates”

224 page displays trends in stock size and vital rates (Figure 6), and the “Productivity” page focuses

225 on trends in Spawning Stock Biomass (SSB) and recruitment. Finally, details on the projections

226 are accessed from the “Projections” drop-down menu (“Assumptions”, “Past projections”, “Retro

227 projections”, and “Results” pages), and key inputs and outputs are accessed from “Tables” drop-

228 down menu (“Inputs”, “Settings”, “Outputs” pages). The plots and tables included in the

229 dashboard are similar to those typically presented at assessment meetings and in research

230 documents. However, there are two key benefits of this approach over the *modus operandi* of

231 producing static documents and slides. First, interactive plots nested in a dashboard permit

relatively easy and efficient access to the details as it replaces scrolling through tens, if not hundreds, of pages or slides with mouse-clicks across a smaller number of dynamic pages holding data-rich illustrations (i.e. both broader patterns and finer details in the data are accessible via zooming and tooltips). Second, the automated nature of the dashboard circumvents the monotonous, time-consuming and error-prone task of copying and pasting figures, tables, and values into documents and slides, although, we note that this issue can be addressed through other approaches (e.g. slide shows can easily be made using R markdown). Both benefits expedite the process of exploring a range of model configurations as the automated output facilitate quick views of standard diagnostics and the interactive plots facilitate detailed explorations and comparisons of models with different configurations. For instance, explorations of the residual plots in the dashboard allowed the authors to quickly identify conflicts between two surveys used in the model. Potential solutions to this problem were then explored by modifying the configuration of the model and these changes were quickly evaluated using a dashboard that is produced in seconds.

The dashboard also makes it easy to share the results with colleagues and stakeholders as it is rendered into a self-contained html file. This allows others to independently scrutinize details of both data and the model that are typically only accessible to the analyst. Such access improves the transparency of the stock assessment model which, in turn, leads to richer discussion and scrutiny of the biological and statistical rigor of the model. For instance, visualizations depicting the model assumptions, process errors and confidence intervals around the projections raised important questions on the impact of the assumptions on the projections from the model. These questions were raised during the first assessment meeting in which this tool was used and the ensuing discussions left us with the impression that this tool helped the assessment biologists,

academics, resource managers, and fisheries representatives in the room gain a deeper understanding of the uncertainties and the patterns in the risk tables. Feedback and personal testimony from multiple stakeholders who have used the dashboard reaffirmed our impression that the tool is helpful as there was general agreement that access to the details eases communication and relieves any potential concerns that something is hidden.




Figure 5: Screenshot of the “RV survey” tab from the NCAM dashboard where total observed (dots) and NCAM model predicted values (lines) for the DFO RV survey index are shown in the left panel and standardized log residuals by year, cohort, age, and expected value (dots), with lowess curves (lines), are shown in the right panel.




Figure 6: Screenshot of the “Trends” tab which displays stock status estimates (abundance, biomass, and biomass relative to B_{lim} [average biomass through the 1980s]) on the left panel, and mortality rates (average F, M, and Z) on the right panel.

From bespoke to general tools

The interactive tools highlighted here were custom built to solve data visualization challenges that are common to many fisheries management organizations but the solutions presented are specific to the Northwest Atlantic Fisheries Centre. The concept is therefore broadly applicable, however, the underlying code will require modifications to accommodate region and stock specific data management and modelling approaches. Even within our own region, different approaches and needs meant that the code behind NCAM explorer (Supplement 2) required modifications when applied to a model developed for another cod stock. Nevertheless, considerable chunks of code were recycled and, in the process, new features were added to allow the visualization of multiple model configurations within the one dashboard. Additionally, a

French colleague is currently modifying the tool to visualize output from SAM, a state-space stock assessment model widely used to assess ICES stocks (Nielsen and Berg 2014). Likewise, the concept behind RStrap Explorer and the tagging tool could be applied to other regions and the most efficient approach may be to build upon existing general frameworks (e.g. StoX software; Johnsen et al. 2019). These are, of course, early days in the development and application of interactive tools to stock assessment. Because the tools we highlight are themselves general, flexible, and accessible, we suspect that bespoke applications will continue to be developed in parallel with more general stock assessment dashboards depending on user needs and preferences. Regardless of the approach, a common goal is to make the workflow more efficient, reproducible, and transparent.

Towards open stock assessment

The amount of data available to scientists has grown by orders of magnitude in recent decades as has the complexities of data management, exploratory data analysis, formal analyses and associated diagnostics (Lewis et al. 2018). The majority of this sequence of events, sometimes called “the data pipeline” (Leek and Peng 2015a), have not traditionally been part of the peer-review process which sees only the end products of an analysis. However, decisions made along the data pipeline increasingly influence the outcome of the study. Gelman and Loken (2014) coined the term “garden of forking paths” to illustrate that different conclusions can be arrived at depending on what decisions are made during different stages of the analysis. Due to a number of limitations, such as available pages in journals, much of the data pipeline is not transparent nor is it reproducible. A number of authors have recently advocated for a culture of open science and reproducible research, i.e., a change in the transparency and reproducibility of science

(Hampton et al. 2013, 2015; Leek and Peng 2015a, 2015b). Proponents of open science and reproducible research highlight a number of benefits including a more productive and responsible scientific culture, an ability to address larger and more complex questions, as well as a more efficient workflow and ability to reproduce one's own work (Fomel and Claerbout 2009; Lowndes et al. 2017).

A culture of openness is actively evolving in the field of stock assessment and, at this point, it is not hard to picture a future where it is commonplace for the full data pipeline to be open and accessible. Open resources are actively being developed and used to improve accessibility to all the data, methods and results that feed into stock assessments (e.g. the Transparent Assessment Framework, <https://taf.ices.dk/app/about>; Magnusson and Millar 2020). Likewise, tools are being developed to facilitate the creation of reproducible advisory documents (e.g. ICES 2018; Anderson et al. 2020; Regular et al. 2020), and these documents can be interactive, as is the case for the VISA tool (ICES 2018), or they can be supplemented by interactive tools. There is plenty of opportunity for synergies between these initiatives, as most are being developed using R, and all details and decisions can be traceable and accessible using an online repository such as GitHub. We therefore foresee a future where stock assessments become increasingly open and reproducible.

Providing open access to code and data, however, does not necessarily make a stock assessment more accessible. We believe that interactive tools, such as those presented here and in Appendix A, represent an important step forward in terms of open science as they make the peer review process more efficient. Although these tools do not reveal the entire data pipeline, a wide range of stakeholders and scientists can easily access and review details of an analysis without running a line of code. For most participants of a stock assessment, even if the entire pipeline was

completely open, the details would remain inaccessible simply because most participants are already overcommitted (Banks 2011) and do not have the time to fully review and recreate a particular analysis in its entirety. Further, in the case of NCAM, considerable statistical experience and expertise is required simply to run the model. However, the dashboard approach removes many of these obstacles. The html file contains all model inputs, outputs and diagnostics in an open, and easy to use, interactive document that can be distributed prior to meetings. As such, participants can assess the results and diagnostics at their leisure. Specific experience with the tools used to generate the results are not required to constructively and critically review the results presented in the dashboard.

Conclusions

Visualizations play an important role in communicating fisheries science to a wide range of stakeholders (Levontin et al. 2017) and here we posit that interactive tools extend the utility of data visualizations by providing a richer approach to communicating scientific information. However, we must acknowledge there are costs to adopting the use of interactive tools. The first and obvious one being that staff are required to have both the time and training to effectively develop these tools. Ideally, professional programmers and graphic designers would be hired to construct dashboards and other interactive info-graphics (McInerny et al. 2014), but fisheries management organizations rarely have the resources to fund such initiatives. Consequently, the process of communicating fisheries science tends to be the responsibility of fisheries scientists who lack formal training in these fields. In our three examples, the developers (first, second and third authors) were relatively proficient with R and have natural aptitudes for programming and graphic design, but all had their formal training in field-based population ecology. While some

learning time was needed, the learning curve was relatively minor because there was no need to learn a new programming language (e.g. JavaScript, CSS, etc.). We can confirm that an R user can construct a basic dashboard within a day, using Supplement 1 as a guide, and a more custom dashboard in a matter of weeks. Moreover, a growing user base means that most programming issues can be readily addressed through simple internet searches. There are also a growing number of exemplars (Appendix A), beyond what we show here, to inspire the development of new interactive tools. Once over the initial learning curve, the time investment may not be much greater than one would invest into a standard presentation. We expect the accessibility and quality of these tools to continue to improve as more people in the fisheries community develop and use interactive documents. It is our experience that the upfront time investment has been worthwhile considering the improved efficiency of delivering products for subsequent stock assessments, and in the quality of the data exploration and understanding.

Acknowledgements

We thank the numerous colleagues and participants of various stakeholder and stock assessment meetings who encouraged us to further develop these interactive visualization tools, and especially those who took the time to make suggestions on how to make them more accessible and useful. We are also grateful for the constructive feedback from Gary Carvalho, Kelli Johnson, Colin Millar, Daniel Goethel and seven anonymous reviewers.

All code used to generate this paper, Supplement 1 (getting started dashboard) and Supplement 2 (NCAM explorer) are available at <https://github.com/PaulRegular/interactive-stock-assessment>.

366 **Appendix A**

367 Partial list of applications developed to explore and communicate marine and fisheries science:

- 368 • Marine Aggregates Application (https://openscience.cefas.co.uk/ma_tool/); a benthic-
369 focused tool to assist with marine license application and compliance monitoring.
- 370 • Species Dashboard (<https://shiny.marine.ie/speciesdash/>); a tool for exploring biological
371 fisheries data collected in Irish waters
- 372 • The Stock Book (<https://shiny.marine.ie/stockbook/>); a tool for accessing up-to-date
373 information on the status of fish stocks in Irish waters.
- 374 • Data-Limited Fisheries Toolkit demo (<https://www.datalimitedtoolkit.org/demo>); an
375 application for demonstrating the key features of the management strategy evaluation
376 toolkit.
- 377 • Toy Tuna MSE application (<https://puntapps.shinyapps.io/tunamse/>); a toy MSE example
378 built to allow users to enter various management procedures and assess their performance.
- 379 • Exploring Groundfish in an Ecosystem Context
380 (<https://incorporatingecosystemapproach.shinyapps.io/indiapp/>); a tool accessing results
381 from an analysis exploring links between stock indices and ecosystem trends.
- 382 • EcoCast Explorer (<https://coastwatch.pfeg.noaa.gov/ecocast/explorer.html>); an application
383 for displaying results from a dynamic ocean management tool focused on bycatch
384 avoidance (see Hazen et al. 2018 for more detail).
- 385 • B-VBGM! Bayesian Von Bertalanffy Growth Model tool
386 (<https://fishecology.shinyapps.io/B-VBGM/>); a supplement Catalán et al. (2018) that
387 facilitates the exploration of the model described in the paper.
- 388 • Beyond Temperature tool (https://heatherwelch.shinyapps.io/beyond_temperature/); a
389 supplement to McHenry et al. (2019) that allows the exploration of habitat suitability
390 hindcasts and projections by species and model type.
- 391 • BRSApp (<https://catalinagomez.shinyapps.io/BRSApp/>); a supplement to Gomez et
392 al. (2016) that allows the exploration of behavioural response severity scores of marine
393 mammals to noise.
- 394 • VISA tool (e.g. [https://ices-tools-dev.github.io/VISA_tool/hke.27.3a46-](https://ices-tools-dev.github.io/VISA_tool/hke.27.3a46-8abd.html#ices_advice_2018)
395 8abd.html#ices_advice_2018); an alternative to pdf files for displaying and exploring up-to-
396 date ICES advice (developed to meet an “EU request on dissemination of ICES advice
397 beyond pdf files”; ICES 2018).

398 **References**

399 Allaire, J. 2017. Flexdashboard: R markdown format for flexible dashboards. Available from
400 <https://CRAN.R-project.org/package=flexdashboard>.

- 401 Allaire, J., Horner, J., Xie, Y., Marti, V., and Porte, N. 2018. Markdown: 'Markdown' rendering
402 for r. Available from <https://CRAN.R-project.org/package=markdown>.
- 403 Anderson, S.C., Grandin, C., Edwards, A.M., Grinnell, M.H., Ricard, D., and Haigh, R. 2020.
404 csasdown: Reproducible CSAS reports with bookdown. Available from
405 <https://github.com/pbs-assess/csasdown>.
- 406 Banks, D. 2011. Reproducible research: A range of response. *Statistics, Politics, and Policy* **2**(1):
407 4. bepress.
- 408 Becker, R.A., Wilks, A.R., and Brownrigg, R. 2018a. Mapdata: Extra map databases. Available
409 from <https://CRAN.R-project.org/package=mapdata>.
- 410 Becker, R.A., Wilks, A.R., Brownrigg, R., Minka, T.P., and Deckmyn, A. 2018b. Maps: Draw
411 geographical maps. Available from <https://CRAN.R-project.org/package=maps>.
- 412 Cadigan, N.G. 2016. A state-space stock assessment model for northern cod, including under-
413 reported catches and variable natural mortality rates. *Canadian Journal of Fisheries and*
414 *Aquatic Sciences* **73**(2): 296–308. NRC Research Press.
- 415 Catalán, I.A., Alós, J., Díaz-Gil, C., Pérez-Mayol, S., Basterretxea, G., Morales-Nin, B., and
416 Palmer, M. 2018. Potential fishing-related effects on fish life history revealed by otolith
417 microchemistry. *Fisheries Research* **199**: 186–195. Elsevier.
- 418 Chang, W., and Borges Ribeiro, B. 2018. Shinydashboard: Create dashboards with 'shiny'.
419 Available from <https://CRAN.R-project.org/package=shinydashboard>.
- 420 Chang, W., Cheng, J., Allaire, J., Xie, Y., and McPherson, J. 2018. Shiny: Web application
421 framework for r. Available from <https://CRAN.R-project.org/package=shiny>.

422 Cheng, J. 2016. Crosstalk: Inter-widget interactivity for html widgets. Available from
423 <https://CRAN.R-project.org/package=crosstalk>.

424 Cheng, J., Karambelkar, B., and Xie, Y. 2018. Leaflet: Create interactive web maps with the
425 javascript 'leaflet' library. Available from <https://CRAN.R-project.org/package=leaflet>.

426 Dwyer, K., Bratney, J., Cadigan, N., Healey, B., Ings, D., Lee, E., Maddock Parsons, D., Morgan,
427 M., Regular, P., and Rideout, R. 2019. Assessment of the northern cod (*Gadus morhua*)
428 stock in nafo divisions 2J3KL in 2018. DFO Can. Sci. Advis. Sec. Res. Doc. **2019/nnn**: v
429 + 126p.

430 Fisherkeller, M.A., Friedman, J.H., and Tukey, J.W. 1988. PRIM-9: An interactive
431 multidimensional data display and analysis system. Dynamic Graphics for Statistics: 91–
432 109. Wadsworth & Brooks/Cole.

433 Fomel, S., and Claerbout, J.F. 2009. Reproducible research. Computing in Science &
434 Engineering **11**(1): 5. IEEE Computer Society.

435 Fournier, D.A., Skaug, H.J., Ancheta, J., Ianelli, J., Magnusson, A., Maunder, M.N., Nielsen, A.,
436 and Sibert, J. 2012. AD model builder: Using automatic differentiation for statistical
437 inference of highly parameterized complex nonlinear models. Optimization Methods and
438 Software **27**(2): 233–249. Taylor & Francis.

439 Gelman, A., and Loken, E. 2014. The statistical crisis in science. American Scientist **102**: 460.
440 doi:10.1511/2014.111.460.

441 Goethel, D.R., Lucey, S.M., Berger, A.M., Gaichas, S.K., Karp, M.A., Lynch, P.D., Walter III,
442 J.F., Deroba, J.J., Miller, S., and Wilberg, M.J. 2019. Closing the feedback loop: On

- 443 stakeholder participation in management strategy evaluation. *Canadian Journal of*
 444 *Fisheries and Aquatic Sciences* **76**(10): 1895–1913. NRC Research Press.
- 445 Gomez, C., Lawson, J., Wright, A.J., Buren, A., Tollit, D., and Lesage, V. 2016. A systematic
 446 review on the behavioural responses of wild marine mammals to noise: The disparity
 447 between science and policy. *Canadian Journal of Zoology* **94**(12): 801–819. NRC
 448 Research Press.
- 449 Hampton, S.E., Anderson, S.S., Bagby, S.C., Gries, C., Han, X., Hart, E.M., Jones, M.B.,
 450 Lenhardt, W.C., MacDonald, A., Michener, W.K., Mudge, J., Pourmokhtarian, A.,
 451 Schildhauer, M.P., Woo, K.H., and Zimmerman, N. 2015. The tao of open science for
 452 ecology. *Ecosphere* **6**(7): 1–13.
- 453 Hampton, S.E., Strasser, C.A., Tewksbury, J.J., Gram, W.K., Budden, A.E., Batcheller, A.L.,
 454 Duke, C.S., and Porter, J.H. 2013. Big data and the future of ecology. *Frontiers in*
 455 *Ecology and the Environment* **11**(3): 156–162. Wiley Online Library.
- 456 Hazen, E.L., Scales, K.L., Maxwell, S.M., Briscoe, D.K., Welch, H., Bograd, S.J., Bailey, H.,
 457 Benson, S.R., Eguchi, T., Dewar, H., and others. 2018. A dynamic ocean management
 458 tool to reduce bycatch and support sustainable fisheries. *Science advances* **4**(5):
 459 eaar3001. American Association for the Advancement of Science.
- 460 Hilborn, R., and Walters, C.J. 1992. Quantitative fisheries stock assessment: Choice, dynamics
 461 and uncertainty. Chapman; Hall.
- 462 ICES. 2018. EU request on dissemination of ICES advice beyond pdf files. **DOI:**
 463 **10.17895/ices.pub.4657.**

- 464 Johnsen, E., Totland, A., Skålevik, Å., Holmin, A.J., Dingsør, G.E., Fuglebakk, E., and
 465 Handegard, N.O. 2019. StoX: An open source software for marine survey analyses.
 466 *Methods in Ecology and Evolution* **10**(9): 1523–1528. Wiley Online Library.
- 467 Jones, A.S., Horsburgh, J.S., Jackson-Smith, D., Ramírez, M., Flint, C.G., and Caraballo, J.
 468 2016. A web-based, interactive visualization tool for social environmental survey data.
 469 *Environmental modelling & software* **84**: 412–426. Elsevier.
- 470 Keena, N., Etman, M.A., Draper, J., Pinheiro, P., and Dyson, A. 2016. Interactive visualization
 471 for interdisciplinary research. *Electronic Imaging* **2016**(1): 1–7. Society for Imaging
 472 Science; Technology.
- 473 Kristensen, K., Nielsen, A., Berg, C., Skaug, H., and Bell, B. 2016. TMB: Automatic
 474 differentiation and laplace approximation. *Journal of Statistical Software* **70**(5): 1–21.
 475 doi:10.18637/jss.v070.i05.
- 476 Leek, J.T., and Peng, R.D. 2015a. Statistics: P values are just the tip of the iceberg. *Nature News*
 477 **520**(7549): 612.
- 478 Leek, J.T., and Peng, R.D. 2015b. Reproducible research can still be wrong: Adopting a
 479 prevention approach. *Proceedings of the National Academy of Sciences* **112**(6): 1645–
 480 1646. National Acad Sciences.
- 481 Letcher, B.H., Walker, J.D., O'Donnell, M.J., Whiteley, A.R., Nislow, K.H., and Coombs, J.A.
 482 2018. Three visualization approaches for communicating and exploring passive
 483 integrated transponder tag data. *Fisheries* **43**(5): 241–248. Wiley Online Library.

- 484 Levontin, P., Baranowski, P., Leach, A.W., Bailey, A., Mumford, J.D., Quetglas, A., and Kell,
 485 L.T. 2017. On the role of visualisation in fisheries management. *Marine Policy* **78**: 114–
 486 121. Elsevier.
- 487 Lewis, K.P., Vander Wal, E., and Fifield, D.A. 2018. Wildlife biology, big data, and
 488 reproducible research. *Wildlife Society Bulletin* **42**(1): 172–179. Wiley Online Library.
- 489 Link, W.A. 1999. Modeling pattern in collections of parameters. *The Journal of Wildlife*
 490 *Management* **63**(3): 1017–1027. [Wiley, Wildlife Society].
- 491 Lowndes, J.S.S., Best, B.D., Scarborough, C., Afflerbach, J.C., Frazier, M.R., O’Hara, C.C.,
 492 Jiang, N., and Halpern, B.S. 2017. Our path to better science in less time using open data
 493 science tools. *Nature ecology & evolution* **1**(6): 0160. Nature Publishing Group.
- 494 Magnusson, A., and Millar, C. 2020. IcesTAF: Functions to support the ices transparent
 495 assessment framework. Available from <https://CRAN.R-project.org/package=icesTAF>.
- 496 Maunder, M.N., and Punt, A.E. 2013. A review of integrated analysis in fisheries stock
 497 assessment. *Fisheries Research* **142**: 61–74. Elsevier.
- 498 Maxwell, S.M., Hazen, E.L., Lewison, R.L., Dunn, D.C., Bailey, H., Bograd, S.J., Briscoe, D.K.,
 499 Fossette, S., Hobday, A.J., Bennett, M., and others. 2015. Dynamic ocean management:
 500 Defining and conceptualizing real-time management of the ocean. *Marine Policy* **58**: 42–
 501 50. Elsevier.
- 502 McHenry, J., Welch, H., Lester, S.E., and Saba, V. 2019. Projecting marine species range shifts
 503 from only temperature can mask climate vulnerability. *Global change biology* **25**(12):
 504 4208–4221. Wiley Online Library.

- 505 McInerny, G.J., Chen, M., Freeman, R., Gavaghan, D., Meyer, M., Rowland, F., Spiegelhalter,
 506 D.J., Stefaner, M., Tessarolo, G., and Hortal, J. 2014. Information visualisation for
 507 science and policy: Engaging users and avoiding bias. *Trends in ecology & evolution*
 508 **29**(3): 148–157. Elsevier.
- 509 Miller, S.K., Anganuzzi, A., Butterworth, D.S., Davies, C.R., Donovan, G.P., Nickson, A.,
 510 Rademeyer, R.A., and Restrepo, V. 2019. Improving communication: The key to more
 511 effective mse processes. *Canadian Journal of Fisheries and Aquatic Sciences* **76**(4): 643–
 512 656. NRC Research Press.
- 513 Nielsen, A., and Berg, C.W. 2014. Estimation of time-varying selectivity in stock assessments
 514 using state-space models. *Fisheries Research* **158**: 96–101. Elsevier.
- 515 Perkel, J.M. 2018. Data visualization tools drive interactivity and reproducibility in online
 516 publishing. *Nature* **554**(7690): 133–134.
- 517 Plummer, M. 2003. JAGS: A program for analysis of bayesian graphical models using gibbs
 518 sampling. *In* Proceedings of the 3rd international workshop on distributed statistical
 519 computing. Vienna, Austria.
- 520 R Core Team. 2017. R: A language and environment for statistical computing. R Foundation for
 521 Statistical Computing, Vienna, Austria. Available from <https://www.R-project.org/>.
- 522 Regular, P., Rodgers, B., Wheeland, L., Anderson, S., Grandin, C., Ismay, C., and Solomon, N.
 523 2020. NAFODown: An R markdown template for producing NAFO scientific council
 524 documents. Available from <https://github.com/nafo-assess/NAFODown>.

- 525 Rideout, R., and Ings, D. 2018. Research Vessel Bottom Trawl Survey Report (NL Region): A
 526 stock-by-stock summary of survey information up to and including the 2017 spring and
 527 autumn surveys. Canadian Technical Report of Fisheries; Aquatic Sciences No. 3267.
- 528 RStudio Team. 2015. RStudio: Integrated development environment for r. RStudio, Inc., Boston,
 529 MA. Available from <http://www.rstudio.com/>.
- 530 Sievert, C. 2018. Plotly for R. Available from <https://plotly-book.cpsievert.me>.
- 531 Smith, S., and Somerton, G. 1981. STRAP: A User-Oriented Computer Analysis System for
 532 Groundfish Research Trawl Survey Data. Canadian Technical Report of Fisheries;
 533 Aquatic Sciences No. 1030.
- 534 Taggart, C., Penney, P., Barrowman, N., and George, C. 1995. The 1954-1993 Newfoundland
 535 cod tagging database: Statistical summaries and spatial-temporal dynamics. Canadian
 536 Technical Report of Fisheries and Aquatic Sciences **2042**.
- 537 Tukey, J. 1977. Exploratory data analysis. Addison-Wesley Publishing Company. Available
 538 from <https://books.google.ca/books?id=UT9dAAAAIAAJ>.
- 539 Tukey, J.W., and Tukey, P.A. 1985. Computer graphics and exploratory data analysis: An
 540 introduction. *In* Proceedings of the sixth annual conference and exposition: Computer
 541 graphics'85. National Computer Graphics Association, Fairfax, VA. pp. 773–785.
- 542 Yeatman, J.D., Richie-Halford, A., Smith, J.K., Keshavan, A., and Rokem, A. 2018. A browser-
 543 based tool for visualization and analysis of diffusion mri data. Nature communications
 544 **9**(1): 940. Nature Publishing Group.